

MARLIN P. JONES & ASSOC. INC.

www.mpja.com **Online Buying**

Phone: Order: 800-652-6733 Fax: 800-432-9937 Info: 561-848-8236

Mail: P.O. Box 530400 Lake Park, FL 33403-8906

MINI 0-30V/3A

LIMITED TIME REDUCED PRICE

Specifications/Features: True Constant Current (Can drive a short). Enclosed Switching bench supply with backlit LCD display for output Volts & Amps. .01% +5mV Line /.2%+5mV Load regulation, <200mV RMS max ripple. Front banana jacks. Internal fan. CE/RoHS

L: 6" W: 2	2-7/8"	H: 6-3/4"		WT: 3.2
STOCK #		DESC.		1EA
9615-PS	Mini 0	-30V/3A B	ench Supply	\$49.95

9615-PS Mini 0-30V/3A Bench Supply

830 TIE POINT BREADBOARD LIMITED QUANTITY

SEE 4443 TE for **SPECIFICATIONS** solderless breadboard with 2 distribution strips



WT:.004

19047-TE 2 BREADBOARDS \$4.95

CRYSTAL OSCILLATOR

Kinseki Ltd. 1/2 Size 4 Pin 10.00MHz. oscillator module. 5VDC powered. No Data

Pin 1: Enable Pin 8: +5VDC Pin 4: Ground Pin 4: Output SQ 1/2 H: 1/4

19080-CY 10.00MHz Crystal Osc. \$0.79

12VDC SPST-NO RELAY MORE

MFG: OMRON P/N: G8P-1114P-US COIL: 12VDC/155 ohms

CONTACT RATING: 30A@ 250,15A @ 125VAC; 1hp@120V; 2hp@250VAC

ACTION: SPST-NO

Sealed HVAC/industrial relay for PCB mounting, UL/CSA

PGS

25,26

L: 1-1/4" W: 1-1/16" H: 7/8" WT: .06 \$5.95 19059-RL 12VDC Omron Relay

MORE PG 12 **12V** RECHARGABLE BATTERY

Power-Sonic 1220 Sealed Lead/Acid gell cell with .187 Quick connect terminals. For general purpose use in Alarms, Portable lighting. 20hr capacity rating. UL listed. W; 1-3/8" H: 2-9/16" WT: 2.8

12V@2.5A Gel Cell \$9.95 18899-BT

SNAP-ON **NOISE FILTERS** TIA-TECH P/N W5 SRH ferrite

snap-on filters. Black Plastic case with type W5 split core material. Clamps around 1/4"cable and blocks noise. Frequencies from 25MHz to above 500MHz. impedance: 100+@ 25MHz /200+ @ 100MHz

WT: .07 Clam Noise Filter .07 18466-FL .25" \$0.99

12V @ 1A SUPPLY

MFG: DPX P/N: GFP101U-1210 Input: 100-120 VAC 50/60Hz Output: 12VDC @ 1A

Specifications/Features: Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft output cord with 10mm X 5.5/2.1mm ID coaxial plug Center +. UL/canada/usa/listed. RoHS

L: 1-3/4"	W: 1-1/4"	T: 7/8"	WT: .16
STOCK #		DESC.	1EA
19087-PS	12V @ 1A	5.5/2.1 Plug	Supply \$4.95

LED LIGHT BAR

Light Bar with 150 Red Micro LEDs. 18-24VDC Operation Draws 19mA @ 18V, 36mA @ 20V, 77mA @ 24V.

L: 14-3/4" Lighted 15" O/A W: 13/16" WT: .04

19079-LA Red LED Lght Bar \$5.95

5V & 12VDC @ **2A SUPPLY**


MFG: LACIE P/N: ACU034A-0512 Input: 100-240 VAC 50-60Hz

Output: #1: +5V @ 2A #2: +12V 2A

Specifications/Features: USED, Switching desktop supply with overvoltage & current limit protection. Non-polarized 2 wire IEC Type 2-C8 input connector. 4ft output cord with 4 Pin Kycon KPPX connector. UL/canada/usa/ TUV/CE listed. POWER CORD NOT INCLUDED. ORDER CORD: Stock # 15447-CB

L: 4-1/4" W: 2" H: 1-1/8" WT: .52 19072-PS 5& 12V @ 2A Desktop Supply \$8.95

VIBRATION **ISOLATOR**



(7/16") long threaded stud on both ends. 2 Nuts Included

L: 5/8" Body 1-1/2" O/A WT: .04 Dia: 5/8'

\$1.49 19076-HD Vibration Isolator

1 GET

LASER POINTER

FLASHLIGHT **SEE 18331 TL for SPECIFICATIONS**

2 super bright white LEDs and a Class III, <5mW, 650nm Red LASER Pointer

19063-TL 2 LASER POINTERS **\$2.95**



SUPPLY

P/N: 9615 Input: 110 VAC 60Hz

Output: 0-30VDC @ 0-3A Constant Voltage/Current

TIME DELAY RELAY

MFG: MIDTEX P/N: 614-43T3A4

Coil: 120VAC Contacts: 10A, 1/3hp @ 120VAC 3PDT adjustable Time Delay relay. 6-60seconds adjustable DELAY on ENER-

GIZE. Socket mount with .187 quick con-

H: 3" O/A W: 1-1/2"

19082-RL

H: 1-7/8"

Midtex Delay Relay \$14.95

WT: .2

19V @2.65A SUPPLY

MFG: GLOBTEK P/N: GS1043

Input: 100-240 VAC 47-63Hz Output: 19VDC @ 2.65A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection. Non-polarized 2 wire IEC Type 2-C8 input connector. 6ft output cord with ferrite filter & a Right Angle, EIAJ-05 Coaxial Plug (6.5mmO/D X 4.3mml/D X 1.4mm Center Pin). TUV/canada/usa/CE listed

POWER CORD NOT INCLUDED. ORDER POWER CORD: Stock # 15447-CB

WT: .65 L: 4-3/4" W: 2-3/8 H: 1-5/16"

19078-PS 19V @ 2.65A Globtek Supply \$3.95

28VDC@1 SUPPL

P/N: PJSP-300-1028 Input: 100-240 VAC 50/60Hz Output: 28VDC @ 10.8A Specifications/Features:

Output rated with 34CFM air flow
Power Factor corrected, Open frame switching supply with current limit & Temperature protection. 1% line/load reg. Molex connectors for input & Output (Pins & Hous-

ings Supplied), UL/usa/canada/CE listed. L: 7-3/4" W: 5-1/4" H:1-3/4" WT: 2.8

18927-PS 28V@10.8A Supply \$29.95



Advanced Search



Fuli Product Index

This Catalog is just a SAMPLING of what our WEBSITE has to Offer!

Quick Order Form Contact Us Support Ordering Info Free Catalog

 1000's of additional products, visit us at: www.mpja.com

- 24/7 SSL SECURE Website Ordering
- Searchable Database of all our Products
- All Products Organized by Categories
- View all Quantity Discount Pricing
- Access to Datasheets (where available)

0-18VDC @ 3A **BENCH SUPPLY**

Input: 110 VAC 60Hz Output: 0-18VDC @ 0-3A Constant

Voltage or Current

Specifications/Features: True Constant Current (Can a short) Enclosed Linear bench supply with dual LCD displays for output Volts & Amps. .01%+3mV Line / .02%+3mV Load regulation, <1mV RMS ripple. Front binding posts. Metal case & rubber feet. Internal Temp. controlled fan

L: 9-1/2 W: 3-5/8' WT: 8.6 0-18V/3A Adj. Supply \$52.95 9600-PS

MINI BENCH SUPPLIES

P/N: 9616/9617 Input: 110 VAC 60Hz Output: 0-30VDC

0-3A Constant Voltage/Current(9616) 0-5A Constant Voltage/Current(9617) Specifications/Features: Adjustable

Voltage/adjustable Current limit. Enclosed regulated switching bench supply with backlit LCD display for output Volts & Amps. 1% +10mV Line/1%+5mV Load regulation, <200mV RMS max ripple. Banana jacks (9616), Binding Posts (9617). Internal fan.

W: 1-1/4" H: 6-1/2' D: 8-3/4" WT: 3.9 9616-PS Mini 0-30V/3A Bench Supply 9617-PS Mini 0-30V/5A Bench Supply \$69.95

0-50VDC @ 3A **BENCH SUPPLY**

P/N: 9612 Input: 110 VAC 60Hz Output: 0-50VDC @ 0-3A Constant Voltage or Current

Specifications/Features: True Constant Current (Can drive a short). Enclosed Linear bench supply with dual LED displays for output Volts & Amps. .01% +3mV Line /.02%+3mV Load regulation, <1mV RMS ripple. Front binding posts. Internal Temp. controlled fan.

L: 11-1/4" W: 5-3/16"

9612-PS 0-50V/3A Adj. Supply \$99.00

0-30VDC/5A **BENCH SUPPLY**

Input: 110 VAC 60Hz Output: 0-30VDC @ 0-5A Constant Voltage or Current

Specifications/Features: True Constant Current (Can drive a short). Enclosed Linear bench supply with dual LED displays for output Volts & Amps. .01% +3mV Line /.02%+3mV Load regulation, <1mV RMS ripple. Front binding posts. Internal Temp. controlled fan.

L: 11-1/4" W: 5-3/16" 9603-PS 0-30V/5A Bench Supply \$110.00 \$95.00

DUAL 0-30VDC/3A **& 5VDC/3A BENCH SUPPLY**

MFG: MPJA Inc. Input: 110 VAC 60Hz Outputs: #1: 0-30VDC @ 0-3A

#2: 0-30VDC @ 0-3A #3: 5VDC @ 3A fixed

Specifications/Features: Dual Constant Voltage or Current supply with dual backlit LCD meters that displays Volts & Amps. Selectable Series or Parallel operation of Adj. supplies (0-60V/3A or 0-30V/6A).10 turn Voltage control, Push button Current control (30ma resolution). <.01 % Line / Load regulation (CV).05% line/load (CC), <1mV/<2mA RMS ripple. Front panel output Banana Jacks & Terminal strips.

WT: 28.7 W: 10-3/4" H: 7-1/2" 9333-PS Dual 0-30V & 5V Bench Supply \$179.00

0-30VDC @ 10A **BENCH SUPPLY**

Output: 0-30VDC @ 0-10A Constant Voltage or Current

Specifications/Features: True Constant Current (Can drive a short) Enclosed Linear bench supply with dual LED displays for output Volts & Amps. .01% +3mV Line /.05%+3mV Load regulation, <1.5mV RMS ripple. Front binding posts.

L: 11-1/4" H: 6-1/2" WT: 28 9604-PS 0-30V/10A Adj. Supply \$169.00

0-30VDC @ 19A **BENCH SUPPLY**

Input: 110 VAC 60Hz Output: 0-30VDC @ 0-19A Constant Voltage or Current

Specifications/Features: True Constant Current (Can drive a short). Enclosed Linear bench supply with dual LED displays for output Volts & Amps. .01% +3mV Line /.05%+3mV Load regulation, <1.5mV RMS ripple. Front binding posts. Internal Temp. controlled fans L: 11-1/4" W: 10-1/2" H: 6-1/2"

9950-PS 0-30V/19A Adj. Supply \$269.00 \$239.00

0-60VDC RACK

Specifications/Features: Enclosed switching supply with dual LED displays for output Volts & Amps. Course & Fine controls for Voltage & Current Limit. 1% Line/Load Reg <1% ripple. Front binding posts & Internal fan. Feet & brackets can be Installed/Removed as needed for Rack

Stacking or bench top use H: 3-1/2" (2U) D: 12-1/4" WT: 12

PROGRAMMABLE 0-36VDC @ 3A **BENCH SUPPLY**

INPUT: 110 VAC 60Hz **OUTPUT: 0-36VDC @ 0-3A** Resolution V: 1mV @<3.999V 10mV @>4.000V

Ripple: <= 2mV RMS

Regulation: <= .02% +10mv Line/Load

Specifications/Features: Programmable supply with back-lit LCD display, numeric keypad, rotary digital control. Operates as Constant Voltage, Current or Power. Up to 10 settings can be stored in memory. Easy set up using keypad. OPTIONAL Control packages allows PC control via RS232 or USB interface, W: 8-1/2" H: 3-3/4" D: 11" WT: 14.9

STOCK # **Programmable Supply** 15316-PS \$199.00 15317-PS **RS232 Computer Interface** \$24.95 15318-PS **USB** Computer Interface \$24.95 **RS485 Computer Interface** 15319-PS \$24.95

0-120VDC/1A **BENCH SUPPLY**

MFG: MPJA Inc. Input: 110 VAC 60Hz Output: 0-120VDC @ 0-1A Specifications/Features:

Constant Voltage or Current Enclosed bench supply with single backlit LCD meter that displays Volts & Amps. 10 turn Voltage control, Push Button Current control (30ma resolution). <.01% Line/Load regulation (CV) .05% line/Load (CC), <1mV / <.2mA RMS ripple. Front panel output Banana Jacks & Terminal strips. Rubber feet, top carry strap

W: 5-1/4" D: 11-1/4" H: 7-1/2" WT: 14.3 9312-PS 0-120V/1A Supply \$129.00 \$119.00

0-120VDC/3A **BENCH SUPPLY**

MFG: MPJA Inc. Input: 110 VAC 60Hz Output: 0-120VDC @ 0-3A

Specifications/Features: Regulated Bench supply with Adjustable Current limit. LED meter displays Volts & Amps. Push button switch connects supply to load. Multi turn Voltage control for precise settings. 5mV RMS ripple. Front panel output Binding Posts & Terminal strip for remote Voltmeter Sensing at the load.

W: 10-3/4" Ship WT: 26.5 9313-PS 0-120V 3A Bench Supply \$265.95



18650-PS 0-60V Adj. Rack Supply \$189.95 150mV

High reliability line of power supplies designed to operate over the wide range of AC power found world wide.

- Overvoltage, Overcurrent, Short Circuit Protected
- •100% Full Load Burn-in Tested--Full rated to 50°C

No minimum load--UL/canada/usa/CE listed.



40W SUPPLIES

Input: 85-264 VAC 47-63Hz Universal H: 40mm L: 129mm W: 98mm

L: 5.08"	W: 3.86"	H: 1.5/"	Wt: 1.	Wt: 1.11b	
STOCK #	OUTPUT	PART #	RIP/NOISE	EFF	CASE
16000-PS	5V/8A	HF-40W-SL5	80mV	72%	A
16001-PS	12V/3.5A	HF-40W-SL12	100mV	76%	Α
16002-PS	15V/2.8A	HF-40W-SL15	100mV	76%	A
16003-PS	24V/1.8A	HF-40W-SL24	100mV	78%	A

HF-40W-SL48 **DISCOUNT PRICING**

Qty: 1-9 Qty: 10-99 Qty: 100+ \$24.50 \$21.52 \$17.93

48V/0.8A



GENERAL SPECIFICATIONS **RoHS** Compliant

Line Regulation (Full Load): < +/- 0.5% Load Regulation: .05% (0-100%) Inrush Current: 20A/115V, 40A/230V Input Leakage Current: <0.7mA@230VAC Output Adjustment Range: +/- 10% 110-150% Overload Protection: 40/60W: 100/150W: 110-130%

Over Voltage Protection: 115-150% Rise Time: 50mS Full Load (Typical) Hold Up Time: 20mS Full Load (typical)

Withstand Voltage (1 Min.):

Input to Output: 3.0KV AC Input to Frame/Ground: 1.5KV AC Output to Frame/Ground: 0.5KV AV

MTBF: 100,000 Hours

Operating Temp. & Humidity: -10° C to +50° C 20%-93% Non Condensing

Storage Temp. & Humidity: -20° C to +85° C 20%-95% Non Condensing

Cooling: Convection Approvals/Standards:

cULus Ref. No.: E22014 Safety: GB4943, UL60950, EN60950 EMC: GB9254, EN55022 class B, EN55024 EN61000-3-2/3 EN61000-4-2/3/4/5/6/8/11

60W SUPPLIES

16004-PS

Input: 85-264 VAC 47-63Hz Universal L: 160mm W: 98mm H: 39mm



80%

L. 0.0	**. 0.00	11. 1.04	** **	210		
STOCK #	OUTPUT	PART#	RIP/NOISE	EFF	CASE	
16005-PS	5V/12A	HF-60W-SL5	80mV	73%	В	
16006-PS	12V/5A	HF-60W-SL12	100mV	76%	В	
16007-PS	15V/4A	HF-60W-SL15	120mV	77%	В	
16008-PS	24V/2.5A	HF-60W-SL24	150mV	80%	В	
16009-PS	48V/1.3A	HF-60W-SL48	200mV	81%	В	

DISCOUNT PRICING

Qty: 1-9 Qty: 10-99 Qty: 100+ \$28.59 \$23.05 \$20.39

150W SUPPLIES

Input: 85-132/170-264 VAC 47-63Hz Switch Selectable Wt: .73 L: 199mm W: 110mm H: 50mm L: 7.83' W: 4.33 H: 1.97 Wt: 1.6lb STOCK OUTPUT 16017-PS 5V/30A HF-150W-SF5 120mV 78% 7.5V/20A HF-150W-SF7.5 16018-PS 120mV 80%

D D HF-150W-SF9 16019-PS 9V/17A 120mV 80% D 16020-PS HF-150W-SF12 12V/12.5A 120mV 82% D 16032-PS 24V/6.5A HF-150W-SF24 150mV 85% D 16033-PS 28V/5.5A HF-150W-SF28 150mV 85% D 16034-PS 36V/4.2A HF-150W-SF36 200mV 86% n

DISCOUNT PRICING

Qty: 1-9 Qty: 10-99 Qty: 100+ \$42.88 \$34.90 \$32.50


100W SUPPLIES



DISCOUNT PRICING

Qty: 1-9 Qty: 10-99 Qty: 100+ \$34.80 \$28.90 \$25.15


240W SUPPLIES



STOCK 18434-PS 5V/40A HF-240W-SE5 100mV 80% D 18435-PS 12V/18A HF-240W-SF12 100mV 83% D 18436-PS 24V/10A HF-240W-SF24 120mV 85% D 18437-PS 48V/5A HF-240W-SF48 150mV 87% D

DISCOUNT PRICING

Qty: 1-9 Qty: 10-99 \$49,90 \$45.25





INTERNATIONAL POWER OPEN FRAME LINEAR SUPPLIES

8523-PS

6611-PS

Specifications/Features: High reliability line of power supplies designed to operate over the wide range of AC power sources found world wide. +-.05% Regulation, Full rated to 50°C, Foldback Current Limit, no minimum load, Remote Sense, UL/CSA/TUV/CE listed. RoHS level 5

\$228.37

\$219.74



\$129.11

\$219.74

5VDC OUTPUT SUPPLIES

IHF5-25/OVP

15VDC OUTPUT SUPPLIES

8522-PS

6618-PS

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below. IP PART # \$40.42 \$38.30 6601-PS IHA5-1.2/OVP 5V/1.2A \$40.42 \$38,30 6602-PS IHA5-1.5/OVP 5V/1.5A В \$40.42 6603-PS IHB5-3/OVP 5V/3.0A В \$38,30 \$67.19 \$63.66 6604-PS IHC5-6/OVP 5V/6.0A C 6605-PS IHN5-9/OVP 5V/9.0A N \$91.77 \$86.94 \$98.85 IHD5-12/OVP \$104.34 6606-PS 5V/12.0A D \$147.21 \$139.46 8521-PS IHE5-18/OVP 5V/18.0A E

5V/25.0A

12VDC OUTPUT SUPPLIES

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below. IP PART 1D+FA \$40.42 \$38.30 6607-PS IHB12-1.7 12V/1.7A B 6608-PS IHC12-3.4 12V/3.4A C \$60.73 \$58,48 6609-PS \$86.31 \$81.77 IHN12-5.1 12V/5.1A N 6610-PS IHD12-6.8 12V/6.8A D \$97.78 \$92.64

E

\$136.29

\$231.94

12V/10.2A

12V/15.0A

F

F

\$241.05

\$231.94

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below. 40.42 \$38,30 6612-PS IHA15-0.5 15V/0.5A 6613-PS IHA15-0.9 15V/0.9A В \$40.42 \$38.30 \$40.42 \$38,30 6614-PS IHB15-1.5 15V/1.5A B \$60.73 \$58.48 6615-PS IHC15-3.0 15V/3.0A 6616-PS \$86.05 \$81.77 IHN15-4.5 15V/4.5A N 6617-PS IHD15-6 15V/6.0A D \$97.78 \$92.64 8524-PS 15V/9.0A E \$136.29 \$129.11 IHF15-9

24VDC OUTPUT SUPPLIES

IHE12-10.2

IHF12-15

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below.

STOCK #	IP PART #	OUTPUT	CASE	1-9EA	10+EA
6619-PS	IHA24-0.5	24V/0.5A	В	\$40.42	\$38.30
12784-PS	IHB24-1.2	24V/1.2A	В	\$40.42	\$38.30
6621-PS	IHC24-2.4	24V/2.4A	C	\$60.73	\$58.48
6622-PS	IHN24-3.6	24V/3.6A	N	\$86.31	\$81.77
6623-PS	IHD24-4.8	24V/4.8A	D	\$97.78	\$92.64
6624-PS	IHE24-7.2	24V/7.2A	E	\$136.29	\$129.11
7377-PS	IHF24-12	24V/12.0A	F	\$231.94	\$219.74

28VDC OUTPUT SUPPLIES

IHF15-15

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below.

15V/15.0A

STOCK #	IP PART #	OUTPUT	CASE	1-9EA	10+EA
6626-PS	IHB28-1	28V/1.0A	В	\$40.42	\$38.30
6627-PS	IHC28-2	28V/2.0A	C	\$60.73	\$58.48
6628-PS	IHN28-3	28V/3.0A	N	\$86.31	\$81.77
6629-PS	IHD28-4	28V/4.0A	D	\$97.78	\$92.64
8525-PS	IHE28-6	28V/6.0A	E	\$136.29	\$129.11

48VDC OUTPUT SUPPLIES

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below.

STOCK #	IP PART #	OUTPUT	CASE	1-9EA	10+EA
6630-PS	IHB48-0.5	48V/0.5A	В	\$52.61	\$40.50
6631-PS	IHC48-1	48V/1.0A	C	\$70.11	\$66.42
6632-PS	IHD48-3	48V/3.0A	D	\$108.87	\$103.14
8526-PS	IHE48-4	48V/4.0A	E	\$147.21	\$139.46
8527-PS	IHF48-8	48V/8.0A	F	\$323.76	\$306.72

HIGH VOLTAGE OUTPUT SUPPLIES

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below

STOCK #	IP PART #	OUTPUT	CASE	1-9EA	10+EA
8528-PS	IHB155-0.12	135-170V/.12A	В	\$52.61	\$49.84
8529-PS	IHB200-0.12	175-210V/.12A	В	\$52.61	\$49.84
8530-PS	IHB250-0.10	215-265V/.10A	В	\$52.61	\$49.84

500 WATT POWER SOURCES

Unregulated power sources for use where full regulated power is not required, such as solenoids, motors, DC/DC converters & lamps. Floating outputs, 3% output ripple at full load (4% on 12V model). Full rated to 55°C, no minimum load. UL/CSA/TUV listed Input: 108/120/132/216/240/264 VAC 50/60Hz. Output: See below.

STOCK #	IP PART #	OUTPUT	CASE	1-9EA	10+EA	
8531-PS	IP500U12	14.7V/0A 13V/15A 12V/30A	U	\$245.67	\$232.74	
6645-PS	IP500U24	29.2/0A 26.8/10A 24.6V/20.0A	U	\$245.67	\$232.74	
6642-PS	IP500U36	42.8/0A 38.2/6.6A 36.1V/13.3A	U	\$245.67	\$232.74	
6646-PS	IP500U48	56.6/0A 52.8/5A 48.8V/10.0A	U	\$245.67	\$232.74	
6643-PS	IP500U65	72.5/0A 68.8/3.8A 65/7.7A	U	\$245.67	\$232.74	
6644-PS	IP500U75	85.5/0A 78.2/3.3A 74.8V/6.6A	U	\$245.67	\$232.74	

CASE SIZE AND WEIGHTS



CA







CASE A

CASE B

CASE C

CASE D







N

ASEE	CASE F	CASE

CASE	LEN.	WIDTH	THICK	WEIGHT
Α	3.75"	3.00"	2.20"	1
В	4.87"	4.00"	2.10"	2
С	5.62"	4.87"	2.95"	4
N	7.00"	4.87"	3.35"	6
D	9.00"	4.87"	3.20"	7.5
E	14.00"	4.87"	3.40"	10
F	16.75"	4.88"	6.30"	19

MULTI. OUTPUT SUPPLIES

Input: 100/120/220/230-240 VAC 50/60Hz Output: See below.

STO	K#	IP PART #	OUTPUT	CASE	1-9EA	10+EA
6633-	PS I	HAA15-0.8	+&-12V/0.8A	AA	\$53.15	\$50.36
6634-	PS I	HTAA16W	5V/2A,+12/.4,-12/.	4 AA	\$67.52	\$63.96
6635-	PS I	HBAA40W	5V/3A,+&-12V/1A	BAA	\$92.64	\$87.77





CASE AA

CASE BAA

CASE U

CASE	LEN.	WIDTH	THICK	WEIGHT
AA	6.50"	4.00"	2.07"	2
BAA	10.25"	4.00"	2.95"	5
U	9.0"	4.62"	5.62"	22



INTERNATIONAL POWER OPEN FRAME MULTIPLE OUTPUT LINEAR SUPPLIES



Input: 100/120/220/230-240 VAC 50/60Hz	Output: See below
--	-------------------

STOCK #	MFG/MODEL #	OUTPUT #1	OUTPUT #2	OUTPUT #3.	CASE	WT.	1EA	10+EA
8532-PS	IHCC5-6/OVP	+5V @ 6.0A	-5V @ 6.0A		CC	7 lbs	\$118.92	\$112.66
8533-PS	IHD12-6.8-504	+5V @ 3.0A	12V @ 6A Isolated	-	D	7.5 lbs	\$148.48	\$140.66
6641-PS	IHCC512	+5V @ 6.0A	12-15V adj @ 2.5A Isolated		CC	7 lbs	\$113.46	\$107.49
6637-PS	IHAD12-0.4	+12V @ 0.4A	-12V @ 0.4A	-	В	2 lbs	\$45.29	\$42.90
6638-PS	IHAD15-0.4	+15V @ 0.4A	-15V @ 0.4A	Maria de la companione de	В	2 lbs	\$45.29	\$42.90
8534-PS	IHBB24-1.2	+24V @ 1.2A	-24V @ 1.2A	•	BB	4 lbs	\$68.83	\$65.21
6639-PS	IHCC15-3.0	+12V @ 3.4A	-12V @ 3.4A	-	CC	7 lbs	\$108.00	\$102.31
	OR	+15V @ 3.0A	-15V @ 3A	<u>-</u>				
6636-PS	IHCAA-60W	+5V @ 6.0A	+12-15V @ 1A	-12-15V @ 1A	D	7.5 lbs	\$110.46	\$104.64
	OR		и	-5V @ 0.4A				
7380-PS	IHBCC512	+5V @ 3.0A	+12V @ 3.4A	-12V @ 3.4A	CC	7 lbs	\$142.90	\$135.38
	OR	n	+15V @ 3A	-15V @ 3A				
8535-PS	IHBCC524	+5V @ 3.0A	+18-20V @ 1.8A	-18-20V @ 1.8A	CC	7 lbs	\$142.90	\$135.38
	OR	II	+24V @ 2.4A	-24V @ 2.4A				
			MULTIPLE OUTPUT LINEAR FO	R HARD/FLOPPY DRIVES				
8536-PS	ICP162	+5V @ 3A	-5V @ .6A	+24V @ 5A (6Apk)	131	9 lbs	\$159.55	\$151.16

OVERVOLTAGE PROTECTORS

6647-PS	IOVP12	Adjustable overvoltage protector for ALL Case sizes Smaller than "D"	.2 lbs	\$11.96	\$11.33
6648-PS	IOVP24	Adjustable overvoltage protector for ALL "E", "F", & "G" Case Sizes	.4 lbs	\$20.70	\$19.61







CASE	LEN.	WIDTH	THICK	WEIGHT	CASE	LEN.	WIDTH	THICK	WEIGHT	CASE	LEN.	WIDTH	THICK	WEIGHT
CC	9.38"	4.87"	3.20"	7	131	11.00"	4.87"	3.20"	9	BB	7.00"	4.87"	2.05"	9

MINI 0-30V/3A SUPPLY



P/N: 9615 Input: 110 VAC 60Hz

Output: 0-30VDC @ 0-3A Constant Voltage/Current Specifications/Features: True Constant Current (Can drive a short). Enclosed Switching bench supply with backlit LCD display for output Volts & Amps. .01% +5mV Line /.2%+5mV Load regulation, <200mV RMS max ripple. Front banana jacks. Internal fan. CE/RoHS

L: 6" W: 2-7/8" H: 6-3/4" WT: 3.2 9615-PS Mini 0-30V/3A Bench Supply \$59.95 **UL/CSA LISTED 10A REGULATED** 13.8VDC BENCHTOP SUPPLY

MFG: SAMLEX Input: 110/120VAC 50-60Hz Output: 13.8VDC @ 10A

Short Circuit & Overload Protected. With Metal Case, Power Cord, Line Fuse and Switch For Cellular Phones, Auto Accessories, Test Equipment. Binding post for output.UL/CSA listed

W : 9-1/2"	H: 5"		D: 9-3/4	1"	WT: 15.3
STOCK #		DESC.		1EA	3EA
5825-PS	13.8V	/10A UL	Supply	\$99.95	\$89.95

SELECTABLE OUTPUT SUPPLY



P/N: 9902-PS Input: 90-250VAC 60Hz

Outputs: 3,4.5, 6, 7.5,9,12VDC @ 2000mA Selectable Specifications/Features: Enclosed, Benchtop regulated, switching supply. Switch selectable output. Front panel Power switch, Select switch & Binding posts. 6ft. 2 wire input power cord with 2 blade plug.

L: 6-1/2" W: 3-7/8" H: 2-1/4" WT: 1.1

9902-PS Multi Output Supply \$19.95 \$17.95

2.5-18VDC @ 2A BENCH SUPPLY WITH

FIXED +5 &-/+12

W: 9.3"

MFG.: ELENCO P/N: XP581 Input:120VAC

Outputs: #1: 2.5-18V @ 1.5A(2Max) #2: +5VDC @ 3A #3: +12VDC @ 1A

Foldback current limit. Volt & Amp Meters, .05V Line/load reg. on fixed outputs; .4V on variable. 5mV ripple. Metal Case, Power Cord, Switch, & Binding Posts.

H: 3.5" D: 8.3" WT: 10 8775-PS 2.6-18V Output Elenco \$124.95 \$115.95

THOUSANDS more Items on www.mpja.com

REGULATED 13.8V DC SUPPLY

MFG: MPJA

Input: 110 VAC 60Hz

Outputs: 13.8V @ 6A 8A Surge Regulated, Fixed output bench supply, Metal Case, Power Cord, Line Fuse and Switch. For Cellular Phones, Auto Accessories, Test Equipment. Front Binding Posts.

Does not have short circuit protection. W: 6" H: 4-1/2" D: 11-1/4"

9323-PS 13.8V@6A Bench Supply \$39.95 \$36.95

1KVA LINE STABILIZER



Specifications/Features: Micro processor controlled, Benchtop autoregulator for

AC line. Automatically compensates for input line voltage variations. Front panel analog meters & power switch, input voltage switch. 110 & 220 AC sockets, fuse, & cord on back. Ideal for testing 110 & 220 equipment. 6ft AC line cord input W- 9-1/2" H- 7-1/4" W- 5-1/2"

4834-PS	1KVA St	abilizer	662.95	\$56.95
STOCK #	DE	SC.	1EA	5+EA
W. U-1/E	11.7 17-7	991 0 1/4		

DC POWER SUPPLIES

DIN RAIL POWER SUPPLIES

MFG: HENGFU P/N: HF150-SDR Series Input: 85-132VAC 50/60Hz Output: 150W See Below



Specifications/Features: Compact supply mounts on TS35/7.5 or /15 DIN rails 0.5% line/load reg, 120/150mV Ripple/noise. Over Voltage/Current/Short circuit protected, LED Power out indicator. Built-in EMI Filter. CE listed

W: 4-1/4"H: 4	WT: 1.6		
STOCK#	DESC.	1EA	
17895-PS	12V/12.5A DIN Supply	\$49.95	
17896-PS	24V/6.3A DIN Supply	\$49.95	
17897-PS	48V/3.1A DIN Supply	\$49.95	

DUAL OUTPUT SUPPLIES

MFG: HENGEL P/N: HF100W-DF series (See Below) Input: 85-132/170-264VAC 50/60Hz. (Switch Select)

Output: See below Specifications/Features: 100W, Enclosed regulated switching supply with Floating outputs. Line Reg: 0.5% Load Reg: 0.5% on 5V; 3% on #2. Over Voltage & Current protected. LED output indicator. Terminal strip In/Out.

L: 7-7/8"	W: 3.7/8	" H: 1	-5/8"	WT: 1.6
STOCK #	SERIES	OUTPUT #1	#2	TEA
18111-PS	DF-A	5V/10A	12V/4A	\$39.95
18112-PS	DF-B	5V/15A	15V/2A	\$39.95
18113-PS	DF-C	5V/15A	24V/1A	\$39.95

INDUSTRIAL 15W SUPPLIES

MFG: HENGFU Input: 85-264VAC 47-63Hz Output: see chart Specifications/Features:

Open Frame regulated switching supply. Over Voltage & Current protected. LED output indicator. Header In/Out. UL/us/canada/CE listed

L: 4.0"	W: 1.82"	H: 1.0"	Wt: .21b
STOCK #	OUTPUT	PART#	1EA
18438-PS	5V/3A	HF15W-SPL-5	\$15.99
18439-PS	12V/1.3A	HF15W-SPL-12	\$15.99
18440-PS	24V/0.6A	HF15W-SPL-24	\$15.99
18441-PS	48V/0.3 A	HF15W-SPL-48	\$15.99

INDUSTRIAL 25W SUPPLIES MFG: HENGFU

Input: 85-264VAC 47-63Hz Output: see chart Specifications/Features:

Open Frame regulated switching supply. Over Voltage & Current protected. LED output indicator. Header In/Out.

L: 4.0"	W: 1.82"	H: 1.0"	Wt: .2lb
STOCK #	OUTPUT	PART #	1EA
18442-PS	5V/5A	HF25W-SPL-5	\$15.95
18443-PS	12V/2.1A	HF25W-SPL-12	\$15.95
18444-PS	24V/1.1A	HF25W-SPL-24	\$15.95
18445-PS	48V/0.5A	HF25W-SPL-48	\$15.95

POWER SUPPLIES/CHARGER

MFG: HENGFU P/N: HF20W-SB series (See Below)

Input: 85-264VAC 50/60Hz. Output: See below

Specifications/Features: 20W, Enclosed regulated switching supply with Charger for Lead Acid or Lithium battery. Auto switch to battery upon AC fail (UPS). Over Voltage, Current & Low Battery protected. LED output indicator, Terminal strip In/Out, CE listed.

L: 4-3/8"	W: 3-1/8	B" H:	1-1/2"	W	T: .6
STOCK #	SERIES	OUTPUT #1	CHAR	GER	1EA
18116-PS	SB-12	12V/1.5A	13.8V/0	.5A	\$19.95
18117-PS	SB-24	24V/0.7A	27.1V/0	.2A	\$19.95

5VDC/5A SUPPLY

Visit

MFG: METAPO Input: 100-240VAC 50/60Hz Output: 5V@5A

Specifications/Features:

Enclosed regulated switching supply. Over Voltage & Current protected. LED output indicator. Terminal strip In/ Out. ULusa/canada/TUV/CE listed.

25W:	L: 3.9"	W: 3.82"	H: 1.4"	WT: .8	
STOC	(#	DESC.	1	EA 40EA	
17431-	PS	5V/5A 25W Sup	pply \$1	2.95 \$11.9	5

300W POWER **SUPPLIES**

High reliability, Enclosed, Switching power

Overvoltage, Overcurrent, Short Circuit Protected

•100% Full Load Burn-in Tested--Full rated to 50°C No minimum load

Input: 90-130 VAC Input 50/60Hz

Output: See below

	*** 1.0			** * * * *
STOCK #	DESC	No. of the last of	1EA	10EA
16486-PS	5V/60A Powe	er Supply	\$97.00	\$88.50
16487-PS	9V/33A Powe	er Supply	\$97.00	\$88.50
	12V/25A Pow		\$97.00	\$88.50
	24V/12.5A Po		\$97.00	\$88.50
	36V/8.5A Pov		\$97.00	\$88.50

25V,10A SUPPLY

MFG: HIGH PERFECTION TECH. P/N: HS250-PS1 Input: 115/230VAC 50/60Hz Output: 25VDC @ 10A

Specifications/Features: ATX form factor switching supply. Standard IEC input and output power connectors on back. Single 2 X 6 (12) socket output connector.

Pin 1: +25V(Red) Pin 2: Turn On(Gray) Pin 3: Common Pin 4: +25V(Red) Pin 5: Common(Blk) Pin 6: Common SUPPLY MUST HAVE LOAD TO OPERATE

Connect "Power On" (Gray) to Common(Black) to activate
V: 5-15/16"
L: 4-3/4"
H: 3-3/8"
WT: 3.8 WT: 3.8 W: 5-15/16 \$19.95

25VDC/10A HPT Supply 18960-PS

5V & 12V & 3.3V SUPPLY

MFG: PowDec P/N: UPN65-31 Input: 115/230VAC 50/60Hz Outputs: #1: +5VDC @ 10A

#2: +3.3VDC @ 10A #3: +12VDC @ 1A Specifications/Features: Max. output 65W, Open frame

switching supply. 3.0% Load Regulation (Vout 1& 2/10% V3), Current Limit. Req. minimum load, Rated to 70 Deg. "C". UL/canada/usa/TUV/CE listed.

L: 5"	W: 3"	H : 1-3/8"	WT: .8
STOC	K#	DESC.	1EA
18847	-PS Po	owDec 3 Output Supply	\$4.95

3 OUTPUT SUPPLY

P/N: VLT130-3100-S2 Input: 90-263 VAC 47-63Hz Output #1: +3.3V @ 16A #2: +5V @ 14A

#3: +12V @ 1.5A Specifications/Features: Requires 32CFM cooling. Power Fail output, Remote Sense on #1 & 2 Outputs, Current share for paralleling (#1 & #2) Over current protection. Header Pins AC Input, Terminal Strip Outputs, Header for Share & remote Sense connections. UL/

canada/usa/VDE/CE Listed. 1 . 5 W- 3"

18090-PS 3 Output EOS Supply \$10.95 \$9.95

INDUSTRIAL SUPPLIES

a.com for our Complete Products Lines.

MFG: MEANWELL Input: 120/240VAC 50/60Hz (Switch Select)

Output: see chart Specifications/Features:

Enclosed regulated switching supply. Over Voltage & Current protected. LED output indicator. Terminal strip In/Out. UL/us/canada/CSA/us/canada/CE/TUV listed

L: 7.83"	W: 3.85"	H: 1.5	WT:	1.5
STOCK #	OUTPUT	M/W PART	NOISE	1EA
17823-PS	5V/20A	S-100F-5	100mV	\$34.95
17824-PS	12V/8.5A	S-100F-12	125mV	\$34.95
17825-PS	24V/4.5A	S-100F-24	150mV	\$34.95
17826-PS	48V/2.2A	S-100F-48	150mV	\$34.95



L: 7.83"	W: 4.33"	H: 1.9	7" WT: 1.8
STOCK #	OUTPUT	M/W PART	# NOISE 1EA
17827-PS	5V/30A	S-150-5	150mV \$44.95
17828-PS	12V/12.5A	S-150-12	180mV \$44.95
17830-PS	48V/3.2A	S-150-48	240mV \$44.95

9V @ 16.7A SUPPLY

MFG: MEANWELL P/N: S-150-9

Input: 120/240VAC 50/60Hz Output: 9VDC @ 16.7A Specifications/Features:

Enclosed regulated switching supply. Over Voltage & Current protected. LED output indicator. Terminal strip

In/Out, ULusa/canada/CE listed.

L: 7-7/8"	W: 4-3/8"	H: 2"	WT: 1.72
STOCK #	DI	ESC.	1EA
18367-PS	9V/16.7A Mea	anwell Supply	\$35.00

24V @ 1.1A SUPPLY

MFG: MEANWELL P/N: S-25-24 Input: 100-240VAC 50/60Hz

Output: 24VDC @ 1.1A Specifications/Features:

Enclosed regulated switching supply. Over Voltage & Current protected. 100mV max Ripple & Noise. LED output indicator. Terminal strip In/Out. UL/CE/TUV listed.

L. 0.0	W. J.UZ	11. 1.42	W 101
STOCK #	DI	ESC.	1EA
17720-PS	24V/1.1A	Meanwell Supp	ly \$18.95

12V/5.1A, SUPPLY

MFG: MULTICOMP P/N: SPC11481

Input: 100/120/215/230-240VAC 47-63Hz Output: 12VDC @ 5.1A Max.

Specifications/Features:

Open frame linear supply. +-.05% Line /.05% Load Regulation (50% change), Foldback Current Limit, Remote Sense, No minimum load, Rated to 50 Deg. "C" UL/ canada/CSA/TUV/CE listed.

L: 7"	STOCK #	4-7/8"	H: 3-1/2"	WT: 7.1
STOC	K#		DESC:	1EA
18425	-PS	Multic	omp 12V/5.1 A Supply	\$ 75.95

DC POWER SUPPLIES

28VDC@10.8A SUPPLY

MFG: NAO P/N: PJSP-300-1028 Input: 100-240 VAC 50/60Hz Output: 28VDC @ 10.8A Specifications/Features:

Output rated with 34CFM air flow

Power Factor corrected, Open frame switching supply with current limit & Temperature protection. 1% line/load reg. Molex connectors for input & Output (Pins & Housings Supplied), UL/usa/canada/CE listed.

W: 5-1/4" H:1-3/4" WT: 2.8 7-3/4"

18927-PS 28V@10.8A Supply \$29:95

28VDC/2A SUPPLY

MFG: CONDOR P/N: GPM55-28 Input: 100-240VAC 47-63Hz Output: 28VDC@ 2A

Specifications/Features: Open switching supply. Over voltage/current protected, 2% Line/Load Regulation, 280mV Noise. Header pins In/Out. UL/CSA/VDE Listed.

L: 6-1/4" W: 4" H: 1-3/4' WT: 1.3

17186-PS 28V @ 2A Condor \$14.95 \$12.95

24V/2A, SUPPLY

MFG: MULTICOMP P/N: MC13584 Input: 115/240VAC 50/60Hz Output: 24VDC @ 2A Max

Specifications/Features: Max. output 40W, Open frame switching supply. +-.5% Line /1.0% Load Regulation, Current Limit. No minimum load, Rated to 70 Deg. "C".

UL/canada/usa/TUV/CE listed. W: 3" H: 1-3/16" 18420-PS Multicomp 24V/2 A Supply \$12.95

+-5V & 12V SUPPLY

MFG: ARTESYN P/N: NFN40-7607

Input: 100-240 VAC 47-440Hz

Outputs: #1: +5V @ 3A #2: +12v@ 2A #3: -5V @ .35A Specifications/Features: Open switching supply. .2% Line/2% Load Reg +5V, 5% others. Over current protected. Header pins In/Out. UL/CSA/VDE listed L: 5' H: 1-1/4" W: 31 WT: .7

17721-PS + &-5V & +12V Supply \$5.95

+5V/4A, +12V/.1A **POWER SUPPLY**

MFG: FORTRON/SOURCE P/N: SLD20W Input: 120VAC 47-63Hz

Outputs: #1: +5V @ 4A #2: +12V @ .1A

Specifications/Features:

Open frame linear supply, .250 quick connect terminals for AC input, Header pins for output.

WT: 3 L: 4-7/8' T: 2-1/2 W: 4" 15347-PS +5V & +12V Supply \$10.95 \$9.95

5V/12A **POWER SUPPLY**

MFG: SPC TECH. P/N: SPC11486

Input: 100/120/220-240VAC 47-63Hz Output: 5V @ 12A

Specifications/Features:

Open frame linear supply, UL/CSA/TUV/CE listed+-.05% Regulation, Full rated to 50°C, Foldback Current Limit, no minimum load, Remote Sense, UL/CSA/TUV/CE listed.

L: 9' W: 4-15/16' T: 3-1/4" WT: 7.8

17638-PS 5V@10A Power Supply

+5V, +/-12VDC SUPPLY

MFG: POWER-ONE P/N: MAP140-3000P Input: 100-240VAC 50/60Hz

Outputs: #1: +5.1V @ 20A #2: +12V @ 4A #3: -12V @ 1A Specifications/Features: 140W max @ 200LFM airflow Open frame, regulated switching supply. Over current protection. Header pins in & out. UL/CSA/TUV listed.

W: 4-1/4

\$24.95 \$22.95 18835-PS 3 Output Power-One

58V @ 1A SUPPLY

MFG: VOLGEN P/N: SP50U-58S Input: 100-230 VAC 50/60Hz

Output: 58V @ 1.0A Specifications/Features: Enclosed

swtiching supply. .5% line, 1% load reg. 1% P/P noise/Ripple. Over load and over voltage protected. Screw terminals. UL/canada/usa/CE listed. W: 3-1/2" H: 1-1/4 WT: 1

15814-PS 58V/1A Volgen Supply \$19.95 \$18.95

24V/7.2A SUPPLY

MFG: MULTICOMP P/N: SPC11478

Input: 100/120/215/230-240VAC 47-63Hz Output: 24VDC @ 7.2A Max.

Specifications/Features:

Open frame linear supply. +-.05% Line /.05% Load Regulation (50% change), Overvoltage & Foldback Current Limit, Remote Sense, No minimum load, Rated to 50 Deg. "C" UL/canada/CSA/TUV/CE listed.

L: 14' W: 4-7/8" H: 3-1/2 WT: 12

18424-PS Multicomp 24V/7.2 A Supply \$89.95

12V/4A DC BRUTE SUPPLY

Input: 115VAC 60Hz Output: 12VDC@ 4A

Specifications/Features: Unrequlated DC supply designed for use in custom equipment. Open supply has

attached 2 wire line cord with in line panel mount switch.

4in, output wires with socket pin housing. L: 4-7/8' W: 2-1/2" HT: 2-1/4" WT: 2.5

12V/4A Brute Supply \$7.95 17636-PS

24V/8.4A SUPPLY

MFG: MULTICOMP P/N: MC13592 Input: 115/240VAC 50/60Hz

Output: 24VDC @ 8.4A Max.

Specifications/Features: Max. output 200W with 24CFM Airflow. Open frame switching supply. +-.5% Line /2.0% Load Regulation, Current Limit, Remote Sense, Fan connector. No minimum load, Rated to 70 Deg. "C". UL/canada/usa/TUV/

CEgisted.w: 5" H: 2-9/16" WT: 2.7 18423-PS Multicomp 24V/8.4 A Supply \$ 99.95

9V/2.2A SUPPLY

MFG: AULT MODEL: SUBVM1020B09 Input: 120VAC 60Hz Output: 9VDC@ 20W (2.2A) Specifications/Features: Regu-

lated board supply. Subassembly for desktop supply. No mounting frame or input/output terminals. Wires or terminals must be soldered to board. L: 3-9/16" W: 2-5/16" T: 1-3/81 WT: .5

9VDC/20W Sub Supply 17630-PS

24V @ 1A SUPPLY

MFG: POWER-ONE P/N: SP612

Input: 115/230 VAC 50/60Hz Output: 24VDC @ 1A

Specifications/Features: Switching supply with overvoltage & current limit protection. 6" wire input leads. 4in. output leadswith header socket. UL/CSA/TUV listed.

L: 5" W: 3" WT: .55 T: 1-1/21 18289-PS 24V @1A Power-1 Supply\$9.95 \$8.95

12V@17A SUPPLY

MFG: PHIHONG P/N: PSM204-120 (AC Input: -100-240VAC 50/60Hz

Output: 12V @ 17A

Specifications/Features: Max. output 204W with 36CFM Airflow. P.C. board switching supply. 1% line Reg./5% load Reg, 200mVP/P noise/ripple. Header pins for input power, 6in. cable with single 2 X7 (14) pin output/ control connector. UL/us/canada/TUV/CE Listed.

L: 7-3/4" W: 4" H: 1-1/4" WT: 1.3

18091-PS 12V@17A Power Supply \$14.95 \$12.95

+5V & +12VSUPPLY

MFG: PHIHONG for CISCO P/N: PSM66-201/34-0963-01 Input: 100-240 VAC 50/60Hz

Outputs: #1: +5V @ 9A #2: +12V @ 0.3A Specifications/Features: 48W Max

Open frame, regulated switching supply originally for Switch/Router. Over current protection. Header pins in. 12 position header connector on 5in. Leads for output. UL/ canada/usa/TUV listed

D: 1-1/4"

18465-PS +5 & +12V Cisco Supply\$10.95 \$9.95

5V/9A SUPPLY

MFG: MULTICOMP P/N: SPC11485

Input: 100/120/215/230-240VAC 47-63Hz

Output: 5VDC @ 9A Max. Specifications/Features:

Open frame linear supply. +-.05% Line /.05% Load Regulation (50% change), Overvoltage & Foldback Current Limit, Remote Sense, No minimum load, Rated to 50 Deg. "C" UL/canada/CSA/TUV/CE listed.

WT: 7 W: 4-7/8" H: 3-1/2 \$49.95 18426-PS Multicomp 5V/9 A Supply

12V/2A, SUPPLY

MFG: APS/HITRON P/N: APS19VI-11(L-B Input: 115/240VAC 47/63Hz Output: 12VDC @ 2A Max

Specifications/Features: Max. output 25W, Open frame switching supply. +-.1% Line /2.0% Load Regulation at 20% minimum load. Over Voltage & Current Limit. Rated

to 50 Deg. "C". UL/canada/usa/TUV/CE listed. W: 2-3/8" H: 1-1/2" L: 4-3/8'

18595-PS APS/Hitron 12V/2A Supply \$8.95

12V @ 3.5A **POWER SUPPLY**

MFG: II AN P/N: F1651

Input: 100-240VAC 50/60 Hz Output: 12VDC @3.5A

Specifications/Features: Open frame switching supply Over Voltage & Current protected. Header pins In/Out. UL/canada Listed

WT: .4 L: 5" W: 3" H: 1-1/8"

16741-PS 12V Ilan Power Supply \$5.95

TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764 MPJA@MPJA.COM

6 OUTPUT SUPPLY

MFG: POWER-ONE P/N: SP647

Input: 85-250VAC 50/60Hz. Outputs: #1: +3.3V @ 30A #2: +5V @ 15A

#3: +12V @ 3A #4: +5V @ 1A #5: -12V @ 1A #6: -12V @ 3A MAX V1+V2 current: 40A

150W Max. output with 300 LFM air Flow

Specfications/Features: Power Factor corrected "U" frame switching supply similiar to MPU150 series. 1.5% Reg on 3.3V Output, 1% Reg. on 5V Output, 7% Reg. on all others. UL/CSA/TUV/CE Listed, Remote sense on V1 & V2

I/O connectors Input: Molex 41695 series
Output V1 & 2 : Terminal strip

Other Outputs: Molex 41695 series Control: Molex 5264-N

L: 9-1/2" W: 4-1/4 H: 1-1/2"

17847-PS 6 Output Power-1 \$34.95 \$29.95

WT: 2.7

\$12.95

130W **1U SUPPLY**

MFG: DELTA for SUN P/N: DPS-129AB A/300-1448 STYLE: CUSTOM 1U Input: 100-240 VAC 47-63Hz

Output #1: +3.3V @ 10A #2: +5V @ 15A #3: +12V @ 6A #4: -12V @ .4A #5: +5VDCSB @ .25A Specifications/Features: 75W Max combined +5V & +3.3V. 1U switching supply for Sun Netra^(R) equipment. Power ON/STANDBY switch & standard IEC input power connector on back. Single 2X7 mother board connector (+3.3V/+5V/Com.), Two 4 (2 X 2) pin mini connectors (+5V/+12V/Com)& one 1 X 17 Pin control connector. UL/canada/usa/TUV/CE listed.

L: 10' W: 4-3/8" H: 1-9/16" WT: 2.9 17602-PS 125W 1U Sun Power Supply

200W COMPUTER SUPPLY

MFG: SKYNET

P/N: SNP-920-1S STYLE: Custom Input: 115/230 VAC 50/60Hz Output #1: +5V @ 20A #2: +12V @ 7.5A #3: -12V @ .3A

Specifications/Features: Custom computer style switching supply for industrial use. Mounted on steel bracket, External mounted Circuit Breaker and Wire harness, Non standard output connectors. 1 15Pin AMP female connector for +5/+12/-12/Return.

2Pin AMP female connector for +12VDC 2Pin AMP Male connector for ???

UL/CSA listed. Limited Data

L: 9-1/4" W: 6" H: 5' WT: 4.2 18492-PS 200W Skynet Supply \$16.95

400W ATX/SATA

MFG: A-POWER STYLE: AGS400-1 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 26A #2: +5V @ 35A #3: +5VDCSB @ 2A

#4: +12V @ 12A #5: +12V @ 20A #6: -12V @ .5A Specifications/Features: 400W Max Combined Output. Rearfan, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range & power switch on back. Single 2 X10 (20) pin with a "slide together" 2 X2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 3 SATA drive connectors, 3 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE, FCC Listed. ROHS Compliant.

W: 5-7/8" D: 5-3/4" H: 3-3/8" 400W A-Power ATX Supply \$24.95 18413-PS

400W COMPUTER SUPPLY

MFG: ASTEC P/N: AE400-4402 STYLE: AT Server Input: 115/230 VAC 50/60Hz Output #1: +5V @ 46A

#2: +12V @ 13A #3: -12V @ 1A #4: -5VDC @ .5A Specifications/Features: Front fan, Custom ATtype switching supply. Standard IEC input power connector with monitor power connector on back. Standard "P-1 (P-8) & P-2 (P-9) mother board connector, 2 Aux +5V & Ground 6 pin connector, 3 molex 4 pin IDE connectors. Additional 12 Pin (3X4) connector mounted on back for

+5V, Ground & +12V. UL/CSA/VDE. L: 9-3/4" W: 7-1/4" WT: 9 18348-PS 400W ASTEC Supply \$16.95

200W ATX SUPPLY

MFG: ASTEC P/N: SA202-3530 STYLE: ATX-1.1(20pin)

Input: 110/220 VAC 50-60Hz

#4: +12V @ 8A #5: -12V @ .8A #6: +5VDCSB @ .2A (23A Max combined +5 and +3.3V) ATX form factor 200W switching supply for replacement in P.C. & Machine tool systems. IEC input power connector & IEC Monitor power connector on back (NO POWER SWITCH). Single 2 X10 (20) pin mother board connector, 4 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. Fan on Back, UL/CSA VDE listed.

L: 5-5/8" W: 5-7/8" H: 3-3/8" WT: 27 17986-PS 200W ATX Power Supply \$9.95

260W COMPAQ SUPPLY

MFG: COMPAQ P/N: 270647-001 STYLE: ATX-1.1(20pin) Input: 110/220 VAC 50-60Hz

Output #1: +3.5V @ 10A #2: +5V @ 32A #3: -5V @ .15A #4: +12V @ 7A #5: -12V @ .15A #6: +5VDCSB @ 1.2A (170W Max combined +5 and +3.5V) ATX form factor 260W switching supply for replacement in Compaq systems.IEC input power connector on back (NO POWER SWITCH). Single 2 X10 (20) pin mother board connector, 4 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. Fan on Back. UL/TUV listed.

W: 6-1/2" L: 7" H: 3-7/8" WT: 2.7 18078-PS 260W ATX Compaq Supply \$19.95

450W ATX/SATA

MFG: A-POWER STYLE: AGS450 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 18A

#2: +5V @ 30A #3: +5VDCSB @ 2A

#4: +12V @ 12A #5: +12V @ .6A #6: -12V @ .5A Specifications/Features: 450W Max Combined Output. Bottom & Rear fans, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range & power switch on back. Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 3 SATA drive connectors, 4 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE, FCC Listed. ROHS Compliant.

W: 5-7/8" D: 5-3/4" H: 3-3/8' 18414-PS 450W A-Power ATX Supply



350W MICRO ATX SUPPLY

MFG: A POWER P/N: AGS350M STYLE: MICROATX

Input: 115/230 VAC 50/60Hz

Output #1: +3.3V @ 14A #2: +5V@14A #3: +12V @ 18A #3: -12V @ .6A #4: +5VSBDC @ 2A Specifications/Features: Standard IEC input power connector on back. Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU Core connector, 1 PCle 8 pin connector, 2 SATA drive connectors, 3 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. Bottom fan. CE Listed RoHS Compliant.

W: 4-7/8" D: 4" H: 2-1/2" WT: 2 18412-PS 350W MicroATX Supply

\$22.95

150W ATX SUPPLY

MFG: SEVENTEAM P/N: ST-150MH STYLE: ATX1.X 20Pin Input: 110/220 VAC 50-60Hz

Multiput #1: +3.3V @ 6A
#2: +5V @ 12A #3: +12V @ 5A
#4: -12V @ .1A #5: -5V @ .1A #6: +5VSB @ 1.5A
Specifications/Features: 80W Max. combined +3.3 & 5V outputs. Mini ATX form factor 150W switching supply for P.C. systems. IEC input power connector, voltage range switch & Power switch on back . Standard 2X10 (20 Pin) mother board connector, 4 molex 4 pin IDE connectors & 2 mini 4 pin for FDD etc. UL/CSA/CE listed.

L: 5-1/4 W: 3-7/8' H: 2-1/2" WT: 2.2 18034-PS 150W Mini ATX Supply

250+250W ATX REDUNDANT SUPPLY

STYLE: ATX1.3 (20pin) MFG: ETASIS P/N: EPR-2251-6B112 Input: 110/220 VAC 50-60Hz Output #1: +3.3V @ 15A

#2: +5V @ 30A #3: -5V @ .5A #4: +12V @ 14A #5: -12V @ 1A #6: +5VDCSB @ 1.5A

Specifications/Features: 2 X 250W redundant, hot swap supply. 230W Max combined +5 &+3.3V output. ATX form factor 250W switching supply for P.C. systems/ servers. Standard IEC input power connector, alarm silence switch & power switch on back. Single 2X10 mother board connector & 6 molex 4 pin connectors & 1 mini 4 pin for drives etc. Remote "Power" Green LED. Supply 1 & 2 fail Amber LEDs, "Fault" output signal leads and Remote Silence leads for remote switch all with 20+in leads. UL/TUV/CE listed.

W: 5-7/8" D: 7-1/2" H: 3-3/8" WT: 7.5 17094-PS 250W X 2 ATX Supply \$29.95 17106-PS Spare Hot Swap 250W Module

450W ATX SUPPLY

Output #1: +3.3V @ 28A #2:+5V @ 34A#3: +5VDCSB @ 2A #4: +12V @ 14A #5: -12V @ .8A (450W Max combined output)

Specifications/Features: ATX form factor switching supply. Replacement or new build. Power Switch, Input range switch & Standard IEC input power connector on back. Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed

WT: 2.2

1 Aux +12V 4 pin CPU connector, SATA drive connector,

3 molex 4 pin IDE connectors, mini 4 pin for FDD. Back fan. CE listed. W: 5-7/8" D: 5-5/8" H: 3-3/8"

18284-PS 450W ECHO-STAR Supply \$22.95



COMPUTER SUPPLIES

400W ATX/SATA

MFG: GEN-MAX STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz

Output #1: +3.3V @ 22A #2: +5V @ 28A #3: +5VDCSB @ 2A

#4: +12V @ 14A #5: -12V @ .6A #6: -5V @ .6A

Specifications/Features: Rear fan, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range switch on back (NO Power Switch). Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 1 SATA drive connector, 3 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE Listed

W: 5-7/8" STOCK #	D: 5-3/4"	H: 3-3/8"	WT: 1.9	
STOCK #		DESC.	1EA	
17981-PS	400W Gen	-Max ATX Supply	\$22.95	

450W ATX/SATA

MFG: BLUE STAR P/N: BL-450-24

STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 28A

#2: +5V @ 34A #3: +5VDCSB @ 2A #4: +12V @ 14A

#5: -12V @ .8A

Specifications/Features: Rear fan, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range & power switches on back. Single 2 X10 (20) pin with a "Side by Side" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 1 SATA drive connector, 4 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE FCC, CB Listed

D: 5-3/4" H: 3-3/8"

17978-PS 450W BlueStar Supply \$24.95 \$22.95

450W ATX/SATA

MFG: GEN-MAX STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz

Output #1: +3.3V @ 28A #2: +5V @ 34A #3: +5VDCSB @ 2A #4: +12V @ 15A #5: -12V @ .6A #6: -5V @ .6A

Specifications/Features: Top & Rear fans, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range switch on back (NO Power Switch). Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 1 SATA drive connector, 6 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE Listed

W: 5-7/8" D: 5-7/8" H: 3-1/2' WT: 2.2 \$24.95 17982-PS 450W Gen-Max ATX Supply

465W SERVER SUPPLY

MODEL: PG465-20ASV01110 P/N: Sun XR004A465WSW STYLE: SSI

Input: 100-240 VAC 47-63Hz Output #1: +3.3V @ 35A

#2:+5V @ 18A #3: +5VDCSB @ 1.5A #4: +12V @ 24A #5: -12V @ .5A (200W Max combined +5V & 3.3V output)

Specifications/Features: SSI form factor switching supply for SUN-MICRO Server. Standard IEC input power connector on back. Single 2 X12 (24) pin mother board connector. Aux 2 X 5 (10) pin +5 & +12V connector, a 3 X 2 (6) pin +12V male connector, 1 molex 4 pin IDE connector & a 2 X 2 (4)pin +5 & +12V connector. Back fan. UL/canada/usa/TUV/CE listed.

D: 7-1/8" H: 3-7/16" WT: 6 17512-PS 465W Server Supply \$14.95

480W ATX/SATA/PCI

MFG: GEN-MAX STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 32A

#2: +5V @ 36A #3: +5VDCSB @ 2A

#4: +12V @ 16A #5: -12V @ .6A #6: -5V @ .6A Specifications/Features: Top & Rear fans, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range switch on back (NO Power Switch). Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 1 PCle 6 pin Connector, 1 SATA drive connector, 6 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE Listed

D: 5-7/8" W: 5-7/8" H: 3-1/2" WT: 2.5 480W Gen-Max ATX Supply \$26.95 17983-PS

550W ATX/SATA

MFG: A-POWER STYLE: AGS550 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 22A

#2: +5V @ 32A #3: +5VDCSB @ 2A #4: +12V @ 24A #5: +12V @ .6A #6: -12V @ .5A

Specifications/Features: 550W Max Combined Output. Bottom & Rear fans, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range & power switch on back. Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 4 SATA drive connectors, 4 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE, FCC Listed. ROHS Compliant.

D: 5-3/4" H: 3-3/8" W: 5-7/8" 18415-PS 550W A-Power ATX Supply \$29.95

575W ATX/PCIe SATA SUPPLY

MFG: LOGISYS STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 38A #2: +5V @ 40A #3: +5VDCSB @ 2A #4: +12V @ 25A #5: -12V @ .8A

Specifications/Features: Dual fan, switching supply

for P.C. systems. IEC input power connector, Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux + 12V 4 pin CPU Core connector, two 6 pin PCIe connectors, 1 SATA drive connectors, 6 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. Top & Back Fans. UL/CSA/TUV/CE listed.

W: 5-1/2" D: 5-3/4" H: 3-1/2" WT: 3.5 17717-PS 575W ATX Logisys Supply \$39.95

600W ATX/SATA/ PCI

MFG: A-POWER P/N: APVA600 STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz

Output #1: +3.3V @ 25A #2: +5V @ 42A #3: +5VDCSB @ 2.5A #4: +12V @ 27A #5: -12V @ .5A

Specifications/Features:

Top & Rear fans, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range & power switches on back. Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 1 PCle 6 pin Connector, 2 SATA drive connectors, 6 molex 4 pin IDE connectors, 1 mini 4 pin for FDD

WT: 2.8 W: 5-7/8" D: 6" H: 3-1/4" \$32.95 17975-PS 600W A-Power ATX Supply

600W ATX/SATA

MFG: ECHO-STAR STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 45A

#2: +5V @ 42A

#3: +5VDCSB @ 3A #4: +12V @ 22A #5: -12V @ .8A Specifications/Features: Dual fans, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector on back. Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 1 SATA drive connector, molex 4 pin IDE connectors, 2 mini 4 pin for FDD. Back & top fans. CE listed.

H: 3-1/4' WT: 3 W: 6' D: 6' \$39.95 17714-PS 600W ATX Supply

650W ATX/SATA

MFG: ECHO-STAR P/N: ES-650-24 STYLE: ATX-20/24 Input: 115/230 VAC 50/60Hz Output #1: +3.3V @ 45A

#2: +5V @ 42A #3: +5VDCSB @ 3A #4: +12V @ 22A #5: -12V @ .8A

Specifications/Features: Top & Rear fans, ATX form factor switching supply. Replacement or new build. Standard IEC input power connector, range & power switches on back. Single 2 X10 (20) pin with a "Side by Side" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU core connector, 1 SATA drive connector, 4 molex 4 pin IDE connectors, 1 mini 4 pin for FDD. CE, CB Listed

17900-PS	OSUVV	ATA Supply	\$34.95	φ32.93		
17000 DC	CEOM	ATX Supply	\$24 OF	\$32.95		
STOCK #		DESC.	1EA	10+EA		
STOCK#	D: 6"	H: 3-1/2"	WT: 2.6			

680W ATX SUPPLY/PCIe

MFG: ECHO STAR STYLE: ATX (20 +4pin) Input: 115/230VAC 50/60Hz Outputs: #1: +3.3V @ 35A #2: +5V @ 50A #3: +12V @ 26A #4: -5V @ 0.6A #5: -12V @ 1.0A

#6: +5V SB @ 2.5A Specifications/Features: Single Blue LED lighted fan, 680W switching supply for P.C. systems. IEC input power connector,

Single 2 X10 (20) pin with a "slide together" 2 X 2 (4) pin connector to make a 24 pin mother board connector as needed, 1 Aux +12V 4 pin CPU Core connector, 1 PCle 6 pin connector, 2 SATA drive connectors, 6 molex 4 pin IDE connectors, 1 mini 4 pin for FDD Single Blue lighted fan.

WT: 2.9 W: 6" D: 6-1/4" T: 3-1/4" \$45.95 680W ATX Supply/PCIe 17715-PS

5V,25A SUPPLY

MFG: HIGH PERFECTION TECH. P/N: HS250-PS2

Input: 115/230VAC 50/60Hz

Outputs: #1: +5VDC @ 25A #2: +5VSB @ .5A Specifications/Features: ATX form factor switching sup-

ply. Standard IEC input and output power connectors on back. Single 2 X 10 (20) socket output motherboard connector Pins: 1,2,10,11,12,18: No Conn.

Common (Black) Pins: 3,5,7,13,15,16,17: Pins: 4,6,19,20: +5V (Red) Pin 8: "Power Good" (Orange)
Pin 9: +5VSB (Violet)
Pin:14: "Power On" (Green)
SUPPLY MUST HAVE LOAD TO OPERATE

Connect "Power On" (Green) to Common(Black) to activate supply

L: 4-3/4" W: 5-15/16" H: 3-3/8" WT: 3.7 18962-PS 5VDC/25A HPT Supply \$24.95

DC POWER SUPPLIES

Visit www.mpja.com for our Complete Products Lines.

20

3.6V @ 2.2A SUPPLY

MFG: KETI

P/N: SA06-8S03R-V Input: 100 -240VAC 50-60Hz Output: 3.6VDC @ 2.2A

Specifications/Features: Desktop switching supply with overvoltage & current limit protection. IEC input AC connector, 6ft output cord with 4/1.7mm coaxial plug Center+. LED power indicator. UL/canada/usa/TUV/CEROHS listed. POWER CORD NOT INCLUDED.

ORDER POWER CORD: Stock # 7378 WI L: 3-3/4" W: 2" T: 1-3/8"

\$4.95 18357-PS 3.6V @2.2A Supply

5V @ 500MA SUPPLY

MFG: SINO-AMERICAN P/N: 217-03814 Input: 100-240 VAC 50/60Hz Output: 5VDC@500mA Specifications/Features:

Switching desktop supply with overvoltage & current limit protection. Std. IEC input connector. 6ft output cord with 5.5 OD/2.1mm ID/10mm coaxial plug Center +. UL/CSA/VDE/CE listed. AC CORD NOT INCLUDED. MATING POWER CORD: ORDER Stock # 7378-CB

L: 3-1/8" W: 1-7/8" T: 1-3/8" WT: .3 18606-PS 5V/500mA Desktop Supply

5V @ 500MA SUPPLY

MFG: GPE P/N: GPE032-050050-1 Input: 100-240 VAC 50/60Hz Output: 5VDC @ .5A

Specifications/Features: Wall Plug supply with overvoltage & current limit protection. 5% Line/Load Rgulation. Non-polarized 2 Blade input connector. 6ft output cord with 5.5 OD/2.1mm ID X12mm coaxial plug, Center +. UL/canada/usa listed.

W: 1-5/8" H: 1-1/8 18745-PS 5V @ 1/2 A Supply \$1.95

9V @ 1A SUPPLY

MFG: KENWOOD Input: 115 VAC 50/60Hz Output: 9VDC @ 1A

Specifications/Features: Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft output cord with 4.7/1.7mm ID coaxial right angle plug

Center +. UL/canada/usa listed. L: 2-7/8" W: 2" T: T: 1-1/4" WT: .23 9V @1A Plug Supply \$2.95 18254-PS

12V @ 5A SUPPLY

P/N: CH1205 Input: 100-240 VAC 50/60Hz Output: 12VDC @ 5A

Specifications/Features: Desktop switching supply with overvoltage & current limit protection. Polarized 3 wire IEC Class 1 Type C6 input connector. 4ft output cord with ferrite filter & 10mm X 5.5/2.5mm ID coaxial plug Center +. CE listed. POWER CORD INCLUDED.

L: 4-1/2" W: 2' H: 1-1/4 WT: .8

18599-PS 12V @ 5A Supply \$15.95 \$14.95

4 OUTPUT 12VDC SUPPLY

P/N: 264-2250-4 Input: 100-240 VAC 50/60Hz Output: +12V @ 5A

10

Specifications/Features: Desktop switching supply Over current protection. Std. IEC input connector. 5ft. output cable with 4 12mm X 5.5/2.1mm coaxial connectors split off 18" from ends. UL/TUV/CE Listed POWER CORD INCLUDED

W: 2-1/4" D: 1-1/2" H: 4-5/8 WT: .6 12VDC Camera Supply 18682-PS \$17.95

5V @ 2A SUPPLY

MFG: H/P

P/N: L2056-60001 Input: 100-240 VAC 50-60Hz Output: 5VDC 2A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection. Non-Polarized 2 wire IEC Type 2- input connector. 6ft output cord with 10mm long X 4mm/1.7mm ID coaxial plug Center +. UL/canada/usa/TUV/CE listed. POWER CORD NOT IN-CLUDED. ORDER CORD: Stock # 15447-CB

W: 1-5/8 H: 1-1/8" 18448-PS 5V @ 2A h/p Supply \$8.95 \$7.95

5V @ 1A SUPPLY

MFG: PHIHONG P/N: PSAA05A-050 Input: 100-240 VAC 50/60Hz Output: 5VDC @ 1A

Specifications/Features: Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft output cord with USB Mini-B Plug. UL/canada/usa listed. L: 2-3/4" W: 1-1/8 D: 1-1/2 WT: .2

18611-PS 5V @1A Plug Supply \$4.95

6V @ .4A SUPPLY

Input: 100-240VAC 50/60Hz Output: 6VDC @ .4A Specifications/Features: Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft output cord with 5.5/2.1mm ID coaxial right angle plug Center +. UL/canada/usa listed.

L: 2-3/4" W: 1-15/16" T: 5/8 WT: .21 6V @.4A Plug Supply \$4.95 18475-PS

12V @ 1A SUPPLY

MFG: CUI P/N: EPA-121DA-21 Input: 100-240 VAC 50/60Hz

Output: 12VDC@1A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection. 2 wire IEC Type 2 C8 input connector. 6ft output cord with 10mm L X 5.5mm/2.1mm ID Rt. Angle coaxial plug Center +. UL/canada/usa/CE listed. RoHS Compliant. POWER CORD NOT INCLUDED. ORDER CORD: Stock #15447-CB

L: 3" W: 1-7/8" T: 1" 12V/1A Desktop Supply

12V @ 1A SUPPLY

P/N: GFP101U-1210 Input: 100-120 VAC 50/60Hz Output: 12VDC @ 1A

Specifications/Features: Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft output cord with 10mm X 5.5/2.1mm ID coaxial plug Center +. UL/canada/usa/listed. RoHS

W: 1-1/4" T: 7/8" WT: .16

12V @ 1A 5.5/2.1 Plug Supply 19087-PS

15V @ 1.6A SUPPLY

MFG: GME P/N: GFP241DA-1516EW Input: 100-240VAC 50/60Hz Output: 15VDC@1.6A

Specifications/Features: Switching wall supply with overvoltage & current limit protection 5% reg Unique "Filp Out" Non-polarized 2 blade input. 6ft output cord with 10mm X 3.5 OD/1.25mm coaxial plug Center

+. UL/canada/usa listed. W: 1-7/8 D: 1-1/8"

18724-PS 15V @ 1.6A GME Supply

5V @ 4A SUPPLY

MFG: OPENPEAK P/n: OP 20004 Input: 90-132 VAC 60Hz Output: 5VDC @ 4A

Specifications/Features: Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft output cord with 10mm X 5.5/2.1mm ID Right Angle coaxial plug Center +. UL/canada/usa/listed. RoHS compliant.

H: 3-3/8" W: 1-1/2" T: 2-1/4" \$6.95

18520-PS 5V @ 4A Plug Supply

5V @ 4A SUPPLY

MFG: DELTA for CISCO P/N: 34-1524-02 Input: 100-240 VAC 50-60Hz

Output: 5VDC 4A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection. IEC input AC connector. 4ff output cord with 8Pin (2X4) Molex "Micro-Fit " connector. UL/canada/usa/CE listed. POWER CORD NOT INCLUDED. ORDER CORD: Stock # 7378-CB

W: 2-1/2' L: 4-1/2" H: 1-3/16 18464-PS 5V @ 4A Cisco Supply \$5.95 \$4.95

9V @ 1.11A SUPPLY

MFG: FAIRWAY P/N: VE10B-090

Input: 100-240 VAC 50/60Hz Output: 9VDC@1.11A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection. 2 wire IEC Type 2-C8 input connector. 6ft output cord with 5.5mm OD & 2.1mm ID Rt. Angle coaxial plug Center +. UL/canada/usa/TUV/CE listed. POWER CORD NOT IN-CLUDED. ORDER CORD: Stock #15447-CB

L: 3-3/8 W: 2-1/4 H: 1" WT: .6 17722-PS 9V/1.11A Desktop P/S \$5.95 \$5.25

12V @ 1.5A SUPPLY

MFG: TEN PAO P/N: S018BU1200150 Input: 100-240 VAC 50/60Hz Output: 12VDC @ 1500mA (1.5A) Specifications/Features: USED Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft

output cord with 10mm L X 5.5/2.5mm ID coaxial plug Center +. UL/canada/usa listed. WT: .3

L: 2-7/8" W: 1-3/4 T: 1-1/2

\$6.95 18668-PS 12V @1.5A Plug Supply

12V @ 2A SUPPLY

MFG: JASPER P/N: AW-024-1-2-A-S Input: 100-240 VAC 47-63Hz Output: 12VDC @ 2A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection. Non-polarized 2 blade input connector. 6ft output cord with ferrite filter & 5.5 OD/

2.1mm ID/10mm coaxial plug Center +. L: 3 -1/4" W: 2 D: 1-1/4

18776 -PS 12V/2A Jasper Supply \$5.95 \$5.25

16V @ 3.36A SUPPLY MFG: FUJITSU

P/N: CA01007-0610 Input: 100-240 VAC 47-63Hz Output: 16VDC @ 3.36A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection Non-polarized 2 wire IEC Type 2-C8 input connector. 6ft output cord with ferrite filter & with EIAJ-5320A Type 5

Right Angle Connector (6.5mmOD with 1.4mm ctr. pin) Center +. UL/canada/usa/TUV/CE listed. POWER CORD NOT INCLUDED. ORDER CORD: Stock # 15447-CB W: 2-3/8" H: 1-1/4"

18468-PS 16V @ 3.36A Fujitsu Supply \$14.95 WWW.MPJA.COM

ORDERS: CALL 800-652-6733 FAX 800-432-9937

18V @ 1A SUPPLY

MFG: ARIANA P/N: ALL-181WU-18 Input: 100-240 VAC 50/60Hz Output: 18VDC @ 1A

Specifications/Features: Switching plug supply with overvoltage & current limit protection. Non-Polarized 2 blade input. 6ft output cord with 3.5/1.3mm ID coaxial plug Center +. UL/canada/usa listed.

L: 2-7/8" W: 2'

18253-PS

T: 1-5/8' WT: .4

18V @1A Plug Supply \$6.95

19V @ 3.42A SUPPLY

MFG: DELTA P/N: SADP-65KB D Input: 100-240 VAC 47-63Hz Output: 19VDC @ 3.42A

Specifications/Features: Switching desktop supply with overvoltage & current limit protection. Polarized 3 wire IEC Class 1 Type C6 input connector. 6ft output cord with ferrite filter & 5.5/2.5mm ID coaxial plug Center +. UL/ canada/usa/TUV/CE listed

POWER CORD NOT INCLUDED

ORDER POWER CORD: Stock # 18227-CB

W: 1-3/4" **WT:** .5 H: 1-1/81 L: 4-1/8"

18226-PS 19V @ 3.42A Supply \$12.95 \$10.95

20V @3.25A SUPPLY

P/N: PCGA-AC20V Input: 100-240 VAC 50/60Hz Output: 20VDC @ 3.25A

Specifications/Features: Switching desktop supply for use as replacement for laptop computers. Overvoltage & current limit protection. Polarized 3 wire IEC Class 1 Type C6 input connector. 3ft output cord with ferrite filter & 13 mmlong X 5.5/2.5mm

coaxial connector. UL/canada/usa/TUV/CE Listed. POWER CORD NOT INCLUDED ORDER POWER CORD: Stock # 18510-CB \$1.10 L: 4-1/2" W: 2" H: 1-1/4" WT: .42

18508-PS 20V @ 3.25A Laptop Supply \$8.95

48V@.38A WALL SUPPLY

MFG: AULT P/N: SC102TA4803B01 Input: 100-240VAC 47-63Hz Output: 48VDC @ 380mA

Specifications/Features: Wall mount switching supply. Non-polarized 2 blade in-put, 6ft. ZIP cord with 10mm long X 5.5/2.5mm coaxial

power plug Center +. ULus/canada listed. L: 3" W: 2" T: 1-5/81

WT:.46 18559-PS 48V Ault Wall Supply \$6.95

+5V& -24V SUPPLY

P/N: RPS661429-1D Input: 115VAC 60Hz Outputs: #1: +5V @2.5A #2: -24V @ 50mA

Specifications/Features: Desktop linear supply. Over current protected. 6ft input 3 wire cord, 6ft output cord with 5 pin DIN female. UL/CSA listed.

WT: 3.4 L: 6-3/8" W: 3-7/8" **H:** 2-3/4

14345-PS +5V@2.5A & -24V/.05A Supply

24V TO 13.8V DC/ **DC CONVERTER**

Input: 20-35VDC

Output: 13.8VDC @ 15A peak (1-2Min)

10A for 7Min/5A continuous.

Heavy duty, linear down converter. Used in applications where truck/boat etc. electrical system is 24V to provide 13.8VDC for Radios, and other communication systems. Isolated metal case, 6in input leads, binding posts for output. For direct connection to batteries only Series 2 units for up to 50VDC Input, Parallel units for higher current

W: 5-3/8 H: 1-1/2" WT: 2.3 \$29.95 9610-PS 24/12V Down Converter

15V @ 13A DC/DC CONVERTER/ BOOSTER

MFG: RELIANCE P/N: LMB32-CU

Input: 42-60V DC (48V)
Output: 15V DC 200W (13A)
Specifications/Features: Similar to Vicor VI-B32-CU. Requires +5VDC Logic for turn on. Booster module operates in parallel with standard module. Control is supplied from standard module. Short circuit protected.

WT: .5 W: 2.4 H: .5 L: 4.6 11325-PS Reliance Module \$25.00 \$22.95

12V@3.8A DC/DC CONVERTER

MFG: IPS P/N: PD65-12-LC Input: 10-30VDC (24V Nom)

Output: 12V @ 3.8A

Specifications/Features: Max. output 45W Enclosed, DC input switching supply. 0.5% line Reg./1% load Reg, 1%P/P noise/ripple. Header pins for Input & Output connections.

L: 6-3/4" W: 4-1/8" H: 2-1/8" WT: 1.3

18132-PS 12V@3.8A DC/DC Supply\$9.95

12V@17A DC/DC CONVERTER

MFG: PHIHONG P/N: PSM204-120 (DC)

Input: -40.5to -72 VDC (-48V Nom) Output: 12V @ 17A

Specifications/Features: Max. output 204W with 36CFM Airflow. DC input switching supply. 1% line Reg./5% load Reg, 200mVP/P noise/ripple. Header pins for input power, 6in. cable with single 2 X7 (14) pin output/control connector. UL/us/canada/TUV/CE Listed. DATA. SUPPLY HAS A -48V INPUT POLARITY/GROUNDING

MUST BE OBSERVED

L: 7-3/4" W: 4" H: 1-1/4' WT: 1.2 \$9.95 18093-PS 12V@17A DC/DC Supply

12V@3.8A DC/DC CONVERTER

MFG: IPS P/N: PD65-12-LC Input: 10-30VDC (24V Nom) Output: 12V @ 3.8A

Specifications/Features: Max. output 45W

Factory Pre-Wired with 24in Output & a12ft. Input cable harness. Enclosed, DC input switching supply. 0.5% line Reg./1% load Reg, 1%P/P noise/ripple. Header pins for Input & Output connections.

SUPPLIESICONVERTERS

L: 6-3/4 W: 4-1/8" H: 2-1/8" WT: 2.2

18136-PS 12V@3.8A DC/DC Supply/Wired \$9.95

5V/10A DC/DC CONVERTER

MFG: DIGITAL POWER MODEL: DP50-105 Input: 36-75VDC

Output: 5VDC@ 8A (10A @ 28CFM air) Specifications/Features: Regulated DC/DC converter. .2% Line/3% load Reg. Over Voltage & Current protected. Header Pins IN/Out. UL/canada/us/TUV

W: 3" T: 1-1/4" WT: .48 L: 5 17634-PS 48 to 5VDC/DC Converter \$5.95

QUAD OUTPUT DC/DC CONVERTER

MFG: POWER-ONE P/N: MDU150-S254 Input: 36-75VDC

#3: 12V @ 6A #4: 12V @ 2A MAX Combined V1 & V2= 30A MAX Combined V3 & V4= 6A

200W Max, output with 300 LFM air Flow

Specfications/Features: DC Input "U" frame switching supply. 1.5% Load Reg on 3.3V Output, 1% Reg. on 5V Output, 7% Reg. on all others. UL/CSA/TUV Listed, Remote sense on V1 & VŽ

I/O connectors Input: Molex 41695 series

Output V1 & 2: 8-32 Terminal strip Other Outputs: Molex 41695 series Control: Molex 5268-N

W: 4-1/4'

WT: 2.2 \$14.95 18248-PS 4 Output Power-1 DC/DC

+-15VDC DC/DC CONVERTER

MFG: INTRONICS P/N: DCS100-3/8/2 Input: 36 to 72VDC

Output: #1: 15V @ 3.4A #2: 15V @ 3.4A

Specifications/Features: Isolated Outputs, Short circuit protected. Remote Sense, Outputs can be connected as + & -. Terminal strip for input & output. 15% Min Load.

WT: 3.1 L: 9-1/2" W: 4-1/2" H: 2-1/4"

18603-PS Intronics DC/DC Converter \$18.95



\$4.95

VICOR DC/DC CONVERTER MODULES

Compact, efficent, High frequencyDC/DC converters for modular systems. 05% line/load reg. 1% P/P ripple, short circuit protected, remote sense. Some feature integral heatsink. Booster modules are used with standard modules for increased output and feature disable input.

1:46 W: 24"

STOCK	MFG/MODEL II	INFUT NOM.	INPUT RANGE	DUTPUT VOLTS	AMPS/WATTS	DESCRIPTION	WT.	le.
6654-PS	Vicor VI-B30-06	48VDC	42-60	5V	20A/100W	Booster Module	.5	\$4.95















ALL PLUG/DESKTOP SUPPLIES LISTED HERE: 120VAC/60HZ INPUT UNREGULATED DC OUTPUT WITH HIGH RIPPLE

18293-PD	FIG.	VOLTS 5VDC	AMPS 2.2A	TERMINATION (ID X OD) 3.0mm /1.0mm - Coaxial-Ctr. Pos.	LEN. 4'	CLR. BLK	DIM. L: X W: X D: 3-1/8" x 2-1/4" x 2"	MANU./PART NUMBER Hon-Kwang/005-22	UL/us/can	WT. 1.6	1EA \$3.95	12+EA
15178-PD 16228-PD 17625-PD	B C E	6VDC 6VDC 6VDC		4mm /1mm - Coaxial-Ctr. Pos. 5.5mm/2.5mm - Rt. Ang.Coaxial-Center Pos. 5.5mm/2.5mm - Coaxial-Ctr. Pos.	6' 6' 6'	BLK WHT BLK	3" x 1-3/4" x 1-7/8" 2-5/8" x 2" x 1-3/4" 2-5/8" x 2-1/4" x 2"	AD6500RDU Otres/CX06V800 AULT/P48061500A000G	JL/CSA UL/CSA	.9 .7 .9	\$2.25 \$4.95 \$3.25	\$1.95 \$2.95
17556-PD 17558-PD	D D	7.5VDC 7.5VDC	.03A .3A	5.5mm/2.1mm- Coaxial-Ctr. Pos. 5.5mm/2.1mm- Coaxial-Ctr. Pos.	5' 5'	BLK BLK	2" x 1-3/8" x 1-3/8" 21/4" x 1-3/4" x 1-1/2"	Metagram/SS-75031 Globtek/WD1C300L95CP	UL/CSA UL/CSA		\$1.95 \$3.95	
18251-PD	F	9VDC	.7A	4.7mm/1.7mm-Rt. Ang.Coaxial-Center Pos.	5'	BLK	2-1/2" x 2" x 1-5/8"	Kenwood	UL/CSA	.61	\$3.95	\$3.49












ALL PLUG/DESKTOP SUPPLIES LISTED HERE: C 120VAC/60HZ INPUT **UNREGULATED DC OUTPUT** WITH HIGH RIPPLE

STOC	CR #	FIG.	VOLTS	AMPS	TERMINATION (ID X 00)	LEN.	CLR.	DIM. L: X W: X O:	MANU./FART NUMBER	LISTED	WT.		12+EA
17565	5-PD	J	12VDC	.15A	Stripped back Mini ZIP Cord	6'	WHT	2-3/8" x 1-3/4" x 1-7/8"	Lucent/4000T	UL	.4	\$2.95	-
17563	3-PD	K	12VDC	1.2A	5.5mm/2.5mm Coaxial-Ctr. NEG. Unfiltered	6'	BLK	3-1/4" X 2-3/8" X 2"	Power Drivers/AU48-120-120T	UL/CSA	1.2	\$4.95	
18558	3-PD	0	15VDC	1A	5.5/2.5mm Coaxial - Center Pos.	6'	BLk	3-1/4" x 2-1/4" x 2"	Ault/ P48151000A000G	UL/CSA	1.3	\$5.95	
18901	I-PD	0	15VDC	1A	4.7/1.7mm Coaxial - Center Pos.	5'	BLk	3-1/4" x 2-1/4" x 2"	OEM/AD-151A	ULus/c	1.3	\$5.95	
18560	0-BC	Ş	26VDC	.21A	3.5/1.3mm Coaxial-Ctr. +	6'	BLK	3" X 2" X 1-5/8"	Black&Decker/ETPCA-180021U3	cULu	.23	\$2.95	
	Actual output is 28.6NL/28V@ 200mA. Wall charger for several 18V B&D tools.												
15890	0-PD	Χ	30VDC	.4A	3' line cord/6.5mm/2.5mm Coaxial-Ctr. Neg	. 5'	BLK	4-1/2"X 2-5/8" X 2-3/16	" H/P /C2183A/9100-5195b		1.4	\$19.95	

9.6V RECHARGABLE



L: 2-1/4" W: 1-1/8" H: 1-7/8' WT: .32 9.6V@600mAH Ni/Cad Pack 18959-BT \$9.95

"AA" NI-CAD/NI-MH **CHARGER**

Input: 120 VAC 50/60Hz Output: 2.4VDC Specifications/Features: Wall plug unit for charging 2 or 4 "AA" rechargeable NI-CAD or NI-MH cells. UL/canada/usa listed.

L: 4-1/8" W: 1-1/2'

P/N: V-888N

16414-PS

D: 1-3/81 "AA" Battery Charger

RECHARGABLE BATTERY

12V

Power-Sonic 1220 Sealed Lead/Acid gell cell with .187 Quick connect terminals. For general purpose use in Alarms, Portable lighting. 20hr capacity rating. UL listed. W: 1-3/8" H: 2-9/16" WT: 2.8

\$9.95 18899-BT 12V@2.5A Gel Cell

> THOUSANDS MORE ITEMS ON MPJA.COM

RECHARGABLE **BATTERIES**



Sealed Lead/Acid gell cells with .187 Quick connect Jean-William Cells Will 187 duck Conflect terminals. For general purpose use in UPS systems, Alarms, Portable lighting. 20hr capacity rating. 17280: 2.8"L X 1.9" W X 4.2" H 14817: 6"L X 1.4" W X 3.9" H 14819: 6"L X 2.6" W X 3.9" H

STOCK #	DESC.	WT.	1EA	5+EA
17280-BT	6V@4A (NP4-6)	2	\$7.95	\$7.45
14817-BT	6V@8A (NP8-6)	4.5	\$18.95	\$17.95
14819-BT	12V@7A (NP7-12)	6	\$20.95	\$19.95





B

PLUG-IN TRANSFORMERS







SUPPLIES/TRANSFORMERS

AC OUTPUT TRANSFORMERS ALL PLUG TRANSFOMERS 120VAC/60HZ INPUT

STOCK	FIG.	VOLT5	AMPS	TERMINATION (ID X OD)	LEN	CLR.	DIM: L: X W: X D:	MANU/PART NUMBER	LISTED	WI	NEA.	12+EA
18556-PA	Α	12VAC	3A	2Pos Screw		Blk.	3-1/4"x 2-5/8" x 2-1/4"	AULT/306-4012-000E	UL	1.4	\$6.95	Call
12635-PA	В	12VAC	3A	2 Pos.Screw-LED Ind.	-	White	4" x 2-5/8" x 2-1/4"	MG Electronics	UŁ	1.6	\$7.95	\$7.45
14175-PA	В	16.5VAC	2.4A	2 Pos. Screw-LED Power Indicator	-	White	4" x 2-5/8" x 2-1/4"	MG Electronics	UL	1.6	\$7.95	\$7.45
18249-PA	В	16.5VAC	2.4A	2 Pos. Screw	~	White	4" x 2-5/8" x 2-1/4"	AMSECO XT-1640	UL	1.6	\$6.95	\$6.45
17560-PA	D	18VAC	1.1A	2 Pos. Screw	-	Beige	2-3/8" x 2-1/4" x 2"	AULT	UL	.8	\$3.95	Call
12637-PA	В	24VAC	1.6A	2 Pos. Screw-LED Ind.	-	White	4" x 2-5/8" x 2-1/4"	MG Electronics	UL	1.6	\$7.95	\$7.45
17561-PA	F	24VAC	1.66A	2Socket Molex Micro-Fit.	6	Black	3-1/4" x 2-3/4" x 2-1/8"	AULT/T57241667D020G	UL	1.8	\$6.95	Call



CHASSIS MOUNT TRANSFORMERS

SELECTING TRANSFORMERS

Volts & Current listed are nominal RMS. Open circuit and loaded values are different. Type of rectifier/filter circuit will effect secondary & output current and they can be very different. Full wave center tap choke input filter: Transformer secondary amps are .7 X required output amps. Full wave center tap cap input filter: Transformer secondary amps are 1.2 X required output amps. For Full wave bridge choke input filter: Transformer secondary amps are = to required output amps. For Full wave bridge cap input filter: Transformer secondary amps are 1.8 X required output amps.



STOCK #	STYLE	INPUT	OUTPUT VOLTS	AMPS	LEADS	DIMN. (L W H)	WT.	1EA .	12EA
The following	Transform	ers have a Center t	apped secondary allowing use	of Half wave, Fu	Ill wave center t	ap or Full wave bridge rectifier of	circuits.		
7838-TR	A	110/220VAC	12VAC (6V-0V-6V)	1A	6"	2-3/4" x 1-1/2" x 1-5/8"	.6	\$3.95	\$3.75
7839-TR	A	110/220VAC	12VAC (6V-0V-6V)	2A	6"	3-1/4" x 2" x 2"	1.3	\$5.95	\$5.75
7840-TR	A	110/220VAC	12VAC (6V-0V-6V)	4A	6"	4" x 2" x 2-1/4"	1.7	\$10.75	\$9.95
7841-TR	A	110/220VAC	18VAC (9V-0V-9V)	1A	6"	3" x 2" x 1-3/4"	.8	\$4.95	\$4.45
7842-TR	A	110/220VAC	18VAC (9V-0V-9V)	1.5A	6"	3-1/4" x 2" x 1-7/8"	1.1	\$5.49	\$4.95
7843-TR	A	110/220VAC	18VAC (9V-0V-9V)	2A	6"	3-1/4" x 2" x 1-7/8"	1.1	\$5.95	\$5.49
7844-TR	A	110/220VAC	24VAC (12V-0V-12V)	2A	6"	3-1/2" x 2-1/4" x 2"	1.4	\$7.95	\$7.45
7845-TR	A	110/220VAC	24VAC (12V-0V-12V)	4A	6"	3-7/8" x 2-1/2" x 2-1/4"	2.3	\$12.95	\$11.95
7846-TR	. В	110/220VAC	24VAC (12V-0V-12V)	10A	6"	3-3/4" x 3-5/8" x 3-3/8"	5.5	\$27.95	\$27.49

120/240VAC TRANSFORMER

MFG: TODD P/N: AT-106

Input: 240/120VAC60Hz Output: 240/120VAC@ 150VA (1.2A)

Frame mount Step Up/Down autotransformer. Unit can be wired for 120/240V input or output. .25" Quick connect for 240 terminals & .187" for 120V terminals.

W: 2-1/2" H: 2-1/2"

STOCK	DESC	TEA
18133-TR	240/120V Auto Transformer	\$12.95

FLAT CABLE NOISE FILTERS

Fair-Rite P/N #0443166651

Snap-On, ferrite filters. Clamps on ribbon cable up to 1.3" wide & up to .05"thick (24-26 conductor). Type 43 material blocks noise frequencies from 1MHz to 100MHz. Permeability=1000, impedance: 77 @ 25MHz 225 @ 100MHz

L: 1-1/4" W: 1-7/8" H: 5/8' WT: .18 \$2.49 \$2.75

12799-FL 26 Cond. Noise Filter



filters. Clamps on ribbon cable up to 1" wide & up to .05"thick (20 conductor). Type 43 material blocks noise frequencies from 1MHz to 100MHz. Permeability=1000, impedance: 77 @ 25MHz 225 @ 100MHz. Peel-n-stick mounting tape on back

WT: .05 H: .375" 15456-FL 20 Cond. Noise Filter

SNAP-ON NOISE FILTERS

TIA-TECH P/N W5 SRH ferrite snapon filters. Black Plastic case with type W5 split core material. Clamps around 3/8"cable and blocks noise. Frequencies from 25MHz to above 500MHz, impedance: 100+@25MHz/200+@100MHz

STOCK #	CABLE	DESC	WT	TEA
18466-FL	.25"	Clam Noise Filter	.07	\$0.99
18461-FL	.37"	Clam Noise Filter	.09	\$2.49
18462-FL	.5"	Clam Noise Filter	.18	\$1.25

SNAP-ON NOISE FILTERS

Fair-Rite P/N 0443167281 ferrite snapon filters. Plastic case with type 44 split core material. Clamps around cable up to .4in Dia. and blocks noise. Frequencies from 30MHz to500MHz. Permeability=500, impedance: 125@25MHz/210@100MHz

W: .94" H: .94 WT: .08 17842-FL .4" Clam Noise Filter \$2.49 \$1.95

TOROID CORE

1" O/D Uncoated toroid. Fair-Rite P/N 5975001301, High PermeabilityType 75 MnZn material. Flux Density: 4300 Gauss, Core Constant: 20, Inductance Factor: 3140nH, Effective Path Length: 6.2cm. For Broadband & Pulse transformers

T: .25 WT: .02 O/D: 1" I/D: .610"

17609-TC 1" Toroid Core \$1.25

SNAP-ON NOISE FILTERS



TIA-TECH P/N W5 SRH ferrite snap-on filters. Black Plastic case with type W5 split core material. Clamps around 3/8"cable and blocks noise. Frequencies from 25MHz to above 500MHz. impedance: 80+ @ 25MHz / 180+@100MHz

L: .75"	W: 1.12'	H: .88"	WT: .04
STOCK #	CABLE	DESC	1EA
18463-FL	.37"	Clam Noise Filter	\$1.95

RFI INLET FILTER



DELTA 10ME3, PC board/Panel mount, power inlet/RFI Filter. Rated: 10A @ 115/250VAC. Standard male 3 blade IEC cord connector. Right angle solder output terminals, UL/CSA /VDElisted.

18456-FL	6A Delta RFI	Module	\$3.95
STOCK #	DESC.	35-37/5-11	TEA
W: 2"	H: 1-1/32" Body	D: 1-5/8"	WT:.1

RFI INLET FILTER

DELTA 06DENG3B-R, Snap-in, power inlet/RFI Filter. Rated: 6A @ , 125/250VAC. Standard male 3 blade IEC cord connector. .250 quick connect output terminals, UL/CSA /VDElisted.

W: 1-1/4" D: 2-3/8" H: 1"

WT: .1 18056-FL 6A Delta RFI Module \$3.95

MPJA@MPJA.COM

TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764

360° VIEW @MPJA.COM

SOLDERING STATION

General purpose solder station for the hobbyist. Adjustable from 5 to 50 Watt (800° F max) heat output for repairing PC boards to soldering transformer terminals. Station provides on-off switch, knob to control wattage, built-in stand, tip cleaning sponge & 1/32' point tip. 115 VAC line.

Base L: 5-5/8" X W: 4-9/16" X T: 3-5/8" STOCK

15860-TL \$13.95 Solder Station \$4.95 15861-TL Replacement handle

REPLACEMENT TIPS

Tips for 15860-TL ONLY soldering station. Different

ory loo for var	***		
STOCK #8	DESC.	1EA	10+EA
15862-TL	1/32" Point Tip	\$1.95	\$1.75
15863-TL	1/16" Point Tip	\$1.95	\$1.75
15864-TL	1/8" Flat Tip	\$1.95	\$1.75
15865-TL	1/8" Chisel Tip	\$1.95	\$1.75

HOT AIR REWORK **STATION**



Hot air repair/rework station for SMT devices. Features: a fast heating ceramic heater, internal air supply, stable temperature, comfort grip handle, interchangeable hot air nozzles for PLCC/SOP/etc. devices. Adjustable temperature & air flow. Temperature range: 150 deg.-500deg. "C'

Station Includes 4 nozzles:

16123-TL QFP 10 X 10 (mm),

16124-TL QFP 14 X 14 (mm),

16122-TL Single 2.5mm Dia.,

16128-TL Single 4mm Dia.

Repair Parts & Other Nozzles Available

3121-TL	SMD Rework Station	\$99.95	
TOCK #	DESC.	1EA	

WT: 9

REPLACEMENT REWORK STATION PARTS

See soldertoolsdepot.com for pictures of replacement parts for 16121-TL

STOCK #	DESC.	1EA
17215-TL	Replacement Heater	\$4.95
17216-TL	Replacement Wide Pickup Wire	\$1.49
17217-TL	Replacement Narrow Pickup	\$1.49
17218-TL	Replacement Pickup Handle	\$1.49



16

HOT AIR STATION NOZZLES

VISIT mpja.com for listing and pictures of QFP/SOP nozzles Tips for 16121-TL. Different styles for various uses.

4 4	VV I :	.2
STOCK #	DESC.	1EA
16122-TL	2.5mm Dia. Nozzle	\$4.95
16123-TL	10mm sq. QFP Nozzle	\$6.95
16124-TL	15mm sq. QFP Nozzle	\$6.95
16125-TL	19 mm sq. QFP Nozzle	\$6.95
16126-TL	15mm X 21mm QFP Nozzle	\$6.95
16127-TL	29mm sq. QFP Nozzle	\$7.95
16128-TL	4.4mm Dia. Nozzle	\$4.95
16129-TL	4.8 X 10mm SOP Nozzle	\$6.95
16130-TL	5.7 X 15mm SOP Nozzle	\$6.95
16131-TL	7.2 X 16mm SOP Nozzle	\$6.95
16132-TL	7.2 X 19mm SOP Nozzle	\$6.95

smart phone fo www.soldertooldepot.com



TEMPERATURE CONTROLLED SOLDER STATION

ZD Electronic Tools ZD-929C Temperature controlled soldering station with LED display. Heat sensor located near the tip for fast re sponse and +-10° "F" control. Rated at 48Watts, 24Vac handle. Temperature range: 320° "F" to 800° "F". Isolated tip, fused line. 117 VAC.

Extra tips are available for general replacement or special Base L: 6-3/4" X W: 4-3/4" X T: 3-9/16" WT: 4.8

STOCK #	DESC.	1EA	5+EA
15845-TL	LED Solder Station	\$46.95	\$39.95
15846-TL	Replacement Handle	\$6.95	\$6.49

REPLACEMENT **TIPS**

Tips for 15845-TL ONLY temperature controlled soldering station. Different styles for various uses.

ı	STOCK #	DESC.	1EA	10+EA
	15849-TL	.02" Round Tip/std. Shank	\$1.95	\$1.75
	15850-TL	.02" Point Tip/thin Shank	\$1.95	\$1.75
	15851-TL	.12" Conical Tip/std. Shank	\$1.95	\$1.75
	15852-TL	.08" Chisel Tip/std. Shank	\$1.95	\$1.75
	15853-TL	.02" Round Tip/med. Shank	\$1.95	\$1.75

SMD HOT TWEEZER **ADAPTER**

48W, Hot tweezer adapter replaces the soldering iron handle/heater assembly on our 15845-TL station. Removes surface mounted components up to 2.5mm with tip supplied. Other size tips are available.

WT: 5 DESC 15847-TL Hot Tweezers Adapter \$12.95 \$11.49

SMD TWEEZER TIP SET

Set of 7 different size tips for SMD tweezer handle 15847-TL. One pair of 2.5mm, 3.5mm, 5mm, 10mm, 15mm, 20mm and 30mm wide tips.

		1	WT: .1
STOCK #	DESC.	1EA	5+EA
15848-TL	Hot Tweezer Tip Set	\$5.95	\$5.49

MINI SOLDER STATION

8W mini temperature controlled soldering station with un-grounded tip and comfort grip handle. Easy off connector for easy replacement of handle/heater. Adjustable Temperature range: 100 deg. "C" to 450 deg. "C" (212-842 "F "). Fused line. 117 VAC L: 4 W: 3" O/A H: 1-7/84" WT: 1.5

16924-TL 8W Mini Station \$12.95 \$11.95

30W SOLDERING

Light weight, 30 watt pencil iron with pointed Tip. Inchudes simple stand & Spare Tip. 4ft, 3 wire line cord. Tip is grounded. Overall length of iron is 9". Ideal for general shop use. CE listed L: 8-1/4" WT: .45

17518-TL 30W Solder Iron/Stand

LEAD FREE SOLDER STATION

MFG: MUELLER P/N: ST-0 Input: 115 VAC 50/60Hz

Max. Power: 60W From the Company that gave us the Alligator Clip; another innovation in soldering. Unit features a variable temperature soldering iron & stand with Fume extractor fan/filter. Ideal for solder touch-up on boards, tinning wires & leads

Specifications/Features:
Temp. range: Adj. ~350-895"F"/175-480"C"
Fan: 4.5W/Active Carbon Filter
Fan ON/OFF Control

Cords: 2m for Power & 1m for Iron

D: 14-1/2	W: 0-1/2	H: 13	Ship WI: 10
STOCK #	1	DESC.	TEA
18168-TL	Muelle	r Lead Free St	ation \$199.95

FIXTURE FREE SOLDER STATION

MFG: MUELLER P/N: ST-1 Input: 115 VAC 50/60Hz Max. Power: 75W

From the Company that gave us the Alligator Clip; the latest in solder productivity. Self contained unit features a variable temperature soldering head with a

variable speed solder feed & Fume extractor fan/filter. Ideal for solder touch-up on boards, tinning wires & leads etc. No fixturing required; operator holds board under head while controlling the solder feed by the foot switch. Specifications/Features:

Temp. range: Adj. ~350-895"F"/175-480"C" Stability: +-5 "C"/+-9 "F" Solder Dia: .024Min/.063 Max (Leaded or Lead free)

Solder Feed: Adj, 0-4"/Sec. Solder Span: Adj. 0-1Sec.

Solder Feed Time: Continuous: As long as foot

switch depressed Pulse: each depression of foot switch as set by "Span" control.

Solder Head Adj.: +15 to -45 degrees from Vertical Left 54 to Right 54 degrees from center Height: 7" min to 10" Max (Head Vertical)

Cords: 2m for Power & Footswitch Includes: Tips, Solder, Wrench

D: 14-1/2" W: 6-1/2" H: 13" Ship WT: 11 \$249.00 18167-TL **Mueller Solder Station**

SOLDERING **IRON**



Light weight, 30 watt pencil iron with pointed tip. 4ft, 2 wire line cord. Overall length of iron is 8-1/4". Ideal for general shop use. Available UL listed

L: 8-1/2 WT: .6 Non UL Solder Iron 3027-TL \$2 95 \$1.95 **UL Solder Iron** \$4.95 3028-TL \$4.49

60W SOLDERING IRON

Light weight, 60 watt pencil iron with pointed Tip. Includes simple stand. 4ft, 2 wire line cord. Ideal for general shop use. Includes simple stand.

L: 9-1/2"			WT: .4
STOCK #		DESC.	
18339-TI	60W	Solder Iron/Stand	\$6.95



DESOLDERING IRON

Light weight, 40 watt desoldering iron. Built in sol-4ft, 3 wire line cord. Overall length of iron is 10-1/2". Ideal for general shop use. 115VAC/40W L: 10-1/2"

WT: .6

STOCK #	DESC.	1EA	10+EA
16922-TL	Desoldering Iron	\$6.95	\$5.95
16923-TL	Replacement Tip	\$1.95	\$1.75

ADJUSTABLE SOLDERING IRON



Clear handle, Light weight, adjustable 50 watt pencil iron with a pointed tip. Temp. Range: 200-450 "C". Red LED indicates heater operation. 4ft, 3 wire line cord. Tip is grounded. Overall length of iron is 9". Ideal for general shop use. CE listed.

L: 9-5/6		G. : I W
STOCK #	DESC.	1EA
17517-TL 17530-TL	Adj. 50W Solder Iron Replacement TIP	\$12.95 \$1.95

LIGHTED **IRON**



with a pointed tip and a White LED that illuminates the tip. 4ft, 3 wire line cord. Tip is grounded. Overall length of iron is 9". Ideal for general shop use. CE listed.

L: 9		WT: .4
STOCK I	DESC.	1EA
17516-TL	Lighted Solder Iron	\$5.95
17531-TL	Replacement TIP	\$1.75

ANTISTATIC SOLDER SUCKER



Antistatic solder removal tool with plastic body and teflon tip. Spring loaded tool with push button release, uses suction to remove solder from circuit board components.

L: 13-1/2"	D : 1-1/4"		WT: .25
STOCK #	DESC	168	50+EA
17220-TL	Solder Sucker	\$5.95	\$4.95
17221-TL	Replacement Tip	\$1.95	\$1.49


ANTISTATIC TIP SOLDER SUCKER



Solder removal tool with Plastic body and Antistatic tip. Spring loaded tool with push button release. L: 11-1/4" **D:** 15/16"

ma 1 1 17 T	D1 10/10		*****
STOCK #	DESC.	1EA	5+EA
15859-TL 15858-TL	Solder Sucker Replacement Tip	\$6.95 \$2.35	\$6.49 \$1.95

MINI SOLDER SUCKER



Plastic tip and aluminum body. Spring loaded with push button release, with replaceable tip.

L: /-//8"	D: 7/8"	,	W 1: .2
STOCK #	DESC.	TEA	5+EA
0041-TL 9178-TL	Mini Solder Sucker Mini Replacement Tip	\$3.95 \$0.69	\$2.95 \$0.59

THOUSANDS MORE ITEMS ON MPJA.COM

ADJUSTABLE ARM SMOKE ABSORBER

Smoke absorber with activated carbon filter removes fumes and smoke from work area. 2 section cantilevered metal arms with 3 joints allows for multi-positions. ESD safe plastic with metal stand. 115VAC fan with 5ft. cord. Includes 2 spare filters

(filters should be changed after 30 days of use), 2 fan exhaust deflectors. +- 85deg. Arm swing.

H: adj 0-16"	WT.: 6	
STOCK #	DESC.	IEA .
17529-TL	Smoke Absorber	\$39.95
15167-TL	Replacement Carbon Filters	\$6.50

360° VIEW

BENCHTOP SMOKE @MPJA.COM ABSORBER

Benchtop smoke absorber with activated carbon filter removes fumes and smoke from work area. safe plastic with metal stand. 115VAC fan with 5ft. cord. Includes 2 filters (filters should be changed after 30 days of use).

H: 10"	W: /-3/4"	D: 4-1/4"	W1.: 3.1
STOCK #		DESC.	1EA
15166-T	L Sm	oke Absorber	\$27.99
15167-T	Renlace	ment Carbon Filt	are \$6.50

SOLDERING IRON STAND

Metal stand for pencil irons. Spring type, 5" X 3-1/4"base with wiping sponge High temperature thermo-plastic collar to

L: 5"	W: 3-1/4"	W	T: .2
STOCK #	DESC.	1EA	5+EA
4455-TL	Solder Iron Stand	\$4.50	\$3.95

SOLDER BRAID

When placed on a solder connection and heated; this rosin coated copper braid will draw up the melted solder. 1.5m (4.9ft) on a plastic spool. Ideal

for PC board repair, field service, etc.	. *************************************	
L: 1.5m	V	VT: .2
STOCK # DESC.	1EA	- de
2648-TL 2mm Wide Solder Wick	\$0.65	\$0.59
16433-TL 4mm WideSolder Wick	\$0.75	\$0.69

LOW LEAD SOLDER

93Sn/7Pb alloy Solidus: 183 deg. "C" Liquidus: 220 deg. "C" 1mm/.039" Dia. ~18AWG

Mildly Activated core For general applications requiring slightly higher temperature range than standard 60/40 alloy

190gm (Appro	ox 110ft.)	
		WT: .5
STOCK #	DESC.	1-4
17718-TL	Low Lead Wire Solder	\$9.99

LEAD FREE SOLDER

NEW YORK SOLDER "Pure Bond" Sn/Cu alloy Cu: 2.8-3.2% Sn: remainder Melt Point: 227-250deg. "C" .125" Dia. (1/8")

For sheet metal joining, plumbing, etc. WT: .54 \$14.95 8oz. Wire Lead Free Solder

SOLDERING EQUIPMENT

HANDY TUBE SOLDER

.04in Dia. 63/37 Tin/Lead, rosin core solder in plasitc Handy Tube. For all electronic uses. WT: .044/.057

STOCK #	DESC)EA
17462-TL	.6oz (8ft+)Tube 63/37 Solder	\$1.25

6-1/2" HARDENED CUTTERS



6-1/2 in, forged high carbon Steel dikes with Cushioned grips. Hardened to 55-60 HRC per Brace Light enring & Stainless stool

18912-TL	6" Hardened Cutter	\$2.95
Mile and Bright and Artist Control of	Walling to the Control of the Contro	AEA
STOCK	DESC	TARREST PROPERTY.
L: 6-1/2"		WT: .34
or mand copp	ber, brass, Light spring & Gran	ness steet,

PC BOARD FLUSH CUTTER

Features: Spring Loaded, cutters with cushion grip handles Use: Trimming PC Board Leads.

.: 5"		WT: .17
STOCK #	DESC	1EA
16761-TL	5in. Flush Cutter	\$1.75

4" DIAGONAL **CUTTERS**

Drop forged, 4" Rounded jaw Diagonal Cutter with cushioned grips and leaf springs. For

eads.	copper	wire	and	component		
: 4-1/4"					WT:	.16

uun v				150
77-TL	4" Mini	Diagonal	Cutter	\$1.95

MINI CUTTERS

181

Mini Diagonial cutters with cushioned dipped vinyl grips, Box Hinge and leaf springs General purpose electrical/craft use

STOCK # DESC.	1EA
17768-TL Box Joint Dikes	\$0.99

5" CUTTERS

Features: Forged, back milled, flush cutters with Standard cutting angle cushion grip handles & spring return

ı	L: 5-1/4"			WT: .3
	STOCK	Marie Maria	DESC	16.
	17877-TL	5in.	Flush Cutter	\$5.95

FLUSH CUTTERS

Spring loaded Flush Cutters Feature: Hardened to HRC 58. cushion grip handles, cut copper wire up to 1mm Use: Trimming PC Board Le L: 5"



STOUR W			OD OF
8334-TL	5in. Flush Cu	utter	\$2.95

TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764

16730-TL

SOLDERING STATIONS

Visit www.mpja.com for our Complete Products Lines.

STAINLESS DIAGONAL **CUTTERS**



Corrosion resistant Stainless Steel Cushioned dipped vinyl grips General purpose electrical/craft use L: 6-1/4

WT: .4 17467-TL 6" Stainless Diagonal Cutter


HARDENED SIDE CUTTERS



Hardened Heavy duty carbon Steel, Cushioned dipped vinyl grips. Hardened to 55-58 HRC For hard copper, Brass, Light spring & Stainless steel, WT: .52 L: 7

18914-TL Hardened 7in. Cutter \$4.50

8" DIAGONAL **CUTTERS**



L: 8" WT: .58 18913-TL 8" Diagonal Cutter \$2.60

3PCS. MICRO PLIERS

Dropped forged, micro pliers with leaf springs & cushioned grips. Includes: Side cutter, Smooth jaw long Nose & Round Nose. For Electronic work.

L: 3 WT: .22 17540-TL 3Pcs. Micro Pliers \$2.95

4 1/2" CLOSED HANDLE FLUSH CUTTER

Features: Spring Loaded, cutters with hard plastic handles Use: Trimming PC Board Leads

L: 4-7/4" WT: .1 **Closed Handle Cutter** 16747-TI

6" CUTTER STRIPPER

Features: Forged cutters with cushion grip handles and 2 holes for wire stripping. Ergonomic cutting angle. Not spring loaded.

WT: .4 L: 6-1/4"

STOCK #	DESC.	1EA
16749-TL	6in. Cutter/Stripper	\$3.95


STAINLESS CUTTERS

16

Features: Forged stainless steel flush cutters with cushion grip handles & spring return. For copper & aluminum.

L: 4-7/8' WT: .22


Stainless Flush Cutter 17882-TL



MINI PLIERS

Chrome plated, 5in. mini pliers with leaf springs & cushioned dipped vinyl grips. For fine Jewerly, or Electronic work

L: 5"	WT: .1			T: .1
STOCK #		FIG. DESC.	1EA	10+EA
4980-TL	Α	Bent Nose Pliers	\$2.95	\$2.49
4982-TL	C	Needle Nose Pliers	\$2.95	\$2.49
8090-TL	D	Round Nose Pliers	\$2.95	\$2.49
8091-TL	Ε	Diagonal Cutters	\$2.95	\$2.49
8092-TL	F	Flat Nose Pliers	\$2.95	\$2.49



Nickel plated, dropped forged, long reach pliers with leaf springs & cushioned dipped vinyl grips. For fine Jewelry or Electronic work. Bulk packed.

L. 5-5/6 to	1 - 17	7		V 1
STOCK #	FIG.	DESC.	1EA	10+EA
15385-TL	Α	Diagonal Cutters	\$2.95	\$2.49
15386-TL	В	Serrated Nose Pliers	\$2.95	\$2.49
15387-TL	C	Bent Nose Pliers	\$2.95	\$2.49
15388-TL	D	Long Nose Pliers	\$2.95	\$2.49
15389-TL	E	Flat Nose Pliers	\$2.95	\$2.49
15390-TL	F	End Cutters	\$2.95	\$2.49
13030-1L		Life Outlers	Ψ2.50	ΦZ.43



Dropped forged, pliers with leaf springs & cushioned dipped vinyl grips. For cutting or bending soft copper wire and component leads. For fine Jewelry or Electronic work

L: 4" to 5-7	/8"		W	/T: .15
STOCK #	FIG.	DESC.	1EA	10+EA
16498-TL	A	Diagonal Cutter	\$2.35	\$2.25
17013-TL	В	Long Nose Pliers	\$1.95	\$1.75
17014-TL	C	Needle Nose Pliers	\$1.95	\$1.75
17015-TL	D	Bent Nose Pliers	\$1.95	\$1.75

HEAVY DUTY SIDE CUTTERS

Cushioned dipped vinyl grips

General purpose electrical/craft use WT: .6 6" H/D Diagonal Cutter 17915-TL



Dropped forged, pliers with leaf springs & cushioned dipped vinyl grips. For fine Jewelry or Electronic work

L: 4" to 6"			WT: .15	
STOCK #	FIG.	DESC.	1EA	10+EA
17111-TL	A	Diagonal Cutters	\$1.95	\$1.75
17113-TL	C	Bent Nose Pliers	\$1.95	\$1.75
17114-TL	D	Long Nose Pliers	\$1.95	\$1.75
17115-TL	E	Combination Pliers	\$1.95	\$1.75
17116-TL	F	End Cutter	\$1.95	\$1.75

4.5" MINI PLIERS



Dropped forged, Box Joint pliers with leaf springs & paddedl grips. For fine Jewelry or Electronic work. L: 4-1/8" to 5-3/4"

STOCK #	FK	DESC.	1EA
17658-TL	В	Smooth Jaw Bent Nose Pliers	\$1.75
17659-TL	С	Serrated Jaw Long Nose Pliers	\$1.75
17660-TL	D	End Nipper	\$1.75



Nickel plated, dropped forged, pliers with leaf springs & cushioned dipped vinyl grips. For fine Jewelry or lectronic

L: 5-1/2"	WT: .15		
STOCK	DESC.	TEA	TÜAEA
15398-TL	Concave Nose Pliers	\$1.95	\$1.75
5 A			



Dropped forged, pliers with leaf springs & cushioned dipped vinyl grips. For fine Jewelry or Electronic work. L: 4" to 5-7/8"

STOCK	FIG.	DESC.	TEA	TOHER
15398-TL	D	Concave Nose Pliers	\$1.95	\$1.75
15401-TL	E	End Cutter	\$1.95	\$1.75

HARDENED **6IN. CUTTERS**

18930-TL

D


6 in, long handle, high carbon steel dikes with Cushioned grips and black anodized finish. Hardened to a min. 42 HRC. Depth of cut adjustment screw. For

hard copper, Brass, Light spring & Stainless steel L: 6' WT: .24 6" Long Handle Cutter \$5.95



Corrosion resistant Stainless Steel Cushioned dipped vinyl grips General purpose electrical/craft use

L: 7-1/4 WT: .6 7" S/S Diagonal Cutter \$3.50 17469-TL



Corrosion resistant Stainless Steel Cushioned dipped vinyl grips Side Cutter & serrated nose General purpose industrial/hobby/craft use

L: 6-1/2' WT: 4 17468-TL 6" Stainless Long Nose \$2.50

8" STAINLESS LONG NOSE PLIERS

Corrosion resistant Stainless Steel Cushioned dipped vinvl grips Side Cutter & serrated nose General purpose industrial/hobby/craft use L: 8

17470-TL 8" Stainless Long Nose \$3.50

WT: .6

5-1/2" LONG NOSE PLIERS

Mini long nose pliers with ergonomic formed cushioned dipped vinyl grips, smooth nose NO Cutter.

General purpose industrial/hobby/craft use L: 5-1/2

WT: 17 17908-TL Mini Long Nose Pliers \$1.95

STAINLESS DIAGONAL CUTTERS

Corrosion resistant Stainless Steel Cushioned dipped vinyl grips General purpose electrical/craft use

WT: .25 17494-TL 6" Stainless Diagonal Cutter \$3.50

STAINLESS BENT NOSE


Corrosion resistant stainless steel. Last 1/2" of nose bent 90deg. Cushioned dipped vinyl grips, leaf springs, General purpose electrical/craft use

WT: .3 L: 6-1/2 \$3.50 **Stainless Bentnose Pliers** 17495-TL

> SIGN-UP FOR OUR EMAIL SPECIALS ON MPJA.COM

CABLE CUTTER

11" Heavy Cable Cutter Features: Ratchet Handle with Release, Cushioned Grips. Soft Copper & Alum. Wire to 1.75" Dia.



CABLE CUTTER

8" Heavy duty cutter for cutting soft copper wire up to 2/0 or communication cable up to 100 pairs. Not for hard drawn copper wire, steel core or steel supported coax cable

12571-TL Heavy Cable Cutter \$9.95 \$10.50

ADJUSTABLE CUTTER **STRIPPERS**

Adjustable Wire Cutter/Stripper Features: Spring Loaded, Cushioned Grips, Screwdriver Adjustable. Handle color may vary. Adj for AWG 10-30 Wire

L: 5-1/2" WT: .2 11714-TL Cutter/Stripper \$3.35

DB CONNECTOR PIN CRIMP TOOL

Multi Purpose Crimp Tool Features: Cushioned Grips. Use: Crimping Open (stamped) D-Sub Pins, Ternimal Lugs. For 14-26 AWG Wire, NOTE: Will not crimp High Density DB Pins

WT: .6 11763-TL **Multi Crimp Tool** \$7.95

DB CRIMP PIN EXTRACTOR.

Tool used to extract crimp pins from insertion type DB connectors. Double ended For Pin & Socket type connectors (16251-PL - 16262-PL)

		44 44 100
STOCK #	DESC.	1EA
17124-TL	DB-Crimp Pin Extractor	\$4.75

TOOLED PIN

CRIMPER

Crimp tool for machined type insert Contacts. Features: Spring Loaded, 4 Indent Crimp Pattern. For 20-26AWG wire, D-Sub, MS Barrel Type Contacts.

WT: .6 15534-TL Machined Pin Crimper \$34.95 \$32.95

GENERAL PURPOSE **CRIMPER**

All in One Crimp Tool Features: Cushioned Grips Cuts 4-40, 6,8,10-32 & 10-24 bolts, Wire Cutter, Crimps Ins. & Non Ins. Terminals

WT: .6 11764-TL All-N-One Tool



PUNCH DOWN TOOL

HT110B Punchdown Tool Handle with Type 110 blade Features: Hi-Lo Spring Loaded Impact, Blade Storage. Use: Tool for solid conductor wire on Type 110 blocks. Reversible blade for looping or cutoff.

STOCK #	DESC.	1EA
18262-TL	110Punch Down Tool	\$9.95

MOD PLUG CRIMPER

Heavy Duty MOD Plug Crimp Too


WT: .8

Features: Cushioned Grips, Ratchet Action, 2 Cavity, Cutter/stripper for Flat & Round Cable Crimps RJ-11/12 & 45 Plugs.

11751-TL **RJ Plug Crimper** \$25.99 \$24.95

HEMOSTATS

Stainless steel multi-purpose hemostats. Serrated tip, clip lock, ideal for holding small compo-



MINI PLIERS

Drop forged, 4-1/4" overall mini Slip-Joint (AKA "Gas") pliers with 7/8" long serrated nose & cushion grip handles.

L: 4-1/4' WT: .15 18281-TL \$1.95 Mini Slip-Joint Pliers

60 cc SYRINGE

Medical Plastic syringe designed to "Irrigate" wounds, provide food for feeding tubes, nurse animals etc. Holds around 2oz (60cc). Transparent plastic with both oz. and cc graduations.

L: 8' WT: .08 18748-MI 60cc Syringe \$0.95

3 mL SYRINGE

Medical Plastic 3mL/CC syringe. Uses standard Luer Lock needles (not Supplied). Transparent plastic with mL graduations. Not sterile.

L: 3-5/8 WT: .01 3mL Syringe \$0.20 18749-MI

20 mL **SYRINGE**

Medical Plastic 20mL/CC syringe. Uses standard Luer Lock needles (not Supplied). Transparent plastic with mL

graduations. Not sterile. WT: .04 L: 5"

18905-MI 20mL Syringe \$0.50

FAX 561-844-8764 TECH. & INFO: CALL 561-848-8236

MPJA@MPJA.COM

CHINESE ARMY HAMMER

Well not really Army but a Stainless Steel Multi tool that Includes: Claw Hammer, Combo Pliers with Wire Cutter, Large Knife Blade, Flat Blade & Phillips Screwdrivers, Saw, Awl, Bottle/ can opener, File & Fishscaler. Woven belt sheath

L: 6-1/2" W: 3-3/8" T: 7/8" WT: 1.1

\$7.95 17543-TL Multi-Tool with Hammer

SUCTION BASE **TABLE VISE**

Light duty table vise with aluminum body, steel screw, rails and jaw inserts. 2-3/4"wide jaw opens 2-3/4". removable rubber jaw covers. Rotates 360deg. Tilts 45deg. Non marring suction base.

WT: 3 18578-TL Vacuum Base Vise \$19.95

STEEL TABLE VISE

Cast steel table vise with smooth jaw 1-1/8" jaw width 3/4" jaw opening

7/8" max table thickness Fixed head.

H: 2" above Table top WT: .8 17890-TL 1-1/8" Steel Table Vise

60MM MINI TABLE VISE

Cast aluminum table vise. 2-3/8" (60mm) jaw width 1-1/2" jaw opening.

" max table thickness Fixed head



WT: .94

\$5.95 17500-TL 60mm Aluminum Table Vise

TABLE VISE WITH DRILL CLAMP

Cast aluminum, 3 In. table vise with adapter, designed to hold a

360 deg. swivel, 90 deg. tilt, 2-1/8" max table thickness, 3-1/4" max jaw opening, Padded Jaw, Rubber pad for top of table. Interchangable Drill clamp holds up to 1-1/12" Dia. Drill throat.

WT:2,42 \$15.95 17498-TL **Table Visewith Drill Clamp**

ADJUSTABLE ANGLE TABLE VISE

Light/medium duty aluminum table vise has rubber jaw grips & allow +-45° tilt from vertical & 360° swivel. 80mm jaw with swivel ball piviot. Clamps to table/bench up to 2" thick. 2" max jaw opening.

H: 10" O/A W: 5-7/8"

Adj. Table Vise \$14.95 \$12.95 11240-TL



ELECTROFORCE #89605, Tie installation tool tightens & cuts nylon ties in one operation. For ties up to .19in. wide. Adjustment knob selects 8 tension settings

H: 5-3/4" WT: .7 1:6-3/4" T: 11 \$4.95 18353-TL Tie Install Tool

STAPLE GUN

FACTORY REFERB TO ORIG. SPECS ARROW T2025 tacker. Features EZ-Squeeze handle, adjustable height guide, Flat or round crown staples. Uses Arrow #25932, 256, 257& 259 Round crown for wire; #205, 206 & 208 Flat crown for Crafts, & upholstery.

WT: 1.6 \$16.95 18782-TL T2025 Staple Gun

GIANT THERMOMETER

MFG: WIKA P/N: TI.50 series

RANGE: -20 to +120° F (2deg. Subd.)

Material: 304 Stainless

Features: 5in. Dia. Bi-metalic tank thermometer with 12in. Stem & 1/2" NPT fitting, 1% accuracy.

18528-MI **Giant Thermometer** \$19.95

LONG REACH SCREWDRIVER SETS

Quality minature screwdriver set contain 3 phillips & 3 flat blade. Ideal for those hard to reach places in VCR, Monitors etc. Hardened carbon steel blades

WT: .3 \$3.49 8083-TL Long Screwdrivers \$4.95

16PC. HOBBY KNIFE SET



Mini precision hobby knife with 13 assorted steel blades 3 handles with 2 jaw blade lock. Large handle: 3/4" dia X 4-1/4" Aluminum body with

plastic grip

Medium handle: 3/8" dia. X 4-1/4" Aluminum. Small handle: 1/4' Aluminum.

For matte cutting, wood , plastic & leather carving, scoring & trimming. Includes plastic hinged storage box with magnetic strip for holding blades.

WT: .31 \$2.95 \$2.49 8246-TL 16pc. Hobby Knife

REVERSABLE **SCREWDRIVER**

Handy, reversable blade screwdriver. #1 Philips on one end and a 3/16in. flatblade on other. Three handle accent colors, yellow, orange or blue but sorry no choice.

L: 4-3/4 WT: .06 18576-TL Reversable Driver \$1.00

DUAL RANGE **HEAT GUN**

Heat Gun with two heat ranges: 800 Watt or 1500 Watt, With control knob to vary the temperature. Low range 50-200° C, high range 200-500° C. 5ft. 3 wire power cord. 115VAC power. Includes concentrator nozzle attachment. Ideal for heatshrink tubing, paint stripping, plastic fabrication.

W: 2-7/8" H: 8-1/4" **WT:** 2 L: 10-1/4" \$18.95 \$17.95 15857-TL Heat Gun

NEEDLE FILES

10 piece assortment of hobby needle files in a plastic pouch, you get round, triangular, square and flat files, with various smooth and cutting sides. Work length = 7cm (2.5").

L: 5-1/2"	WT: .3		
STOCK #	DESC.	1EA	5+EA
2614-TL	10Pc. Needle Files	\$4.50	\$3.95

NEEDLE FILES

10 piece assortment of hobby needle files in a plastic pouch. Includes round, triangular, square, flat files and more with various smooth and cutting sides each with plastic handle. Work length = 7 cm (2.5")

L: 5-1/2" WT: .3 17535-TL 10Pc. Set Needle Files \$2.95

NEEDLE FILES

12piece assortment of Heat treated HRC60-65 hobby needle files with plastic handles. cludes 2ea. round, 1/2 round, triangular, square, & flat files. Work length = 7cm (2.5").

L: 5-3/4" **WT:** .5 12Pc. Needle Files \$7.95 17594-TL



MINI LOCK GRIP PLIERS

Drop forged jaws, 4-3/4" over-all with 1-1/4" long serrated nose, Adjustable locking grip with release.

L: 4-3/4" WT: .23 16701-TL Mini Vise Type Pliers \$2.65

MINI LOCK GRIP PLIERS



Drop forged jaws, 4" overall with 5/8" long serrated jaw designed for gripping circular objects. Adjustable locking grip with release.

WT: .3 16734-TL Mini Vise Type Pliers

CALL 800-652-6733

"TEE" HANDLE **HEX KEYS**

Plastic "T" handles with Chrome Vanadium steel blades, order S.A.E. or Metric

-SAE--Metric 3/32" 5/321 5/16" 2mm 4.5mm 7/64" 3/16" 3/81 2.5mm 5mm 1/8" 7/32 3_{mm} 5.5mm 4mm 6mm

WT: 2.8

8mm

10mm

5676-TL SAE Hex Key Wrenches \$6.95 5677-TL Metric Hex Key Wrenches \$9.95 \$9.65

6" DIAL CALIPER

6" Dial caliper, graduated in .001in. for both inside & outside measurements. Made from stainless steel. Adjustable & lockable "0" set. Ideal for us who have problem reading those lines on other calipers. Includes padded, hard plastic case.

WT: .78

WT: .7

16700-TL 6" Dial Calipers \$17.95



Digital caliper features selctable Inch or mm range. Hardened stainless steel with plastic cased electronics. For ID or OD measurments. "Zero" button for resetting or setting offsets. 6in/ 150mm Max

.0005"/.01mm accuracy/min. reading. Requires a 357A Button cell (Supplied).

Stores in foam lined plastic case.

L: 9-1/4

17471-TL 6" S/S Digital Calipers \$12.95

SAE MICROMETER

Machinist, all steel, 0-1"/.001" Caliper micrometer. Handy wood storage case with latching lid.

L: 4-3/8" WT: .62 \$12.95 18577-TL 1" Micrometer/Case

SAFETY GLASSES

7949-TL

Medium duty, ANSI (Z87.1) approved plastic safety glasses. Adjustable temple length, Do not fit over all corrective lens glasses. Holes for neck cord (not included).

State Address April 1997

18340-TL **ANSI Safety Glasses** \$1.95

FLEXIBLE GRABBER

Long reach grabber. 18" flexible shaft with spring handle. Push handle and 4 spring steel "fingers" extend out other end. Use to retrieve small parts dropped where you can't put your arm.

L: 23' WT: .12 \$0.99

Flex Grabber

PLASTIC HANDLE BRUSH SET

Industrial cleaning brush set has 1 each of the following brushes: brass bristle; Nylon bristle; & Stain less steel bristle. Each 7" plastic handle brush has 1/2" long bristles in a 1-3/8" X 5/16" pattern.

WT: .18

7467-TL 3pc Brush Set \$1.95 \$1.59

PLASTIC HANDLE UTILITY BRUSHES

Curved handle cleaning brush with 3/4" long Brass bristles. Handle color varies.

W: 7/8" WT: .1 16847-TL **Brass Utility Brush** \$1.20

PLASTIC HANDLE **BRUSH SET**

Industrial cleaning brush set has 1 each of the following brushes:

Brass bristle; Nylon bristle; & Stainless steel bristle. Each brush has 1/2" long bristles in a 1-1/4" X 5/16" pattern. Shaped handle for comfort & leverage

L: 6-3/4" WT: .24 \$1.95 3pc. Brush Set 18915-TL

5PCS. PRECISION **TAMPER PROOF** DRIVERS

Quality miniature tamper proof Star driver sets contain T-6, T-7, T-8, T-9 & T-10 sizes. Handles have free spinning finger caps. Plastic handles with Nickel-chrome molybdenum steel bits. Includes plastic storage case. L: 4-3/8" WT: .18

12093-TL 5Pc. T/P Star Drivers \$6.95 \$5.95

MINI SCREWDRIVERS

Miniature screwdriver sets contain 2 Phillips(#0 & #1), 4 flat blade (1.4,2.0,2.4 & 3mm) in a plastic case. Free spinning finger caps. Ideal for glasses, watches, or electronics.



\$2.49 \$1.98

Mini Screwdriver Set

PRUNING SHEARS

General purpose prunning shears feature precision ground stainless steel blades, spring loaded plastic handles and locking arm. 3/8" max cutting Dia. 1-3/8" cutting length.

L: 8" O/A WT: .26

17378-TL 8" Prunning Shears \$1,69

CRAFT SCISSORS

General purpose craft scissors feature precision ground, hardened stainless steel blades with one blade serrated, plastic handles. Pointed nose. 1" cutting length.

L: 4-1/4" WT: .07 4-1/4" Craft Scissors 17656-TL

HEX **BIT DRIVER**

FOR A LIMITED TIME RECIEVE A FREE 4 PIECE BIT SET!

While supplies last.



Cordless driver for 1/4" (6.35mm) HEX shaft Bits. 130RPM, Uses 4 "AA" cells (not supplied) L: 8-1/4" DIA: 1-5/8"

DIA: 1-5/8 WT: .55 18706-TL **HEX Bit Driver** \$8.95

CORDLESS ROTARY TOOL

9.6V Cordless high speed rotary tool. Packaged for sanding pet nails. Accepts all 1/8"bits &

mandrils normally used with hobby rotary tools. 8000-20000RPM. Supplied with 3 sanding tubes, tube mandril, chuck wrench and charging stand.

L: 9-1/4" DIA: 2-1/8" WT: 1.7 18931-TL \$9.95 **Cordless Rotary Tool**

DENTAL MIRROR

Disposable dental mirror. Plastic handle with 3/4" dia mirror. Approx. 30° handle to mirror angle. Ideal tool for examining electronic equipment or do-it-yourself root canals.

L: 6"

17907-TL Disposable Dental Mirror \$0.79

POINTED TWEEZERS

Sharp point tweezers with fiber finger grips. Ideal for picking up small components or parts.

L: 6-1/2" WT: .06 17619-TL **Sharp Nose Tweezers** \$1.59

8 IN 1 PRECISION SCREWDRIVERS

Quality miniature screwdriver set contains 4 double ended hardened steel bits with Phillips on one end & flat blade on

other as follows: 000P/2mm, 00P/ 2.5mm, 0P/3mm, 1P/4mm, store in the plastic handle.

L: 4-3/4" WT: .08 17011-TL 8/1 Mini Screwdrivers \$1.99

7PCS. PRECISION SCREWDRIVERS

Quality miniature screwdriver set contain: 00, 0, 1 Phillips, 1.4mm, 2.4mm, 3.0mm Flat Blade sizes.

Handles have free spinning finger caps. Plastic handles with steel bits. Includes slide top plastic storage case.

WT: .32 L: 4-3/8 7Pc. Mini Screwdrivers 17010-TL

THOUSANDS MORE ITEMS



9 pc

WT: 1.7

\$7.95

WT: .4

\$7.95

WT: .44

\$6.95

WT: .54

\$14.99 \$13.75

\$7.95

100 PIECE

BIT SET

Vast assortment of hard top locate

Chrome/Vanadium steel bits 1" long

9pc Star mm

8pc Phillips8 Positive Drive

5 pc. Security HEX

4pc Square

4 pc Spanner

100pc. Drive Bit Set

9pc Security Star 1pc Wingnut (5,6,8mm)

1/4" to 1/4Hex Socket

Plastic storage Case

drive bits

HEX mm 3pc XZN mm

18571-TL

SET

L: 1" Bit

12088-TL

33 PIECE

Set includes: 8 pc. security HEX

4 pc Tri-wing 4 Phillips

12579-TL

12pc security Torx 4 pc Spanner

1/4" mag. bit holder

plastic storage holder

SECURITY BIT SET

Set includes:

T-10,15 & 20 bits

DOUBLE

Set includes:

9pc Flat Blade

3pc Torque set

4 pc Tri-wing 3pc Clutch Drive

1/4" Sq to 1/4Hex

1/4" mag. bit holder P SEE WEB FOR DETAILS

ENDED TOOL

11 Pcs. DriverTool set.

5,6,7mm Flat blade bits #1 & 2 Philips bits #1 & 2 8 pt. Philips

22PCS.

POWER

L: 4-1/4" X 1-3/8" "L" Handle

15243-TL Double End Driver

Double end/right angle non rattaching handle

Magnetic Hex drive adapter and 20 bits all in a spill

1, 2 & 3 Square 10, 15, 20, 25, 27, 30 & 40 Star 1/8", 3/16", 7/32" & 1/4" Hex 1/4" X2-1/2" magnetic bit holder. Ideal for bench or tool

resistant carry box. Includes the following sizes: 1/8", 3/16", 1/4" flat blade #1, 2 & 3 Phillips

22Pc. Driver Bits

Security Bit Set

DRILL SET

MASONARY

 $4~\rm pc.$ Industrial type bits with carbide tips for drilling through concrete walls, floors, & blocks. Set contains 1/ $4".\,5/16",\,3/8",\,$ and $1/2".\,1/2"$ bit is turned to fit 3/8" drill chucks.

L: 12" WT: .9

STOCK	DESC.	1EA	5-EA
8209-TL	4pc Masonary Drills	\$7.95	\$6.95

39PCS. SAE BIT/SOCKET SET



Magnetic driver handle and 37 bits/sockets in a spill

Magnetic driver handle and 37 bits/sockets in a spill resistant carry box . Includes the following sizes: 1/8" 5/32", 3/16", 1/4" flat blade #0, 1, 2 & 3 Phillips #1, 2 & 3 Square #10, 15, 20, 25, 27, 30, 40 Star 5/64", 3/32", 1/8", 5/32", 3/16", 7/32", 1/4", 5/16" Hex 3/16", 7/32", 1/4", 5/16", 11/32", 3/8", 7/16", 15/32", 1/2" secretate. sockets

Hex to 1/4" & 1/4" to Hex drive adapters.

L: 1" Bit	WT: 1.2	
STOCK # DESC.	TEA	5+EA
12097-TL 39Pc. SAE Driver Bits	\$12.95	\$11.95

30PCS, DRIVER SET WITH TAMPER PROOF STAR BITS



Magnetic driver handle and 28 bits all in a spill resistant carry box. Includes the following sizes: 7, 8, 9, 10, 15, 20, 25, 27, 30 & 40 Tamper resistant Star; 5/32", 3/16", 1/4" flat blade, #1, 2 & 3 Phillips; 0, 1, 2 & 3 Square; 5/64", 3/32", 1/8", 5/32", 3/16", 7/32" & 1/4" Hex; Hex to 1/4" & 1/ 4" Hex drive adapters. Ideal for bench or tool box.

L. I DILS			1
STOCK #	DESC.	1EA	5+EA
12086-TL	30Pc. Set/Star Bits	\$24.95	\$22.95

TAMPER RESISTANT STAR BITS



Used as security fasteners in equipment. 1/4" driver bits fit in ratchets, drills, handles etc. Available in following

A: Tamper resistant Star Sizes:T-7,8,9,10,15,20, &25

B: Tamper resistant Star Sizes:T-10,15,20,27,30, &40

STOCK	DESC.	TEA	5+EA	
8551-TL	"A" Tamper Star Bits	\$3.95	\$3.49	
8552-TL	"B" Tamper Star Bits	\$3.95	\$3.49	

Magnetic 1/4" Hex drive adapter and 11 bits. Includes

the following sizes: Flat blade: 0.6 X 4.5, 0.8 X 5.5, 1 X 6.5, 1.2 X 6.5, 1.6 X 8 mm

20PC. **DRIVER BIT SET**

20pc. driver set contains: 7 sockets: 5,6,7,8,9,10, 11mm

4 Slotted: 2X 4mm, & 2X 7mm 4 Phillips: 2X #0, 2X #2

4 Star: 2X T15, 2X T20 1 Magnetic Bit Holder

L: Bits: 1" Sockets: 1-3/8" WT: .5 37PCS.



Includes, dual function ratchet handle (socket drive & Bit driver), stubby ratchet screwdriver handle, 5-3/4" O/A flex extension, 1/4" X 2-1/2" magnetic bit holder & 33 bits in a Sockets & Hex to 1/4" drive adapter

12094-TL 37Pc. Rachet Set \$19.95 \$17.95

30PCS. **DRIVER BIT SET**



Magnetic driver handle and 28 bits all in a spill resistant carry box. Includes the following sizes: 1/8" 5/32", 3/16", 1/4", 9/32 flat blade;

1/8" 5/32", 3/16", 1/4", 9/32 flat blade; #0, 1, 2 & 3 Phillips #1, 2 & 3 Square #10, 15, 20, 25, 30 & 40 Star; 5/64", 3/32", 1/8", 5/32", 3/16", 7/32" & 1/4", 5/16" Hex Hex to 1/4" & 1/4" to Hex drive adapters.

L: 1" Bits WT: .92

12096-TL 30Pc. Driver Bits \$12.95 \$11.95

11PC COMPUTER REPAIR KIT

Basic tool kit Includes: IC extractor, tweezers 1/4" & 3/16" nut drivers,

#0 & #1 Phillips

3/16" & 1/8" Flat Blade screwdrivers, T-15 Star driver, 3 prong gripper, 5" X 3/4" [Dia] parts container. Zipper carry WT: .7

14053-TL Computer Tool Kit \$7.95 \$6.95

STRAP WRENCH



Strap wrenches with plastic handle and rubber strap. Small for ust on objects up to 5". Strap is 1/2" wide X 3/2" thick with 5-1/2" long handle. Larger size for objects up to 7". Strap is 3/4" wide X 3/16" thick with 8" handle Small

WT: .25 WT: .55 Larger


STOCK	DESC	1EA	SHEA
14390-TL	6" Strap wrench	\$2.95	\$2.49
14391-TL	8" Strap Wrench	\$3.79	\$3.25
14455-TL	Both Strap Wrenches	\$5.95	\$4.95

200PCS CABLE **TIE & CUTTER**

Assortment of multi colored 3" cable ties with a cushion handle cable/tie cutter. Ideal for tagging cables or bundling up wire or cable feeds.



200Pc. Cable Ties 12089-TL \$4.49 \$3.95





REAMERS

WT: .09

4 piece assortment of Diamond coated reamers. Includes Long taper (5cm), Medium, Fine Taper (3cm), Short, Fat Taper (1.5cm), Bullet, counter sink shape (1.4cm). Long tapered plastic 7.2cm handles. For plastic & wood beads, soft gemstones, modeling etc.

\$2.95

11pc, Drive Bits 20

1/4" X 2-3/8" magnetic bit holder.

L: Flat: 1-1/2" Phil & Pozi: 1

11PC. DRIVE BITS

Phillips: #1, 2 & 3

Pozi: #1,2,3

11957-TL

17891-TL

WT: .44

\$2.95

20 Pc. Driver Set

\$3.95

18179-TL 3Pc. Set Diamond Reamers

ORDERS:

CALL 800-652-6733

FAX 800-432-9937



HEAVY DUTY TWEEZERS

Stainless steel industrial tweezers with fiber grips. Standard pointed nose or bent nose to lower fatigue. Ideal for picking up small components or parts. Squeeze to open.

L: 6-1/2 4979-TL Bent Nose Tweezers \$1.59 \$1.95 8249-TL Straight Nose Tweezers \$1.95 \$1.69

BENT NOSE TWEEZERS

Stainless steel tweezers with the last 3/4" of the pointed tip bent at approx. 45deg. Tip Not serriated.

L: 5" WT: .06

STOCK N	DESC.	1EA	10+EA
17007-TL	Bent Pointed Tweezers	\$2.95	\$2.49

STAINLESS TWEEZERS



Stainless steel, sharp point, industrial tweezers. Available either standard straight or curved for lower fatique. Ideal for picking up small components or parts.

WT:.08

STOCK #	FIG	DESC.	TEA	10-EA
16039-TL	A	5"Straight Nose	\$2.95	\$2.49
17007-TL	В	5"Curved Nose	\$2.95	\$2.49
17022-TL	C	4-3/8" Straight Nose	\$2.95	\$2.49
17023-TL	D	4-3/8"Cutback Nose	\$2.95	\$2.49
17024-TL	Е	5-3/8"Straight Nose	\$2.95	\$2.49

STAINLESS STEEL PICKS

piece assortment of double ended stainless steel hobby picks in a plas-tic pouch. Various shapes with knurled grips.

L: 6-1/21

12Pc. S/S Picks \$6.95 \$5.95 14388-TL

HOBBY PICKS

4 piece assortment of double ended steel sharp point, hobby picks. Various shapes with knurled grips.

L: 6-1/2"-7-1/4" WT: .19 4Pc. Hobby Steel Picks \$1.95 17917-TL



Dip coated plastic grip industrial tweezers. Serrated bent nose to lower fatigue. Ideal for picking up small components or parts. Squeeze to open.

L: 6-3/4"		WT: .09
STOCK #	DESC.	1EA
17618-TL	Bent Nose Tweezers	\$1.95

STAINLESS STEEL TWEEZERS

5 piece assortment of stainless steel tweezers in a plastic hanging pouch. Includes: needle, spade, bent, blunt & flat.

L: 4-1/8"to 4-5/8"1

17538-TL 5Pc. Stainless Tweezers \$3.95

STAINLESS CHISEL SET

6 piece assortment of stainless steel hobby chisels. For working wood, unfired clay or epoxies. Includes plastic

L: 5-7/8"		WT: .33
STOCK #	DESC.	1EA
17613-TL	6 Pc. Set Chisel Set	\$5.95

SHARP POINTED TWEEZERS

Very Sharp pointed Stainless Steel tweezers. Ideal for picking up small components or parts.

L: 4-3/4"		WT: .03
STOCK #	DESC.	1EA
17126-TL	Sharp Pointed Tweezers	\$2.95

SPRING HOOK **TOOLS**

Stainless steel hook style picks used to attach & detach springs and also to untangle jewelry chains. Tip Style "A": last 3/8" bent 60deg. Tip Style "B: last 1/2" reverse bend with 1/2 circle loop

STOCK #	DESC.	TEA	10+EA
15236-TL	Spring Hook Tip "A"	\$0.79	\$0.63
15237-TL	Spring Hook Tip "B"	\$0.79	\$0.63

EXAM MIRRORS



Dental style mirrors. 4-1/4 in long steel (NOT STAIN-LESS) knurled handle. 30 deg. Angled mirror head

2 diameters available: 25mm & 30mm

L: 6-1/4" O/A WT: .051/.1

STOCK #	DESC.	TEA
17379-TL	25mm Exam Mirror	\$0.69
17380-TL	30mm Exam Mirror	\$0.89

ANTI STAT TWEEZER SET

Black Antistatic non-magnetic, non-marring plastic tweezer set. 1ea as follows: pointed tip, 1/8" flat jaw tip 1/8" rounded tip 1/4" flat tip



: 4-3/4" W: 5/16" O/A **4pc. Antistatic Tweezers** 17623-TL

MAGNETIC TOOL BAR

24" Magnetic tool bar. Designed to attach to wall or bench and hold screwdrivers, wrenches, pliers or any steel item. Magnet Length: 22"

W: 1" H: 1/2 WT: 2.4

STOCK #	DESC.	IEA
18280-TL	Magnet Tool Bar	\$12.95

PICK-UP MAGNET

Magnet with an "Eye" loop used to retrieve iron & steel items. Will lift in excess

: 1-7/8"	W: 1"	H: 1-1/2"	WT: .25
STOCK #		DESC.	1EA
18279-MG	Pic	k-Up-Magnet	\$1.99

RETRIEVING MAGNETS



Magnet assemblies used to hold or retrieve steel objects. Cased magnets with Eye bolt for the attachment of rope,

equipinent.	
2"X 2" X 1/2"	WT: .43
2"X 2" X 1"	WT : .8
5"X 2" X 1"	WT: 1.8
5"X 2" X 2"	WT: 3.8
	2"X 2" X 1/2" 2"X 2" X 1" 5"X 2" X 1"

STOCK II DESC.	TER.	DITEA
12961-MG 40lb Retreiv. Magnet	\$7.95	\$6.95
12962-MG 100lb Retreiv. Magnet \$	10.95	\$8.95
12963-MG 150lb Retreiv. Magnet \$	15.95	\$14.95
12964-MG 225lb Retreiv. Magnet \$2	29.95	\$22.95

HANDLE MAGNETS



Magnet assemblies used to hold or retrieve steel objects.

Cased magnets with metal handle 12956-MG up to 25lb 1-1/16"X 3/4" X 2-1/4" WT: .22 12957-MG up to 50lb 2"X 3/4" X 2" 4"X 3/4" X 2-1/4 WT: .4 WT: .75 12958-MG up to 100lb 12959-MG up to 150lb 5"X 2" X 5-1/2" WT: 2.4 5-1/4 X 2" X 4-1/2 12960-MG up to 225lb

STOCK #	DESC.	TEA	5+rA
12956-MG	25lb Handle Magnet	\$5.95	\$4.95
12957-MG	50lb Handle Magnet	\$7.95	\$6.95
12958-MG	100lb Handle Magnet	\$10.95	\$8.95
12959-MG	150lb Handle Magnet	\$17.95	\$13.95
12960-MG	225lb Handle Magnet	\$34.95	\$26.95

LIFTING MAGNET



Handy, hand held Magnet assembly used to hold or retrieve steel objects. Plastic Cased magnet with easy grip handle. Approx. 100lb lift of flat mild steel

plate.include	es steel "Neep	per plate to pro	nect magnet.
L: 5"	W: 1-1/8"	H: 3-`1/2"	WT: 1
STOCK #	nes	11 1 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1	164

\$7.95 18771-MG Lift Magnet

TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764

MPJA@MPJA.COM



Semi transparent, flexible plastic boxes with multiple compartments. For screws, fish hooks, LED's, Transistors, Resistors etc. 6-1/8" LX3-1/2" WX1-1/8" D overall.

A: 12 compartments: All measure 7/8" wide X 1-3/8" long X 7/8"deep

B: 10 total compartments: 2 measure 7/8" wide X 2-3/4 long X 1" deep. 8 measure 7/8" W X 1-3/8" L X 1" D

L: 6-1/8"	W: 3-1/2" T:1-1/8"		WI:.17
STOCK	DESC	164	10+E8
6479-BX	12 Compartment Box	\$1.85	\$1.69
5994-BX	10 Compartment Box	\$1.75	\$1.59



PLASTIC PARTS BOX

Semi transparent, flexible plastic box with multiple compartments. For screws, fish hooks, LED's, Transistors, Resistors etc. Latch holds lid closed.

5 compartments that run length of box: 3 measure 7/8" wide X 6-3/4" long X 3/4" deep. 2 others are 7/8" wide X 3-3/8" long.

10 compartments that all measure 1-5/16" wide X 1-11/

L: 7" W:	3-3/4" T: 1-1/4"	WT: .14
STOCK #	DESC.	TEA
17614-BX	5 Compartment Box	\$2.59
17616-BX	10 Compartment Box	\$1.99

PLASTIC PARTS BOX

Hard, clear plastic box with multiple compartments. For screws, fish hooks, LED's, Transistors, Resistors etc

18 compartments measure 1-1/4" sq. X 1-1/8"deep.

L: 8-1/4"	W: 4-1/4"	T:1-3/8"		WT: .34
STOCK #	DES	iC.	1EA	25+EA
16042-BX	Small 18 Co	mp. Box	\$1.95	\$1.49

SUPER SLEUTH MAGNIFIER

5in. Dia. Magnifier with metal handle & Glass lens. 3X Magnification L: 10-1/4" Dia: 5"

WT: .9 17874-LN \$6.95 5in. Dia. Hand Magnifier

4" MAGNIFIER



4in. Dia. Magnifier with padded plastic handle & Glass lens. 3X Magnification 1.0 5/0 | Dia 4 4/4

STOCK # DESC.	
JIOUN DESC.	EA
18911-LN 4in. Dia. Hand Magnifier \$	1.95

LIGHTED **POCKET** MAGNIFIER

22



Pocket mini microscope with white mini LED illumination 45X magnification. Glass lens in plastic housing. Slide action switch. Uses 3 "LR927" coin cells (supplied.) & fake leather case. Ideal for collectors, jewlers, electronic

L: 1-3/4"		WT: .05
STOCK	DESC.	1 EA
17967-TL	Pocket Mini Microscope	\$3.95

DESK LAMP & MAGNIFIER

Adjustable desk/bcnch lamp with 4" dia, 2X lens. Circular 'Cool White" fluorescent lamp surrounding the lens. 2 joint

arm allows for multi-positions. Max parallel surface elevation approx. 13". 6ft. 115VAC cord, power switch on base. Ideal for collectors, jewlers, electronic repairs

17663-TL	Desk Lamp/2X Magnifier	\$24.95
STOCK #	DESC	WT: 3.1

DESK LAMP & MAGNIFIER

Adjustable desk/bench lamp with 3-1/4" dia, 5X lens. Circular 60 White superbrite LEDs surrounding the lens. 10in. "goose neck allows for multi-positions. 6ft. 115VAC cord, power switch on base. Ideal for collectors, jewlers, electronic repairs.



DESK MAGNIFIER

2.5X magnifier with fully articulated neck, 90 X 45mm rectanglar graded plastic lens. Lighted by 3 white LEDs mounted in on end. Slide power switch on top face. 4-3/4" Dia. Base, 5-1/4" X 3-3/4" lens assembly Max neck height: 9in. Requires 2 "AAÁ" batteries (Not Included).

		** * * * * * * * * * * * * * * * * * * *
STOCK #	DESC.	1EA
17493-LN	LED Lighted Magnifier	\$6.95

MINI LIGHTED MAGNIFIER



WT- 16

Pocket magnifier with 2 white mini LED for illumination. 30X magnification. Slide action switch. Uses 3 "LR927" coin cells (supplied.) Includes mini spanner to access batteries & Padded plastic box. Ideal for collectors, iewlers, electronic repairs.

L: 2-1/8"	W: 1-3/8"	T: 1"	WT: .2
STOCK #	DESC.		1EA
17930-LN	30X Mini Lighted	Magnifier	\$3.99

FOLDING POCKET MAGNIFIERS



Folding 20X magnifier. Folds into 1-3/8" x 1-1/8" protective case. Ideal for school, or reading the fine print on your insurance

L: 1-3/8"	W: 1-1/8"	T: 1/2"	WT: .04
STOCK		DESC.	1EA
18585-LN	20X Foldir	ng Magnifier	\$1.95

3X LIGHTED MAGNIFIER



Lighted Handheld 3X magnifier with 2 superbright white LEDs. Plastic body with 3"dia. glass lens. Requires 3 "AAA" cells (Not Supplied). 2 Position Slide switch on

L: 6-3/4"	Dia: 3-1/4"	T: 1"	WT: .3
STOCK #	DESC.	and the second	1EA
18922-LN	3X Lighted Han	nd Magnifier	\$3.95

LIGHTED 3 LEVEL **MAGNIFIER**



Flip up magnifier with adjustable headband & 3 levels of magnification. 1st. level is 1.5X, 2nd. lens folds down to increase magnification by 1.5X, 3rd. Lens rotates down over Right eye to increase magnification by 7.5X. Dual LEDs provide illumination. Do not interfere with eyeglasses, & flip up out of the way without removing from head. Requires 2"AAA" cells (Not Included)

		W 11.0
STOCK #	DESC.	1EA
18336-TL	3 Level Magnifier	\$6.95

BINOCULAR MAGNIFIERS



5X magnifier with adjustable padded headband. Optical grade Acrylic lens. Do not interfere with eye or safety glasses. Flip up out of the way without removing from head. Made in USA.

		WT: .41	
STOCK	DESC.	1EA	
17653-TL	USA Binocular Magnifier	\$12.95	

2.5X BINOCULAR MAGNIFIERS

Professional OVP, 2.5X magnifier with adjustable padded headband. 8in. Focal length. Optical glass lens. Do not interfere with eye or safety glasses. Flip up out of the way without removing

from head. Made in USA. WT: .55

17654-TL OVP 2.5X Binocular Magnifier \$49.95

TABLE TOP MAGNIFIER

5X magnifier with glass lens & plastic base. 2-1/2" X 1-7/8" lens. Base open on 1 side. Ideal for stamps, coins or


	Jewelly Work			8 11
	W: 3-3/16"	D: 2-5/8"	H: 2-7/8"	WT: .7
	STOCK #		DESC:	1EA
_	16703-LN	Table	Top Magnifier	\$2.50

DUAL LENS MAGNIFIER

10X Plastic eye loupe with dual lens. Removable lower lens for less mag. but wider field. Used to do watch & jewelery repair, and to check circuit

Dia:1-1/2"	T: 1-1/2"	WT: .03
STOCK #	DESC.	1EA
17283-LN	Dual Lens Eve-Loupe	\$1.95

DESK TOP MAGNIFIER




		441.7.2
STOCK	DESC.	TEA
16725-LN	Desk Top Magnifier	\$9.95

LIGHTED HAND MICROSCOPE

30X hand held magnifier with adj. focus and light source. Requiers 2 "AA" cells (not included). Black plastic case with clear plastic end for added illumination. Soft plastic carry pouch.





LENS Fol

0079-LN

GIANT FOLDING

Dia go Ide tro L:

a. glass le 1-5/8" fo en bottoi	gnifier with a quens. 7" tall who Ided. 6-1/2" X m has inch/cm Ilectors, jewler rs.	en open (5-1/4" scales.	C	
6-1/2"	W: 5-1/4"	T: 7"		WT: 1
TOCK #	DES	C.	TEA	SHEA





(Not included)	
H: 6-3/4"	WT: 1.7
STOCIC# DESC.	TEA
17932-TL Lighted/Mag.Helping Hands	\$9.95

LIGHTED MAGNIFIER

Lighted Handheld 4X magnifier with 5 white LEDs and a UV LED. Plastic body and 2" X 2"glass lens. Requires 2 "AAA" cells (Not Supplied). 3 Position Slide switch on top.

L: 8"	W: 3-3/8"	H: 1"	WT: .3
STOCK #	DESC.		1EA
18586-TL	4X Lighted Ha	ind Magnifier	\$6.95

SMALLER FOLDING LENSES

Smaller and more compact than our Giant lens, these folding magnifiers have open bottom with inch/cm scales. Ideal for collectors, jewlers, electronic repairs. 14042-LN 4-1/8" tall open X 3/4" folded. 3-5/8" X 3-1/4" Base

Giant Folding Lens

WT:.16 14043-LN 5" tall open X 1" folded.

3-5/8" X 4-1/4" Base			W1:.3	
STOCK 4	DESC.	TEA	B+EA	
14042-LN	Small Folding Lens	\$1.95	\$1.39	
14043-LN	Medium Folding Lens	\$2.49	\$1.69	


HELPING HANDS

A must for circuit board, model or iewelry work, cast iron base with 2 alligator clips on a cross arm, move & adjust every which way, leaving your hands free, also available with 2-1/2" dia. magnifying lens.

H: 6"	WT: 1.4
STOCK # DESC.	TEN SHEA
1006-TL Helping Hands no Ler	ns \$4.00 \$3.75
3628-TL Helping Hands /2X Le	ns \$5.50 \$4.95
18929-TL Helping Hands/4X Le	ns \$5.50 \$4.95

LIGHTED EYE LOUPE

10X power, plastic eye loupe with a



\$2,49

FOLDING POCKET **MAGNIFIERS**




\$6.95

Folding 10X magnifier. Folds into 3-1/2" x 2-1/2" protective case. Ideal for school, or reading the fine print on your

L: 3-1/2"	W: 2-1/2"	W	T: .3
STOCK V	DESC	TEA	5+fA
8251-LN	Folding Magnifier	\$5.95	\$4.95

LARGE HELPING HANDS



H: 8-1/2"	or jeweny work.	WT: 1.4
STOCK #	DESC.	1+EA
16037-TL	Helping Hands & Lens	\$5.95

super brite white LED. Uses single Coin Cell (included). L: 1-3/8

17651-LN **Lighted Eye Loupe**

LIGHTED MAGNIFIER

Close focus (35mm) Handheld 10X magnifier with plastic case and plastic circular lens. Required 2 "C" cells (Not Supplied). Replaceable incandescent bulb. Slide switch on top.

L: 8"		WT: .3	
STOCK#	DESC,	1EA	
17491-LN	Hand Held Magnifier	\$3.50	

EYE LOUPE MAGNIFIERS

Plastic eye loupes used to do watch & jewelery repair, and to check circuit boards.

Dia:1-1/2"	T: 1-1/4"	'	WT: .03
STOCK #	DESC.	1EA	5+EA
7433-LN	10X Eye Loupe	\$1.95	\$1.49

TWEEZERS WITH MAGNIFIER

H:

Stainless steel tweezer with tached 3X magnifier.

Ideal for sorting small parts etc. Folds to only 3/8" thick L: 3-5/8" W: 1-1/4"

STOCK #	DESC	TEA	5+EA
9186-TL	Tweezer/ Magnifier	\$1.95	\$1.49

MINI LIGHTED MAGNIFIER

Pocket magnifier with 2 white mini LED for illumination. 20X magnification. Slide action switch. Uses 3 "LR927" coin cells (supplied.) Includes mini spaller to access batteries & Padded plastic box. Ideal for collectors, jewlers, electronic repairs

L: 1-7/8"	W: 1"	T: 1"	WT: .23
STOCK #	DESC.		TEA
17593-LN	Mini Lighted M	agnifier	\$7.95

MAGNIFIER SET

12 Pc. set of Magnifiers with Metal handles & glass lens. Perfect for schools, Labs, Retail. Includes 4pcs. each as follows: 10X 2in. Dia. X 5" long 8X 2.5in. Dia. X 5-3/4" long 6X 3in. Dia. X 6-1/2 long.



		WT: 3.6
STOCK #	DESC.	1EA
537-I N	Metal Handle Magnifier Set	\$19.95

UVTHIN **POCKET** MAGNIFIER



Thin pocket magnifier with a mini UV & a white superbrite LED for illumination. Switch select of UV or White light 14X magnification glass lens. Includes 2 CR2016 coin cells, soft protective pouch, Ideal for collectors, jewlers, electronic repairs.

18338-LN		ocket Magnif	ier \$3.95
L: 4" \	N: 1-1/2"	1:5/16" DESC.	W1:.09

LIGHTED POCKET MAGNIFIER

LICHTED

Pocket magnifier with a white mini LED for illumination. 10X magnification. Alternate action switch. Uses 3 "LR1130" coin cells (supplied.) Includes mini screwdriver & Padded plastic box. Ideal for collectors, jewlers, electronic repairs.

L: 2-3/4"	VV: 1-1/4	4" 1: 7/8"	WI: .24
STOCK #	0.6	5G	TEA
17592-LN	Lighted	Pocket Magnifier	\$4.92

MAGNIFIER	A MANAGE OF THE SECOND
X power, pocket sized, plastic mag- fier with a super brite mini white ED. Uses single Coin Cell (included).	La Ligarita Mariana de la


L: 3-3/8"	W: 2-1/4"	T: 5/16"	WT: .073
STOCK W		DESC.	166
17652-LN	Lighted	Card Magnifier	\$1.95



MULTI MAGNIFIER

Round, Plastic magnifier with 8 different magnifications (5X-12X). Internal wheel rotates to expose the different lenses.

Di



a: 3-1/2"	1: 3/4"	VV	1:.2
STOCK #	DESC.	JUA	5+EA
5195-LN	Multi Magnifier	\$3.95	\$3.25
		A STATE OF THE STA	

10X EYE LOUPE/ UV LEDS

Pocket magnifier with mini Ultraviolet LED illumination. 10X magnification, 21mm focal

length. Glass triplet lens in stainless housing. Slide action switch. Uses 3 "LR927" coin cells (supplied.) Includes mini spanner to access batteries & leather case. Ideal for collectors, jewlers, electronic repairs.

L: 1-7/8" W: 1" H: 11 WT: .21

1EA STOCK # 18079-TL 10X Loupe/UV LEDs

UV LIGHTED POCKET MAGNIFIER

Pocket mini microscope with dual Ultraviolet mini LED illumination. 45X magnification. Glass lens in plastic housing. Slide action switch. Uses 3 "LR927" coin cells (supplied.) & fake leather case. Ideal for collectors, jewlers, etc.

L: 1-3/4" WT:.05

TEA 18080-TL Pocket Mini UV Microscope

30X EYE LOUPE WHITE/UV LEDS



Pocket magnifier with mini Ultraviolet & White LED illumination. 30X magnification. Glass lens in plastic housing. Slide action switch: OFF/Dual White/UV. Uses 3 "LR1130/ 3AG10" coin cells (supplied.) Includes mini spanner to access batteries. Plastic presestation box. Ideal for collectors, jewlers, electronic repairs.

L: 2-1/8" (Closed) W: 1-1/8" H: 1-1/8" WT:.19

STOCK #	DESC.	1EA
18337-TL	30X Loupe/UV LEDs	\$7.95




Telescoping, rectangular inspection mirror with 2 super brite mini white LEDs. Mirror head is 2-1/2" X 1-5/8". 11 collapsed (max), 34" extended (max). Uses two Coin Cells (included)

L: 11-34" W: 2-1/4" WT: .28

Telescoping Lighted Mirror 18916-TL \$9.95

LIGHTED MAGNIFIER



L: 12 WT: .3 H: 3-1/2"

17872-TL **Lighted Hand Magnifier** \$5.95

GOOSENECK **LED LIGHT**

Mini LED flashlight. Single (White super bright LED at the end of a 4-1/2" flexable metal "Gooseneck". Aluminum case holds 3 type AG13 "button" cells (supplied). Alternate action push button switch on side. Set includes key chain and removable pocket clip.

L: 2-1/4" (Body) DIA: 9/16" (Body)

LED Gooseneck Light 15996-TL \$3.95

UV/WHITE LED FLASHLIGHT LASER POINTER

LED "Stubby" flashlight with 4 White super bright LEDs, 4 Ultra Violet LEDs and a Red LASER pointer. Titanium colored aluminum case. Fixed focus lens. Requires 3 "AAA" cells (not supplied). 4 Step Alternate action push button switch on side (ÓN White LEDs only/ON UV LEDs only/ON LASER only/OFF. Includes 2" strap and soft belt pouch.

NOTE: CLASS IIIA Laser <5mW. Do not shine into eyes! DO NOT EXPOSE Eyes or Skin to UV Light!

L: 4-1/2

STOCK # DESC 17645-TL UV/White LED Flashlight/LASER \$12.95

UV FLASHLIGHT

Medium duty LED "Stubby" UV flashlight, 8 ULTRA-VIOLET LEDs in aluminum case for corrosion resistance. Fixed focus lens. Requires 3 "AAA" cells (not supplied). Alternate action push button switch on back end. Includes 4" strap. For currency examination, chemicial analysis, gem indentification etc.

1 . 4 DESC. STOCK # 8 LED UV Flashlight

UV LIGHTED MAGNIFIER

17346-TL

Lighted Handheld 4.5X magnifier with 8 white LEDs and a UV LED (390-395nm). Plastic body and 2-1/3" glass lens. Requires 3 "AAA" cells (Not Supplied). 3 Position Push Buttonswitch on top.

L: 7-1/2" W: 3-3/8" H: 1-3/8" WT: .3

STOCK # DESC 1EA 18925-LN 4.5X Lighted Magnifier/ UV

LED **FINGERLIGHT**

4 pack of Unique, "finger" flashlights that straps to your finger, pen & tools with a hookn-loop strap. White LED uses 3 replaceable AG10 coin cells (In-

cluded). Slide switch on top. Assorted body colors. L: 1-5/81 WT: .1

16711-TL 4 pack Finger Flashlights \$2.95

MULTI BIKE LIGHT

Bike light with White super bright LED in plastic case. Includes a handle bar mount and a head band mount. 4 posi tion push button switch: (LOW, HIGH, STROBE, OFF) Requires 3 "AAA" cells (Not supplied)

L: 4" O/L" W: 2-3/41 WT: .37 LED Bike/Head Light

LED LAMP

17377-TL

30 Superbright LED Plastic desk type light operates on 3 "D" cells (not supplied). Switch provides 2 lighting levels: 1/3 (10LEDs) and Full (30LEDs). Top loop for hanging. Rubberized grip for use as flashlight.

H: 10-1/4 WT: .9

3 LED **FLASHLIGHTS**

Light duty LED "Stubby" flashlight. 3 White ultra bright LEDs in colored aluminum case. Fixed focus lens. Requires 3 "AAA" cells (not supplied). Alternate action push button switch on back end. Includes 2" strap.

L: 3-1/4 WT: 07

\$1.95 17649-TL 3 LED Flashlight-Titainium Case 18326-TL 3 LED Flashlight-Black Case \$1.95 18325-TL 3 LED Flashlight-Red Case \$1.95

WHITE FLASHLIGHT LASER POINTER

LED "Stubby" flashlight with 8 White super bright LEDs and a Red LASER pointer. Titanium colored aluminum case, Fixed focus lens. Requires 3 "AAA" cells (not supplied). 3 Step Alternate action push button switch on side (ON LED only /ON LASER only/OFF, includes 2" strap and soft belt pouch. NOTE: CLASS IIIA Laser <5mW . Do not shine into eyes!

L: 4-1/2' 17475-TL White LED Flashlight/LASER

RED/WHITE FLASHLIGHT LASER POINTER

\$12.95

"Stubby" flashlight with 4 White super bright LEDs, 4 Red Super bright LEDs and a Red LASER pointer. Titanium colored aluminum case. Fixed focus lens. Requires 3 "AAA" cells (not supplied). 4 Step Alternate action push button switch on side (ON White LEDs only/ON Red LEDs only/ON LASER only/OFF. Includes 2" strap.

NOTE: CLASS IIIA Laser <5mW. Do not shine into eyes!

L: 4-1/2"

17474-TL Color LED Flashlight/LASER \$4.95

LASER POINTER & FLASHLIGHT

Thin LASER Pointer with flashlight. Only a 3/8" thick and contains 2 super bright white LEDs and a Class III, <5mW, 650nm Red LASER Pointer. Push button switches on top for LASER & LEDs. Uses 3 LR1130 button cells (included) W: 1" T: 3/8 WT: .06 L: 3-3/8"

18331-TL LASER Pointer LED Flashlight \$2.95

8 LED **FLASHLIGHT**

Medium duty LED "Stubby" flashlight. 8 White super bright LEDs in aluminum case for corrosion resistance. Fixed focus lens. Requires 3 "AAA" cells (not supplied). Alternate action push button switch on back end. Includes 4" strap.

L: 4" WT: .18 8 LED Stubby Flashlight 15984-TL \$7.95

MINI SUPERBRIGHT **FLASHLIGHT**

Flashlight with a single White super bright white LED. Black, plastic case. Fixed focus lens & reflector. Requires 1 "AA"

cell (Not supplied). Alternate action push button switch on back. Includes 4" strap.

L: 3-5/8"

18333-TL 30 LED Desk Lamp 17482-TL Superbright Plastic Flashlight \$1.95

\$6.95

2W SUPERBRIGHT **FLASHLIGHT**

Heavy Duty Flashlight with a single 2W CREE White super bright white LED Rated 70Lumens. Black, water resistant machined aluminum case. Fixed focus lens & reflector. Requires 2 "AA" cells (Not supplied). Alternate action push button switch on back. Includes belt pouch.

L: 6-1/4" D: 1-5/8"

WT: .34

17912-TL Heavy Duty 2W LED Flashlight \$14.00

3W SUPERBRIGHT **FLASHLIGHT**

Heavy Duty Flashlight with a single 3W CREE White super bright white LED Rated 100-120Lumens, Black, water resistant machined aluminum case. Fixed focus lens & reflector. Requires 3 "AA" cells (Not supplied). Alternate action push button switch on back. Includes belt pouch. WT- 48

L: 8-1/4" D: 1-7/8

17766-TL Heavy Duty 3W LED Flashlight

SUPERBRIGH1 **FLASHLIGHT**

Heavy Duty Flashlight with a single SW CREE White super bright white LED
Rated 160-180 Lumens. Black, water resistant machined aluminum case. Fixed focus lens & reflector. Requires 2 "D" cells (Not supplied). Alternate action push button switch on side. Includes belt pouch.

L: 9-3/8" D: 2-5/161

17767-TL Heavy Duty 5W LED Flashlight \$39.95

WEATHERPROOF **FLASHLIGHT**



Medium duty, weatherproof LED "Stubby" flashlight. 7 White ultra bright LEDs in shock resistant aluminum case with rubberized coating. Fixed focus lens. Requires 3 "AAA" cells (not supplied). Push button switch on back end selects HI/MEDIUM/FLASH/OFF. Includes 6" strap. L: 3-7/8"

18329-TL Weatherproof 7 LED Flashlight \$4.95

9 LED **FLASHLIGHT**

Light duty LED "Stubby" flashlight.

9 White super bright LEDs in Titanium colored aluminum case. Fixed focus lens. Requires 3 "AAA" cells (not supplied). Alternate action push button switch on back end. Includes 2" strap. WT: .08

L: 3-1/4

17018-TL 9 LED Stubby Flashlight

9 LED **FLASHLIGHT**

Light duty LED "Stubby" flashlight White super bright LEDs in Black colored aluminum case. Fixed focus lens. Requires 3 "AAA" cells (not supplied). Alternate action push button switch on back end. Includes 2" strap. L: 3-1/4" WT: .08

18581-TL 9 LED Black Stubby Flashlight

TECH. & INFO: CALL 561-848-8236

2W **SUPERBRIGHT FLASHLIGHT**

Heavy Duty Flashlight with a single 2W OSRAM W5AM White super bright white LED Rated 70-80Lumens. Black, water resistant machined aluminum case. Fixed focus lens & reflector. Requires 2 "AA" cells (Not supplied). Alternate action push button switch on back. Includes belt pouch.

L: 6-1/4" D: 1-3/8"

18920-TL 2W Osram LED Flashlight \$9.95

27 LED WORKLIGHT

Mini worklight with 24 super bright white LEDs on face with 3 more on front for use a flashlight. Plastic swivel hook on end for hanging and a strong magnet on back for attaching to steel. 4 position Push button switch. Required 3 "AAA" batteries (Included)

L: 3-3/41 W: 2-1/2 T: 1-1/2" WT: 24 27 LED Mini Worklight 18583-TL

EMERGENCY RADIO

Unique Hand crank Radio/ Flashlight/Siren.

Turning the Hand crank for 1 minute will power the Radio/Siren or light for up 90 minutes Switch selection of 1 or 3 Superbright white LEDs. Std. AM/FM Radio with telescoping Antenna. 1/8" jack for headphones (Not Included)

L: 7-1/2"

17646-TL **Emergency Radio/Light**

SOLAR **FLASHLIGHT**

Solar charged flashlight. 5 White super bright LEDs in plastic case with a .22W Solar Panel. 6hr. exposer to sun charges 2 "AAA" NI-MH cell for up to 3hr. of light. Includes small compass in handle and power switch on side.

L: 6"

17381-TL

5 LED Solar Flashlight

28 LED FLASHLIGHT

LED flashlight with 28 White super bright LEDs. Titanium colored aluminum case. Fixed focus lens. Requires 3 "AAA" cells (not supplied). Alternate action push button switch on back. Includes 2" strap and soft belt pouch.

WT: .34 L: 4-1/4" Dia: 1-3/4" O/A

\$5.95 28 LED Flashlight 17476-TL

25 LED WORKLIGHT

\$1.95

Mini worklight with 25 super bright white LEDs on face . Plastic case withplastic swivel hook on end for hanging and a strong magnet on back for attaching to steel. 4 position Push button switch. Re-quired 3 "AAA" batteries (NOT SUPPLIED)

T: 1-3/8" SQ.: 2-3/4" WT: .18 25 LED Mini Worklight 18921-TL

24VDC DPST-NO RELAY

MFG: MAGNECRAFT P/N: 199QX-5 COIL: 24VDC/290 ohms

CONTACT RATING: 30A@28VDC/300VAC

1.5hp@120-600VAC **ACTION: DPST-NO**

New but made in 1980s. General purpose contactor with .250" Quick connect terminals for contacts & coil. UL

listed. 2-1/2" sq. mounting base L: 3-1/2" W: 3" H: 2-1/4"

WT: .6 18955-RL 30A Magecraft 24V Relay \$6.95

240VAC 4PDT RELAY

MFG: MIDLAND-ROSS P/N: 156-24U100 COIL: 240VAC/14.7Kohms

CONTACT RATING: 3A@ 28VDC/120VAC Resistive;

1/10hp@120/240VAC **ACTION: 4PDT**

General purpose relay with PC terminals UL/CSA listed. H: 1-1/4"(Body) W: 1-1/8" T: 7/8" WT: 06

STOCK I TEA 18954-RL 240VAC Midland Relay \$5.95

12VDC SPST-NO RELAY

MFG: OMRON P/N: G8P-1114P-US COIL: 12VDC/155 ohms

\$19.95

WT: .2

CONTACT RATING: 30A@ 250,15A @ 125VAC; 1hp@120V; 2hp@250VAC

ACTION: SPST-NO

Sealed HVAC/industrial relay for PCB mounting, UL/CSA

L: 1-1/4" W: 1-1/16" WT: .06

12VDC Omron Relay \$5.95 19059-RL

SHOZEL

110VAC DPST-NO RELAY

MFG: OMRON P/N: G7L-2A-P-CB COIL: 100-110VAC CONTACTS: DPST-NO

RATED: 20A@277VAC Restive & Inductive, 1.3KW (Tungsten)

P.C. Board mount, UL/CSA/TUV/CE Listed

W: 1-3/8" H: 1-1/2" (Body) L: 2-1/16"

18900-RL 20A Omron110VAC Relay

\$4.95


120VAC SPST-NO RELAY

MFG: P & B P/N: PRD3AG1-DM COIL: 120VAC/290 ohms CONTACT RATING: 30A@ 277,10A @600VAC; 1hp@120; 2hp@240VAC

ACTION: SPST-NO Double Make General purpose relay with .250" Quick connect terminals. UL/CSA Listed

L: 2-1/2" W: 2-1/2" H: 2-3/8" WT: .5 120VAC P & B Relay 18963-RL \$6.95

WT: .6



							7			- Allen	Miles Co.
STOCK			CONTACTS		COMM	DIM. LWH	MFG. PART #	LISTED	WT.	1EA	
18474-RL	В	5VDC	DPDT	1A@24DC/125VAC Res	PC/SKT	13/16" x 3/8" x 1/2"	FORWARD IND./FRT2H-S DC5	UL/us/c/CE	.02	\$1.95	
18482-RL	F	5VDC/47 Ω	DPDT	5A @ 250VAC	PC	1-1/16" x 1/2" x 1"	MAGNECRAFT/W76EURCPCX-6		.04	\$5.95	
18454-RL	C	12VDC	SPDT	3A@125VAC ind. /28V Res.	PC	1-3/16" x 3/4" x 1-1/4"	ESSEX/RBM/MS64-901	UL/CSA	.06	\$1.25	\$0.9
19024-RL	E	12VDC	SPDT	NO-40A@12VDC/NC-30A	QC1	1-1/8" x 1-1/4" x 1-5/8"	XPRESS/RL50	-	.08	\$1.95	-
18483-RL	F	12VDC/275Ω	SPDT	10A @ 250VAC/30DC	PC	1-1/16" x1/2" x 1"	MAGNECRAFT/W76EURCPCX-1	6 UL/CSA	.04	\$5.95	- Company
18610-RL	Р	12VDC/100 Ω	DPDT	20A@250V/3/4hp@120VAC	QC1	2-1/2" x 1-3/8"x 1-3/8"	AROMAT/HG2-DC12V	CSA	.3	\$5.95	
18502-RL	1	120VAC	4PDT	3A@125VACind./28V Res.	PC/SKT	1-1/8" x 7/8" x 1-1/4"	P&B/KH5569-1	CSA	.1	\$4.95	
9139-RL	J	24VDC	SPDT	10A@125VAC/6A@277VAC	PC	5/8" x 3/4" x 3/4"	AROMAT/PN JS1E-24V	UL	.027	\$1.95	\$1.7
4197-RL	K	48VDC/2.8KΩ	4PDT1A	@120VAC/30VDC Res. 1/10hp@120V	AC PC	1-1/4" x 13/16" x 1/2"	FUJITSU/PN FRL414D048/04CT	F #1.	.03	\$0.99	\$0.7
12120-RL	L	24VDC	SPST-NO	15A@250VAC/24VDC Res.	PC	1-3/16" x 3/4" x 1-1/8"	OMRON/G4W-1112P-VD-TV8-HF	UL	.06	\$1.95	\$1.7
15831-RL	N	24VDC	3PST-NO	35A/600VAC Resistive	QC1	2-1/4" x 2-1/2" x 2-7/8"	P&B/PN P31-E1014-1	UL	,95	\$3.50	\$3.2
			25	FLA/150LRA/240VAC/pole Motor Lo	ad						
18230-RL	R	24VDC	4PST-NO	35A/600VAC Resistive 25FLA/150LRA/240VAC/pole	QC1	3-3/4" x 2-1/2"x 2-7/8"	P&B/PN P41C47DH0103Z03	UL/CSA	1	\$5.95	
18067-RL	M	24VAC	DPST-NO	40A/277VAC/28VDC Resistive 1-1/2hp/120-600VAC Motor	SCW	2-1/2" x 2-1/2" x 2-1/2"	MAGNECRAFT/W199AX-8	UL/CSA/CE	.52	\$10.95	100 May 100 Ma
18255-RL	S	120VAC	3PDT	30A/75LRA @ 277V/Pole	PC	2" x 2-1/8" x 2-1/8"	DELTROL/375P	UL/us/c/CE	.3	\$9.95	\$8.9
16726-RL	U	110VAC	DPDT	1/2 hp/120VAC 12A res/240VAC	QC2	1-3/4" x 13/16" x 1-5	OMRON/LY2-UA-006244	UL	.2	\$2.95	\$2.7
19082RL	0	120VAC	3PDT	10A/120VAC Resistive	SKT/QC2	3" x 1-1/2" x 1-7/8"	MMIDTEX/614-43T3A4		.2	\$ 14.95	-
			1/3 hp	p/120VAC 6-60Seconds Delay on En	ergize Time	Delay Relay					
17769-RL	Α	3-32VDC	SPST-NO	35A @ 280VAC	SCW	3-7/8" x 1-3/4" x 4-1/4"	CRYDOM/CMRD2435	UL/CSA/VDE	1 [\$24.95	C. T. Marie and
18193-RL	ь.	0.45400		ail Mount Solid State Relay AC load		4 4 (411 - 0 (011 - 0 (411	0.110.1.10014000			64.00	
10193-KL	U	3-15VDC	SPST-NO	2A@ 110VDC	PC	1-1/4" x 3/8" x 3/4"	Gold Control/SDI102D		.03	\$4.95	\$4.4
10404 DI	0	0.45400	ODOT NO	Solid State Relay DC loads only	20						
18194-RL	Q	3-15VDC	SPST-NO	3A @ 480VAC	PC	1-11/16" x 3/8" x 3/4"	Gold Control/SAI4003D	mineralizada	.03	\$5.95	\$5.4
(7454 D)		0.001100		IEW Solid State Relay AC loads only							
17154-RL	G	3-32VDC	SPST-NO	10A @ 480VAC	SCW	2-7/8" x 1-1/2" x 1"	Gold Control/SAP4810D		.11	\$7.95	\$6.9
mare Di		0.00000		IEW Solid State Relay AC loads only							
17155-RL	Н	3-32VDC	SPST-NO	25A @ 480VAC	SCW	2-7/8" x 1-1/2" x 1"	Gold Control/SAP4825D	UL	.11	\$11.95	\$9.9
				IEW Solid State Relay AC loads only							
17157-RL	Н	3-32VDC	SPST-NO	40A @ 480VAC	SCW	2-7/8" x 1-1/2" x 1"	Gold Control/SAP4840D	UL	.11	\$15.95	\$11.9
	_			IEW Solid State Relay AC loads only	•						
17288-RL	G	3.5-32VDC	SPST-NO	20A @ 12 to 480VDC	SCW	2-1/4" x 1-3/4" x 1-1/4"	Gold Control/SDP4020D	CE	2	\$12.95	\$9.9
				IEW Solid State Relay DC loads only	,						
7289-RL	G	3.5-32VDC	SPST-NO	40A @ 12 to 480VDC	SCW	2-1/4" x 1-3/4" x 1-1/4"	Gold Control/SDP4040D	CE	2	\$16.95	\$14.9
				IEW Solid State Relay DC loads only							
18500-IN	T			Thermal pad for Solid State Relay.2- C. Thermal Conductivity: .9 W/m-k F			· 4500VAC		.001	\$0.49	Call
C=PC MOL	IAIT	·		•				01111 / 515	DID	/ 10 11	(004
J=PU IVIU	ווונ	/ 20K=2	OLDER .	/ SCW=SCREW / SKT=SC	JUKET /	QC1=.25" QUICK CONN	/ QC2=.187" QUICK C	ONN / DIP=	אוט	/ UL=U	IL/CSA



26

A

SOLID STATE INTERFACE MODULE

STOCK	FIG.	IN/OUT	FUNCTION	RATINGS	CONN.	DIM. LWH	MFG. PART N	LISTED	WT.	1EA	12-EA
14419-RL	A	35-60VAC/DC	SPST	6mA Max @ 60V in, 4KV isolation	PC	1-11/16" x 9/16" x 1"	GRAYHILI/PN 70-IDC5G	UL	.1	\$3.95	\$3.55
122	nout Mo	dula Interface	hotwoon Ext	Loads and Microproposar 2 GV Output (E)	VDC Namimal	0 10m1					

Gold Plated Contacts, All Lines Wired Through.

DB-25 DATA CABLES

STOCK #	DESCRIPTION	WT	1EA	5+EA
2887-CB	6' DB-25 Male/Male	.5	\$4.95	\$4.49
7716-CB	6' DB-25 Male/Female	.5	\$4.95	\$4.49
11451-CB	10' DB-25 Male/Female	.7	\$5.95	\$5.45
11452-CB	15' DB-25 Male/Male	.9	\$7.95	\$7.45
11453-CB	15' DB-25 Male/Female	.9	\$7.95	\$7.45
11454-CB	25' DB-25 M/M Cable	1.4	\$10.95	\$10.45
11455-CB	25' DB-25 M/F Cable	1.4	\$10.95	\$10.45
11456-CB	50' DB-25 M/M Cable	2.8	\$20.95	\$19.95
11457-CB	50' DB-25 M/F Cable	2.8	\$20.95	\$19.95
11459-CB	100' DB-25 M/F Cable	5.5	\$38.95	\$36.95

DB-25 M TO HALF PITCH **CENTRONICS**

IEEE 1284 compliant, 10ft. parallel printer cable. For use with Standard, ECP & EPP printer ports. Cable has a DB-25 male on one end and a 36pin Half Pitch Centronics male on the other. Platnium jacket with with foil & braided shielding. Molded strain relief on connectors

L: 10ft		WT: .8
STOCK #	DESC.	1EA
16238-CB	10ft. IEEE Printer Cable	\$0.99

RS232 BREAK-OUT BOX

Used to test & rewire RS232 interfaces. Unit gives you control of interface. 10 Bi-Polar LEDs monitor all std signals + 2 spare LEDs for

your use. Switches & jumper positions allow reconfiguration of the 24 active lines. 8" flat ribbon cable to DB-25 Male connector, panel mounted DB-25

7865-MI	DES Breakou		1EA \$23.95	5+EA \$22.55
L: 3-1/2"	H: 3-1/4"	T: 1"		WT: .3
	nector. 20 jum	•	cluded.	

KVM CABLE

6ft KVM (Ketboard/Video/Mouse) cable with 10" breakout on each end. Color coded 2 PS-2 Males on bothends with DB-15HD male on one end and DB-15HD female on other. Connect multiple computers to KVM switch

L: 6ft WT: 5 6ft KVM Cable \$7.95 14258-CB

6FT. MONITOR CABLE

Hi-Density DB-15 connectors. Gold plated pins. Platinum jacket,

filters on both ends.	200
L: 6ft.	WT: .47
STOCK # DESC.	1EA

.: 6ft.		WT: .47
STOCK #	DESC.	1EA
18095-CB	DB-15HD M/M Cable	\$2.49

DB-9 EXTENSION CABLES

DB-9 connectors. Gold Plated Pins

STOCK #	DESCRIPTION	WT.	1EA	5+EA
8641-CB	6' DB-9 Male/Male	.22	\$2.95	\$2.49
8642-CB	6' DB-9 Male/Female	.22	\$2.95	\$2.75
8643-CB	10' DB-9 Male/Male	.4	\$3.49	\$2.95
8644-CB	10' DB-9 Male/Female	e .4	\$3.49	\$2.95

MONITOR CABLES

Hi density DB-15 connectors Gold Plated Pins

STOCK #	DESCRIPTION	WT.	1EA	5+EA
8647-CB	6' Monitor Cbl. M/F	.2	\$3.95	\$3.49
12259-CB	10' Monitor Cbl. M/M	1 .5	\$4.95	\$4.49
8649-CB	10' Monitor Cbl.M/F	.2	\$4.95	\$4.49
10512 CD	25! Monitor Chi M/M	2	\$10 OF	\$46.05

6 FT FIREWIRE CABLE

IEEE 1394 Firewire cable with males on both ends. Black jacket with molded black strain relief on connectors. UL listed, RoHS compli-

STOCK #	DESC.	1EA
17262-CB	6ft, Black Firewire Cable	\$2.95

RS232 CABLE

10ft serial cable with a DB9-Fe male on one end and a DB25 male on the other. Molded strain reliefs

L: 10'		W	/T: .5
STOCK #	DESC.	1EA	10+EA
12919-CB	10ft. RS232 Cable	\$2.95	\$2.49

6FT. DB-9 CABLE

DB-9 cable with Gray jacket and Female DB-9 molded connectors on both ends. All lines wired

L: 6ft		WT: .5
STOCK #	DESC.	1EA
17985-CB	6ft. DB-9F/F Cable	\$4.95
	E STATE OF THE STA	The state of the s

NULL MODEM CABLE

DB-9 connectors. Gold plated pins.

VVIII CU U	3 10110	7440							
DB-9F	1+6	2	3	4	5	7	8	NC	
DB-9F	4	3	2	1 & 6	5	8	7	NC	
1 • 10ft							W	T: 4	

STOCK #	DESC.	1EA	5+ EA
18892-CB	F/F NULL Modem Cable	\$3.25	\$2.95

COMPUTER ACCESSORIES THIN GENDER CHANGERS

Ser am mile marie an	estacione estac	12 20	CONTRACTOR OF
Sem th		0	
A Cold plated a	В	C	D

Description is gender changer configuration.

STOCK #	FIG	DESCRIPTION	1EA	5+EA
7006-PL	Α	DB-9 Male/Male	\$1.95	\$1.65
7007-PL	A	DB-9 Female/Female	\$1.95	\$1.65
11216-PL	В	DB-15 Male/Male	\$2.95	\$2.39
11217-PL	В	DB-15 Female/Female	\$2.95	\$2.39
8036-PL	C	DB-15 Hi Den. M/M	\$3.95	\$2.49
8037-PL	C	DB-15 Hi Den. F/F	\$3.95	\$2.49
7008-PL	D	DB-25 Male/Male	\$1.95	\$1.65
7009-PL	D	DB-25 Female/Female	\$1.95	\$1.65

SERIAL PORT ADAPTERS

DB-9 to DB-25 serial Port Adapter, Connections shown below DB-9 to DB-25 DB-9 to DB-25 DB-9 to DB-25 6 20 8 8 WT:.1

DB9 Male/DB25 Female

DB9 Female/DB25 Male **USB CABLES**

4724-PI 8042-PL

USB inter-connect cables



\$1.95 \$1.59

WT: .1

STOCK #	DESCRIPTION	WT.	1EA	5+EA
11160-CB	6ft. USB A/A M/M	.15	\$2.95	\$2.59
12389-CB	6ft. USB A to A M/F	.15	\$2.95	\$2.59
11161-CB	6 ft. USB A to B M/M	.16	\$2.95	\$2.59
12390-CB	10ft, USB A to B M/M	.22	\$3.95	\$3.59

2 FT USB CABLE

USB 1.1 extension cable with a TYPE A male on one end and a Type A Female on the other. Charcoal jacket with molded strain reliefs.

STOCK #	DESC.	1+EA
18481-CB	2ft.USB Cable	\$1.29

GOLD USB CABLE

Type A male to Type B Male USB cable. Gold plated connectors.

L: 6ft		WT: .2
STOCK #	DESC	IEA
15743-CB	6ft, USB A/B Cable	\$1.49

2.0 USB CABLE

USB 2.0 cable with a TYPE A male on one end and a Type B

L: 36"	other. Diack jacket.	N	/T: .1
STOCK #	DESC.	1+EA	25+EA
18976-CB	36in USB 2 Cable	\$1.49	\$1,25

DATA SWITCHES

Data switches with gold contact switch, Metal case, and non-slip feet. All lines wired through. Available as listed below in most standard configurations such as High Density & Standard DB-15, Phone jacks, 5 Pin DIN, Mini 8 pin DIN, BNC and Centronics (Printer).



W: 7"	D: 5-1/2"	H: 2-1/4"	WT: 3

STOCK #	CONN	COM. CONN.	VO CONN.	DESCRIPTION	150	DICA
18604-SW	DB-25	DB-25 Female	4X DB-25 Female	4 way Data Switch with DB-25 Connectors	\$18.95	\$17.95
4703-SW	DB15	DB-15 Female	4X DB-15 Females	4 Way Data Switch with Std. DB-15 Connectors	\$15.95	\$12.95
4702-SW	DB15HD	DB-15HD Female	4X DB-15HD Females	4 Way Data Switch with DB-15 Hi Density Conn.	\$19.95	\$17.95
4705-SW	Mini 8 Pin DIN	Mini 8P DIN Female	4X Mini 8 DIN Females	4 Way Data Switch with Mini 8 Pin Din	\$18.95	\$17.95
					1 1202	

MOBILE COM. PACK

Universal cable adapter kit allows you make up many communication cables. Set has a retractable 32in. USB cable with Type A Male on 1 end & Type A Female on other. Includes the following Adapters: USB A-F to RJ45 USB A-N

USB A-M to USB Mini B USB A-M to RJ45 USB A-M to USB B-M USB A-F to RJ11 USB A-M to USB Mini 4 USB A-M to RJ11 USB A-M to USB Mini 5 All stored in folding case

NOTE: Some combinations can damage Computer or external systems. Varify Compatability

STOCKA	DESC.	1EA
18471-PL	Mobile Comm. Adapters	\$9.95

6 FT USB CABLE

6ft. USB cable with a TYPE A male on one end and a Type B Male on the other. Platnium jacket with molded black strain relief on Type A on connector.

WT: L: 6ft 16144-CB 6ft.USB Cable \$1.25

USB CAMERA CABLE

KODAK, USB cable with a Type A male on one end and a 4 Pin Mitsumi Male on the other. For C-300, Camera Dock 6000,4 Dock II, Dock 420/443, Various

CX, DX, LX cameras, Printer Dock, Dock 4000,6000, Plus. Black jacket with molded black strain relief on connectors. Ferrite filter on Mini Mitsumi end L: 4.5ft WT: .13

17505-CB 4.5ft. Black USB Mitsumi Cable

5 FT USB CABLE

3COM P/N 10043601 FOXCONN P/N CUDA005C-K14 USB 1.1 cable with a Type A male on one end and a Type B Male on the other. White jacket with molded strain relief on connectors. L: 5ft

17973-CB 5ft. White USB Cable \$0.59

USB CHASSIS BRACKET

Computer chassis bracket Port Adapters with 2 Type "A" Female connectors. 6" cables to header sockets.

WT: .13 11162-CB **Dual 1X4 Header** \$3.59

20" SATA CABLE

MFG: FOXCONN P/N: C95764 SATA Male/Male data cable

for internal drive connection. Both ends have Latches. L: 20' WT: .035

18201-CB 20" SATA Cable



Power adapter cables for upgrading or add aditional to SATA Hard Drives. 18765 Converts from conventional 4 Pin IDE connector

to 1 SATA Power jack 18075 Converts from conventional 4 Pin IDE connector

to 2 SATA Power jacks 18076 Splits 1 SATA into 2 SATA Jacks

L: 6"		WT: .05
STOCK	DESC.	TEA
18765-CB	IDE to Single SATA Cable	\$0.99
18075-CB	IDE to 2 SATA Power Cable	\$5.95
18076-CB	SATA Splitter Power Cable	\$4.05



USB **GENDER CHANGERS**

Description is gender changer configuration.

		**	1
STOCK #	DESC.	1EA	5+EA
12452-CB	A Female/B Female	\$3.75	\$3.25
12453-CB	A Male/B Female	\$3.50	\$2.95
12454-CB	A Female/ B Male	\$3.50	\$2.95
15476-PL	A Male/A Male	\$3.50	\$2.95
15477-PL	A Male/A Female	\$3.50	\$2.95
15478-PL	A Female/A Female	\$3.50	\$2.95
15479-PL	B Male/B Male	\$3.50	\$2.95
15480-PL	B Female/B Female	\$3.50	\$2.95



USB/RJ ADAPTERS

Description is connector configuration. L: 2-1/4" WT: .04 15485-PL A Male/RJ-45 Male \$2.95 \$2.50 15486-PL A Female/RJ-45 Male \$2.95 \$2.50



USB-PS2 ADAPTERS

Computer keyboard Adapters, 2 Type available: 6 Pin Mini DIN Female to USB Type A Male 6 Pin Mini DIN Male to USB Type A Female

L: Z-1/4		WI:.U4		
STOCK #	DESC.	1EA	10+EA	
14256-PL	PS2-F to USB-A-Male	\$1.95	\$1.59	
14257-PL	PS2-M to USB-A-Female	\$1.95	\$1.59	

USB 4 PORT INTERNAL HUB

Hub supports full speed (12Mbps) and low speed (1.5Mbps) devices. Features 1 upstream type "B" female port and 4 downstream type "A" female ports. Includes 1ft upstream cable (A male/B male), 6in long power cable (connects into HDD/ CD/Floppy Power).

		V	VI:.5	
STOCK #	DESC.	1EA	5+EA	
12484-CP	USB 4 Port Hub	\$29.95	\$26.95	

2.0 USB CABLE

USB 2.0 cable with a TYPE male on one end and a Type B Male on the other. Black jacket.

E. OIL.		•	
STOCK #	DESC.	1+EA	25+EA
18976-CB	3ft. USB 2.0 Cable	\$1.25	\$0.99

6FT. DB-9 CABLE

DB-9 extension cable with white jacket and a Female molded connector on one end Male on other. All lines wired through. L: 6ft



SECURE ON-LINE ORDERING www.mpja.com

USB 107-KEY KEYBOARDS

Black OR Beige 107 key,
4ft. cable with USB Type A
male connector. Keysfor ACPI power
management "WAKE UP", "SLEEP" & "POWER". Black
base & keys with white letters OR Beige base & keys with Black letters, tactile feedback, LED's for Number, Caps. & Scroll Lock. 98/ME/2K/NT/XP compatable, FCC/CE

W: 17-3/4"	D: 6-1/4" H: 1"	WT: 2.1
STOCK #	DESC.	1EA 5+EA
15903-KB	USB Black Keyboa	ard \$8.95 \$7.95
15930-KB	USB Beige Keybo	ard \$8.95 \$7.95

MINI PS-2 **KEYBOARDS**

Mini footprint 88 key key board. With Windows 95™.

enhanced keys 6ft. cord with 6 pin Mini DIN connector. Two colors to choose from. UL/CSA/CE Listed

L: 11-3/8"	W: 5-5/8"	H: 1"	WT	: 1.5
STOCK #	DES	SC.	1EA	5+EA
	Ivory Mini K Black Mini I		\$29.95 \$29.95	\$28.95 \$28.95


RETRACTABLE **USB CABLE SET**



USB 2.0 adapter set includes retractable 1m cable with Type A Male on 1 end & Type A Female on other. Adapters have Type A Male on end while other end include: Type B Male, Mini B Male, Micro 8 Pin for Kodak and Micro 5 Pin for Panasonic. Includes a cloth storage pouch L: 1m Ext/11cm retracted WT: .22

18723-CB Retractable USB Adaptors Set

USB/WIFI DONGLE



ZyDAS WLAN wireless net dongle with on board antenna. No case/cover

Standards: IEEE802.11b 11Mbps 802.11g 54Mbps USB: 2.0

Supports: WPA, 64/128 WEP security,

Access point & ad-hoc network.
System: Windows 98SE-XP Pro. (Not tried with Vista) MAC: OS-X

Pentium 233 UP, 64Mb RAM/100Mb of disc USB Port.

Transmit: 17dBm

Receive (@11Mbps): -80dBm@ 8% FER. Range: 50-200m dépending on conditions/building Driver NOT provided. Available on-line.

L: 2-7/8" O/A W: 7/8' WT: .018

WiFi-USB LAN Dongle 18569-CP \$5.95

USB TO SERIAL CONVERTER

Allows you to free up your RS-232 Port or add Port to Laptop. No IRQ required.

Supports auto handshake mode, remote wake-up & power management. Works with ISDN terminal adapters, moderns. Driver files provided on disk, latest drivers available Via Internet from Mfg. website. No external power required. Type "B" Female input, DB-25Male output, includes 6ft cable with USB Type A male on one end & Type "B" male on other.

		WI: 5
TOCK #	DESC.	1EA
1246-CP	USB RS-232 Link	\$19.95

ORDERS: CALL 800-652-6733 FAX 800-432-9937

DISC DRIVE CABLES



Cables to inter-connect floppy or hard drives to your system controllers

7368-CB for 5-1/2 or 3-1/2 A/B floppys: 34 Pin header to two 34 Pin edge connectors & 34 Pin headers. 7369 & 7981-CB For IDE drives: 40 Pin Header to one/


two 40 Pin Headers

7982 & 7983-CB For SCSI drives: 50Pin header to one/ two 50 Pin headers

W	Т		1	7	

STOCK #	DESC.	YEA	5+EA
7368-CB	28" Dual Floppy Cable	\$2.95	\$1.95
7369-CB	24" IDE Dual Hard Drive	\$2.95	\$1,95
7981-CB	18" IDE SingleHard Drive	\$1.95	\$1.59
7982-CB	18" SCSI Single Hard Drive	\$2.95	\$1.95
7983-CB	24" SCSI Dual Hard Drive	\$2.95	\$1.95

AT/ATX POWER CABLE EXTENSION



Motherboard power extension cable. Connects between your power supply connectors & the mother board. AT: 12 conductor ATX: 20Conductor (ATX-V1.3)

L: 8" (AI) 6"	(AIX)		WT: .15
STOCK #	DESC.	1EA	5+EA
11219-CB	AT Extension Cable	\$3.95	\$2.95
15430-CB	ATX Extension Cable	\$3.95	\$2.95

DISC DRIVE POWER CABLES



\$1.95

\$1.75

Adapt large 4 Pin molex power connectors to mini 4 pin connectors. "Y"s for connecting two drives from one connector.

			NT: .044
STOCK #	DESC.	1EA	5+EA
7206-CB	Large to Mini	\$1.95	\$1.75
7207-CB	Large "Y"	\$1.95	\$1.75
7208-CB	Large to 2 Mini (Y)	\$1.95	\$1.75



11218-CB Large to Mini & Large

Power adapter cables for upgrading or add aditional to SATA Hard Drives

18765 Converts from conventional 4 Pin IDE connector to 1 SATA Power jack

18075 Converts from conventional 4 Pin IDE connector to 2 SATA Power jacks 18076 Splits 1 SATA into 2 SATA Jacks

L: 6"		WT: .05
STOCK #	DESC.	1EA
18765-CB	IDE to Single SATA Cable	\$0.99
18075-CB	IDE to 2 SATA Power Cable	\$5.95
18076-CB	SATA Splitter Power Cable	\$4.95

PREMIUM RGB CABLE

Monster Cable 800 series, THX Certified, Premium Component Video (RGB) cable. 3 color coded video cables. 95%Copper braid & 100% aluminum foil double shielding. 24kt gold plated Red, Blue &

L: 1m	WT: .85	
STOCK #	DESC	1EA
18473-CB	Monster RGB Cable	\$8.95

A/V CABLES

Premium Stereo audio & composite video cable with Oxygen free copper wire. Left & Right Stereo cables & video coax. Copper braid & aluminum foil double shielding, stranded center conduc-

tor. Molded strain relief 24kt gold plated Red, White & Yellow coded RCA Plugs.

STOCK #	DESCRIPTION	WE	TEA
17188-CB	9ft. H/D A/V Cable	1.2	\$7.95
17189-CB	13ft. H/D A/V Cable	1.4	\$9.95
		1.4	į.

FIBER OPTIC DUBBING CABLES

Siamese dubbing cable with fiber optic cable with TOSLINK connec tors for audio and coax cable with Gold plated RCA Plugs for video. L: 6/12ft

15504-CB 12' F/Optic Dubbing Cable \$8.95 \$7.95 16740-CB 6' F/Optic Dubbing Cable \$2.95

WT: .4/.62

18IN. FIBER OPTIC **AUDIO CABLE**

18" optical cable with 3.5mm optical mini plugs on both ends. For digital interconnects between properly equipped Amps, Tuners, CD's etc. Max loss: 2db/m @ 600nM wavelength. Min bending radius: 22mm (1in).

L: 18in.	W	DESG. VEA	
STOCK #	DESC.	1EA	
15257-FO	18in. Optical Cable	\$0.99	

6FT. FIBER OPTIC AUDIO CABLE

6 ft. optical cable with 3.5mm optical mini plugs on both ends. For digital interconnects between properly equipped Amps. Tuners, CD's etc. Max loss: 2db/m@600nM wavelength. Min bending radius: 22mm (1in).

L: 6ft	WT: .14
STOCK N DESC.	1EA
14493-CB 3.5mm Optical Cable	\$1.49

6FT. FIBER OPTIC CABLE

6ft. TOSLINK to 1/8" Optical Phone Plug cable. For digital

cD's etc. Max loss: .2db/m. Min bending radius: 30mm	
L: 6ft	WT: .09

L: 6ft			WT: .09
STOCK	DESC.	TEA	10eEA
15533-FO	Fiber Optic Audio	o Cable	\$1.99

OPTICAL SWITCH

3 way bi-directional optical switch with 3.5mm optical in/outputs. Select from 3 different audio sources, or receivers. Includes TOSLINK to 3.5mm optical adapters.



		W1: .23
STOCK #	DESC.	TEA
15189-FO	Fiber Optic Switch	\$4.99

PREMIUM A/V CABLES



Premium Stereo audio & composite video cable made with Oxygen free copper wire. Left & Right Stereo cables & video coax. Copper braid & aluminum foil double shielding. 24kt gold plated Red, White & Yellow coded

STOCK #	DESCRIPTION	WT.	TEA	5+EA
16885-CB	6ft. Prem. A/V Cable	.6	\$29.95	\$27.95
16886-CB	12ft. Prem. A/V Cable	1.1	\$36.95	\$33.95
16887-CB	25ft. Prem. A/V Cable	2.2	\$54.95	\$49.95

HEAVY DUTY A/V CABLES



Heavy duty stereo audio & composite video cable with Oxygen free copper wire. Left & Right Stereo cables & video coax. Copper braid & aluminum foil double shielding. Molded strain relief 24kt gold plated Red, White & Yellow coded RCA Plugs.

STOCK #	DESCRIPTION	WT	TEA	5+EA
16891-CB	6ft. H/D A/V Cable	.6	\$15.95	\$12.95
16892-CB	12ft. H/D A/V Cable	1.1	\$24.95	\$21.95
16893-CB	25ft. H/D A/V Cable	2.1	\$45.95	\$41.95

STANDARD A/V CABLES



Stereo audio & composite video cable. Left & Right Stereo cables & video coax. Copper braid. Molded strain relief 24kt gold plated Red, White & Yellow coded RCA Plugs.

STOCK #		DESCRIPTION	WT.	TEA	SHEA
16896-CB	3ft.	Std. A/V Cable	.2	\$4.95	\$4.49
16898-CB	12ft.	Std. A/V Cable	.6	\$6.95	\$6.49


A/V PATCH CABLES WITH RCA PLUGS



Single & Dual cables for audio/ video equipment patching

STOCK #	DESCRIPTION	WT.	TEA	10+EA
4906-TV	6ft. Single Cable	.11	\$1.25	\$0.99
4907-TV	12ft. Single Cable	.18	\$1.95	\$1.75
4903-TV	3ft. Dual Cable	.33	\$1.49	\$1.35
4904-TV	6ft. Dual Cable	.48	\$1.75	\$1.49
4905-TV	12ft. Dual Cable	.52	\$2.49	\$2.25

1/8" PHONE STEREO **CABLES**



Black cable with molded connectors. M = Male, F = Female. WT: 12

STOCK #	DESC.	1EA	10-EA
11291-CB	12ft. 3.5mm M/F Cable	\$1.69	\$1.49
11292-CB	12ft. 3.5mm M/M Cable	\$1.69	\$1.49
11293-CB	6ft. 3.5mm M/M Cable	\$1.65	\$1.49

PREMIUM **RGB CABLES**



Premium Component Video (RGB) cable. 3 color coded video cables with OFC conductors, 93%Copper braid & 100% aluminum foil double shielding. 24kt gold plated Red, Blue & Green coded RCA Plugs with metal shells.

STOCK #	DESCRIPTION W	T.	1EA	5+EA
16901-CB	3ft. Prem. RGB Cable	1	\$24.95	\$23.95
16902-CB	6ft. Prem. RGB Cable	2	\$34.95	\$32.95
16903-CB	12ft. Prem. RGB Cable	3	\$37.95	\$36.95
16904-CB	25ft. Prem RGB Cable	5	\$49.95	\$47.95

DELUXE **RGB CABLES**



Heavy duty Component Video (RGB) cable. 3 color coded video cables with OFC conductors, 69%Copper braid & 100% aluminum foil double shielding. Molded strain relief, 24kt gold plated Red, Blue & Green coded RCA Plugs

STOCK #	DESCRIPTION	AΤ	1EA	5+EA
16907-CB	6ft. H/D RGB Cable	2	\$34.95	\$32.95
16908-CB	12ft. H/D RGB Cable	3	\$37.95	\$36.95
16909-CB	25ft. H/D RGB Cable	5	\$49.95	\$47.95


DELUXE RGB/STEREO CABLES



Heavy duty Component Video (RGB) & Stereo cable. 3 color coded video and 2 Audio cables with OFC conductors, 86% Video/69% Audio Copper braid & 100% aluminum foil double shielding. Molded strain relief, 24kt gold plated Red. White. Blue & Green coded RCA Plugs

STOCK #	DESCRIPTION	WT	TEA	5+EA
16912-CB	12ft. RGB/Stereo Ca	ble 5	\$29.95	\$27.95
16913-CB	25ft. RGB /StereoCa	able 6	\$39.95	\$37.95

STEREO AUDIO **CABLES**



L: 3ft.			WT: .3
STOCK#	DESC.	1EA	25+EA
15788-CB	3ft Gold Stereo Cable	\$1.95	\$1.75

1/8" PHONE AUDIO CABLE


Audio patch cables with 1/8" stereo phone plug connectors on both ends. Molded strain reliefs

A: 5ft. Platinum jacket/Blue & Green connector

B: 5ft. Platinum jacket/Green Connectors/RFI Filter on ends

		V	VT: .13
STOCK #	DESC.	1E4	10+EA
15561-CB	(A) Platinum Jacket	\$1.29	\$1.09
15562-CB	(B) Platinum Jacket/Filters	\$1.29	\$1.09

VGA TO RGB CABLE



STOCK #	DESC	W	T. I LEA
17224-CB	6ft VGA to RGB Cable	.3	\$8.95
17225-CB	12ft VGA to RGB Cable	.6	\$12.95

HDMI CABLE



STOCK #	DESC.	WT.	TEA
16864-CB	12ft. Hi Def. TV Cable	2	\$26.95

HDMI/DVI **ADAPTERS**

HDMI/DVI Cable adapters with gold plated connectors. Top quality for the highest quality viewing.

		W	T: .1	
	STOCK #	DESCRIPTION	1EA	5+EA
	16870-PL	HDMI-F to DVI-M	\$11.95	\$9.95
	16871-PL	HDMI-M to DVI-F	\$11.95	\$9.95
	16872-PL	HDMI-F to DVI-F	\$12.95	\$10.95
	16873-PL	HDMI-M to DVI-M	\$11.95	\$9.95

HDMI COUPLERS



HDMI cable Gender changers/Couplersaccessories. Top quality for the highest quality viewing.


L: 12"		WT: .1	
STOCK II	DESCRIPTION	1EA	Setta
16875-PL	HDMI-F to HDMI-F	\$12.95	\$11.25
16876-PL	HDMI-M to HDMI-M	\$12.45	\$10.95
16877-PL	HDMI-F to HDMI-M	\$12.45	\$10.95

HDMI SPLITTER

HDMI signal splitter. HDMI Male connector with 1ft lead connects to 2 HDMI Females. Gold plated connectors

L: 12"		WT: .6	
STOCK	DESCRIPTION	TEA	5+EA
16880-PL	HDMI Signal Splitter	\$19.95	\$18.95

RG-58 CABLES



Cable with BNC Male connectors on both ends. Black with molded strain relief

STOCK #	DESCRIPTION	WT.	1EA	10+EA
8011-CB	10ft 50ohm RG-58	1	\$3.95	\$3.49
8012-CB	25ft 50ohm RG-58	1	\$4.95	\$4.49
8013-CB	50ft 50ohm RG-58	1.5	\$8.95	\$7.49
8014-CB	100ft 50ohm RG-58	5	\$15.95	\$14.95

RG-59 CABLE WITH BNC CONN.



Convienent lengths of black 75 ohm RG-59 CCTV cables. With strain relieved male BNC connectors on both ends. Use to interconnect Cameras, Monitors, Switchers etc.

STOCK	DESCRIPTION	WT.	TEA	当+6人
8952-CB	3ft. RG-59 Cable	.3	\$3.25	\$2.95
8953-CB	6ft. RG-59 Cable	.6	\$3.85	\$3.49
8954-CB	12ft. RG-59 Cable	2	\$4.50	\$3.95
8955-CB	25ft. RG-59 Cable	3.1	\$5.95	\$5.49
8956-CB	50ft. RG-59 Cable	4.2	\$8.95	\$7.95
12386-CB	100ft. RG-59 Cable	8.5	\$14.95	\$12.95

6FT HDMI CABLE

HDMI (High Definition Multimedia Interface) cable with gold plated male connectors and filters on both ends. Top quality signal for all Hi-Def. TV, Set Top cable boxes, recorder/players etc. Supports standard, enhanced, & High Definition video plus standard &

L: 2m (6ft.)	iu.	WT: .5
STOCK #	DESC.	TEA
16921-CB	Hi Def. TV Cable	\$14.95

4m DVI CABLE

ULTRALINK Platinum Series, 13 ft. with a DVI-D (24+1, Dual Link-2X Digital cable) male connector on both ends. Dark Gray cable with Black molded connectors. Gold shells & Pins, Quad shielded, silver plated copper conductors,

L: 13ft.		WT: 1.1	
STOCK	DESC.	TEA	
18107-CB	Illtral ink 13ft DVI-D Cable	\$6.05	

DVI/VGA ADAPTER

MFG: PULSE DVI-A Male (12+5) to VGA DB-15HD Female molded adapter. Top quality for the highest quality viewing.

_			
	18200-PL	DVI-VGA Adapter	\$11.95
	STOCK #	DESC.	1.EA
	L: 1-7/8"		WT: .075

1FT. MONITOR CABLE

Hi-Density DB-15 Male connectors on both ends. Black jacket with Dark Blue molded connectors. Pins 4 & 11 tied to shell

L: 1ft.		WT: .14
STOCK #	DESC.	1EA
18654-CB	DB-15HD M/M Cable	\$1.79

6FT DVI CABLE

6 ft. with a DVI-D ((18+1, Single Link- Digital cable) male connector on both ends. Platinum cable with white molded connectors

L: bπ.	W	1:.44
STOCK #	DESC.	1EA
16587-CB	Platinum 6ft. DVI-D Cable	\$1.25


UL LISTED COAX CABLES WITH "F" CONNECTORS

UL listed CATV cables. Convienent lengths of black RG-6 cable. With strain relieved male "F" connectors on both ends. Suitable for commercial installations, 64% braid & 100% foil shield.

STOCK #	DESCRIPTION	WT	1EA	5+EA
5948-TV	15' UL RG-6 Cable	.7	\$2.99	\$2.49
5949-TV	25' UL RG-6 Cable	10	\$4.25	\$3.95
5950-TV	50' UL RG-6 Cable	2.2	\$7.50	\$6.95
5951-TV	75' UL RG-6 Cable	3.1	\$12.95	\$11.95
5952-TV	100' UL RG-6 Cable	4.2	\$13.95	\$12.95
5953-TV	150' UL RG-6 Cable	6.2	\$19.95	\$18.80

DVI-VGA CABLE

6 ft. with a Male DVI-A (16+1, Single Link-Analog) connector on one end and a VGA Male DB-15HD connector on other (no Pin 9). Platinum cable with molded connectors and a ferite suppressor on each end



В

VIDEO COAX TO UTP CONVERTER

Isolated balun converts video signals using coaxial cable to telcom UTP cable (CAT 3-5)

Sends color video up to 1000ft or B/W up to

2000ft. Bandwidth 35Hz to 4.5MHz. Transpedance: 75ohm unbalanced to 100 ohm balanced. Use existing phone wiring to send video. Connects to RJ-45 pins 7&8.

1 needed at each end

Des n Au	*** 0/0	11. 770	***	
STOCK #	DESC.		TEA	5+EA
12238-ST	BNC-M to RJ	45	\$24.95	\$19.95.
12239-ST	BNC-F to RJ-	45	\$24.95	\$19.95
12240-ST	"F" Female to R	J-45	\$24.95	\$19.95

H- 7/9"

6FT DVI CABLE

6 ft. with a DVI-D ((18+1, Single Link-Digital cable) male connector on both ends. Gray cable with Gray molded connectors

L: 6ft.	WT: .44	
STOCK #	DESC.	1EA
16594-CB	Gray 6ft. DVI-D Cable	\$2.95

CAMERA **VIDEO/POWER CABLE**

Siamese cable for cameras. Cable splits out 8" from ends into a video cable with a BNC

male on one end and a RCA male on other and a power cable with a 2.1mm I/D coaxial power Plug on end (same end as video RCA) and a 2.5mm I/D power Jack on other. Includes a BNC Male to RCA Female adapter.

STOCK #	DESC.	WT.	TEA
15460-WI	25ft. Camera Cable	0.6	\$6.95
15461-WI	50ft. Camera Cable	1.8	\$9.95
15462-WI	100ft. Camera Cable	3.4	\$17.95
15463-WI	150ft. Camera Cable	4.9	\$22.95

S-VIDEO

5ft-8in. platinum cable with a 4 pin mini DIN male connectors & ferrite filters on both ends. Quality cable


L: 5ft/8in	WT: .22	
STOCK #	DESC.	1EA
16236-CB	Platinum S-Video Cable	\$0.95

S-VIDEO CABLE

5ft.-8in. black S-Video cable with a 4 pin mini DIN male connectors & ferrite filters on both ends. Quality cable with molded strain relief on connectors

L: 5ft/8in		WT: .22
STOCK	DESC.	TEA
16303-CB	Black S-Video Cable	\$2.9

S-VIDEO



6ft. cable with a Gold 4 pin mini DIN male on both ends. Ideal patch cord from DVD/ Sat. receiver to your TV. Quality cable with molded strain relief on connectors

L: 6ft.		WT: .12		
STOCK	DESC	TEA	5+EA	
11052-CB	6ft S-VHS Cable	\$3.50	\$2.95	

CB/RADIO EXTENSION **CABLES**



10in. long, Small, flat pin extension cables. Male connector on one end, mating Female on other. Color coded

.110" flat quick connect type Pins in plastic housing.

178

178

	1	
DESC.	WI	TEA
2 Pin Extension Cable	.02	\$1.29
3 Pin Extension Cable	.03	\$1.95
4 Pin Extension Cable	.05	\$1.95
6 Pin Extension Cable	.07	\$2.95
9 Pin Extension Cable	.09	\$4.59
	3 Pin Extension Cable 4 Pin Extension Cable 6 Pin Extension Cable	3 Pin Extension Cable .03 4 Pin Extension Cable .05 6 Pin Extension Cable .07

CB/RADIO EXTENSION CABLES



2.95

MIT- 001

10in. long, Round pin extension cables. Male connector with .084"O/D round on one end, mating Female on other. Color coded wires. Plastic housing.

L: 10"			
STOCK #	DESC	WT.	TEA
17861-CB	3 Pin Extension Cable	.033	\$2.95
17862-CB	6 Pin Extension Cable	.066	\$4.59
17863-CB	9 Pin Extension Cable	.10	\$6.95

CB/R	ADIO			سعنجنيز	\
65-CB	15 Pin	Extension	Cable	.13	\$12
64-CB	12 Pin	Extension	Cable	.11	\$9
63-CB	9 Pin E	xtension (Cable	.10	\$6

EXTENSION CABLE

10in. long, extension cables with .250" Quick connect type terminals. Male connector on one end, mating Female on other, Color coded wires, Plastic housing


L: 10"	WT: .03/.06		
STOCK	DESC	TEA	
17857-CB	3 Pin Extension/Faston	\$1.95	

"B" SPLICES

Standard type "B" crimp splices. Provides permanent connection for phone or alarm wires.

STOCK #	DESC.	TEA 1		MINNEA
5873-TT	"B" Splice	\$0.15	\$0.10	\$0.09


EURO TERMINAL



10mm terminal Spacing & mounting holes. Voltage: 300V/Rated Current: 30A Wire: 12-22AWGSolid/Stranded 10AWG Solid Recessed screws in top. UL/VDE/CE Listed. RoHS com-

L: 4-5/8"	H: 11/16"	W : 13/16"	WT: .08
STOCK		DESC.	1EA
18538-TS	12 Pc	s. Euro Strip	\$2.95

CIGARETTE ADAPTER



		** * * * * * *
STOCK #	DESC.	1+EA
261-PL	Cigarette Socket Multiplier	\$5.95

RIBBON CABLE

100ft rolls of multiconductor flat ribbon cable. .050" conductor spacing to match up to IDC connectors. Stranded, 28 awg, 105deg "C" 300 volt insulation. Gray PVC insulation with tracer on one edge For SCSI, disc drive and other cables.




STOCK #	DESC.	WT.	I Fak		
8566-WI	9 Conductor Flat	1.5	\$16.95	\$12.95	
8568-WI	20 Conductor Flat	2.7	\$28.95	\$25.83	
8569-WI	25 Conductor Flat	3.4	\$33.95	\$29.95	
8570-WI	34 Conductor Flat	5	\$45.95	\$43.95	
8571-WI	40 Conductor Flat	6	\$57.95	\$56.95	
8572-WI	50 Conductor Flat	7	\$69.95	\$64.95	

QUICK CONNECT SPEAKER TERMINAL



2 or 4 position red & black terminal strip for speakers, audio equipment etc. Solder tabs on back

WT:				.03	
STOCK #	DESC.	TEA	10÷EA		
298-TS	2 Pos. Quick Connect	\$0.50	\$0.39		
297-TS	4 Pos. Quick Connect	\$0.79	\$0.59		



Type A: Side exit, vinyl, 4" tinned red & black leads. Type B: End exit, vinyl cover, 6" tinned red & black leads

STOCK #	DESC.	1EA	25+EA
6392-BT	Side Exit 9V Clip	\$0.25	\$0.22
2600-BT	End Exit 9V Clip	\$0.19	\$0.17

HIGH POWER TERMINAL BLOCK



4 position, end stackable, P.C. mount, terminal blocks. Voltage: 1000V/Rated Current: 90A Wire: 2-20AWG,35mm²

Recessed screws in top. RoHS compliant

L: 60mm	H: 39mm	w:31mm	W1:.18
STOCK #		DESC.	TEA
18522-TS	4 Pos.	Hi-Power Strip	\$1.25

LOCKING DIN PLUG

Full size, 8 Pin. DIN connector with 30deg. turn locking ring. 7 male Pins in 270Deg. circle Plus Pin 8 slight offset from center. Metal body with Soft rubber


strain relief, solder cup pins for #22 Max. L: 2-5/16" [Dia:] .75 O/A WT: .04

STOCK #	DESC	1EA
18778-PL	8Pin DIN Plug	\$2.95

4 COND. MINI COIL CORD

High quality, super flexable, medical grade white coil cord designed for use as medical sensor leads. 12in. collapsed, 80in. extended. 4 color coded # 26 AWG stranded, copper conductors. Ideal for control systems, robots, alarms

MPJA@MPJA.COM





\$0.99 17574-CB Mini Coil Cord



			WT: .0	1
STOCK II	FIG.	DESCRIPTION	1EA	10+EA
11295-AD	Α	RCA Jack to RCA Jack	\$0.45	\$0.36
11296-AD	В	RCA Plug to RCA Plug	\$0.49	\$0.39
11297-AD	C	3.5mm Stereo Jack to 3.5mm Stereo Jack	\$1.95	\$1.59
11298-AD	D	3.5mm Mono Jack to 2.5mm Mono Plug	\$0.95	\$0.79
11299-AD	E	RCA Jack to 3.5mm Mono Plug	\$0.95	\$0.79
11300-AD	F	2X 3.5mm Stereo Jack to 3.5mm Stereo Plug	\$1.25	\$0.99
11301-AD	G	RCA Jack to 1/4" Mono Plug	\$0.75	\$0.59
11302-AD	Н	1/4" Mono Jack to RCA Plug	\$0. 95	\$0.79
11303-AD	- 1	3.5mm Mono Jack to RCA Plug	\$0.95	\$0.79
11304-AD	J	1/4" Mono Jack to 3.5mm Mono Plug	\$0.75	\$0.59
11305-AD	J	1/4" Stereo Jack to 3.5mm Stereo Plug	\$0.94	\$0.79
11306-AD	L	3.5mm Mono Jack to 1/4" Mono Plug	\$0.7~	\$0.59
11307-AD	L	3.5mm Stereo Jack to 1/4" Stereo Plug	\$0.75	\$0.59
11308-AD	M	2X 1/4" Stereo Jack to 3.5mm Stereo Plug	\$1.75	\$1.39
11309-AD	N	2X 3.5mm Stereo Jack to 1/4" Stereo Plug	\$1.50	\$1.19
11400-AD	0	3.5mm Mono to 3.5/1.3mm ID Coxial Plug	\$1.50	\$1.25
11401-AD	Р	3.5mm Mono to 6.5/3mm ID Coxial Plug	\$1.50	\$1.19
15334-PL	Q	Red RCA Plug to Jack Rt. Ang Adapter	\$0.79	\$0.64
15335-PL	Q	Black RCA Plug to Jack Rt. Ang Adapter	\$0.79	\$0.64

AUDIO ADAPTOR & SPLITTER CABLES















			WI: .	J5
STOCK #	FIG.	DESCRIPTION	1EA	10+EA
11420-AC	Α	Black RCA Plug to Red/White RCA Jack (Y)	\$0.89	\$0.69
11421-AC	В	Black RCA Plug to Red/White RCA Plug (Y)	\$0.89	\$0.69
11422-AC	C	Black RCA Jack to Red/White RCA Plug (Y)	\$0.89	\$0.69
11423-AC	D	3.5mm St. Plug to Red/White RCA Plug (Split)	\$0.95	\$0.79
11424-AC	E	3.5mm St. Plug to Red/White RCA Jack (Split)	\$0.95	\$0.79
11425-AC	F	3.5mm Mno. Plug to Red/White RCA Jack (Y)	\$0.95	\$0.79
11426-AC	G	3.5mm St. Jack to Red/White 3.5mm St. Plug (Y)	\$0.95	\$0.79
11427-AC	Н	3.5mm St. Plug to 3.5mm St. Jacks (Y)	\$0.95	\$0.79

3 PIN XLR MIKE CONNECTORS



				WT: .01	
STOCK #	FIG.	DESCRIPTION	WT.	1EA	10EA
2983-PL	Α	XLR Cable Male Mike Connector	.2	\$1.95	\$1.59
2971-PL	В	XLR Cable Female Mike Connector	.2	\$1.95	\$1.59
2972-PL	С	XLR Male Chassis Mike Connector	.2	\$2.25	\$1.79
3136-PL	D	XLR Female Chassis Mike Connector	.2	\$3.95	\$2.95
11403-PL	E	XLR Female to Female Inline Conn.	.15	\$4.45	\$3.59
11404-PL	F	XLR Male to Male Inline Conn.	.13	\$4.25	\$3.39
11405-PL	G	XLR Female to 1/4" Mono Plug	.1	\$4.25	\$3.39
11406-PL	Н	XLR Male to 1/4" Mono Plug	.1	\$3.95	\$2.95

1/8" (3.5MM) PHONE PLUGS & JACKS



STOCK #	FIG.	DESCRIPTION	1EA	10EA	100+EA
2187-PL	Α	Mono Plug Metal Back	\$0.52	\$0.43	\$0.35
1868-PL	В	Mono Plug Plastic Back	\$0.15	\$0.13	\$0.10
5514-PL	Α	Stereo Plug Metal Back	\$0.64	\$0.53	\$0.43
4015-PL	В	Stereo Plug Plastic Back	\$0.37	\$0.31	\$0.25
1927-PL	С	Mono Jack Plastic Back	\$0.50	\$0.46	\$0.39
5515-PL	E	Stereo Enc. Panel Jack	\$0.38	\$0.32	\$0.25

1/4" PHONE PLUGS









.40	2 Sanda	A STATE OF THE PARTY OF
	AV- SERVICE	
ENGLISHED STATE	The state of the s	
		A similar



STOCK #	FIG.	TYPE
4674-PL	Α	Plug
4675-PL	Α	Plug
5518-PL	В	Plug
5519-PL	С	Jack
5520-PL	C	Jack
5521-PL	D	Jack
5522-PL	E	Jack

DESCRIPTION **Red Plastic Back Black Plastic Back** Metal Back **Red Plastic Back Black Plastic Back Metal Back Panel Mount**

10E4 100+E4 1EA \$0.19 \$0.16 \$0.13 \$0.19 \$0.16 \$0.13 \$0.57 \$0.47 \$0.23 \$0.19 \$0.15 \$0.23 \$0.19 \$0.15 \$0.76 \$0.63 \$0.51 \$0.41 \$0.34 \$0.27

WT: .004

VC = Norm	nally Clo	sed Auxillary Tip Contact		WT:	.02
STOCK #	FIG.	DESCRIPTION	1EA	10EA	100+EA
7236-PL	A	Mono Plug Metal Back	\$0.72	\$0.60	\$0.48
7237-PL	В	Mono Plug Plastic Back	\$0.48	\$0.40	\$0.32
7238-PL	A	Stereo Plug Metal Back	\$0.97	\$0.81	\$0.64
7239-PL	В	Stereo Plug Plastic Back	\$0.52	\$0.43	\$0.35

\$1.99

7FT. RIGHT **ANGLE IEC** CORDSET



Removed from Equipment, 6ft, 18-3 AWG SVT platinum jacket, Right Angle power cord for electronic equipment. Standard 3 prong molded plug on one end, right angle IEC female on other end. Rated 120VAC 10A.

L: 7ft		WT: .4
STOCK #	DESC.	TEA
17723-CB	7ft, Right Angle IEC Cord	\$2.45

10FT, LAPTOP **POWER CORD**



6FT. RIGHT ANGLE IEC

18227-CB 10ft Laptop Cordset



Removed from Equipment, 6ft, 18-3 AWG SVT platinum jacket, Right Angle power cord for electronic equipment. Standard 3 prong molded plug on one end, right angle IEC female on other end. CSA listed. Rated 120VAC 10A. L: 6ft

STOCK #	DESC.	1EA
17446-CB	6ft. CSA Right Angle IEC Cord	\$2.49

6FT. RIGHT **ANGLE IEC** CORDSET



Removed from Equipment, 6ft, 18-3 AWG SVT platinum jacket, Right Angle power cord for electronic equipment. Standard 3 prong molded plug on one end, right angle IEC female on other end. Rated 120VAC 10A.

L: 6ft.		WT: .34
STOCK	DESC.	TEA
17730-CB	6ft, Right Angle Cord	\$2.49

7FT. RIGHT **ANGLE CSA** CORDSET



Removed from Equipment, 7ft,18-3 AWG SVT platinum jacket, Right Angle power cord for electronic equipment. Standard 3 prong molded plug on one end, right angle IEC female on other end. CSA listed. Rated 120VAC 10A.

mm , , , , , ,				
STOCK #	The second	DESC	A. 18 A. L.	TEA
17725-CB	7ft. Right	Angle CS	A IEC Co	rd \$2.49

6FT. LAPTOP POWER CORD

6ft,18-3 AWG power cord used with some desktop power supplies & equipment. Standard 3 prong molded plug on one end, IEC Class 1-C5 female (3 round sockets) on other end. SJT White jacket. Rated 120VAC 2.5A. CSA/VDE/CE Listed

L: 6ft	WT: .4	
STOCK	DESC. 1EA 10+EA	

STOCK	DESC.	1EA	10+EA
17193-WI	6ft Laptop Cordset	\$2.95	\$2.49

6FT. UL 18-3 AWG **IEC POWER CORD**



6ft,18-3 AWG power cord used in equipment. Standard 3 prong molded plug on one end, std. IEC type C-13 female on other end. Black jacket. UL/CSA listed. Rated 120VAC 10A.

L: 6ft			WT: .4
STOCK #	DESC.	TEA	10+EA
12943-CB	6ftUL IEC Cordset	\$3.95	\$3.49

1FT. IEC **POWER CORD**

1ft. long, 18-3 SVT, power cord for such items as computers, printers. equip. etc. Std. 3 prong plug on one end and sdt. IEC female on other. Ideal for racks or benches with plug strips. No tangle of cords. CSA listed

with plug sti	ips, ivo langle of colus.	JOA IISLEU	١.
L: 1ft			WT: .9
STOCK	DESC.	TEA	5+EA
14908-WI	1ft IECPower Cord	\$2.25	\$1.99

10FT IEC **POWER CORD**

10ft,18-3 AWG SJT Black jacket, power cord for electronic equipment. Clear hospital Grade, 3 prong molded plug on one end, standard IEC female on other end. CSA/CE listed.

L: 10ft		WT: .7
STOCK	DESC.	1EA
17605-CB	10ft IEC Black Cordset	\$4.95

6FT. IEC CLASS-1 **POWER CORD**

6ft, 18-3 AWG power cord used with some desktop power supplies & equipment. Standard 3 prong molded plug on one end, IEC Class 1 female -C5 (3 round socket) on other end. SVT gray jacket. International Rating 120/220VAC/ 2.5A. North America rating: 120VAC/7A

L: 6ft.	WT: .4	
STOCK # DESC.	1EA	10+EA
16225-WI Gray Class1 Cordset	\$2.49	\$2.25

5.5FT. UL 18-3 AWG **IEC POWER**



3 prong molded plug on one end, standard IEC female on other end. Black jacket. UL/CSA listed. Rated 120VAC 10A. WT: .33

STOCK #	DESC.	TEA
17415-CB	5.5ft. UL IEC Cordset	\$2.95

6FT, 18-2 AWG **AUDIO EQUIP.** CORD



6ft,18-2AWG power cord. 2 blade polarized molded plug on one end, 2 pin keyed female notebook/laptop/

L: 6ft	ment plug on other. or		WT: .25
STOCK V	DESC.	1EA	5+EA
15009-CB	6ft Notebook Cord	\$1.49	\$1.25

3FT. POWER CORD

Removed from Equipment, 3ft,18-2AWG power cord. 250VAC/2.5A Max. 2 blade Non-polarized molded plug on one end, IEC Class 2-C7, 2 pin female notebook/laptop/ Audio/TV equipment plug on other. Black jacket. CSA Listed WT: .13

	3ft. Class 2 Power Cord	\$0.	69
STOCK #	DESC.	1E/	Δ.

POWER CORD SPECIAL

6ft, 18-3 AWG, black PVC jacketed power cords. Standard 3 prong male

molded plug on one end, & 3 blade molded IEC C-13 female on the other. 120VAC 10A rated.

L: 6ft		WT: .5
STOCK	DESC.	164
7378-WI	6ft. IEC Power Cord	\$3.49


EQUIPMENT EXTENSION CABLE

Extension power cord with IEC Male on one end & IEC female on other. Use to extend monitors, computers Etc.

		WT: .5
STOCK #	DESC.	1EA
18042-CB	4.5ft Black CSA IEC Ext.	\$1.95
18045-CB	6ft Plat. IEC Ext.	\$2.50
18046-CB	6ft Black IEC Ext.	\$2.95
12462-CB	6 ft Black UL IEC Ext.	\$2.50

5.5FT. REPLACEMENT **CORDS**





Non-polarized molded plug on one end, 2 pin female notebook/laptop/Audio/TV equipment plug on other.

L: 5-1/2ft		WT: .25
STOCK #	FIG DESC. TEA	SHEA
15447-CB	A Rnd. Non-Polar Cord \$1.25	\$0.99
15448-CB	B Rnd. Non-Polar Cord \$1.25	\$0.99
15449-CB	C Polar Cord Set \$1.25	\$0.99
15452-CB	F Keyed TV Cord \$1.25	\$0.99

10FT,18-3 AWG **IEC POWER** CORD

10ft, 18-3 AWG SJT platinum jacket, power

cord for electronic equipment. Hospital Grade

3 prong molded plug on one end, standard IEC class 1, female on other end. CSA listed. Rated 250VAC

L. TOIL		-	110.16
STOCK #	DESC.	ita	1DO+EA
16045-CB	10ft IEC Cordset	\$4.95	\$4.25

6FT, RIGHT **ANGLE 14/3** CORDSET



6ft,14-3 AWG SJT Black jacket, Right Angle power cord for electronic equipment. Standard 3 prong molded plug on one end, right angle IEC female on other end. Rated

15A/125VAC. UL/	CSA listed.	
L: 6ft.		WT: .7
STOCK #	DESC	 154

п	STOCK	DESC.	1EA
	18041-CB	6ft. UL Right Angle IEC Cord	\$4.95

HOSPITAL **GRADE AC** CORD



9ft. 16-3 AWG, Gray SJT jacketed pigtail power cord. Hospital Grade 3 prong male molded AC plug on one end and stripped back 2in on other end. UL/CSA Listed

L: 9ft		W1:.8
STOCK	DESC	JEA
18851-WI	9ft. Hospital AC Cord	\$4.95

WT. 22

10FT,18-3 AWG IEC CORD

10ft,18-3 AWG SJT Gray jacket power cord for electronic equipment. Hospital Grade 3 prong molded plug on one end, standard IEC class 1, female on other end. CSA listed. Rated 10A, 125VAC WT: .72

10ft IEC Cordset 18184-CB

3FT,18-3 AWG **IEC CORD**

3ft,18-3 AWG Black, power cord used in equipment. Standard 3 prong molded plug on one end standard IEC female on other end. Black jacket. Rated 10A@ 250V; 125V 15A @ 125V. CE/VDE Listed.

L: 3ft WT: .26 18657-CB 3ft Volex IEC Cordset \$2.49



HI-TEMP **IEC CONNECTOR**

Snap-in, Chassis mount, Black thermoplastic, 120/220 VAC @ 10A, IEC 60320/C-16 three wire primary power connector for High Temperature appliances. Rated for "HOT" use @ 120deg. "C". .250" quick connect terminals. UL/CSA listed 15A@250V:VDE/TUV listed 10A@250V NOTE: Connector is "Keyed" for C-15 Plug & will not accept Std. C-13 Plug

W: 1-3/16"	H: //8"	D: 1-1/8"	W1: .016
STOCK	and the same of the 18 to the same	DESC.	1EA
17371-PL	High	Temp. IEC	Inlet \$0.49

IEC POWER INLET

Snap-in, Chassis mount, Black thermoplastic, 120/220 VAC @

10A, IEC 60320/C-14 three wire primary "C" power connector. Rated for 70deg. "C". .250" quick connect terminals. UL/CSA listed 15A@250V/ VDE,TUV etc. listed 10A@250V, accepts Std. C-13 Plug

W: 1-3/16" H: 1" D: 1-1/8 WT: .018 18260-PL Standard IEC Power Inlet \$0.75

IEC POWER INLET

IEC 60320 type C-14 Right Angle P.C. mount, power inlet. Rated: 15A @ 250VAC UL/CSA. Standard IEC equipment end male 3 blade cord connector. Solder terminals

W: 2"	H: 1-1/16"	D: 1-1/16"	WT: .04
STOCK #		DESC.	TEA
18022-PL	IEC P.C	. Mount Power Inlet	\$0.79

CIGARETTE ADAPTER CORD

34

Cigarette lighter plug with Replaceable 2A GMA fuse 12ft ZIP cord with a Female .187" quick connect on center pin lead & a Male .187" on the outside contacts

WT: .22 18525-CB 12ft. Cigarette Adapter Cord \$1.95

CIGARETTE LIGHTER **ADAPTER**



Adapter has 3 built in LEDs showing battery status. Expands dash cigarette lighter socket to handle a cagarette lighter & 2 devices. Replaceable 10A fuse.

L: 5-1/4"	H: 3"	T: 1-1/4"	WT: .22
STOCK #		DESC	TIEA
18030-MI	3 Wa	y Cigarette Lighter Adp.	\$5.95

6 WAY SAFETY ADAPTER

Wall mount shock protector Provides 6 outlets from standard Duplex outlet. Internal

cover plates Prevent objects from being inserted in live holes. Both Blades must be inserted at the same time. NOT A SURGE LIMITER. UL/CSA Listed.

STOCK#	DESC.	VV 1: .4
18534-MI	6 Way Shock Protector	\$3.95

6 WAY SURGE PROTECTOR

Wall mount surge protector. Protect elec-40

4370-MI 6 Way Surge Protector

nic equipment from electrical spikes. ilt in status indicator light. Clamp Volts: 0, U/L listed.	The second
	WT: .7
TOCK # DESC. 16	A SHEA

6 WAY SURGE PROTECTOR

Wall mount surge protector plugs into Duplex recp. 6 outlets protected L/N & L/Gnd. 1875 W max. Load. Protect electronic equipment from electrical spikes. Built in status indicator light, Clamp Volts: 330V, UL listed.

	6 Way Surge Protector		\$4.49	
STOCK #	DESC.	1EA	10+EA	

COAXIAL POWER SPLITTER

5in. splitter cord with 5.5X2.1mm power connectors. Male Right Angle on one end & a piggyback Male/Female on the other

L: 5"		WT: .04
STOCK #	DESC.	
18553-CB	5.5/2.1mm Splitter Cable	\$1.95

COAXIAL POWER JACK

Plastic, P.C. mount power connector. Designed for 5.5mm/2.1mm dia. power plugs.

18027-PL	5.5/2.1mm Power Jack	\$0.49	\$0.39
STOCK #	DESC.	1EA	100EA
			1004

POWER PLUG PLUG (M) **ADAPTERS**

Plastic body Barrel connector 5.5mm O/D Plug TO 2.5 or 2.1mm

L: 1-7/16"	JACK (F)/	Г : .014
STOCK #	DESC.	TEA
17573-PL	5.5/2.1F to 5.5/2.5M Adapter	\$1.95
18238-PL	5.5/2.5F to 5.5/2.1M Adapter	\$1.95

COAXIAL **POWER JACKS**



Plastic, Chassis mount power connector. Designed for 5.5mmO/D plugs. Aux. contact connected to sleeve with no plug inserted. Solder terminals

L: //o IVILY	. noie: 5/16	Dia.: 15/32	W 1: .007
STOCK	DES	C.	1EA
18549-PL	5.5/2.1mm	Power Jack	\$1.49
18550-PL	5.5/2.5mm	Power Jack	\$1.49

3 WAY SURGE PROTECTOR



Heavy duty EMI/surge protector. 15A max. Load. Clamp voltage: 330V/140Joules. Outlets protected L/N, L/Gnd. & N/Gnd. Free standing or can be screwed to wall, cabnet or desk, 9ft. 14-3 AWG cord plugs into wall reop. 2 outlets on face + 1 receptacle on 4" cord for pigtailing more units. Surge suppression also provided for Phone & LAN RJ jacks. UL listed.

L: 8-1/4"	W: 2-3/4"	D: 3-3/4"	WT: 2.1
STOCK #	DES	C.	1EA
18265-MI	Cubical S	Surge Protector	\$8.95

CABLE ORGANIZER



10pcs, set of velcro cable tys. 7in. of Loop with 1in. of hook on reverse side used to organize all those Computer, or home entertainment cables and cords. Holds up to 2in. bundle.

L: /-1/2"	W: 3/4"		WI:.05
STOCKA		DESC.	1EA
17918-TY	10 Pac	k 7.5" Hook/Loop Ties	\$1.25

CABLE ORGANIZERS

10pcs, set of velcro cable tys. 6in, of Loop with 2in, of hook on reverse side used to organize all those Computer, or home entertainment cables and cords. Holds up to 1-3/4in. bundle.



SURFACE MTG. **DUAL JACK**

Surface mount "Mod" RJ-11 jacks with internal block. Two jacks wired in parallel. For single line with two out-

STOCK	DESC.	1EA	2+EA
9233-TT	Dual Jack	\$3.25	\$2.95

WT: .01

WIT: OO

"MOD" CORD **COUPLER**

RJ-12 to RJ-12, (6X6) Telephone line corc coupler. Wired straight through. Ivory cold

STOCK #	DESC.	1EA	10+EA
15474-TT	RJ-12 Straight Coupler	\$0.95	\$0.79

STUCK#	DESC.	TEA	TU+EA
15474-TT	RJ-12 Straight Coupler	\$0.95	\$0.79

SURFACE MOUNT

Surface mount RJ-11 "Mod" jack with internal terminal block

STOCK II	DESC.	TEN	2+E4
4230-TT	4 Wire Surface Jack	\$1.68	\$1.49
4231-TT	6 Wire Surface Jack	\$1.95	\$1.79

CPU FAN POWER ADAPTOR

Use to remove 3 pin CPU fan connector from motherboard and connect it direct to your power supply. Standard large 4 pin drive M/Fconnectors to mini fan plug.

L: 2"tap / 6" Fan			WT: .02
STOCK #	DESC.	1EA	5+EA
12834-CB	CPU Fan Adapt, Cable	\$2.49	\$1.95

WWW.MPJA.COM



CISCO P/NWS-F56K-48X2-SPLTR= for Catalyst 6500 systems. Dark Gray steel panel fits standard 19" racks. 48 Inputs X 96 Output Ports. Accepts std. Cat-5e RJ-45 plug & splits to 2 RJ-45 Output Jacks.

H: 3-1/2" (2U)

16769-TT Cisco Splitter Panel \$2	9.95
STOCK # DESC.	1EA

CAT-5 RJ-45 "MOD" CRIMP PLUGS

"Modular" RJ-45 plugs feature .35mm phor-bronze contacts with 50 u-inch gold over 50-100 u-in. nickel plated plating For 24-28AWG solid/stranded wire. Conforms to FCC-68.5 requirements. UL Listed. 2 prong for medium duty use (2 point wire connection) 3 prong for heavy duty use (3 Point wire connection)

STOCK #	DESC.	TEA	25+EA
11118-TT	RJ-45 Stranded Wire	\$0.30	\$0.28
11119-TT	RJ-45 Solid Wire 2 Prong	\$0.35	\$0.33
11120-TT	RJ-45 Solid Wire 3 Prong	\$0.42	\$0.39

"Y" ADAPTERS

"Y" adapter allow multiple pieces of phone equipment to share one outlet. One "Mod" plug to "Mod jacks. 6X4 RJ-11 jacks (4 Wire), 6X6 RJ-12 (6 Wire)

WT: .01

STOCK #	DESC.	1EA	10+EA
4225-TT	2 Way 6X4 Adapter	\$0.95	\$0.79
4226-TT	2 Way 6X6 Adapter	\$1.00	\$0.89
4909-TT	3 Way 6X4 Adapter	\$1.80	\$1.49

"Y" LINE SPLITTER

Splitter changes a RJ-11 4 X 6 "MOD" 2 line jack into 3 jacks. One jack has Line 1 & Line 2; second jack has Line 1 only and third jack has line 2 only.



WT: .01

STOCK #	DESC.	1EA	2+EA
5936-TT	"Y" Line Splitter	\$1.95	\$1.69

MODULAR PHONE CABLES



RJ-11(4X6) Mod cables made up in convienent lengths. Cross wired for telephone use; or parallel for data use.

STOCK #	LENGTH	DESC.	WT	1EA	10+EA
4241-TT	7ft	Phone	.1	\$1.45	\$1.29
4243-TT	14ft	Phone	.5	\$2.45	\$1.99
4244-TT	14ft	Data	.5	\$2.45	\$1.99
4245-TT	25ft	Phone	ii	\$3.49	\$2.99
4246-TT	25ft	Data	1	\$3.49	\$2.99

CAT-5E CROSSOVER CABLE

14ft. Red Cat 5e, 10/100 Base-T Crossover wired (EIA/TIA568B) patch cable. For Uplink or Computer to computer link Pinned as follows:



L: 14ft WT: .3

17580-TT Cat-5e Crossover Cable

TELCO TYPE TEST CLIPS

Mueller JP-8078, 2-1/4"Angled Telco alligator clips with cable piercing tool steel spike. Designed to grip punch-down blocks as well as wire posts etc. Nickelsilver, with brass screw, washer & bronze lock washer. Includes pair of clips plus 1 Red & 1 Black flexible vinyl

boot. For test leads, clip leads, or test jigs.

STOCK #	DESC.	TOTAL PROPERTY.
18160-TL	Mueller Telco Gator Clips	\$6.95



25FT. **EXTENSION** CORD

4 wire cords with "Mod" Plug on one end & either a single RJ-11 jack or a dual RJ-11 "Y" jack on other.

STOCK #	DESC.	1EA	24EA
4912-TT	25 Ft Extender	\$2.50	\$2.25
4910-TT	25 Ft "Y" Extender	\$2.90	\$2.49



TYPE 66 PUNCH-DOWN BLOCK

Type 66M punchdown block for termininating 25 pair, multi-line phone cables. Also used for security systems &

similar applications
Type 89 Plastic Mounting Bracket for 66M Block 2 Support Bracket

** 1O DIO	on .2 Support Bracket	July 100.	13
STOCK #	DESC.	THE STATE	10+EA
7186-TT	66 Punch Down Block	\$21.95	\$21.45
7187-TT	Block Support Bracket	\$2.79	\$2.29
11080-TT	Bridging Clip	\$0.15	\$0.13

UL LISTED FLAT PHONE CABLE

Flat, UL listed multi conductor 26 AWG bulk pack cable. Used to interconnect phone equipment to wall jack, or handset to phone. Silver color, 1000ft put-ups only.

WT: 12lb/1000ft, 4 conductor

8349-WI	4 Cond. UL Cable	\$69.95	\$59.95
STOCK #	DESC.	TEA	5.FA

UL LISTED "MOD" **CRIMP PLUGS**



Cat-3 Standard crimp-on "Modular" plugs for Flat Cable.

			WT: .001		
STOCK #	DESC.	1EA	25EA	100-EA	
6282-TT 6284-TT	6X4 RJ-11 P 8X8 RJ-45 P	•	\$0.11 \$0.20	\$0.10 \$0.19	

ECONOMY "MOD" CRIMP PLUGS

Cat-3 Standard crimp-on "Modular" plugs. For flat cable Available for line or handset.

			W1: .001		
STOCK #	DESC.	1EA	25EA	100+EA	
4236-TT	6X4 RJ-11 Plug	\$0.15	\$0.10	\$0.08	
4237-TT	6X6 RJ-12 Plug	\$0.20	\$0.15	\$0.12	
4238-TT	4X4 Handset Plug	\$0.30	\$0.25	\$0.24	

"BEENIE" SPLICE

UR or UY style "Beenie" splices for phone & alarm systems. UR: 2port UY: 3port

Marin Committee	
	d 23
UY	WT: .2

STOCK #	DESC.	1PK	5+PK
14444-TT	100pcs. "UR" Slice	\$12.95	\$10.95
14445-TT	100pcs. "UY" Slice	\$16.95	\$14.95

DSL CABLE

3-COM "Polarity" patch cable used to connect DSL Modem to Network RJ-45 plugs each end Wired:

Pin 1 to Pin 1 Pin 3 to Pin 6 Pin 6 to Pin 3

Pin 2 to Pin 2 Pin 4 & 5 Open

L: 6ft 17754-TT 3-COM DSL "Polarity Cable

CAT- 5E **PATCH CABLES**



WT: 12

\$0.59

Flexible, Solid conductor patch cables with RJ-45 (8X8) plugs. Straight wired to T568B ATT-258A standards. 100% tested wire sequence & continuity. Verified to EIA/TIA Cat. 5E standards. Plugs feature 50 micro inch gold plated contacts. Conforms to **FCCrequirements**

STORKS	BESQUIPTION	777.3	mbert-men er	THE PERSON NAMED IN
A PROPERTY OF THE PARTY OF THE	All the second s	00	20042	10 NEA
16931-TT	1ft. Yellow Cat-5e Cable	.03	\$0.49	\$0.45
16932-TT	1ft. Blue Cat-5e Cable	.03	\$0.49	\$0.45
16934-TT	3ft. Yellow Cat-5e Cable	.05	\$0.69	\$0.59
16935-TT	3ft. Blue Cat-5e Cable	.05	\$0.69	\$0.59
16461-TT	3ft. Gray Cat-5e Cable	.05	\$0.69	\$0.59
16937-TT	7ft. Yellow Cat-5e Cable	.1	\$1.25	\$0.99
16938-TT	7ft. Blue Cat-5e Cable	.1	\$1.25	\$0.99
16462-TT	7ft. Gray Cat-5e Cable	.1	\$1.25	\$0.99
17120-TT	14ft. Yellow Cat-5e Cable	.1	\$1.99	\$1.69
17121-TT	14ft. Blue Cat-5e Cable	.1	\$1.99	\$1.69
17122-TT	14ft. Gray Cat-5e Cable	.1	\$1.99	\$1.69
16943-TT	25ft. Yellow Cat-5e Cable	.4	\$2.39	\$2.69
16944-TT	25ft. Blue Cat-5e Cable	.4	\$2.99	\$2.69
16464-TT	25ft. Gray Cat-5E Cable	.4	\$2.99	\$2.69
16946-TT	50ft. Yellow Cat-5e Cable	.7	\$5.49	\$4.99
16947-TT	50ft. Blue Cat-5e Cable	.7	\$5.49	\$4.99
16465-TT	50ft. Gray Cat-5e Cable	.7	\$5.49	\$4.99
16949-TT 1	100ft, Yellow Cat-5e Cable	1.2	\$9.95	\$8.95
16950-TT			\$9.95	\$8.95
16951-TT	100ft. Gray Cat-5E Cable	1.2	\$9.95	\$8.95

KEYSTONE VIDEO CONNECTOR

White snap in Keystone Bezels with a 75 ohm type "F" video female connector. For use in distribution systems using keystone style wall plates.

WT: .02

14477-TT F Connector Keystone \$1.75

FILTERED RJ-45 JACK

Corcom F9600D Single position, PC mount 8X8 contact (RJ-45) telephone modular jack. Each lead feeds through a Ferrite block with a 820pF cap to the shield (ground). Shield covers all but face & bottom. White plastic body & gold pins. Frequency stop band: 30-

1000MHz. Frequency Pass Band; 2-100MHz. Face fits in .6" sq. cutout. Plug fits Tab Down.

L: 15/16" W: 3/4" H 3/4" WT: .022 Filtered RJ-45 Jack 11438-TT

"B" SPLICES

Standard type "B" crimp splices. Provides

permanent connection for phone or alarm wires.	
WT	:
THE PARTY OF THE P	

.001 5873-TT "B" Splice \$5 15 \$0.10 \$0.09

STANDARD DIN CABLE CONNECTORS



WT: .02

STOCK #	TYPE	DESC	TEA	25EA	100+EA
5607-PL	Male	5 Pin 45°	\$0.42	\$0.35	\$0.28
5608-PL	Female	5 Pin 45°	\$0.63	\$0.53	\$0.42
5611-PL	Male	6 Pin	\$0.48	\$0.40	\$0.32
5612-PL	Female	6 Pin	\$0.72	\$0.60	\$0.48
5614-PL	Female	7 Pin	\$0.81	\$0.68	\$0.54
5615-PL	Male	8 Pin	\$0.56	\$0.46	\$0.37

MINI DIN **CABLE CONNECTORS**



				WIUZ		
STOCK W	TYPE	DESC.	TEA	25E4	100+EA	
5601-PL	Male	4 Pin	\$0.87	\$0.73	\$0.58	
5602-PL	Female	4 Pin	\$1.12	\$0.93	\$0.74	
5603-PL	Male	6 Pin	\$1.05	\$0.88	\$0.70	
5604-PL	Female	6 Pin	\$1.26	\$1.05	\$0.84	
5605-PL	Male	8 Pin	\$1.46	\$1.21	\$0.97	

DB PC MOUNT **CONNECTORS**



M/T. OO

Right angle PC mount connectors. Metal face, gold plated contacts. 3/4" from face to back.

WT: .02

STOCK #	DESC.	1EA	25+EA
4840-PL	DB-9 Female 90° Mount	\$0.59	\$0.55
4896-PL	DB-9 Male 90° Mount	\$0.45	\$0.41
5687-PL	DB-15 Male 90° Mount	\$0.65	\$0.58

DB CONNECTORS



		WT: .05	
STOCK #	DESC.	1EA	25+EA
2856-PL	DB-9 Male Solder	\$0.24	\$0.19
2857-PL	DB-9 Female Solder	\$0.28	\$0.24
5395-PL	DB-15 Male Hi Den.	\$0.69	\$0.59
5394-PL	DB-15 Female Hi Den.	\$0.79	\$0.69
2859-PL	DB-9 Plastic Hood	\$0.39	\$0.35
2860-PL	DB-15 Male Solder	\$0.45	\$0.36
2861-PL	DB-15 Female Solder	\$0.45	\$0.36
0133-PL	DB-15 Hood	\$0.75	\$0.59
2444-PL	DB-25 Male Solder	\$0.39	\$0.29
2445-PL	DB-25 Female Solder	\$0.59	\$0.49
2446-PL	DB-25 Plastic Hood	\$0.39	
2865-PL	DB-37 Male Solder	\$0.65	\$0.52
2866-PL	DB-37 Female Solder	\$0.79	\$0.75
0134-PL	DB-37 Hood	\$1.00	\$0.79
6949-PL	DB-50 Male Solder	\$1.95	\$1.59
6950-PL	DB-50 Female Solder	\$1.85	\$1.39
0136-PL	DB-50 Hood	\$1.25	\$0.95

SIGN-UP FOR OUR EMAIL SPECIALS ON MPJA.COM

IDC CONNECTORS

Insulation displacement header connectors. Gold plated, .025 square pins with .100 spacing.

WT: .03

STOCK # DESC:	TEA	25+EA
0891-HC 10 (2X5) Socket Header	\$0,39	\$0,29
0893-HC 16 (2X8) Socket Header	\$0.68	\$0.59
2883-HC 20 (2X10) Socket Header	\$0.75	\$0.59
0895-HC 26 (2X13) Socket Header	\$0.75	\$0.59
4709-PL 34 (2X17) Socket Header	\$0.45	\$0.32
2884-HC 40 (2X20) Socket Header	\$0.49	\$0.39
4710-PL 50 (2X25) Socket Header	\$0.49	\$0.39

TELCO TYPE TEST CLIPS

Visit

Mueller JP-8078, 2-1/4"Angled Telco alligator clips with cable piercing tool steel spike. Designed

to grip punch-down blocks as well as wire posts etc. Nickel-silver, with brass screw, washer & bronze lock washer. Includes pair of clips plus 1 Red & 1 Black flexible vinyl boot. For test leads, clip leads, or test jigs. WT: .088

18160-TL Mueller Telco Gator Clips\$6,95

BATTERY **CLIPS & BOOTS**



Handy mesh jaw, steel battery clip with insulated Red or Black Vinyl plastic boot. Amp listed is Max for part.

STOCK #	DESC	WT	1EA	5+EA
16437-BC	5A Clip Red	.015	\$0.25	\$0.15
16438-BC	5A Clip Black	.015	\$0.25	\$0.15
16439-BC	10A Clip Red	.05	\$0.35	\$0.25
16440-BC	10A Clip Black	.05	\$0.35	\$0.25
16441-BC	20A Clip Red	.03	\$0.40	\$0.30
16442-BC	20A Clip Black	.03	\$0.40	\$0.30
16443-BC	30A Clip Red	.04	\$0.45	\$0.35
16444-BC	30A Clip Black	.04	\$0.45	\$0.35
16445-BC	50A Clip Red	.06	\$0.59	\$0.49
16446-BC	50A Clip Black	.06	\$0.59	\$0.49

ALLIGATOR CLIPS & BOOTS

Alligator clips with Red or Black Vinyl boot. Solder or crimp. mm listed is length of metal clip

STOCK	DESC.	WT.	1EA	5+EA
16450-AL	27mm Clip Red	.003	\$0.10	\$0.05
16451-AL	27mm Clip Blk	.003	\$0.10	\$0.05
16452-AL	35mm Clip Red	.005	\$0.15	\$0.07
16453-AL	35mm Clip Blk	.005	\$0.15	\$0.07
16454-AL	45mm Clip Red	.009	\$0.19	\$0.09
16455-AL	45mm Clip Blk	.009	\$0.19	\$0.09
16456-AL	50mm Clip Red	.013	\$0.29	\$0.12
16457-AL	50mm Clip Blk	.013	\$0.29	\$0.12

DUAL BINDING POSTS

Red & Black, safety binding posts accept banana plug in top or wire through hole in side. All front panel connections are recessed to pervent contact. Mounts in double .50" holes on .75" ctr. Solder terminals onback

Dual BindingPost



\$1.95 \$1.75

DB CRIMP CONNECTORS

Metal face DB Housings





STOCK #	DESC	THE AMERICAN	25+EA
16251-PL	DB-9 Male Crimp	\$0.59	\$0.49
16252-PL	DB-9 Female Crimp	\$0.59	\$0.49
16253-PL	DB-15 Male Crimp	\$0.69	\$0.59
16254-PL	DB-15 Female Crimp	\$0.69	\$0.59
16255-PL	DB-25 Male Crimp	\$0.69	\$0.59
16256-PL	DB-25 Female Crimp	\$0.69	\$0.59
16257-PL	DB-37 Male Crimp	\$1.19	\$0.99
16258-PL	DB-37 Female Crimp	\$1.19	\$0.99
16259-PL	DB-50 Male Crimp	\$2.99	\$2.79
16260-PL	DB-50 Female Crimp	\$2.99	\$2.79
16261-PL	DB-15 Male Hi Den.	\$0.79	\$0.69
16262-PL	DB-15 Female Hi Den.	\$0.79	\$0.69

DB CRIMP PINS

3 micro inch Gold over 50micro in. nickel for 24-28AWG Wire

STOCK # DESC.	1EA	4+EA
16265-PL Male Crimp Pin/100	\$4.99	\$4.49
16266-PL Female Crimp Pin/100	\$4.99	\$4.49
16267-PL Male Crimp Pin/5KReel	\$99.00	
16268-PL Female Crimp Pin/5KReel	\$99.00	
16269-PL HD Male Crimp Pin/100	\$4.99	\$4.49
16270-PL HD Female Crimp/100	\$4.99	\$4.49
16271-PL HD Male Crimp/5KReel	\$99.00	
16272-PL HD Female Crimp/5KReel	\$99.00	

DB CONNECTOR PIN CRIMP TOOL

Multi Purpose Crimp Tool Features: Cushioned Grips. Use: Crimping Open (stamped) D-Sub Pins, Ternimal Lugs. For 14-26 AWG Wire NOTE: Will not crimp High Density DB Pins.

WT: .6 \$9.95 \$7.95 11763-TL **Multi Crimp Tool**

DB CRIMP PIN EXTRACTOR.

Tool used to extract crimp pins from insertion type DB connectors. Double ended For Pin & Socket type connectors (16251-PL - 16262-PL)

WT: .03 17124-TL **DB-Crimp Pin Extractor** \$4.75

DB CONNECTORS INSULATION DISPLACEMENT

GOLD PLATED CONTACTS FOR .05" SPACING FLAT CABLE



		VV 1:.1	
STOCK #	DESE	IEA	25+EA
2870-PL	DB-9 Male IDC	\$1.95	\$1.59
2871-PL	DB-9 Female IDC	\$1.95	\$1.59
2872-PL	DB-15 Male IDC	\$2.25	\$1.79
2873-PL	DB-15 Female IDC	\$2.25	\$1.79
0922-PL	DB-25 Male IDC	\$1.50	\$1.19
0928-PL	DB-25 Female IDC	\$1.50	\$1.19

BANANA PLUGS

Black banana plugs with nickel plated brass Four leaved spring # tip, thermoplastic cover, Solder connection

			WT : 05
STOCK	DESC.	1EA	10+EA
8070-PL	Red Banana Plug	\$0.25	\$0.19
2071_DI	Black Banana Blue	\$0.0E	60 40

14492-PL

BNC CONNECTORS




STOCK	FIG.	TYPE	RG CABLE	DESCRIPTION	WF	1EA	25+EA	1004EA
3999-RC	Α		58	2 Piece Crimp BNC Female Connector	.02	\$1.25	\$0.99	\$0.89
4585-RC	Α		59,62	2 Piece Crimp BNC Female Connector	.02	\$1.25	\$0.99	\$0.89
4586-RC	Α		6	2 Piece Crimp BNC Female Connector	.02	\$1.25	\$0.99	\$0.89
4587-RC	Α		Teflon 59, 62	2 Piece Crimp BNC Female Connector	.02	\$1.50	\$1.25	\$0.99
5416-RC	В		58	Twist-on BNC Female Connector	.02	\$1.65	\$1.39	\$1.25
5417-RC	В		59,62	Twist-on BNC Female Connector	.02	\$1.65	\$1.39	\$1.25
5418-RC	В		Teflon 59,62	Twist-on BNC Female Connector	.02	\$1.65	\$1.39	\$1.25
5401-RC	C		58	Standard 3 Piece Crimp BNC Male Connector	.02	\$1.25	\$0.99	\$0.89
5402-RC	C		Teflon 58	Standard 3 Piece Crimp BNC Male Connector	.02	\$1.25	\$0.99	\$0.89
5403-RC	C		59,62	Standard 3 Piece Crimp BNC Male Connector	.02	\$1.25	\$0.99	\$0.89
5404-RC	С		Teflon 59, 62	Standard 3 Piece Crimp BNC Male Connector	.02	\$1.25	\$0.99	\$0.89
5405-RC	С		6	Standard 3 Piece Crimp BNC Male Connector	.02	\$1.25	\$0.99	\$0.89
5406-RC	С		Belden 8281	Standard 3 Piece Crimp BNC Male Connector	.02	\$1.25	\$0.99	\$0.89
5426-RC	D		58	2 Piece Crimp BNC Male Connector	.02	\$1.20	\$0.99	\$0.89
5427-RC	D		Teflon 58	2 Piece Crimp BNC Male Connector	.02	\$1.20	\$0.99	\$0.89
5428-RC	D		59,62	2 Piece Crimp BNC Male Connector	.02	\$1.20	\$0.99	\$0.89
5429-RC	D		Stranded 59,62	2 Piece Crimp BNC Male Connector	.02	\$1.20	\$0.99	\$0.89
5430-RC	D		Teflon 59,62	2 Piece Crimp BNC Male Connector	.02	\$1,20	\$0.99	\$0.89
5431-RC	D		6	2 Piece Crimp BNC Male Connector	.02	\$1.45	\$1.25	\$1.15
5432-RC	D		Belden 8281	2 Piece Crimp BNC Male Connector	.02	\$1.49	\$1.25	\$1,10
5420-RC	Ē		58	Twist-on BNC Male Connector	.02	\$1.50	\$1.25	\$0.99
5421-RC	Ē		Teflon 58	Twist-on BNC Male Connector	.02	\$1.50	\$1.25	\$0.99
5422-RC	Ē		59,62	Twist-on BNC Male Connector	.02	\$1.50	\$1.25	\$0.99
5423-RC	Ē		Teflon 59,62	Twist-on BNC Male Connector	.02	\$1.50	\$1.25	\$0.99
5424-RC	Ē		6	Twist-on BNC Male Connector	.02	\$1.50	\$1.25	\$0.99
5425-RC	Ē		Belden 8281	Twist-on BNC Male Connector	.02	\$1.65	\$1.35	\$1.15
5412-RC	F		58	3 piece Solder BNC Male Connector	.02	\$2.35	\$2.15	\$2.05
5413-RC	F		59.62	3 piece Solder BNC Male Connector	.02	\$1.50	\$1.30	\$1.19
5414-RC	F		Teflon 59,62	3 piece Solder BNC Male Connector	.02	\$1.50	\$1.30	\$1.19
5433-RC	G		58	Standard Solder BNC Male Connector	.02	\$1.45	\$1.25	\$1.15
5434-RC	G		59,62	Standard Solder BNC Male Connector	.02	\$1.45	\$1.25	\$1.15
9224-RC	ĭ	UG-290	-	BNC Female 4 Hole Panel Mount	.1	\$1.69	\$1.59	\$1.49
0507-RC	j	UG1094	_	BNC Female Single Hole Panel Mount	.1	\$1.00	\$0.89	\$0.79
0508-RC	Ľ	001004		BNC Adaptor 2 Female Connectors	.1	\$0.99		
0509-RC	М			BNC Adaptor 2 Male Connectors	.1	\$1.95	\$1.79	\$1.60
0557-RC	N	UG492		BNC Bulkhead Mount 2 Female Connectors Not Isolated	.1	\$2.95	\$2.59	\$2.19
5435-RC	N	UG492		BNC Bulkhead Mount 2 Female Connectors Isolated	.1	\$3.35	\$2.79	\$2.25
0511-RC	P	00432		BNC "TEE" 2 Female & 1 Male Caonnectors	.1	\$2.25	\$1.99	\$1.59
5437-RC	á		_	BNC "TEE" 3 Male Connectors	.1	\$4.95	\$4.49	\$4.25
6518-RC	R		_	BNC LAN "TEE" 2 Female & 1 Male Connectors	.1	\$4.99	\$4.59	\$4.29
0510-RC	S	UG306		BNC "Elbow" 1 Female - 1 Male Connectors	.1	\$2.50	\$1.95	\$1.59
3131-PL	T	00000		BNC Male 93 Ohm 1/2 Watt Terminator	.1	\$2,49	\$1.95	\$1.59
3137-PL	Ť		-	BNC Male 75 Ohm 1/2 Watt Terminator	.1	\$2.49	\$1.95	\$1.59
3137-PL 3138-PL	Ť			BNC Male 50 Ohm 1/2 Watt Terminator	.1	\$2.49	\$1.95	\$1.59
7547-RC	ΰ			BNC Male 50 Ohm 1/2 Watt Terminator/4" Chain	.1	\$1.95	\$1.89	ψ1.00
11564-RC	V			BNC Straight "TEE" 2 Female & 1 Male Connectors	.03	\$5.95	\$5.59	\$4.69
				through Nove Afairman, Afairman, Afairman, Afairman, Afairman, Afairman, Afairman, Afairman, Afairman, Afairman		ASS A STORAGE OF CO.	10.00	
TEC	u s	PINIEN	. CALL E64_9	ARROOG EAY 561-8AA-876A MD IAC	TRAP. LA	CON	- TO STORY	37

SMA CONNECTORS & ADAPTERS



STOCK #	FIG.	RG CABLE	DESCRIPTION	WT	TEA	25+EA	100+EA
11833-RC	В	RG-58A	3 pc. Crimp type Male Connector, Teflon Insulator, Gold Plated Center Pin	.02	\$1.49	\$1.28	\$1.03
11834-RC	В	RG-59/62	3 pc. Crimp type Male Connector, Teflon Insulator, Gold Plated Center Pin	.02	\$1.49	\$1.28	\$1.03
11836-RC	С	RG-59/62	3 pc. Crimp type Female Connector, Teflon Insulator, Gold Plated Center Pin	.02	\$1.89	\$1.62	\$1.31
11840-RC	G		3 Female "TEE" Connector, Teflon Insulator, Gold Plated Center Pin	.02	\$3.75	\$3.20	\$2.58
11841-RC	Н		1 Male-2 Female "TEE" Connector, Teflon Insulator, Gold Plated Center Pin	.02	\$3.75	\$3.20	\$2.58
11842-RC	l l		Male- Female Right Angle Connector, Teflon Insulator, Gold Plated Center Pin	.02	\$3.39	\$2.75	\$2.22
11843-RC	J		Male SMA-BNC Female	.02	\$2.79	\$2.59	
11844-RC	K		Male SMA-BNC Male	.02	\$3.29	\$2.75	\$2.65
11845-RC	L		Female SMA-BNC Male	.02	\$2.95	\$2.59	\$2.09
11846-RC	M		Male SMA-UHF Female	.02	\$2.99	\$2.65	\$2.13

"N" CONNECTORS



STOCK #	FIG	TYPE	RG CABLE	DESCRIPTION	WT		25+EA	100+ER
5445-RC	Α	-	8,11,213,214	Twist-on "N" Male Connector	.05	\$3.25	\$2.95	\$2.25
5446-RC	В	-	8,11,213,214	3 pc Crimp-on "N" Male Connector	.05	\$4.95	\$4.75	\$4.59
5447-RC	В	-	59U	3 pc Crimp-on "N" Male Connector	.05	\$2.95	\$2.75	\$2.45
5448-RC	E	-	-	50 Ohm Terminator "N" Male Connector	.1	\$3.95	\$3.69	\$2.95
0534-RC	G	UG-28	•	"N" "TEE" with 3 Female Connectors	.1	\$5.95	\$5.75	\$5.49
0517-RC	Н	UG-107	-	"N" "TEE" 2 Female & 1 Male Connectors	.1	\$5.00	\$4.59	\$3.98
0516-RC	J	UG-27	-	"N" "Elbow" 1 Female & 1 Male Connector	.1	\$4.95	\$4.49	\$4.25
0515-RC	K	UG-57	-	"N" Adaptor with 2 Male Connectors	.1	\$2.95	\$2.77	\$2.59
0514-RC	L	UG-29	-	"N" Adaptor with 2 Female Connectors	.1	\$3.45	\$2.95	\$2.79
0513-RC	M	UG-58	-	"N" Female 4 Hole Panel Mount	.1	\$2.50	\$2.33	\$1.98

UHF CONNECTORS





















C

C

D

E

G

F	١		

0500

4690

4691

4692-RC

5438-RC

5439-RC

5442-RC

5443-RC

0505-RC

0504-RC

0502-RC

0503-RC

0583-RC

0501-RC

5444-RC

CKI	FIG.	TYPE	RG CABLE
-RC	Α	PL-259	8,11,213,214
-RC	Α	PL-259	8,11,213,214
-RC	В	175	Reducer For 58U

PL-259

M-358

M-359

PL-258

SO-239

DM-1

363

PL-259	8,11,213,214
PL-259	8,11,213,214
175	Reducer For 581
176	Reducer For 59L
PL-259	58
PL-259	59
PL-259	58

59

	Solder
	Sc
58U	Silver
59U	Silver



\$1.30

\$3.95

\$1.75

\$1.25

\$2.10

\$3.75

\$1,60

\$1.65

\$1,20

\$1.99

\$0.49

\$0.49

\$0.89

\$1.55

\$0.99

\$1.95

\$1.59

\$0.99

\$2.25

\$3.45

\$1.55

JCK i	FIG.	TYPE	RG CABLE	DESCRIPTION	Wr.
D-RC	Α	PL-259	8,11,213,214	Solder Type UHF Male Connector with Plastic Insulat	or .02
0-RC	Α	PL-259	8,11,213,214	Solder Type Silver Plated UHF Male Connector	.02
1-RC	В	175	Reducer For 58U	Silver Plated Adaptor RG-58 Cable to UHF Connector	or .01

r Plated Adaptor RG-58 Cable to UHF Connector	.01	\$0.59	\$0.55
r Plated Adaptor RG-59 Cable to UHF Connector	.01	\$0.59	\$0.55
2 Piece Crimp UHF Male Connector	.05	\$1.65	\$1.45
2 Piece Crimp UHF Male Connector	.05	\$1.25	\$0.99
Twist-on UHF Male Connector	.05	\$1.75	\$1.65
Twist-on UHF Male Connector	.05	\$1.25	\$1.10
UHF "TEE" 2 Female-1 Male	.1	\$2.45	\$2.25
UHF "Elbow" 1 Female-1 Male	.1	\$2.00	\$1.79
UHF Adaptor 2 Females	.1	\$1.25	\$1.10
UHF Adaptor 2 Males	.1	\$2.49	\$2.35

"F" TYPE CONNECTORS & ADAPTORS





C









UHF Threaded Bulkhead 2 Females

UHF Female 4 Hole Panel Mount

UHF Female Single Hole Mount



C



D





.1

.1

BETWEEN SERIES ADAPTORS











D



Type "F" connectors & adaptors are used to match Antenna & Cable TV equipment to

Ε











В







G



39

Audio/Visual Jacks on VCRs. Monitors, Switchers etc. WT: .01 Connectors & adaptors are used to match Transceivers, Antenna, Cable TV, etc to other various equipment.

STOCK #	FIG.	TYPE	CABLE	DESCRIPTION	1EA	10±EA
0538-RC	Α	F-59	59U	Male Cable Attached 1/4 Ring	\$0.20	\$0.16
5450-RC	Α	F-56	6U	Male Cable Attached 1/4 Ring	\$0.20	\$0.18
9231-RC	В	F-59	6U	Male Cable separate 1/4 Ring	\$0.17	\$0.16
9232-RC	В	F-59	59U	Male Cable separate 1/4 Ring	\$0.17	\$0.16
0563-RC	С	F-59T	59U	Male Cable Twist-on	\$0.35	\$0.29
5451-RC	C	F-56T	6U	Male Cable Twist-on	\$0.35	\$0.29
5453-RC	D		6U	Female Cable Attached 1/2 Ring	\$0.89	\$0.75
0588-RC	Ε		59U	Male Twist-on Quick Connect	\$0.35	\$0.29
5455-RC	F		59U	Male Quick Conn./Crimp Ring	\$0.49	\$0.39
0539-RC	G	F-61		Female Panel Mount with Nut	\$0.49	\$0.39
5454-RC	Н	F-71		Male to Male In-line	\$0.69	\$0.55
0541-RC	K	F-81	Fema	le to Female Bulkhead with Nut	\$0.49	\$0.39
0586-RC	M		Male Q	uick conn. to Standard Female	\$0.50	\$0.39
7097-RC	N		Male to	Female Right Angle Adaptor	\$0.75	\$0.59
0591-RC	0			Male to BNC Female Adaptor	\$1.50	\$1.19
0540-RC	Р			Female to BNC Male Adaptor	\$1.30	\$0.95
0589-RC	Q			Female to RCA Jack	\$1.30	\$0.95
0590-RC	R			Female to RCA Plug	\$0.75	\$0.59
11448-RC	S			Male to RCA Jack	\$1.30	\$1.19
5456-RC	T			Male 75ohm Terminator 1/2W	\$0.33	\$0.29

				VV 1: .0	11
STOCK#	FIG.	TYPE	DESCRIPTION	1EA	10+EA
0519-RC	Α	UG255	BNC Male to UHF Female	\$2.50	\$1.95
7296-RC	В	-	BNC Male to UHF Male	\$4.95	\$4.65
0518-RC	С	UG273	BNC Female to UHF Male	\$1.95	\$1.65
7297-RC	D	-	BNC Female to UHF Female	\$2.95	\$2.75
0523-RC	Е	UG349	BNC Male to "N" Female	\$3.95	\$3.65
0521-RC	F	UG201	BNC Female to "N" Male	\$2.50	\$1.95
0574-RC	G	-	BNC Female to "N" Female	\$4.95	\$4.75
11031-PL	Н	-	1/8in Male to RCA Female	\$0.89	\$0.79
7298-RC	- 1	-	BNC Male to RCA Male	\$2.10	\$1.69
0548-RC	J	-	BNC Female to RCA Male	\$1.30	\$0.95
0549-RC	K	-	BNC Male to RCA Female	\$1.25	\$0.95
0522-RC	L	UG83	UHF Male to "N" Female	\$3.95	\$3.65
0520-RC	M		UG146UHF Female to "N" Male	\$3.40	\$2.75
0547-RC	N	-	UHF Female to RCA Male	\$1.50	\$0.95
0546-RC	0	-	UHF Male to RCA Female	\$1.50	\$0.95
0578-RC	Q	-	TNC male to BNC Female	\$2.50	\$1.95
15336-RC	R	-	"N" male to "F" Female	\$3.25	\$2.50



Visit





31001	THE PARTY OF THE P	DISCRIPTION	,DlM, L; X, W, X, H,	MANU,/PART NUMBER	WT.	1EA	5+EA
17045-HK	A Natura	AMDDuron/Athlon XP2100/MP1200 Socket A Assembly	3-1/8" X 2-1/2" X 2-1/2"	AVC/112C80FBL03	.63	\$4.95	\$3.95/25
	Alu	ninum sink with Thermal pad. Attached 60mm sq. 12VDC/.1A	14+CFM fan with stall detection, 5" I	eads			
18710-HK	B Natura	H/P motherboard INTEL CPU	3-1/2" X 3-1/2" X 2-7/8"	AVC-hp/617755-001	.78	\$6.95	-
	Fan offset from	nmtg. screws. Rounded Aluminum sink with round Thermal pa	ad. Attached 80mm sq. 12VDC CFM far	with stall detection, 4" leads			
18709-HK	C Natural	H/P motherboard INTEL CPU	4" X 3-1/4" X 2-1/2"	AVC-hp/583417-001	.56	\$6.95	
	Fan aligned to	Mtg. screws. Rect. Aluminum sink with round Thermal pad. At	ttached 80mm sq. 12VDC CFM fan with	stall detection, 4" leads			
16801-HK	D Natura	IntelP4 Prescott Socket 478 Heatsink Assembly	3-5/8" X 2-11/16" X 1-5/16"	Delta	1	\$6.95	\$5.95(10+)
	Alu	ninum sink/massive copper base, with 80mm Rnd. 12VDC far	n with stall detection, 5" leads (for Son	y VAIO & PCs with Socket 478 Me	otherBoard		

CPU LIQUID COOLING **SYSTEM**

MFG: SANYO DENKI P/N: 109-LC1-003 Input: 12VDC X 2 Fan: .25A Max.

Thermal Resistance: .22K/W HI/ .255K/W lo speed (for Ref: Std. Heatsink/Fan: ~.4K/W)

360° WEB

Self contained, Sealed Air/liquid heat exchange CPU Cooler for Socket LGA775 P.C. motherboards provides 30%+ improvement over standard CPU fan/heatsink System consists of Fan/Radiator/Pump assembly with Flexable plastic piping to nickel plated Copper Plate, includes metal CPU clamp.

Variable speed fan Rated 2400RPM Max @ 42db noise

above 35deg. "C", 1300RPM Min. @ 28db noise below 25

Radiator: Aluminum multi Fin & tube. 6-1/4" X 6-1/2" X 1/2"

O/A: 6-7/8" X 7-3/4" X 3" Cold Plate: 2-1/8" X 1-3/4"

Tubing: Fluorpolymer 8" long.
NOTE: DESIGNED TO FIT A SPECIAL TOWER CASE MAY REQUIRE MODIFICATIONS TO YOUR CASE No Case hardware supplied

STOCK #	DESC.	1EA
17515-HK	CPU Cooler Assembly	\$39.95

24VDC IMPULSE COUNTER

14444 TAMURA E630 6 Digit, non-resettable impulse counter rated: 24VDC, 2W, 10CPS. Plastic case Base mounts 2in. leads to 4 Pin Connector. All are set to "0"

W: 1-3/16"	H: 39/64"	D: 2"	WT: .16
STOCK #	DESC	The state of the s	1EA
17949-MI	Tamura	24VDC Counter	\$1.95

250 PSI **GAUGE**

2" Dia, 0-250 PSI gauge with right side 1/8" NPT brass nipple. Rec needle, Black legend on white bac ground. Steel case with plastic face.

Dia: 2"	T: 1"	W: 2-7/8" O/A	WT: .18
STOCK	The same of the sa	DESC.	IEA
18755-1	4D	250PSI Gauge	\$4.0E

THOUSANDS more Items on www.mpja.com

GAS SUSPA P/N C16 **SPRING**

09786 gas extension spring. Used to lift & support equipment hoods & doors, car hoods & trunk lids. Ball pivot on both ends, threaded 1/4-20 Center -to-center Extended length: 19.7in Center -to-center Compressed length: 11.8in Extension Force: 30lbs.

WT: .8 16694-HD Suspa Gas Spring \$3.95 \$3.50

24VDC RUNNING TIME METER

ENM T33 series low power, Non-Resetable Time meter. 7 digit, crystal contolled impulse counter. Black Face with White & Red numbers, Max 99999.99 hrs. 24VDC Operation, 10mW draw. Snap-in, front mounts in 1.18" X .51 cutout, 11" leads

FEEE

W: 1-1/4" H: 9/16" D: 1-7/16" 17906-MI 24VDC ENM Time Meter \$14.95 \$12.95

DUAL WHEEL CASTER-SET

Set of 4 Faultless Plate casters, 2 with brake & 2 plane. Rated load of 100lb/caster.

Twin 60mm dia, plastic wheels offer independent rotation for use on carpeting or tile. 2-1/2" square steel top plate with 2 holes H: 3" O/A T: 1

WT: 1.1 17343-HD Plate Caster 4 Pc. Set \$8.95

6VDC IMPULSE COUNTER

KEP P/N KE610FB, nonresettable, 6 Digit, impulse counter. Rated 5-6VDC/2V 10CPS. Plastic case with

mounting base. 9in. leads. All start below "0" (9998xx) to allow setup & testing of end equipment.

H: 2-3/8" W: 1-3/8 D: 2-1/4" O/A WT: .2 18314-MI **6VDC KEP Counter**

24VDC IMPULSE COUNTER

HANG ZHOU P/N DJ625, non-resettable, 6 Digit, impulse counter. Rated 24VDC/.6W/10CPS. Plastic case snap-in mounts into a 1" X 17/32" cutout. 12in. leads. All have a couple of test counts on them

W: 1-1/16" H: 7/8" D: 1-3/8 WT: .04 16521-MI 24VDC Counter \$1.95 \$1.50

24VDC IMPULSE COUNTER

TAMURA ot 6 Digit, non-resettable 24VDC impulse counter. Plastic case snap-in mounts into a 1" X 17/32 cutout. 4in. leads. All are set around 999XXX to allow testing of equipment once installed.

W: 1-1/16" H: 7/8" D: 1-3/81 WT: 04 15551-MI **Tamura Counter** \$3.95 \$3.50

SUCTION **CUP MOUNT**

Adjustable Plastic bracket with 2-3/4" suction cup for attachment to really smooth surface like glass. Possibly holds a GPS or microphone, we're not sure.

WT: .3 18521-MI Adj. Arm /Suction Cup \$3,95

MINI PNEUMATIC **PUMP**

MFG: KOGE P/N: KPM27H

Power: 12VDC nom@.3A Ports: 0.19" hose Bib

REMOVED FROM EQUIPMENT Diaphragm, oilless air pump rated 2.0l/min. no load. Max pressure: 350mmHg. Plastic pump body. For use in coffee units, lab equipment, blood pressure monitors, sampling inst. 2in. leads.

Single hole stainless mounting bracket. L: 3" O/A W: 1-1/2" H: 1-1/8" WT: .14 18831-MI Koge Mini Air Pump \$4.95



4 corner mtg, holes, Steel Shaft, 24" leads

STOCK #	FIG.	NEMA	VOLTS	AMPS	INO.	OHMS	HOLD TORG,	P/ NUMBER	Commence of the State of the St	DIM. (BOOV) L X SQ.	THAFT	No.	THE
18735-MS	Α	17	5.2VDC	.5	7mH	10.5	1.5Kg/cm	42BYGH3404	4 Phase/Uni-Polar6 lead	1-3/8" x 1-5/8"	5 X 17mm	.5	\$9.95
18733-MS	Α	17	12VDC	.31	18.5mH	38	1.6Kg/cm	42BYGH007	4 Phase/Uni-Polar6 lead	1-3/8" x 1-5/8"	5 X 17mm/flat	.5	\$9.95
17453-MS	Α	17	5.2VDC	1	5.2mH	5.2	3.2Kg/cm	42BYGH4806	4 Phase/Uni-Polar6 lead	2" x 1-5/8"	5 X 22mm	.84	\$15.95
18734-MS	Α	17	12VDC	.4	25mH	30	3.2Kg/cm	42BYGH404	4 Phase/Uni-Polar6 lead	1-7/8" x 1-5/8"	5 X 22mm	.76	\$10.95
18686-MS	В	23	2.8VDC	2	1.2mH	1.4	4.2Kg/cm	57BYGH008	4 Phase/Uni-Polar6 lead	1-5/8" x 2-3/16"	6.35 X19mm	1	\$17.95
17454-MS	В	23	24VDC	.34	90mH	71	4.4Kg/cm	57BYGH006	4 Phase/Uni-Polar6 lead	1-5/8" x 2-3/16"	6.35 X19mm	1	\$17.95
17455-MS	C	23	6.2VDC	1	10mH	6.2	9Kg/cm	57BYGH213	4 Phase/Uni-Polar6 lead	2-3/8" x 2-3/16"	6.35 X19mm	1.6	\$14.95
18728-MS	C1	23	6.2VDC	1	10mH	6.2	9Kg/cm	57BYGH213-25	4 Phase/Uni-Polar6 lead	2-3/8" x 2-3/16"	6.35 X20mm/Dual	1.6	\$15.95
18189-MS	D	23	5.7VDC	2.3	5.3mH	2.5	16Kg/cm	57BYGH303	4 Phase/Uni-Polar6 lead	3" x 2-3/16"	6.35 X25mm	2.3	\$23.95
18729-MS	D1	23	5.7VDC	2.3	5.3mH	2.5	16Kg/cm	57BYGH303-50	4 Phase/Uni-Polar6 lead	3" x 2-3/16"	6.35 X24mm/Dual	2.4	\$22.95
18687-MS	D	23	4.5VDC	2.5	3mH	1.8	18Kg/cm	57BYGH317	4 Phase/Uni-Polar6 lead	3" x 2-3/16"	6.35 X25mm	3.4	\$24.95
17456-MS	Ε	23	3.6VDC	3	2.4mH	1.2	21Kg/cm	57BYGH405A	4 Phase/Uni-Polar6 lead	3-1/4" x 2-3/16"	6.35 X19mm	2.6	\$34.95
17458-MS	F	34	3.0VDC	3	4.05mH	1	23Kg/cm	85BYGH450A-04	4 Phase/Uni-Polar6 lead	3" x 3-3/8"	13 X35mm	4.7	\$54.95
18190-MS	G	34	6.0VDC	2	12mH	. 3	48Kg/cm	85BYGH450B-03	4 Phase/Uni-Polar8 lead	4-17/32" x 3-3/8"	13 X35mm	8.1	\$68.00
17457-MS	H	34	7.8VDC	2	24mH	3.9	63Kg/cm	85BYGH450C-01	4 Phase/Uni-Polar8 lead	6" x 3-3/8"	13 X35mm	11	\$79.95

MINI STEP MOTOR DRIVER

P/N: QJ-215 INPUT: 12-36VDC

OUTPUT: Selectable up to 1.5A max. STEP ANGLE: 1.8 deg (200steps/Rev.) Microstep: 1/2-1/4-1/8-1/16-1/32-1/64

Full bridge driver for hybrid stepmotors. Switch Selectable output current.

Over temp Protected.

Opto isolated Step pulse input (Clock input +5V Level). Opto Isolated Direction input (+5V Level)
Opto Isolated Reset input (+5V Level)

Terminal strips in/out.

L: 3-15/16" W: 2-5/16"

WT: .5

18187-MS

Mini Stepper Driver

3A STEP MOTOR DRIVER

P/N: CW230

INPUT: 24-36VDC OUTPUT: Selectable up to 3A max

STEP ANGLE: 1.8 deg (200steps/Rev.) Microstep: 1/2-1/4-1/8-1/16-1/32-1/64 Full bridge driver for hybrid stepmotors. Switch Selectable output current.

Over temp & Output miswire Protected. Opto isolated Step pulse input (Clock input +5V Level).

Opto Isolated Direction input (+5V Level) Opto Isolated Reset input (+5V Level)

Terminal strips in/out. L: 4-5/8" W: 2-3/4

OUTPUT: Selectable from .5 to 8A max.

stepmotors. Switch Selectable output current

18727-MS CW1180 AC Stepmotor Drive

Terminal strips in/out. Internal cooling Fan.

AC POWERED

DRIVER

INPUT: 110VAC, 60hz

L: 7-11/16" W: 3-1/4"

WT: .7

548.50 17451-MS CW230 Stepmotor Driver

STEP ANGLE: 1.8 deg (200steps/Rev.) Microstep: 1;1/2;1/4;1/5,1/6;1/8;1/10;1/16;1/18; 1/20;1/32;1/40;1/50;1/64;1/1/128;1/256

Internal micro controller chip, Full bridge driver for hybrid

Opto isolated Step pulse input (Clock input +5V Level).

Opto Isolated Direction & Enable inputs (+5V Level)

5A STEP MOTOR DRIVER

P/N: CW250

INPUT: 20-60VDC OUTPUT: Selectable up to 5A max

STEP ANGLE: 1.8 deg (200steps/Rev.)
Microstep: 1/8: 1600 steps/Rev.
Full bridge driver for hybrid stepmotors.
Switch Selectable output current. Over temp & Output miswire Protected.

Opto isolated Step pulse input (Clock input +5V Level). Opto Isolated Direction input (+5V Level)

Terminal strips in/out.

L: 5-3/4" W: 3-3/4" H: 1-3/4"

CW250 Stepmotor Driver 17452-MS \$49.95

6A STEP MOTOR DRIVER

P/N: CW260C INPUT: 24-70VDC

MFG: ASTROSYN

P/N: 23KM-K213-P7V

COIL: 3VDC/1.8 ohms/2.6mH TYPE: 2 Phase Uni-Polar, 6 lead

OUTPUT: Selectable up to 6A max. STEP ANGLE: 1.8 deg (200steps/Rev.) Microstep: 1/2-1/4-1/8-1/16-1/32-1/64-1/128-1/256

1/5-1/10-1/25-1/50-1/125-1/250 Full bridge driver for hybrid stepmotors.

Switch Selectable output current. Over temp & Output miswire Protected Opto isolated Step pulse input (Clock input +5V Level). Opto Isolated Direction input (+5V Level)

Opto Isolated Reset input (+5V Level) Terminal strips in/out.

L: 5-13/16" W: 3-13/16" T: 1-3/16"

3V/ 1.8Deg.STEP MOTOR

pully. Four corner mounting holes. 4" leads. L: 1-3/4" (Body) SQ: 2-3/16"

18188-MS CW260C Step Motor Driver

STEP ANGLE: 1.8 deg 1/4" [Dia.] X 1" steel shaft with press fit steel COG belt

17276-MS Astrosyn 1.8Deg. Stepmotor \$10.95

WT: 1.2

WT: 1.1

1.8Deg. STEP MOTOR

MFG: MINEBEA P/N: 23KM-K102-P1V COIL: 3A/1ohm/2.2mH TYPE: 2 Phase Bi-Polar 4 lead

tooth, aluminum cog belt gear. Ball bearings, 6pin connector (supplied), 4 corner mounting holes threaded M4.5

L: 2-5/8"(Body) SQ: 2-3/16"

16320-MS 1.8 Minebea Step Motor \$12.95 \$10.95 TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764

2.88V STEP MOTOR

MFG: SHINANO KENSHI P/N: STH-56D309 COIL: 2.88VDC/2.4A

TYPE: 2 Phase Uni-Polar 6 lead STEP ANGLE: 1.8 deg (Motor) Assembly#: 127K80020

6.5mm dia. X 22mm steel shaft with a rollpinned 3/4" dia. 22 tooth, plastic cog belt gear. Ball bearings, 5in leads. Removable anti-vibration bracket with mtg. ears. 4 corner mounting holes (motor). WT: 1.5

L: 2-1/4"(Body) SQ: 2-3/16"

1.8Deg. STEP MOTOR

STEP ANGLE: 1.8 deg

\$12.95 17504-MS Shinano 2.88V Step Motor

H: 1-3/4"

MFG: SANYO DENKI P/N: 103G770-1856 COIL: 3.5V/1.5A/2.4ohm/2.9mH TYPE: 2 Phase Bi-Polar 6 lead

WT: 3.5

5169.95

STEP ANGLE: 1.8 deg 8mm dia. X 18mm steel shaft with a pressfit 13/16" dia. 18

16321-MS 1.8 Sanyo Step Motor MPJA@MPJA.COM

L: 2-1/8"(Body) SQ: 2-3/16"



WT: 1.5







WT: 1.3

\$8.95

41

3V 1.8DEG. STEP MOTOR

MFG: SHINANO KENSHI P/N: STP42D4009 **NEMA: 17 COIL:** 3V/1.6 ohm TYPE: 2 Phase Uni-Polar 6 lead

STEP ANGLE: 1.8 deg 120step/rev 5mm dia. X 24mm steel shaft with metal 20 tooth X 11/16" dia. gear & 22 tooth X 9/16" dia


cog belt pully. 4 corner m3x0.5 mounting holes. 5" leads L: 1-5/8" (Body) SQ: 1-9/16" \$7.95 16231-MS 1.8Deg. Step Motor



MFG: SANYO DENKI P/N: 103-771-18 COIL: 24V/.18A TYPE: Uni-Polar 5 lead STEP ANGLE: 1.8 deg

Specifications/Features: Used motor with a 1/4" dia. X 3/4" steel shaft. 50oz/in Holding torque, 30oz/in. running depending on drive. 4 corner mounting holes.

L: 2" (Body) W: 2-3/16"sq 15837-MS 24VDC Step Motor \$8.95 \$7.95



P/N: 23LM-C712-P4 **NEMA: 23** COIL: 1.4ohm/2.3mH TYPE: Bi-Polar 4 lead STEP ANGLE: 1.8 dea

Specifications/Features: Custom motor with a 1/4" dia. X 9/16" steel shaft with a pressfit 15/32"dia.13 tooth, sintered steel cog belt pully.

4 corner mounting holes. 13" leads L: 2-3/4" (Body)

18956-MS Astrosyn Step Motor

W: 2-3/16"sa

\$12.95

GEARHEAD STEP MOTOR

P/N: 82919004 COIL: 56VDC/648ohm/5W TYPE: 2 Phase Uni-Polar 4 lead

7.5 Degree stepmotor driving a 1440/1 gearhead, 6mm 7.5 begree stephnotor driving a '1-7-7 goard' dia, X 10mm flatted steel shaft. Removable 7/8" dia, 20 tooth plastic gear. 3 M3 mounting holes. 4" leads. L: 2-9/16" (Body) W: 2-1/8" H: 2-1/2" WT: .5

18891-MS Crouzet Gearhead Stepmotor \$17.95

3V/ 1.8Deg. STEP MOTOR

MFG: SHINANO KENSHI P/N: STP-58D4002-03 COIL: 3VDC/.42ohms TYPE: 2 Phase Bi-Polar 4 lead STEP ANGLE: 1.8 deg

7mm dia. X 18mm steel shaft with a pressfit 1-1/2" dia 36 tooth, sintered steel cog belt gear. Ball bearings, 3' leads, 4 corner mounting holes threaded M4.5, Remov-

able steel mtg. bracket L: 2-5/8"(Body) SQ: 2-3/16'

17153-MS 3V SKC Step Motor \$14.95 \$12.95

1.8 Deg. STEP MOTOR

MFG: SHINANO KENSHI P/N: STP-42D0003 **NEMA: 17**

COIL: 3.8ohm/4.8mH TYPE: 2 Phase Uni-Polar 4 lead STEP ANGLE: 1.8 deg

Custom motor with a 5mm dia. X 7/8" steel shaft with a 13/16" dia., 25 tooth, press fit metal cog belt gear. Ball bearings, 3" leads and four M3-.5 mm corner mounting

L: 1-3/16"(Body) SQ: 1-5/8"

18958-MS Shinano NEMA17 Step Motor \$8.95

24V 15DEG. **STEPMOTOR**

MFG: SLO-SYN P/N: SM-024-0065-RX COIL: 24V/9-11ohms/2.4A TYPE: Uni-Polar 5 lead STEP ANGLE: 15 deg

Used motor with a 1/4" dia. X 1-3/16" steel front shaft with a removable plastic COG Belt pully. 1/4"dia. X 3/4" rear shaft with a Photo interrupter/Tach assembly.

W: 5-1/2"	D: 5-3/4"	H: 3-1/2"	WT: 3.5
STOCK		DESC.	1EA
17758-MS	Slo-Sv	n Step Motor	\$9.95

1.8DEG. STEP **MOTOR**

MFG: SANYO DENKI P/N: 103H7121-0415 COIL: 2A/1.25 ohm/1.9mH TYPE: 2 Phase Uni-Polar 6 lead STEP ANGLE: 1.8 deg 120step/rev

6mm dia. X2 4mm serrated steel front shaft with plastic 16 tooth X 1/2" dia. worm gear (removable). 6mm X 10mm smooth back shaft, removable 3/8" thick steel/rubber shock mounting plate with 4 corner

mounting holes. 3" leads L: 2" (Body) SQ: 2-3/16" WT: 1.2 16817-MS 1.8 Deg. Sanyo Motor \$6.95

6V/ 1.8Deg. GEARS

MFG: SHINANO KENSHI P/N: STP-42D217

NEMA: 17
COIL: 6VDC/.76A/7.9ohms/10mH
TYPE: 2 Phase Bipolar, 6 lead
STEP ANGLE: 1.8 deg
5mm (Dia.) X 20mm (3/4") steel shaft with pinned plastic
21 tooth .75"id. cog belt pulley. Four M3-.5 mm corner
mounting holes. 4" leads.

L: 1-9/16" (Body) SQ: 1-5/8" WT: .6

18957-MS 1.8Deg. Kenshi Stepmotor \$9.95

3V/1.8 Deg.STEP MO-

MFG: JAPAN SERVO P/N: KH56KM2R003 **NEMA: 23**

COIL: 3VDC/.75ohms
TYPE: 2 Phase Bi-Polar 6 lead STEP ANGLE: 1.8 deg

Custom motor with a Front 6mm dia. X 27mm steel shaft with a pressfit 9mmdia.16 tooth, sintered steel cog belt gear. Stepped Rear shaft 17mm long with a flatted shaft end section is .25" long X .195" dia, 2nd step is .25" long X .238"dia. Ball bearings, 10" leads, 4 corner mounting holes.

L: 2-1/8"(Body) SQ: 2-3/16 WT: 1.5 18854-MS 3V Japan Servo Motor \$14.95

24V/3.6 DEG. **STEPMOTOR**

MFG: HOWARD P/N: 1-19-4201

COIL: 24V/.16A/140ohm/68mH TYPE: 2 Phase Bi-Polar 5 lead

STEP ANGLE: 3.6 deg

600gm/cm holding torque. 3/16" dia. X 7/16" shaft with a smooth 11/16" dia. aluminum hub. 2 corner mounting studs, 7" leads

L: 1-1/2" (Bo	ody) W: 1-5/8"s	6. WT:
STOCK #	DESC	TEA
4318-MS	3.6deg. 24V Stepmotor	\$4.95

1.8 Deg.STEP MOTOR

MFG: MINEBEA P/N: 23LM-K202-33V

NEMA: 23

COIL: 6VDC/3.5ohms/1.3A
TYPE: 2 Phase Uni-Polar 4 lead
STEP ANGLE: 1.8 deg
Custom motor with a flatted .25" dia. X

3/4" steel shaft with a 7/8 dia., 28 tooth,

plastic cog belt gear attached by a set screw. Ball bearings, 6" leads, 4 corner mounting holes, removable steel mtg. bracket with shock mounts.

L: 1-5/8"(Body) SQ: 2-3/16" WT: 1.1

18857-MS 6V Minebea Step Motor \$9.95

1.8 Deg. STEP MOTOR

MFG: SHINANO KENSHI P/N: STP58D-1007-01

NEMA: 23

COIL: .6ohms/1.3uH TYPE: 2 Phase Uni-Polar 4 lead

STEP ANGLE:1.8 deg Custom motor with a flatted 7mm dia. X 3/4" steel shaft with a 9/16" dia., 18 tooth, press fit metal cog belt gear Ball bearings, 3" leads, 4 corner mounting holes.

L: 1-5/8"(Body) SQ: 2-3/16"

18866-MS Shinano NEMA 23 Step Motor



MFG: SHINANO KENSHI P/N: STP-57D211 COIL: 3.84VDC/4.7 ohms/.8A

STEP ANGLE: 1.8 deg (Motor) 6.5mm dia. X 18mm steel shaft with a 3/4" dia., 16 tooth, plastic cog belt gear attached by a steel roll pin. Ball bearings, 3" leads, 4 corner mounting holes, Removable

Sq.: 2-3/16" L: 2" Body 17607-MS 3.84VDC Stepmotor




MFG: HOWARD P/N: 1-19-4201 COIL: 24V/.16A/140ohm/68mH

TYPE: 2 Phase Bi-Polar 5 lead


STEP ANGLE: 3.6 deg 600gm/cm holding torque. 3/16" dia. X 7/16" shaft. 2 corner mounting studs. 7" leads. WT: .52

L: 1-1/2" (Body) W: 1-5/8"sq 18885-MS 3.6deg. 24V Stepmotor






TYPE: 2 Phase Uni-Polar 5 lead




















MOTOR/GEAR **ASSEMBLY** 360° VIEW @MPJA.COM

MFG: SHINANO KENSHI P/N: STP-57D505 COIL: 5.3VDC/1A

TYPE: 2 Phase Uni-Polar 5 lead STEP ANGLE: 1.8 deg (Motor)

Assembly#: 127K18074 Step motor & gear assembly for copy machine. Motor has 7mm steel shaft with a pressed on aluminum spur gear. Removable gear unit contains 5 various plastic gears, 2

have mechanical unidirectional clutch. 5in. WT: 2.3 H: 2-7/8" WT: 2.9 Motor: L: 3" Sq.: 2-1/4" W: 5-1/4"

17461-MS \$14.95 Stepmotor Assembly

6V/ 1.8Deg. STEP MOTOR/ **GEARS**

MFG: SHINANO KENSHI P/N: STP-42D217 COIL: 6VDC/.76A/7.9ohms TYPE: 2 Phase Bipolar, 6 lead

STEP ANGLE: 1.8 deg
5mm (Dia.) X 20mm (3/4") steel shaft with pinned plastic
21 tooth .75"id. COG belt pulley. Pully/belt drives 1", 28
tooth pully/1.25", 30 tooth spur gear/and another .57" COG Belt pully assembly on a 6mm jack shaft. Removable rubber vibration bracket, Four corner mounting holes, 4" leads. Steel frame 3-1/8" X 3-1/8" X 1-3/16" includes 1.4" Dia, 34 tooth plastic spur gear with a 5mm

L: 1-9/16" (Body) SQ: 1-5/8"

18305-MS 1.8Deg. Stepmotor/Gears \$9.95

3V STEP MOTOR

MFG: SHINANO KENSHI P/N: STP-58D4001 COIL: 3VDC/.42ohms TYPE: 2 Phase Bi-Polar 4 lead

STEP ANGLE: 1.8 deg 7mm dia. X 18mm steel shaft with a pressfit 7/8" dia. 19 tooth, sintered steel cog belt gear. Ball bearings, 3" leads, 4 corner mounting holes

L: 2-5/8"(Body) SQ: 2-3/16" 18590-MS 3V NEMA 23 Step Motor \$9.95

1.8 Deg. STEP MOTOR

MFG: JAPAN SERVO P/N: KH42JM2-070 **NEMA: 17**

COIL:3.4V/3.2ohms/2.5uH TYPE: 2 Phase Bi-Polar 6 lead


STEP ANGLE:1.8 deg Custom motor with a flatted 5mm dia. X 7/8" steel shaft with a 7/8" dia., 36 tooth, Removable plastic cog belt gear. Ball bearings, 7" leads, 4 M3-0.5mm threaded corner mounting holes. Removable vibration pad & steel bracket

L: 1-9/16"(Body) SQ: 1-5/8" WT: .7 18867-MS Japan Servo Step Motor

VIBRATION ISOLATOR

Rubber shock mount/isolator with M6-1 X 12mm (7/16") long threaded stud on both ends. 2 Nuts Included.

L: 5/8" Body 1-1/2" O/A **Vibration Isolator** 19076-HD



MFG: SHINANO KENSHI P/N: STH-54D500-03Y **NEMA: 23**

COIL: 6.5VDC/5.1ohms/1.3A TYPE: 2 Phase Bi-Polar 5 lead

STEP ANGLE: 1.8 deg

Custom motor with a flatted 7.1mm dia. X 15mm steel shaft with with a 1-5/8 dia., 30 tooth, plastic cog belt gear attached by a steel roll pin. 1-1/2" dia. X 5/16" rubber pad attached to shaft behind pully. Ball bearings, 6" leads, 4 corner mounting holes.

L: 3"(Body) SQ: 2-3/16"

6.5V Kenshi Step Motor \$12.95 18855-MS

12V GEARHEAD STEPMOTOR

MFG: NMB-MAT P/N: PG35L-048 COIL: 12VDC/70Ohms/5.3mH/

TYPE: 2 Phase Bi-Polar 4 lead STEP ANGLE: .2118 deg

Gearhead step motor, 5mm X 8mm steel shaft with a 22.3mm dia, 26tooth aluminum gear. 2 mtg. holes. 12'

leads. Mtg. holes on 1-5/16" ctrs. L: 2" Body WT: .25

\$9.95 18840-MS 12VGearhead Step Motor

7.5 DEG. STEP MOTOR

MFG: AIRPAX P/N: M82201-P2SB COIL: 12VDC/64ohm

TYPE: 2 Phase Uni-Polar 6 lead

7.5 Degree stepmotor with Bronze Bearings, 2mm dia. X 10mm steel shaft, 2 mounting holes. Holding Torq: 3.9 oz/ln 7" leads. Mtg. Ctrs.: 1.65 **Dia:** 1.97" (Body) **D:** 7/8

WT: .18

18501-MS Airpax 7.5 deg. 12V Motor \$6.95

24V 7.5 DEG. STEP MOTOR

MFG: NPM P/N: PFC55-48B1 COIL: 24V/14ohm

TYPE: 2 Phase Uni-Polar 6 lead

7.5 Degree step angle. 2.2mm dia. X 15mm steel shaft with a 8 tooth 1/4" dia. X .187" long brass spur gear. 2 mounting holes. 10" leads. Includes a matching pitch steel 32 tooth gear for a 7/32" shaft

Dia: 55mm(Body) 76.2 O/A D: 25mm (1")

18086-MS 24V Nippon Step Motor \$4.95

24V 7.5 DEG. STEP MOTOR

MFG: NMB P/N: PM55L-048 COIL: 24V/30 Ohm

TYPE: 2 Phase Uni-Polar 5 lead 7.5 Degree step angle. 500PPS, Max rate. 4mm dia. X 10mm steel shaft with 11 tooth, 14mm dia X 7mm , brass gear. 2 mounting ears. 2" leads.

W: 3"(Max Body) 18368-MS 24V NMB PM55 Step Motor

7.5 DEG. STEP MOTOR

MFG: AIRPAX P/N: LB82715-M1 COIL: 12VDC/32ohm TYPE: 2 Phase Uni-Polar 6 lead

7.5 Degree stepmotor with Bronze Bearings, 1/4" dia. X5/

18304-MS Airpax 7.5 deg. Step Motor \$3.95

THOUSANDS more Items on www.mpja.com

24V 7.5 DEG. STEP MOTOR

MFG: NMB P/N: PM35S-048 **COIL:** 24V/50 Ohm

TYPE: 2 Phase Uni-Polar 6 lead 7.5 Degree step angle. 800PPS, Max rate. 3mm dia. X 10mm steel shaft. 2 mounting ears. 7" leads. Dia: 2"(Max Body) T: 5/8" WT: .15

Dia: 2"(Max Body)

18349-MS 24V NMB Step Motor \$3.95

24V LINEAR STEP MOTOR

MFG: EASTERN AIR DEVICES P/N: LB11ABM-4R

COIL: 24VDC/.96A/725ohms TYPE: 4 Phase Uni-Polar 5 lead STEP ANGLE:15 deg(motor)

Removed fron equipment linear step motor. 1/8" dia. X 3/8" rear shaft. 4-56UNS-3A threaded X 1-5/8" long steel front shaft, 4 mounting holes threaded 4-40. 12" leads.

L: 1-7/8"Body Dia: 1-1/16" WT: .3

16385-MS **EAD Linear Stepmotor** \$4.95

5V DC STEP MOTOR WITH LEADSCREW MFG: HSI

P/N: 20841-05-028 TYPE: 2 Phase Bi-Polar 4 lead

COIL: 5VDC/18ohms/5.5mH/.27A LINEAR STEP: .001

Linear actuator/step motor with rotating, 9/64" (.140") Dia. X 2-5/8" steel shaft. 1-1/4" max travel.1-3/64" (1.031") mounting ctrs. 20" leads. Shaft end thread: 2-56 UNC 2A X .15" long

L: 3-1/2" O/A W: 1-5/16" O/A WT: .06

17284-MS **HSI 5V Linear Actuator** \$9.95

12V STEP MOTOR/ LINEAR ACTUATOR

MFG: SONCEBOZ

TYPE: 2 Phase Uni-Polar 6 lead COIL: 12VDC/84ohms

LINEAR STEP: .002

Linear actuator/step motor with non-rotating, 9/64" (.140") Dia. X 5/16" steel shaft. 1/2" max travel. 21oz force. 6" leads. Not sure how these mount as there is no

hardware. L: 2" retracted Dia: 1 WT: .1

STOCK # DESC. 18313-MS 12V Linear Actuator \$9.95

43


TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764


WT: .04

\$1.49









12V MOTOR **ASSEMBLY**

12V Motor assembly containing a HTI Series 42 Sleeve Bearing Motor in plastic housing, 16ft, SPT-2 16AWG cord with

Lighter Plug, Momentary action slide switch and a current limitter. 14400+RPM@ 12V/ 1.1A No Load. Stall Current in excess of 20A. MotorBody: L: 3" X Dia: 1-5/8", 1-1/2in. X 3/16in dia. Steel shaft

STOCK #	DESC	1EA
18770-MD	12VMotor/Cigarette Plug	\$9.95

RECIPROCATING MOTOR ASSEMB.

Removed from new equipment, Motor assembly with a Buehler 1.61.046.520.01 Gearhead motor driving a reciprocating 4-7/8" removable plastic arm. 7/ 8"Stroke. 115 Strokes/Min @ 6V/ 230 @ 12V/460 @ 24V.12 Slot Photo sensor on rear motor shaft, 2 Slot Photo sensor on Cam plate. Removable steel base plate L: 9-3/8" O/A W: 6"O/A

12VDC ACME **GEAR MOTOR**

P/N: 5503740 D COIL: 12VDC

90Deg. Angled gearhead DC motor rated: 88/178/380RPM @ 6/12/24VDC. 1.5A No Load /17A Stall @ 12V

.187 male quick connect terminals 4-1/8" long 7/16"-8 Modified class 4G single thread

Leadscrew with the custom traveler nut. L: 5-1/2" (OA) H: 2-1/4" (OA) H: 6" **WT: 1.8**

19007-MD 12VDC Acme Motor & Nut \$14.95

12V MOTOR/ LEADSCREW

Removed from new equipment, Buehler 1.61.046.53

Gearhead motor driving a 4 3/8" X 1.50"-9 Start Rig........., 100" Max travel, 1.5"/Rev. Plastic anti-backlash nut with removable steel bracket. 50 Slot Photo Tach. (5V powered) on rear motor shaft. 3 front mtg. holes threaded M3-.50 Approx. 105RPM/6V/125mA No Load/1.3A Stall

207RPM/12V/140mA No Load/3.2A Stall

L: 9-1/4"		W1:./2
STOCK	DESC.	TEA
18758-MS	12VMotor/Leadscrew	\$19.95

13.6 VDC MOTOR

Johnson 13.6VDC motor with Bronze sleeve bearings. Used in tools & appliances etc. 6290+RPM, .32A, no load, 13.6V. MaxTorque:6.15oz/in@13.6V/3.6A.1/8' [Dia.] X 5/8" serated steel shaft. Solder terminals

L: 2-3/8" (Body	/) Dia: 1-1/2"	WT: .37
STOCK #	DESC.	1EA
17942-MD	13.6VDCJohnson Motor	\$3.95

12 VDC MOTOR

MABUCHU 12VDC motor with Bronze § sleeve bearings. Used in tools & appliances etc. 3300+RPM/.04A, no load/.7A Stall @ 12V. 2.3mmDia. X 14mm steel shaft. Two M2.6X 0.45

tapped Front mounting holes. Solder terminals. L: 2-3/4" (Body) Dia: 1-1/16" WT: .16

17946-MD 12VDC Mabuchi Motor

ELECTRONIC SPEED CONTROL

INPUT: 120VAC 60HZ OUTPUT: 0-120VAC 15A max Double insulated, and fused. Speed control for brush type AC tools & motors, 3 position switch for OFF,

VARIABLE. 6ft. 16-3 power cord, std. 3 prong AC ouput socket. Not Weatherproof.

W: 1-3/4" H: 2-1/2" WT: .72 18327-TL **Motor Speed Control** \$24.95

DC MOTOR & SPEED CONTROL

MFG: BUEHLER (motor) P/N: 13.65.054.08 Voltage: 24VDC Current: .07NL /.9A Stall

Board: 3-1/2" X 1-3/8". 18-24VDC Power with 5V input to control direction. 1250-1650

speed range.

Motor: L: 2-1/4" Dia: 1-1/4" with 2.5mm dia. X 16mm steel shaft with a press fit 1/2" dia. 3 start plastic worm gear. Bronze bearings, 8" motor leads, 13" board leads. 2 mounting holes on motor. WT: .4

18591-MD Motor with Speed Control

LEAD SCREW MOTOR ASSEMB.

Removed from new equipment, Steel baseplate with a Buehler 1.61.046.531.00 Gearhead motor driving a 4-3/8" long 3/8" X 1.50"-9 Start @MPJA.COM Right Hand, Fast thread stainless steel lead screw. 3.0" Max travel, 1.5"/Rev.

Plastic anti-backlash nut with removable steel bracket. Approx. 105RPM/6VDC/125mA No Load/1.3A Stall, 50 Slot Photo Tach. (5V powered) on rear motor shaft

L: 9-3/8" O/A W: 6"O/A WT: 2.3 17265-MD Lead Screw Motor Assembly \$24.95

12VDC MINI MOTOR

Mabuchi FC-280PT-20150 DC moto with carbon brushes. Rated 8-16VDC 12V nominal. 11800 RPM, 81mA no load/3.9A Stall @ 12V, Torque @ Stall 335g/cm. 2mm dia. X 10mm serrated shaft. Insertion/Compression terminals Dia: 1

L: 1-3/8" (Body) WT: .09 18298-MD 12VDC Mabuchi Motor \$0.99

12/24VDC MOTOR

MFG: BUHLER P/N: 1.13.043.223.12 COIL: 12V

360° VIEW

Rated: 1100 RPM @ 12VDC NL, 2140 RPM @ 24VDC. 4mm dia. X 20mm steel front shaft with pressfit 14mm dia. X 13mm 16 tooth brass gear. 3 M3 threaded mounting holes in front. 3" leads.

L: 3-1/8" (Body) DIA: 1-9/16" WT: 1 16717-MD 12/24VDC Buhler Motor \$12.95

12V 110RPM MOTOR

MFG: COPAL P/N: LC37G-183 COIL: 12VDC

Removed from New Equipment, Gearhead DC motor rated 110RPM@ 12V/ 220RPM @ 24V. 6mm dia. X 27mm flatted steel shaft with metal gears. 3 corner mounting holes. 5" leads. 1-7/8" X 1-5/8" mtg. flange.

L: 2" (Body) Dia: 1-15/16" (Body) WT: .4

\$14.95

15530-MD 12VDC 120 RPM Motor \$16.95

12V GEARMOTOR

COIL: 12VDC Gearhead DC motor rated: 6V= 65RPM/.1A no load/.5A Stall 12V=140RPM/.12A no load/1A Stall 15V=178RPM/.13A no load/1.2A Stall 5mm dia. X 10mm flatted steel shaft. 3 metric (M3)

threaded mounting holes. 2" leads L: 2-7/16" (Body) Dia: 1-1/4" WT: .24

18746-MD 12VDC Gearhead Motor \$12.95

12/24VDC MOTOR

MFG: BUHLER P/N: 1.13.043.242.03 COIL: 12V/3.5ohms

USED DC motor Rated: 2300 RPM @ 12VDC NL, 4700 RPM @ 24VDC. 4mm dia. X 49mm steel front shaft. Front ball bearing, rear sleeve bearing. 3 M3 threaded mounting holes in front. 3" leads.

L: 3-1/8" (Body) DIA: 1-9/16" WT: .92 17295-MD 12VDC Long Shaft Motor \$9.95

24V MOTOR & BELT DRIVE ASSEMB.

USED, Motor assembly with a 24VDC motor driving a COG belt & pulley that in turn drives Worm & gear assembly Approx. RPM @ 24VDC NL: Motor: 3380,

Worm gear: 1650, Spur gear: 116. Plastic gears/steel shafts, Bronze shaft&motor bearings. PC board on motor terminals with noise filters. Steel frame, 5in.

wire leads with ferrite filter. Included is Spur gear without a shaft that matches output spur gear. Motor COG Belt Pully. 478": Jack Shaft COG Belt Pully: .975" Jack Shaft: .309": Output Spur Gear: .608" loose Spur Gear: 1.527" O/D /.320" I/D

L: 3-1/2" O/A W: 3-1/2"O/A H: 3-1/2" O/A WT: 1.1

17294-MD Belt Drive24V Motor \$9.95 \$8.95

13V 700 RPM **MOTOR**

MFG: BUEHLER P/N: 1.61.046.178.01 COIL: 13VDC

Gearhead DC motor rated 700RPM/.13A@13VNoload,3.3A@ 13V Stall, 500RPM @ 13V with 6oz/in torque load. 5mm dia. X 11mm flatted steel

shaft. 3 metric (M3) threaded mounting holes in front plate. 36" leads. L: 2-1/2" (Body) Dia: 1-3/81 WT: .4

16392-MD 13V 700RPM Buehler Motor

IMMERSION/ DEFROST HEATER

MFG: SPRINGFIELD WIRE P/N: CUSTOM POWER: 120VAC/140W Specifications/Features:

Heater element for heating oil/water and other nonflammables & used in icemakers to free up the cubes. "U" shaped with 8" depth and 2-5/8" base. overall length in approx.18". .187" quick connect terminals, 1/4" Dia. 316 stainless jacket, rubber sealing grommets at terminals.

Requires external temperature control. H: 9' W: 2-3/4" T: 7/16' WT: .1

18259-MI Stainless Heater \$5.95 \$4.95

\$1.75

12V @ 58RPM GEARHEAD MOTOR

P/N: 12SM-AT3 COIL: 12VDC

Micro Gearhead DC motor rated:

30RPM @ 6V, 9mA NL 62RPM @ 12V, 20mA NL 58RPM @ 12V, 45mA @ .25kg/cm rated torque 2mm dia. X 5.4mm flatted steel shaft with pin hole. metric

(M5.5 P=0.5) threaded mounting holes. Solder terminals L: 1-3/8"(Body) DIA: 15/32"

17269-MD 12V Micro Gearhead Motor \$12.95

21RPM 12VDC MOTOR/TACH

MFG: BUEHLER P/N: 1.61.031.119.00 COIL: 12VDC USED, 90Deg. Angled gearhead DC motor rated:

10/21/42RPM @ 6/12/24VDC, 300mA No Load/4.5A Stall @ 12V. Has 5VDC, TTL Compatable, 50Pulse/RPM Tach. mounted on rear. 8mm dia. X 50mm removable/ reversable steel shaft held in place by a collet. Removable sheet metal mtg. bracket. 5" Tach leads, 8" motor

L: 8-1/2" (OA) W: 4-1/4" H: 3' WT: 2.9 17249-MD 12V 21 RPM Motor/Encoder \$36.95

> THOUSANDS more Items on www.mpja.com

> > 360° VIEW

24 VDC GEARMOTOR

MFG: MOLON P/N: CHM-2435-1 Voltage: 24VDC

Reversable DC gearhead motor with 5/ 16" dia X 5/8" long steel shaft. Mounted on shaft is 4-7/8" dia. plastic wheel with "O" ring in wheel rim for use as friction drive 45RPM/50mA @24VDC No Load; 1A/7.5in-lb torque @

Stall. 7in. leads. : 2-1/2" (Body) W: 2-3/4" H: 3" DESC 1EA

10+EA STOCK I 24VDC Gear Motor \$9.95 17971-MD \$8.95

135RPM 24V **GEARMOTOR**

MFG: BUHLER P/N: 1.61.046.132.00 COIL: 24V

Gearhead DC motor rated: 12V: 68RPM/30mA No Load/190mA Stall 24V: 135RPM/35mA No Load/420mA Stall

5mm dia. X 26mm flatted stainless steel shaft. 3 metric (M3) threaded mounting holes. 3" leads.

WT: .4 L: 2-3/4" (Body) DIA: 1-3/8'

15585-MD 24VDC/138RPM Motor \$24 \$19.95

12VDC/6.8RPM **GEAR MOTOR**

MFG: IGARASHI MOTORS (IGUSA) P/N: Custom 2732-0300 COIL: 12V

Gear motor rated: 6.8 RPM @ 12VDC, 5mm (3/16") dia. X 10mm (3/8"), flatted steel shaft, bronze bearings. Three M3-.5 threaded mounting holes in front. Solder terminals L: 2-11/16" (Body) Dia: 1-1/4

15870-MD 12V 6.8RPM Motor \$12.95 \$9.95

19V/82 RPM **GEARHEAD MOTOR**

MFG: PITTMAN P/N: GM8712F191 COIL: 19.1VDC/12ohm USED, Gearhead DC motor rated: 82RPM @ 19.1V, .08A NL,1.5A Stall 51RPM @ 12V, .07A NL, 1A Stall

.187" dia. X .625" steel shaft with a clamp-on 30 tooth steel gear. Removable mtg. plate. Three 4-40 threaded mounting holes. 4" leads.

L: 2-3/4"(Body) DIA: 1-3/8" WT: .4 18609-MD 82 RPM/19V Motor \$12.95

12V 360 RPM MOTOR

MFG: BUEHLER P/N: 1.61.046.112.00 COIL: 12-24VDC

Gearhead DC motor rated 700RPM @ 24V/360RPM @ 12V with 6oz/in torque load, 5mm dia, X 10mm flatted steel shaft, 3 metric (M3) threaded mounting holes, 3" leads.

L: 3-1/2" (Body) Dia: 1-3/81 WT: .56 12V-24VDC Gear Motor 16815-MD \$9.95

12V 40 RPM MOTOR

MFG: BUEHLER P/N: 1.61.046.116.00 **COIL: 12-24VDC** Gearhead DC motor rated: 24V/.064mA NL/1.55A Stall/81RPM 12V/.058mA NL/.45A Stall/40RPM 5mm dia. X30mm steel shaft with a 20mm, 16 tooth, plastic gear held by a roll pin. Removable heavy steel bracket & a non-removable cast metal secondary bracket with four 6-32 threaded mounting holes. 3" leads

L: 3-1/2" (Body) Dia: 1-3/8" **WT:** .56 \$14.95 16816-MD 12V/40RPM Gear Motor

DUAL TOY MOTORS

Pair of 3-6VDC motors Mounted in plastic housings with 2-1/2" dia. X 3/

4" foam rubber wheels. Appears to use 2 or more "C" or "D" cells. Wiring harness has 2 Battery contacts and a 3 position switch. In one position a diode is connected in series with the motors to reduce the voltage. Motors & housings are almost identical with the exception of one motor has a small belt drive hub.

H: 2-3/4" Each: L: 3-3/8" W: 3-1/4" 18310-MD **Dual Toy DC Motors** \$1.95

1 RPM TIMER MOTOR

MFG: BRISTOL COIL: 120VAC 60Hz. **DUTY:** Cont. 1RPM Timer motot. Output CCW as viewed from shaft end. .31" dia. 18 tooth brass gear on 3/16" long shaft. 6in. leads.

L: 1-1/2" O/A WT: .27 Dia: 2"

\$5.95 120VAC 1RPM Motor 17843-MA

SINGLE ACTION SPRING LOADED CYLINDER

MFG: Bimba **BORE: 1-1/2**

STROKE: 7/8' USED. Single action, Spring loaded extension, pressure retract. Stainless steel tube, aluminum heads, air cylinder. 200 PSI max pressure. 7/16" Dia.steel rod X 1-3/4" (extended) with 7/16-20 thread. Front mount 3/4"-16 threaded. 12 lbs to compress spring. Sorry,No Mtg. Nuts L: 4-3/4"Body DIA: 1-5/8" WT: .8

PORTS: 1/8" NPT

8849-HD Pneumatic Cylinder

RUBBERIZED MINI MAGNETS

Very small rubberized magnet possibly used with hall effect sensors as position sensing. These magnets are only 20mm long X 2mm wide with an adheasive backing. You receive a strip of 100pcs for one low price.

L: 20mm W: 2mm T: 1mm 14582-MG 100 Rubber Magnets \$1.00 \$0.50

2-3/4" DIA. RING MAGNET

Strong uncoated ferrite ring magnet with 1-1/4" dia. center hole

Dia: 2-3/4" T: 7/16 WT: 46 15262-MG Ferrite Donut Magnet \$1.95

RARE EARTH DISC MAGNET

Disc shaped, nickel plated, strong, rare earth magnet.

WT: .002 D: 3/81 T: 1/16' 3/8" Disc Magnet 18097-MG \$0.39 \$0.25


RARE EARTH MAGNET

Removed from new equipment. Strong rare earth (Neodymium) magnets. Roughly a irregular cube. All have a nickel plating that maybe chipped.

L: 9mm (3/8") W: 7mm (9/32") T: 6mm7/32") WT: .001

14581-MG Mini R/E Magnet \$1.95 \$1,49

RUBBERIZED **MAGNET**



Counter sunk screw holes at each end with a slanted center section with a 1/4" dia. hole for latch pin. Magnet is 1-1/2" X 1/2" wide X 11/32" thick (max).

L: 1-1/2" W: 1/2" T: 11/321 WT: .014 11443-MG RubberMagnet \$0.40 \$0.29

FERRITE POLE MAGNETS



Pair of Ferrite magnet assemblies each containing 2 trapazodial magnets between 2 steel plates supported by steel spacers. Each magnet is 1/4" Thick X 5/8"tall X

3/4" wide (max).

WT: .23 L: 2-1/4" W: 1-1/8' T: 1/2"

11628-MG Dual Magnet Assembly \$1.95

GIANT **THERMOMETER**

MFG: WIKA

P/N: TI.50 series RANGE: -20 to +120°F (2deg. Subd.) Material: 304 Stainless

Features: 5in. Dia. Bi-metalic tank thermometer with 12in. Stem & 1/2" NPT fitting. 1% accuracy.

WT: 1.12 L: 13

\$19.95 18528-MI **Giant Thermometer**

0-60VDC RACK MOUNT SUPPLY

P/N: BTI-150 Input: 110 VAC/60Hz

Output: Three switch selectable Ranges:

0-15VDC/0-10A 0-30VDC/0-5A 0-60VDC/0-2.5A

Specifications/Features: Enclosed switching supply with dual LED displays for output Volts & Amps. Course & Fine controls for Voltage & Current Limit. 1% Line/Load Reg. <1% ripple. Front binding posts & Internal fan. Feet & brackets can be Installed/Removed as needed for Rack Stacking or bench top use

W: 19" H: 3-1/2" (2U) D: 12-1/4' 18650-PS 0-60V Adj. Rack Supply \$189.95

0-18VDC @ 3A **BENCH SUPPLY**

Input: 110 VAC 60Hz

Output: 0-18VDC @ 0-3A Constant Voltage or Current

Specifications/Features: True Constant Current (Can a short) Enclosed Linear bench supply with dual LCD displays for output Volts & Amps. .01%+3mV Line / .02%+3mV Load regulation, <1mV RMS ripple. Front binding posts. Metal case & rubber feet. Internal Temp. controlled fan

L: 9-1/2 W: 3-5/8 H: 6 WT: 8.6 \$59.95 \$52.95 9600-PS 0-18V/3A Adj. Supply

0-30VDC/5A BENCH SUPPLY

Input: 110 VAC 60Hz Output: 0-30VDC @ 0-5A Constant Voltage or Current

Specifications/Features: True Constant Current (Can drive a short). Enclosed Linear bench supply with dual LED displays for output Volts & Amps. .01% +3mV Line /.02%+3mV Load regulation, <1mV RMS ripple. Front binding posts. Internal Temp. controlled fan.

L: 11-1/4" W: 5-3/16" H: 6-1/4" WT: 14 9603-PS 0-30V/5A Bench Supply \$110.00 \$95.00

MINI 0-30V/3A **SUPPLY**

P/N: 9615 Input: 110 VAC 60Hz

Output: 0-30VDC @ 0-3A Constant Voltage/Current Specifications/Features: True Constant Current (Can drive a short). Enclosed Switching bench supply with backlit LCD display for output Volts & Amps. .01% +5mV Line /.2%+5mV Load regulation, <200mV RMS max ripple. Front banana jacks. Internal fan. CE/RoHS

L: 6" W: 2-7/8" H: 6-3/41 WT: 3.2 \$59.95 9615-PS Mini 0-30V/3A Bench Supply

0-30VDC @ 19A **BENCH SUPPLY**

P/N: 9950 Input: 110 VAC 60Hz

46

Output: 0-30VDC @ 0-19A Constant Voltage or Current Specifications/Features: True Constant Current (Can drive a short). Enclosed Linear bench supply with dual LED displays for output Volts & Amps. .01% +3mV Line /.05%+3mV Load regulation, <1.5mV RMS ripple. Front binding posts. Internal Temp. controlled fans

L: 11-1/4' W: 10-1/2' H: 6-1/2" WT: 41 9950-PS 0-30V/19A Adj. Supply \$269.00 \$239.00

TRIPLE OUTPUT **BENCH SUPPLY**

MFG: MPJA Inc Input: 110 VAC 60Hz Outputs: #1: 0-30VDC @ 0-5A

#2: 0-30VDC @ 0-5A #3: 5VDC @ 3A Specifications/Features: Dual Constant Voltage or Cur-

rent supply with dual backlit LCD meters. Selectable Series/Parallel operation of Adj. supplies.10 turn Voltage control, Push button Current control (30ma resolution) <.05% Line/Load regulation (CV) .05% line/load (CC) Front panel output Banana Jacks & Terminal strips

W: 10-3/4" D: 13" H: 7-1/2" \$259.00 9335-PS Three Output BenchSupply

0-60VDC BENCH SUPPLY

Input: 110 VAC 60Hz Output: 0-60VDC @ 0-10A Constant Voltage or Current Specifications/Features: True Constant Current (Can drive a short) Enclosed Linear bench supply with dual LED displays for output Volts & Amps. .01% +3mV Line /.05%+3mV Load regulation, <1.5mV RMS ripple. Front

binding posts L: 11-1/4" W W: 10-1/2" H: 6-1/2" \$259.00 9960-PS 0-60V Bench Supply

.5KVA ADJUSTABLE AUTOTRANSFORMER

@MPJA.COM Input: 110 VAC 50/60Hz Output: 0-130V@ 500VA (4A) Specifications/Features: Enclosed, Illi non-isolated, Adjustable transformer Features: Output Volt Meter, lighted Switch, fuse & single 3 blade outlet.

H: 6" W: 4-3/4" D: 6-D: 6-1/2

15162-TR .5KVA Adj. Transformer \$49.95 \$43.80

WT: 10

2KVA ADJUSTABLE AUTOTRANSFORMER

Input: 110 VAC 50/60Hz Output: 0-130V@ 2KVA (15A) Specifications/Features: Enclosed. non-isolated, Adjustable transformer Features: Output Volt Meter, lighted Switch, 20A fuse & single 3 blade outlet

H: 7-1/2" W: 8-3/4" D: 6-7/81 WT: 22 15163-TR 2KVA Adj. Transformer \$104.95

STEPDOWN ISO. TRANSFORMER

MFG: STANCOR P/N: GSID150 Input: 230 VAC 50/60Hz Output: 115VAC@1.3A(150W)

Specifications/Features: Step down Isolation transformer with grounded core shield. 5-1/2ft. input cord with 230V NEMA 6-15P molded plug, 8in. output cord with Std. 115V NEMA 5-15R molded receptacle. Ground pass through

L: 4-3/16" H: 3-7/8" W: 3-3/16" 18679-PS Stancor Stepdown Transformer \$29.95

I/R SMALL SPOT THERMOMETER

Highly advanced, Close focus, non-contact, I/R temperature meter. Featuring bright Class II Dual lasers "Spot-On" aiming for accurate measurements. Measure the temperature of components, skin and other close surfaces as small as .1in. with pinpoint accuracy MFG: ZYTEMP

P/N: TN01U Range: Temp: -55 "C" to +220 "C" -67 to 428 "F"

Features:

17782-TL

Large Multi-function Backlit LCD display Selectable degree F or C readout

Digit Temp, readout Min/Max measurements

Stopwatch

Realtime Clock Specifications:

ocus: 18mm (.7") Measurement Spot Size: 2.5mm (.1") @ .7in Emissivity: Adj. 0.05-1.00 factory Preset at .95 Accuracy: +-2%/+-2Deg. Whichever is greater Display Resolution: 0.1 "C" (.1 < 199.9 /1>200)

Response Time: 1Sec. Power: 2 "AAA" Cells (Approx. 18hr. continious use)

L: 6-3/4" **W:** 1-1/2" T: 1" WT: .3 Shp. WT: .51 I/R Temperature Meter

\$79.95

PISTOL GRIP I/R THERMOMETER

Single hand, Pistol grip type Non-contact infrared digital thermometer with LASER pointer, Auto Turn Off, selectable "F" or "C" display, LED Backlight. Includes soft sided woven case. CE listed.

Display: 3-1/2 digit Backlit LCD

Detection Range: 5-14um
Range: -58 "F" to +716 "F" (-50 "C" to 380 "C")
Selectable "F" or "C"

Accuracy: +- 2% or 2 deg. "C" Resolution: .1Deg.

Sample Rate: approx. 2/Sec while holding Trigger. Single shot per trigger pull

Distance Factor: 8/1 (at 8" spot size is 1")

Emissivity Factor: fixed @ .95 Power: 9 VDC battery

H: 6-1/8" W: 1-1/2" L: 3-1/4" WT: .34 Shp. WT: .6

\$24.95 9910-TE I/R Temperature Meter

PHOTO TACHOMETER

Hand held photo reflective tachometer. 5 digit LCD display measures RPM from 5-99,999 with auto range select. Resolution: .1RPM < 1000, 1RPM/above 1000. Features Hi/Lo/ Last reading memory. Powered by 4 "AA" cells or included 120VAC adapter. Requires reflective area on a non reflective

WT: 1.52 STOCK # \$39.00 15161-TE **PHOTO Tachometer**

LASER TACHOMETER

Hand held photoreflective tachometer uses LASER beam. 5 digit LCD dis-play measures RPM from 2.5-99,999. Resolution: .1RPM /2.5-999, 1RPM/above 1000. Features Hi/ Lo/ Last reading memory. Powered by 4 "AA" cells or included 120VAC adapter. Requires reflective area on a non reflective surface.

WT: 1.52 15160-TE **LASER Tachometer** \$39.95

ORDERS: CALL 800-652-6733 FAX 800-432-9937 WWW.MPJA.COM

CLAMP-ON DIGITAL AMMETER/MULTIMETER

Clamp-on digital Ammeter/multi-meter with 3-1/2 digit LCD display. Features Data Hold, 2" Jaw opening, 2" clamp diameter closed for large conductors or buss bars. Impact plastic case. With test leads, wrist lanyard, storage pouch & instructions. Note: Meter designed for reading AC/DC lines not low level uses. Not auto-ranging

AC CURRENT: 200,1000, Accuracy +-2% +-5LSD, Fre-

quency 50-60Hz, Overload 1200A 1min. AC VOLTS 750V, Accuracy +-1.0% +- 4LSD, Overload 750V AC/DC

DC VOLTS 1000 Volts, Accuracy +-.5% +- 1LS, Impedance 9M ohms

RESISTANCE Ranges: 200, 20Kohms Accuracy: +-1% +-3LSD @ 200 +-1% +-1LSD@ 20K

CONTINUITY TEST: (200ohm Range) BUZZER < 30 +-20 ohms H: 9-1/4" W: 3-1/21 T: 1-3/4

\$9.95 11469-TE **Digital Amp Meter**

WT: .9

0000

TRUE RMS AUTORANGE DMM

Quality 3-7/8 digit (6000 count) DMM with .8" char. ht. LCD display. Autoranging with Max/Min, Data Hold, AC & DC voltage/Current, frequency to 600KHz, Capacitance, Resistance to 60M Ohm, Fused input. Includes Test leads. **Batteries not Included**

DC VOLTS 6V to 1KV, Accuracy .3% +3 LS digit/.8%+4 on 1KV. Impedance 10 Mohm

DC CURRENT 600uA to 20A, Accuracy .8% + 5 LS digit/ 1.2% +5 on 10A. Overload .8A Fuse on uA,mA 20A: 15sec/30min off. Fused @ 15A

AC VOLTS 6V to 750V, Accuracy 1% +8 LS digit, Impedance10M ohm, Overload 750VRMS

ACCURRENT 600uA to 20A, Accuracy 1.2% + 8LS digit 2% +8 on 10A

20A: 15sec/30min off. Fused @ 15A
CAPACITANCE 60nF to 100uF, Accuracy 10% + 25 LS 2.5% +10 on 100uF

RESISTANCE 600 to 60M Ohm, Accuracy .5% + 5LS digit, 2% + 10 on 60M Ohm

FREQUENCY 11Hz-600KHz, Accuracy .2% +3LS digit, OTHER Continunity buzzer <400hm, Diode/Transistor tests

T: 7-3/8' W: 3-5/8" D: 1-3/4" **WT:** .8 True RMS DMM \$89.00 16375-TE

DIGITAL MULTIMETER

Light weight 3-1/2" digit hand held meter with LCD display. With battery, test leads & instructions. Fuse & Diode Overload protection. 10A Unfused) 9V Powered

SPECIFICATIONS

DC VOLTS & CURRENT

Range Volts .2,2,20,200,1KV Volts:

MISCELLANEOUS

Current: 200ua,2,20,200mA,10A

AC VOLTS Volts: 200,750V Ranges

RESISTANCE

anges: 200-2K-20K-200K-2M Test V: 2.8 VDC open cir. Ranges:

Diode Test: ~1.5mA Transistor Test: Test I =~10uA Vce=~2.8V Accuracy: 2% worst case (10A range)

W: 2-5/8" H: 5" WT: .9 17892-TE Lightweight 3.5 Digit DMM \$6.95 **BACKLIT DMM**

3-1/2 digit, 15mm (.6") char. Ht. LCD digital multimeter. Features HOLD Button, backlight button (~5sec. on). With 9V battery, test leads & instructions. Fuse & Diode protected (not 10A range). Yellow protective Boot. CE listed. Cat 2 use. Not Auto Turnoff

DC VOLTS 200mV,2,20,200,600, Accuracy .8% + 2 LS digit

DC CURRENT 200uA,2,20,200mA, 10A

Accuracy1.5% + 2 LS digit, 250V on 200mV 600V Max AC VOLTS 200,600V, Accuracy 1.2% + 10 LS digit, 40-400Hz. Ave. Responding, 600V RMS/DC Max RESISTANCE 200,2K,20K,20K,2M Ohm, Accuracy 1%

2 LS Digit, 250V RMS Max **DIODE & TRANSISTOR TEST**

Diode Displays forward drop hre 0-1000 lb =10ua/Vce=3V

H: 5-3/4" W: 3" WT: .8 14213-TE Mini Deluxe Backlit DMM \$14.95

BACKLIT AUTORANGE DMM

Quality 3-3/4 digit (4000 count) DMM with .8" char. ht. backlighted LCD display. Autoranging and Range & Data Hold, AC & DC voltage/Current, frequency to 400KHz, Capacitance, Resistance to 40M Ohm, Fused input. Includes Test leads, 9V Battery not included

DC VOLTS: .4V to 1KV, Accuracy .8% +5 LS digit Imped-

00

000

\$5.95 \$4.95

DC CURRENT 400uA to 20A, Accuracy 1.2% +5 LS digit/ 1.8% on 4A/ 2% on 10A. Overload .5A Fuse on uA,mA. 20A: 15sec on/30min off. Fused @ 20A

AC VOLTS 4V to 750V, Accuracy 0.8% +8 LS digit, Impedance10M ohm, Overload 750VRMS

CURRENT 400uA to 10A, Accuracy 1.2% + 8LS digit 2.5% +5 on 4A, 3%+5 on 10A, Overload fuse. 20A: 15sec on/30min off. Fused @ 20A

CAPACITANCE 4nF to 100uF, Accuracy 6% + 6 LS digit on 40nF, 2% +5 on others

RESISTANCE 400 to 40M Ohm, Accuracy .8% + 5LS

digit, 1.2% + 10 on 40M Ohm. FREQUENCY 10Hz-400KHz, Accuracy .2% + 3 LS digit, OTHER Continunity buzzer < 200hm, Diode/Transistor tests

T: 7-3/8" W: 3-5/8" D: 1-3/4" WT: .8 16373-TE Lge. Char. Backlit DMM \$34.95

LARGE CHARACTER MULTIMETER

1in.Character Hight, 3-1/2 digit LCD digital multimeter. With 9V battery, test leads & instructions. CE Listed **SPECIFICATIONS**

DC VOLTS & CURRENT

Ranges: Volts: 200m,2,20,200,1KV Accuracy: .5% +- 3 LS digit Overload: 200V ACrms for 200mV 1KV/750RMS for all other Current: 200ua,2,20,200mA,10A Accuracy: 1% +- 3 LS digit (2%/10A) Overload: 500mA Fuse/ Unfused 10A

AC VOLTS

Ranges: 200,750V

Accuracy: 1.2% +- 10 LS digit
Overload: 1KV/750RMS for all other

RESISTANCE

200,2K,20K,200K,2M Accuracy: <200: 1% +-10 LS I > 200: 1% +-2 LS Digit Overload: 200V AC/DC15Sec. Max. DIODE & TRANSISTOR TEST: 1% +-10 LS Digit

2.8VDC Test V 10uA Base drive hFE

Lg. Char. DMM

H: 5" W: 2-3/4" WT: 1.2

MPJA@MPJA.COM

AUTORANGE DMM RS232 INTERFACE

Quality 3-3/4 digit (3999 count) DMM with 1" char. ht. Connects to your PC port & software provides data capture, tracking & printing. Autoranging or manual, Data Hold, AC & DC voltage/ Current, frequency to 300KHz, Capacitance, Resistance, 40M Ohm, Fused input. Includes Test

leads, Black Boot, RS232 cable & Software.
Requires: Pent. 90MHz or better, Win95 above, 16M RAM, 20M Hard drive space, Floppy Drive. Batteries not Included

DC VOLTS: 4V to 1KV, Accuracy .5% +3 LS digit (0.8%+3 on 1000), Impedance 10 Mohm

DC CURRENT 400uA to 20A, Accuracy 1.2% + 5 LS digit, Overload .8A Fuse on uA,mA/20A

30sec on/15min off. Fused @ 20A

AC VOLTS .4V to 750V, Accuracy 0.8% +8 LS digit, Impedance10M ohm, Overload 750VRMS

AC CURRENT 400uA to 20A, Accuracy 1.2% + 10LS digit (3%+5 on 20A), Overload fuse.

20A: 30sec on/15min off. Fused @ 20A

CAPACITANCE 4nF to 40uF, Accuracy 5% + 25 LS digit (2% 40uF), Test Voltage .45V, Overload 1000Vp RESISTANCE 400 to 40M Ohm, Accuracy 1.5% + 5LS

digit, (5% 40M Ohm) FREQUENCY 10Hz-300KHz, Accuracy .5% + 3 LS digit,

OTHER Continunity buzzer <200hm, Diode/Transistor: 2.8V Test

Transistor HFE @ 10uA

T: 7-3/4" W: 3-1/4" D: 1-1/2" WT: 1.3 16374-TE Lge. Char. DMM/RS-232

AUTO RANGE TRUE RMS DMM

UL Listed, Auto Ranging, Quality 3-3/4 digit (4000 count) DMM with .8" char. ht. LCD display. Data & Range Hold, AC & DC voltage/Current, Frequency, Resistance, Temerature, Capactance, Fused input. Includes Test leads & Temp. probe Batteries not Included (2 X AA)

DC VOLTS .4V to 1KV, Accuracy .8% +1 LS digit, Impedance 10 Mohm

DC CURRENT 400uA to 20A, Accuracy 1.2% + 5 LS digit, 2% +5LS digit on 20A. Overload .5A Fuse on uA,mA, 20A: 15sec on/30min off. Fused @ 20A AC VOLTS 4V to 750V, Accuracy 0.8% +8 LS digit,

Impedance 10 Mohm

AC CURRENT 400uA to 20A, Accuracy 1.2% + 8LS digit, 3%+5 LS digit on 20A, Overload fuse. 20A: 15sec on/30min off. Fused @ 20A

20A: 15sec on/sumin ori. Fused © 20A RESISTANCE 400 to 40M Ohm, Accuracy .8% + 5LS digit, 1.2% + 10LS digit on 40M Ohm. CAPACITANCE 4nF-100uF, Accuracy 6%+6 LS digit on

40nF, 2% +5 LS digit other ranges FREQUENCY 4Hz-400KHz, Accuracy .1% + 3 LS digit,

250V max DUTY CYCLE 0.1%~99.9%, Accuracy1.2%+2LS digit,

Pulse Width: 100uS~100mS TEMPERATURE

C: -20~ 300deg Accuracy 3deg. C + 3 LS digit F: -4~ 572deg Accuracy 3deg. F +6 LS digit OTHER Continunity buzzer <200hm,

Diode/Transistor HFE

T: 7-1/4" W: 3-3/8" WT: 1.1 \$59.00 17350-TE Auto True RMS DMM

LED TESTER

Compact, pocket sized checker/comparator for LEDs. 12 position test socket strip provides tes currents of 2,5,10,20.30 &50mA.7 center positions provide 10mA test current allowing you to compare several LED at the same time. Requires 9V battery (not supplied)



W: 2-3/8" T: 7/8" H: 3-1/8"

\$5.95 14371-TE LED Tester \$6.95

TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764

17191-TE

47

METERSI TEST EQUIPMENT Visit www.mpja.com for our Complete Products Lines.

CABLE TRACER

Two part cable tracer with 2 test leads & a 4 conductor MOD cable. Tone generator sends signal into cable that can be traced by probe. Generator features: color LED for Phone line polarity, continunity and voltage testing. 30in Red, Black leads, 12in Phone cable, Modeswitch. Probe features: Non-conductive, inductive tip, Adj. volume level,



Probe works with most existing tone generators. Both use 9V batteries. Includes zippered cloth carry pouch. WT: .52

STOCK #	DESC.	TEA.
6812-TE	Wire/Cable Tracer	\$19.95

FIBER OPTIC TESTER

2 piece unit allows testing of installed lines.

Receiver displays signal level Test Wavelength: 1300nM. Fiber Core: 62.5/125uM (Multimode)

Range: -20~-40dbm also " HI" &" LO" when outside range

Termination: ST Female
Requires 9V battery for each unit (Not Supplied). Includes zippered cloth case.

W: 2-1/2" T: 1" WT: .5 (Pair)

STOCK	DESC.	1EA
6820-TE	Fiber Optic Test Set	\$120.00

DC PANEL METERS




ELENCO DC panel meters, Black legends/Red over-ange, Plastic case. Back Mounts in 2" X 1-1/8" cutout NO MOUNTING HARDWARE

W: 2-1/4" H: 1-7/8" D: 1-1/4" WT· 1

STOCK V	DESC.	TEA	10+EA
5333-ME	0-30V DC Voltmeter	\$6.95	\$6.59
5334-ME	0-40V DC Voltmeter	\$6.95	\$6.59
5336-ME	0-3A DC Ammeter	\$6.95	\$6.59

SWITCHBOARD PANEL METERS





on white face with mirror scale. Plastic case with "zero" adjustment. Front mounts in 1-1/2" hole. Four mounting screws on 1-1/4" ctrs. 30A DC meter includes External Shunt. 5A AC meter Includes external CT.

W: 2-3/16" H:	1-13/16" D: 1-1/2" W1: .16 (.35	for 3UA)
STOCK #	DESC.	TEA
17671-ME	0-15V DC Voltmeter	\$8.95
17672-ME	0-30V DC Voltmeter	\$8.95
17674-ME	0-3A DCAmmeter	\$8.95
17679-ME	0-30A DCAmmeter/Shunt	\$9.95
17681-ME	0-150V AC Voltmeter	\$8.95
17683-ME	0-5A AC Ammeter	\$9.95

GENERAL USE VOLT & AMP METERS



Quality general use panel meters. Accuracy: 2-1/2% Black legends on white face. Plastic case with "zero' adjustment. Front mounts in 1.772" (45mm) hole. Two mounting screws on diaognal.

W: 2-3/4" H:	2-1/4" D: 1-7/8"	WT: .2
STOCK	DESC.	TEA
16557-ME	0-150VAC Voltmeter	\$7.95
17255-ME	0-3AAC Ammeter	\$7.95
16558-ME	0-15AAC Ammeter	\$12.95

BACKLIT LCD METER

Compact,200mV input, polarity, 3-1/2 Digit, 1/2" character height, Back lit LCD panel meter with black plastic bezel &



face plate. Adj. decimal point, .5% accuracy. >100Mohm input imp.Chip On Board design for economy & compactness. For battery powered monitoring or test equipment. Through panel mounting.

9 VDC powered, Meter power must be isolated from input (Cannot monitor own power source).

AVAILABLE: Scaling Resistors for you to install.

20.0 VDC Resistor set 12073-RS 200 VDC Resistor set 12074-RS

W: 2-3/4" H: 1-3/4" D: 1-1/8" (Inc. Bezel) WT: .13

STOCK #	DESC.	1EA	10+EA
11273-ME 9V	BackLit Panel Meter	\$12.95	\$11.95
12073-RS	20V Resistors	\$1.00	\$0.90
12074-RS	200V Resistors	\$1.00	\$0.90

SNAP-IN LCD PANEL METER PM438

Compact, Snap-In, 200mV 3-1/2 Digit, reflective LCD Digi

tal panel meter with black plastic bezel & face plate. New Chip On Board design for economy as well as compactness. Ideal for battery powered monitoring or test equipment.

Basic meter features:

1/2" character height Adj. decimal point >100Mohm input imp. Auto polarity .5% accuracy. 2 readings/sec. Snap-In Through front of panel

9 VDC powered, Meter power must be isolated from input (Cannot monitor own power source).

W: 2-5/8"	H: 1-9/16"	D: 3/4"	V	/1:.1
STOCK #	DE	SG.	16A	10+EA
15978-ME	9V Snap-In	LCD DPM	\$9.95	\$8.95
12073-RS	20V Res	istors	\$1.00	\$0.90
12074-RS	200V Res	sistors	\$1.00	\$0.90

LCD PANEL **METERS**



200mVDC Compact, 3-1/2 Digit, reflective LCD Digital panel meter with black plastic

bezel & face plate. Chip On Board design for economy as well as compactness. Ideal for battery powered monitoring or test equipment

Basic meter features:

1/2" character height Adj. decimal point Auto polarity >100Mohm input imp. .5% accuracy. 2 readings/sec.,

Through panel mounting. 9 VDC powered, Meter power must be isolated from input (Cannot monitor own power source).

5 VDC powered, Meter power and Input can share a common Ground (-input/-Power)

AVAILABLE: Scaling Resistors for you to install. 20.0 VDC Resistor set 12073-RS

200 VDC Resistor set 12074-RS

W: 2-5/6	n: 1-3/4	D: 3/0	٧	VII.I
STOCK #	DESC.	TEA	25EA	100+EA
6929-ME	9V LCD DPM	\$7.95	\$6.40	\$5.95
15977-ME	5V LCD DPM	\$10.95	\$9.95	\$8.95
12073-RS	20V Resistors	\$1.00	\$0.80	\$0.70
12074-RS	200V Resistors	\$1.00	\$0.80	\$0.70

scan with your smart phone



MINI LED PANEL METER

CX102



3-1/2 Digit, 200.0mV DC input, . Compact, LED DPM with black plastic face. 1/2" character height, adj. decimal point, auto polarity, >10Mohm input imp. 2 read-

ings/sec., .05% accuracy. Snap-in panel mounting. Gold plated pins on .10" spacing. RECOMMEND YOU PURCHASE SCALE BOARD 12209-ME Scaling board for 20V, 200V & 500V. Plugs on back, MUST BE ORDERED SEPARATELY

5 VDC powered, Meter power and Input can share a common Ground (-input/-Power)


W: 2-7/16" H: 1" D: 1-13/16"

12208-ME Mini 5VLED Panel Meter \$14.95 \$10.49

360° WEB

MINI LCD PANEL METER

CX101



spacing RECOMMEND YOU PURCHASE SCALE BOARD

12209-ME Scaling board for 20V,200V & 500V.Plugs on back. MUST BE ORDERED SEPARATELY

Meter power:

Must be isolated from Signal input (Cannot monitor own power source)


W: 2-7/16" H: 11 D: 1-13/16" WT: .07

12205-ME Mini 9VLCD Panel Meter \$13.50

DPM SCALE BOARD

SCALE BOARD FOR 12205, 12206, 12207, 12208 DPM'S

Scale board plugs on back of meter. Includes scaling resistors for 20V,200V & 500V ranges.



360° VIEW

12209-ME DPM Scale Board

MULTI FUNCTION PANEL METER

Compact, Auto polarity, 3-1/2 Digit, 1/2" character height, reflective LCD panel meter with black plastic bezel & face plate. Adj. decimal point, .8% accuracy (1% AC). >100Mohminputimp.ChipOnBoard

design for economy & compactness For battery powered monitoring or test equipment.

RANGES: (jumper selected) 00mA VAC: 200V/500V VDC: 200mV/2V/20V/200V/500V ADC: 200mA

Selectable Power: 9VDC (Isolated power) or 5VDC (input & power can share common Ground) W: 2-5/8" H: 1-3/4" D: 3/81 WT: .1

16177-ME Multi.LCD Panel Meter \$8.95 \$8.40

LARGE DIGIT WEB PANEL METERS

3-1/2 digit, LED, 200.0mV DC basic input, .8" character height,

DPMs with black plastic face. adj. decimal point, auto polarity, >100Mohm input imp. 2 readings/sec., 0.5% accuracy. Snap-in panel mounting. Built in scaling resistors for 20V, 200V & 500V ranges

5 VDC powered. Meter power and Input can share a common Ground (-input/-Power)

W: 3-3/8" H: 1-5/8" D: 1" O/A WT: .13

12308-ME 5V LED Panel Meter \$12.95 \$11.95



DUAL RANGE LED PANEL METER



3-1/2 Digit, 200.0mV/20V DC input. Compact, LED DPM with black plastic face. .56" character height, adj. decimal point, auto polarity, >1Mohm input imp. 2 readings/sec., .2% accuracy. Snap-in panel mounting. Header connector for input/ output. (Includes mating connector with leads.)
DIP Switch for Decimal point, Differential input, and
100X input (Switch "ON" for 20V input) selection.

5 VDC powered. Meter power and Input can share a common Ground (-input/-Power) EXCEPT in "Differential" mode.

W: 72mm	H: 36mm	D: 27mm	WT: .13
STOCK #		DESC.	1EA
16565-ME	Mini 5VL	ED Panel Meter	\$9.95

360° WEB LARGE DIGIT **PANEL METERS**



3-1/2 digit, LCD, 200.0mV DC basic input, .8" character height,

DPMs with black plastic face. adj. decimal point, auto polarity, >100Mohm input imp. 2 readings/sec., 0.5%

polarity, >100Month Input Irrip. 2 readings/sec., 0.5% accuracy. Snap-in panel mounting.

Built in scaling resistors for 20V, 200V & 500V ranges

9 VDC powered, Meter power must be isolated from input (Cannot monitor own power source).

5 VDC powered. Meter power and Input can share a common Ground (-input/-Power)

W: 3-3/8"	H: 1-5/8"	D: 1" O/A	VV	/1:.13
STOCK #	DESC.		TEX.	10+EA
12305-ME	9V LCD Panel	Meter	\$9.95	\$9.49
12306-ME	5V LCD Panel	Meter	\$9.95	\$9.49

4-1/2 **DIGIT PANEL METER**

200.00mV DC input, Compact 4-1/2 Digit LCD DPM with black plastic face. 3/8" char-

acter height, adj. decimal point, auto polarity, >100Mohm input imp. 2 readings/sec, 0.05% accuracy. Through panel mounting. Holes on board to add scale resistors. 9V powered, Meter power must be isolated from input

(Cannot monitor own power source). W- 2-5/8" H- 1-3/4" D: 1/2

STOCK #	DESC.	TEA	10+EA
7160-ME 4-1	1/2 Digit Panel Meter	\$18.95	\$17.95
12073-RS	20V Resistors	\$1.00	\$0.90
12074-RS	200V Resistor	\$1.00	\$0.90

LED DIGITAL PANEL METER



plastic bezel & face plate. .56" character height, 200mV DC in-

put, adj. decimal point, auto polarity, >100Mohm input imp. 2 readings/sec., 9V powered, .5% accuracy. Through panel mounting. Holes on board to add scale resistors. Meter power must be isolated from input (Cannot monitor own power source).

W: 2-5/8"	H: 1-3/4"	D: 3/8"	V	/1:.1
STOCK #	DE	SC,	TEA	10+EA
7516-ME	LED Pane	el Meter	\$11.95	\$10.95
12073-RS	20V Re	esistors	\$1.00	\$0.90
12074-RS	200V F	lesistor	\$1.00	\$0.90

SIGN-UP FOR OUR EMAIL SPECIALS ON MPJA.COM

SWITCHBOARD VOLTMETER



Quality switchboard panel meter. Accuracy rated 2-1/2%. Black legends on white face with red tip pointer. Plastic case with "zero" adjustment. Front mounts in 2-3/8" (60mm) hole. Two mounting screws.

W: 3-1/8"	H: 2-1/2"	D: 2-3/8	14	WT: .24
STOCK #	DE	SC.	TEA	10+EA
8720-ME	0-50V DC	Voltmeter	\$13.95	\$12.95

DC CURRENT SHUNTS

A: L: 4-3/4" W: 1" H: 3/4"

Panel mount DC current shunts for use with 50mV or 100mV DC ammeters. Type A have Thermoplastic mounting base with mounting holes. Screw terminals for input & meter leads. B,C,D have bolts for input.

B: L: 3-7/8"	W	! : 3/4"	H:	1-1/2"	W	T : .42
STOCK #	FIG	0	ESC.		TEA	5+EA
15320-ME	A	10 A/5	50m\	/ Shunt	\$6.95	\$5.49
15321-ME	Α	25 A/5	50m\	/ Shunt	\$6.95	\$5.49
16360-ME	Α	30 A/7	75m\	/ Shunt	\$6.95	\$5.49
15322-ME	Α	50 A/	50m\	/ Shunt	\$6.95	\$5.49
15431-ME	В	100 A	/50m	V Shunt	\$7.95	\$6.95
15985-ME	В	100 A/	100n	nV Shunt	\$7.95	\$6.95

40MHZ SCOPE PROBE

Mueller Quality 40MHz oscilloscope probe with a BNC con-

nector to match to most equipment. With ground lead & retractable hook tip, IC tip. For field service, schools or shop. CE Listed

Max Input: X1: <200VDC + Peak AC. X10: <600VDC + Peak AC Imped: 1X= 1M ohm 10X= 10M ohm

Bandwidth:1X = >6MHz +-3db. 10X=>40MHz +-3db: Capacitance 1X = 85-115pF; 10X = 18.5 - 22.5 pFIncludes: Adj. screwdriver, Gnd. Lead, storage Pouch,

STOCK I	DESC.	1EA
18164-TE	Mueller Scope Probe	\$8.95

250MHZ HV SCOPE PROBES

Quality 250MHz oscilloscope probes with a BNC connector

to match to most equipment.

Impedance: 100X= 100M ohm. With ground lead & retractable hook tip, IC tip.
For field service, schools or shop. CEListed

1.2KV PROBE: Working Voltage: 1,200VDC + Pk AC. Bandwidth: 100X = >250MHz +-3db. Capacitance 1X =

L: 1.2m	WT: .2	
STOCK #	DESC.	TEA
18147-TF	1.2KV 250MHZ Probe	\$34.95

2.0KV PROBE: Working Voltage: 2,000VDC + Pk AC. Bandwidth: 100X = >250MHz +-3db. Capacitance 1X = 6.5pF(+ scope input)

STOCK #	DESC.	1EA
18148-TF	2 OKV 250MHZ Probe	\$38.95

SCOPE PROBES SELECTABLE 10X OR 1X

Quality oscilloscope probes with a BNC connector to match to most equipment. Max Input: 600V AC P/P + DC. Impedance: 1X= 1M ohm: 10X=10M ohm. With ground lead & retractable hook

For field service, schools or shop.

20MHz PROBE: Bandwidth:1X = >15MHz +-3db. 10X=>20MHz +-3db: Capacitance 1X = 46pF; 10X = (+ scope input)

40MHz PROBE: Bandwidth:1X = >15MHz +-3db. 10X=>40MHz +-3db: Capacitance 1X = 46pF; 10X = 15pF, (+ scope input)

60MHz PROBE: Bandwidth: 1X = >15MHz +-3db 10X=>60MHz +-3db: Capacitance 1X = 46pF; 10X = 15pF, (+ scope input).

100MHz PROBE: Bandwidth: 1X = >6MHz +-3db 10X=>100MHz+-3db. Capacitance 1X=150pF; 10X=14pF,


(+ scope input).

200MHz PROBE: Bandwidth: 1X = >10MHz +-3db. 10X=>200MHz +-3db: Capacitance 1X = 46pF; 10X =

12pF, (+ scope input): L: 1.2m WT: .2

Description of	THE RESERVE OF THE PERSON OF T	
STOCK #	DESC.	EA
15085-TE	20MHz Probe	\$7.95 any qty.
15086-TE	40MHz Probe	\$8.95 any qty.
8630-TE	60MHz Probe	\$9.95 any qty.
8682-TE	100MHz Probe	\$15.95 any qty.
15087-TE	200MHz Probe	\$18.95 any qty.

DIFFERENTIAL **SCOPE PROBE**



For use in circuits that are referenced to high common

mode voltages and floating high voltages. Bandwidth: 35MHz (-3db) Impedance: 1/1=10M/5PF

10/1=10M/5PF 100/1= 11M/5PF

Differential DC Input Resistance: 20M Ohm Max. Input Diff.: Volts: (DC+AC) 1/1 = +-10V

10/1=+-100V 100/1=+-1000V Max. Common Mode: 1/1= +-100V

10/1=+-100V 100/1=+-1000V

Output: +-10V into 1M scope input (2X if into 500hm input.) Output Imp.: 50 Ohms

CMRR: >40db @ 1MHz Input leads: 40cm (15in) Output BNC Cable: 90cm (35+in.)


Ground Lead: (Banana Plug to scope) 16cm (6in.) lead from BNC connector.

Includes: 2 retractable hook tips for input leads and 6V @ 400mA Plug-in power supply

Requires 4 "AA" batteries (Not Included) for portable use. Ship. WT: 2.5 L: 6.9" W: 2.52" T: .9"

18149-TE Differential Scope Probe \$295.95

ATTENUATORS TERMINATOR



Power: 1W BNC-M to BNC-F Attenuators & feedthrough terminator for test equipment, probes and fixtures

STOCK #	DESC.	TEA.	5+EA
16545-TE	3∓.5db BNC Attenuator	\$9.95	\$7.95
16546-TE	6∓1db BNC Attenuator	\$9.95	\$7.95
16547-TE	10∓1.5db BNC Attenuator	\$9.95	\$7.95
16548-TE	20 ∓ 1.5 db BNC Attenuator	\$9.95	\$7.95
16549-TF	50ohm BNC Terminator	\$9.95	\$7.95

1 - 1 2m

WT: 2

BINDING POST/ BNC ADAPTER

Quality, test adapter features Dual Binding posts to a BNC Male connecor Binding posts have wire hole and accept Banana Plugs as well. Black Post is connected to BNC Shell & is marked "GND" while the Red Post is connected

to BNC center pin

L: 2-3/8" Bod	У		WT: .06
STOCK #	DESC.	TEA	TULEA
17579-PL	Binding Post to BNC	\$2.95	\$2.75

DUAL BANANA/ BINDING POSTS

Quality, Gold plated, stackable, .75" C/C spacing. For test equipment & cables. Dual banana plug with:

Binding Posts OR Set screws to attach wire, cable, component or spade lugs

WT: .11(Banana/Posts) WT: .03 (Banana only)

STOCK #	DESC.	TEA	TOFEA
14901-PL	Red Dual Banana Plug A	\$1.25	\$0.99
14902-PL	Black Dual Banana Plug A	\$1.25	\$0.99
14903-PL	Red Dual Binding Post B	\$2.50	\$1.95
14904-PL	Black Dual Binding Post B	\$2.50	\$1.95

DUAL BINDING POSTS

Red & Black, safety binding posts accept banana plug in top or wire through hole in side. All front panel connections are recessed to pervent contact. Mounts in double .50" holes on .75" ctr. Solder terminals onback.



B

WT: .07

STOCK #	DESC	1EA.	10 .EA
14492-PL	Dual BindingPost	\$1.95	\$1.75

TELCO TYPE TEST CLIPS

Mueller JP-8078, 2-1/4"Angled Telco alligator clips with cable piercing tool steel spike. Designed

to grip punch-down blocks as well as wire posts etc. Nickel-silver, with brass screw, washer & bronze lock washer. Includes pair of clips plus 1 Red & 1 Black flexible vinyl boot. For test leads, clip leads, or test jigs. L: 2-1/4 WT: .088

STOCK #	DESC.	TEA
18160-TL	Mueller Telco Gator Clips	\$6.95

MICRO CLIP **TEST LEADS**



Red & Black test leads with Banana Plugs on one end and Micro clips on the

L: 34"		WT: .	
STOCK	DESC	TEA	10+EA
15971-TE	Test Hook Leads	\$1.95	\$1.79

ALLIGATOR CLIPS



H.H. Smith: #350 10pc. pack of 2" bright Tin Plated steel alligator clips. Can be soldered, accepts a banana Plug attached using the screw. For test leads, clip leads, or test jigs.

L: 2"O/A	H: 1/2" O/A			WT: .1
STOCK A	THE RESERVE OF THE PARTY OF THE	y 50 15 15 15 15 15 15 15 15 15 15 15 15 15	-357	

18612-AL Smith Alligator Clips

ALLIGATOR CLIP LEAD SET

Handy set of 10 multi colored clip leads. 26 AWG leads 12" long, with insulated 27mm or 35mm alligator clips on each end, 2 leads each in five colors. For shop or lab.

		WT: .2	
STOCK I	DESC.	TEA.	5+EA
	Mini Clip Lead Set 27mm E Clip Lead Set 35mm	\$1.95 \$2.50	\$1.75 \$1.99

MED. ALLIGATOR **CLIP LEAD SET**

Handy set of 5 multi colored clip leads, 24 AWG leads 12 long, with insulated 45mm alligator clips on each end, 1 lead each in five colors. For shop

L: 12"		: 12" WT: .	
STOCKA	DESC.	1EA	5+EA
16435-TE	Med. Clip Lead Set	\$2.50	\$1.99

BATTERY CLIP LEAD SET

Handy set of 6 multi colored clip leads. 24 AWG leads 12" long, with insulated 10mm mesh jaw clips on each end, 1 lead each in six colors. For shop or lab

L: 12	12		1:.2
STOCK #	DESC	1EA	5+EA
16436-TE	Clip Lead Set	\$2.99	\$2.50

18AWG ALLIGATOR CLIP LEADS



Handy set of 2 Red, 2 Black & 1 Green clip leads. 18 AWG leads 20" long, with insulated alligator clips on each end For shop or lab.

STOCK #	DESC.	TEA	10+EA
16050-TE	5pc. Clip Lead Set	\$1.65	\$1.25

7FT. **CLIPLEAD**

7ft long SPT-2 18AWG ZIP cord. Black with wide Red stripe. Each end has 2" alligator clips with Red

L: 7ft.		WT: .3
STOCK w	DESC.	1EA
17585-TF	7ft Clin lead Pair	\$4.05

BANANA PLUGS

Black banana plugs with nickel plated brass Four leaved spring tip, thermoplastic cover. Solder connection.

STOCK #	DESC.	16A	10+EA
8070-PL	Red Banana Plug	\$0.25	\$0.19
8071-PL	Black Banana Plug	\$0.25	\$0.19



TEST CABLES



with a molded strain relief BNC connector on one end and red & black clips on the other. RG-58 cable is 3ft long with an additional 4-1/2" of red & 8" of black wire from a strain

ı	L: 40"		wi:	
	STOCK	DESC.	1EA	5+EA
	2802-TE	Test Hook Cable	\$3.99	\$2.99
	12845-TE	Alligator clips Cable	\$3.99	\$2.99
	12819-TE	Banana Plugs Cable	\$3.99	\$2.99

MICRO CLIP TEST LEADS



Red & Black test leads with a molded BNC Female on one end and Micro clips on the other.

-	L: 5"		W	/T: .03
	STOCK #	DESC.	1EA	10+EA
	17559-TE	5in. Test Hook Leads	\$3.95	\$2.95

TEST HOOKS



Red & Black beryllium copper test hooks designed to clip to component leads leaving your hands free.1-1/2" probe length, 2-1/4" long overall, 1/2" body Dia, Add your own wire for custom lengths. For lab, shop or school.

		V	VT: 005
STOCK #	DESC.	1eA	25-EA
7161-MI	Red Component Clip	\$0.50	\$0.45
7163-MI	Black Component Clip	\$0.50	\$0.45

TEST PROBE SET

General purpose, pair of red and black test probes, 36in leads with banana plugs on one end nickel plated brass

L: 36"	WT		WT: .15	
STOCK #	DESC.	TEA	5+EA	
11214-TE	Banana Test Probe	\$2.49	\$2.25	

MINI BREADBOARD

3 individual 230 tie point solderless breadboards with 2 distribution strips each & 3 binding posts.

Features: Aluminum mounting base ABS plastic body, Nickel plated phosphor bronze contacts Rated 2A Max. Contact resistance less than 1 milliohm @ 1kHz. Tested for over 10,000 cycles. Suitable for 19-29 AWG wire & all DIP size components

W: 6-1/2" H: 5-1/4" T: 1/2" (Body) WT: .53

STOCK #	DESC.	1EA
18861-TE	Mini Breadboard	\$8.95

MINI BREADBLOCK

240 tie point solderless bread-



18862-TE		Breadblock	1EA \$2.95
L: 3-1/4"	W: 2-1/8"	T: 3/8"	WT: .09
		e components.	able 101 19-29

WT: 05

BREADIPROTO BOARDS

BREADBOARDS



B









White ABS plastic body (except G clear), Aluminum mounting base for figures B,C,D and E. Nickel plated phosphor bronze contacts. Contact resistance less than 1 milliohm @ 1kHz. Tested for over 10,000 cycles. Snap lock molded dovetail for combining multiple boards, Suitable for 19-29 AWG wire & all DIP size components. Please visit our web site for more detailed information.

D

STOCK	FIG.	DESCRIPTION	SIZE L X W	W T	TEA	TUEA	
4443-TE	Α	830 point	6-1/2" X 2-1/8"	.3	\$4.95	\$3.95	
4444-TE	В	830 point 3 Binding Post and Jumper kit	7-7/8" X 4-1/8"	.6	\$9.95	\$8.95	
4445-TE	C	1660 point 3 Binding Post and Jumper Kit	8-3/8" X 5-1/8"	.9	\$12.95	\$11.49	
4446-TE	D	2390 point 4 Binding Post and Jumper Kit	10-1/8" X 7-7/8"	1.3	\$18.95	\$16.95	
4447-TE	Ε	3220 point 4 Binding Post and Jumper Kit	10-3/8" X 9-1/8"	1.5	\$22.95	\$19.49	
7027-TE	F	140 Piece 22 AWG Jumper Wire Klt		.3	\$3.95	\$3.49	
18103-TE	G	830 point Clear ABS Body	6-1/2" X 2-1/8"	.3	\$4.95	\$3.95	

1-3/4" X 1-1/2" **PROTO BOARD**

Single Sided .062"phenolic board .1" pad spacing unplated copper pads

Mini general purpose prototyping board. 17 X 14 grid pattern with 202 total holes (9 missing in corners). Holds 1+ 14 or 16 pin ICs with room for several discrete components. Ideal for interface or signal isolation circuits. Fits 15917-BX Case.

L: 1-3/4" W: 1-1/2 WT: .009 Mini Proto Board 15918-PB \$0.59 \$0.39

8-1/8" X 5-3/4" **PROTO BOARD**

Single Sided .062"Epoxy-glass board .1" pad spacing Plated copper pads

Wide use board for prototyping. Onboard set up for a 7805 & 78 series + regulator & a 79 series - Reg. +5 & Common buss on one edge & +, - & Common busses on opposite edge. 1083 total holes in strips of 3 for breadboarding along with misc. holes for busses & edge connector(s) and the regulators.

E. 0 1/0 W	.007	******
STOCK #	DESC.	1EA.
18863-PB	Large Proto Board	\$5.95

2-5/16" X 1-15/16" **PROTO BOARD**

Single Sided .062"phenolic board .1" pad spacing

unplatedcopperpads

Mini general purpose board for prototyping. 23 X 18 grid pattern with 378 total holes (9 missing in corners). Holds 2+ 14 or 16 pin ICs with room for several discrete components. Ideal for interface or signal isolation circuits. Fits 15915-BX. 1 . 2 5/16" W. 1-15/16

16227-PB	Small Proto Board	\$0.79	\$0.49
STOCK #	DESC.	164	10+EA
L. 2-3/10	W. 1-13/10	V	1013

COPPER CLAD BOARDS

Double (DS) or single sided (SS) copper clad PC Board material. Standard 1/16" thick FR4 Base material with 1 oz. copper/side



STOCK #	DESC,	WT.	TEA	5+EA
14868-DT	3" X 5" S/S	.1	\$1.95	\$1.49
14869-DT	4" X 6" S/S	.12	\$2.25	\$1.95
14870-DT	6" X 9" S/S	.3	\$4.75	\$3.95
14871-DT	6" X 6" D/S	.2	\$3.95	\$3.25
14872-DT	8" X 10" D/S	.4	\$12.49	\$10.95

3-3/16" X 2-1/2" **PROTO BOARD**

Single Sided, .062" phenolic board, .1" pad spacing, unplated copper pads. 31 X 24 grid pattern with 708 total holes (9 missing in corners). Holds 3+ 16 pin ICs. Fits 15913-BX Case.

L: 3-3/16"	W: 2-1/2"	V	/T: .024
STOCK #	DESC.	TEA	10+EA
15914-PB	Medium Proto Board	\$1.10	\$0.89

4-5/16" X 3-1/8" PROTO BOARD

Single Sided .062"phenolic board

.1" pad spacing unplatedcopperpads

General purpose board for prototyping. 42 X 31 grid pattern with 1293 total holes (9 missing in corners). Holds 10+ 14 or 16 pin ICs with room for several discrete components. Ideal for interface or signal isolation circuits. Fits 15911-BX Case.

L: 4-5/16" W: 3-1/8 WT: .036 15912-PB Large Proto Board \$1.75 \$1,10

COPPER CLAD BOARD

12" X 12" Double Sided copper clad PC Board material. 1.6mm (1/16") thick FR4 Base material with 1 oz. copper/side.

Sq: 12"	WT: .74		
STOCK #	DESC.	1EA	1D+EA
15537-BD	12 X 12 Copper Clad	\$8.95	\$7.95

TIN PLATING KIT

Will plate a copper board with a bright, protective tin plate approx. .0004" thick. Improves solderibility, resists oxidation/tarnish & produces a professional appearance. Supplied as a dry power concentrate. When mixed

will plate approx. 600sq./in. Kit includes: Concentrate, Tray, handling tool & 16oz. storage bottle for mix.

			44107.4
STOCK	DESC.	TEA	5+EA
14896-DT	TIn Plating Kit	\$16.95	\$15.49
14897-DT	1 Pt. Concentrate	\$7.50	\$7.25

POWERED PROTO-TYPE SYSTEM

Breadboard with built-in multi-output power supply with LCD Meters. Dual LCD Meters monitor the + & -Variable output supplies

Features: 2 LCD Voltmeters, 4 power supply binding posts, 5 Distribution strips (500 pts), 3 Breadboard panels (1890Pts.), one +5VDC @ 1A supply, one 0 to +15VDC

D: 10-1/2"

@ .5A supply, one 0 to-15VDC @ .5A supply All parts are mounted in a metal case. Includes 6ft. IEC power cord.

STOCK #	DESC.	1EA
17710-TE	Metered Powered Breadboard	\$89.95

T: 3-1/2"

WT: 5.7

PREMIER SERIES **COATED BOARDS**

W: 8"

Premier Series boards are ideal for repeatedly making PC boards from POSI-TIVE films (Opaque lines/ patterns on clear film). Re-

sist coated Premier boards do not require U/V light, only a 100W light bulb. Double (DS) or single sided (SS) copper clad PC Board material, FR4 Base material with1oz. copper/side coated with resist and covered with a peel off plastic sheet (removed before exposer).

Exposing frame recommended

Apooning main	o rooominionaoa	•		
STOCK #	DESC	WT	TEA	5+EA
14880-DT	3" X 4" S/S	.1	\$4.95	\$4.49
14881-DT	3" X 6" S/S	.12	\$5.95	\$4.95
14882-DT	4" X 6" S/S	.15	\$6.82	\$5.99
14883-DT	6" X 9" S/S	.3	\$11.00	\$10.85
14884-DT	6" X 12" S/S	.4	\$17.95	\$15.95
14885-DT	3" X 4" D/S	.1	\$5.49	\$4.49
14886-DT	6" X 6" D/S	.22	\$10.95	\$9.95
14887-DT	6" X 9" D/S	.33	\$13.95	\$12.49
14888-DT	6" X 12" D/S	.5	\$19.95	\$18.95

BOARD **ETCHANT**

Dry concentrated Ferric Chloride. A dry powder that is mixed with water to produce a liquid used to remove the excess copper from

PC board material. 1/4 lb. will makeup 1 pint of etchant solution. 1 pint will etch approx. 200sq/in of 1 oz. copper single side board. NOTE: Must be mixed/stored/used in glass or plastic containers NO metal!

		VV	1:.5/1.1
STOCK #	DESC.	TEA	5+EA
14894-DT	1/4 lb. Etchant	\$5.25	\$4.75

COPY SHEETS

8-1/2" X 11" clear film suitable for LASER copier or printer to make artwork POSI-TIVES from magazines etc. Also can be used by directly taping, placing patterns or opaque inks to generate artwork. PACK of 5 Sheets

WT: .12

\$3.75 14875-DT 5pcs. Copy Film Sheets \$4.49

PREMIER BOARD **DEVELOPER**

Concentrated developer (not etchant) for PRE-MIER Resist coated board material. Mix 10/1 with water. 10 oz. of mix will develop 10-22sq. ft. of board depending on art complexity.



TOCK #	DESC.	TEA	5+EA
1890-DT	2oz. Developer	\$7.95	\$7.49
1891-DT	4oz. Developer	\$13.95	\$13.49

BURNISHING TOOLS

A Quality stylus tool that will give you a better, eaiser job with dry transfer DIRECT ETCH patterns. For characters, lines & patterns. Back end has 3/8i felt burnisher Standard: patterns .08-.25

Spoon Tip: Patterns .25in. & larger

WT- 1

		-	
STOCK	DESC.	TEA	5±EA
14873-DT	Standard Tool	\$4.95	\$3.95
14874-DT	Spoon Tip Tool	\$5.99	\$5.75

CONTACT EXPOSURE FRAME

For board material up to 9in. X 12in. Metal frame holds your artwork tight aginst the PC Board during exposure. Includes Metal frame, Glass Front cover, backing board & instructions



STOCK # DESC.	1EA	5+EA
14892-DT ER-10 Exposure Frame	\$28.95	\$23.95

RESIST PENS

Lacquer based black resist ink can be used directly on bare copper boards to touch up breaks, add a trace etc. before etching, Can also be used on clear film artwork (Positives)to correct or add traces before exposing board. MIT. OA

		** 1
STOCK #	DESC.	TEA
14876-DT	Fine Point Pen	\$2.25
14877-DT	Extra Fine Point Pen	\$2.45

"DUST OFF" **AEROSOL DUSTER**

FALCON Dust-Off", 12oz. can of duster used to blow dust and durt off equipment. Includes extension tube for hard to reach spots. Contains difluoroethane, Does not contain CFC's!. CANNOT BE SHIPPED AIR

WT· 1

STOCK II	DESC.	1EA	A-EA
16495-CE	DUST-OFF Duster	\$4.95	\$4.00

INSTRUMENT CASE

PACTEC CM59-135, Clamshell design ABS plastic instrument case Internal posts for holding PC boards up to 8.6" X5.4". Black shells and endplates. Slightly contoured top & bottom, Includes 4 screws & 4 rubber feet

D: 8.79" W: 5.57"		H: 1.54"	WT : .65	
STOCK #		DESC.	1EA	
17695-BX	PAC-TE	K CM59-135 Case	\$8.95	

GRAY & BEIGE PLASTIC CABINETS

Beige clam shell plastic project boxes with gray end plates. Internal 1/4" high threaded standoffs on both halves for PC boards. Includes cover screws, NO PC board mtg. screws.

L: 7.7"	W: 4.3 W: 4.3"	H: 1.4"		T: .45
STOCK #	DI	SC.	1EA	10.EA
15519-BX	3" Thk. Two	Tone Case	\$8.95	\$7.95
15884-BX	1.4" Thk. Tw	o Tone Case	\$8.49	\$6.95

PLASTIC SNAP CASES

2 tone (Light Gray/Gray), snap to gether small case made from Hiimpact UL-94-HB ABS Plastic. Interlocking Top & Bottom held by snap-on Front & Back. 4 molded standoffs on 17547/48/49

6 molded standoffs on top & bottom 17550-BX Stick-on Feet: 8.3mm dia Clear: Order 17551-HD (4pcs.) 6mm dia Black: Order 17552-HD

STOCK #	DfM. (W/D/Hin)	WT.	TEA
17547-BX	4.13 x 1.61 x0 .99 Box	.08	\$2.95
17548-BX	5.12 x 2.99 x 1.18 Box	.17	\$3.75
17549-BX	6.10 x 3.62 x 1.61 Box	.27	\$3.95
17550-BX	7.87 x 4.76 x 1.57 Box	.5	\$4.95

PLASTIC INSTRUMENT CASES

Clamshell design ABS plastic instrument case. Internal posts for holding PC boards. Light gray shells with Dark Gray endplates. Slightly contoured top & bottom. Includes 4 screws.



\$3.95

\$7.95

.66 \$11.95

.1

.24 \$5.95

.37

\$3,59

\$4,95

\$6.95

\$9.95

CLAMSHELL CASES

17199-BX

17200-BX

17201-BX

17202-BX

Clamshell design plastic instrument case. Internal posts and slots for holding PC boards. Off white shells and end plates. Slightly contoured top & bottom. Square front face. O/D listed below

 $3.5 \times 2 \times 1.3$

4.72 x 2.36 x 2

5.9 x 3.15 x 2.4

7.5 x 3.9 x 3.15

17800-BX: **L:** 7.5" 17801-BX: **L:** 4.7" W: 4.7" W: 3.2" H: 2.4 WT: H: 1.6" WT: .21 17802-BX: L: 5.9" W: 3.8" W: 2.75" 17803-BX: L: 3.9"

STOCK	DESC	
17800-BX	7.5in. Clamshell Case	\$4.95
17801-BX	4.7in. Clamshell Case	\$3.49
17802-BX	5.9in. Clamshell Case	\$4.59
17803-BX	3.9in. Clamshell Case	\$3.39

PLASTIC PROJECT **CABINETS**

Black plastic project boxes with flat lids. Internal guides on ends & sides for holding PC boards. Includes cover screws. Outside Dimn. Shown 15881-BX NO Internal Guides

STOCK	DRM: (L/W/(HID))	WY.	TEA	THEEA
15522-BX	3 x 2 x 1.16 Box	.07	\$1.95	\$1.59
15523-BX	4 x 3 x 1.6 Box	.13	\$2.49	\$1.95
15881-BX 4	1.41 x 2.24 x .87 Box	.08	\$1.95	\$1.59
15518-BX	5 x 2.5 x 1.75 Box	.17	\$2.95	\$2.49
15882-BX	5.9 x 3.9 x 2.36 Box	.27	\$3.49	\$2.95
15883-BX 7	7.25 x 4.5 x 2.52 Box	.50	\$5.49	\$4.49

PLASTIC PROJECT CABINETS

Black plastic project boxes with deep lids. Internal guides on ends & sides for holding PC boards. Includes cover screws. Outside Dimn. Shown

STOCK # DIM. (L/W/Hin)	WT.	TEA	TOFEA
15885-BX 3.74 x 1.89 x 1.46 Box	.11	\$2.95	\$2.49
15886-BX 4.53 x 2.46 x 1.73 Box	.15	\$3.49	\$2.95
15520-BX 5.3 x 3 x 1.9 Box	.14	\$3.95	\$3.49
15887-BX 6.3 x 3.74 x 2.44 Box	.33	\$3.95	\$2.95
15888-BX 7.6 x 4.53 x 2.95 Box	.43	\$7.95	\$6.49
15521-BX 8.8 x 5.5 x 3.6 Box	.75	\$7.95	\$7.25

EXTRUDED **INST. CASES/** PERF BOARD

Extruded aluminum case with mounting flanges on end plates. Natural Aluminum finish on case and end plates. Slots for PC Board on inside. Groved outside with smooth end plates

Includes Double Sided FR-4 board

with Plated Through .032 holes on .1" spacing. Board For 17804 BX contains 20X57 Holes Board For 17805 BX contains 24X67 Holes Board For 17806 BX contains 32X77 Holes I/D listed below 17804-BX: L: 6"

W: 2.4" W: 2.75" **H:** 0.9" **H:** 1.187" 7805-BX: L: 7" W: 3.75" 17806-BX: L: 8" H: 1.62"

17804-BX 6in, Extruded Alum, Case/Board 17805-BX 7in. Extruded Alum. Case/Board 17806-BX 8in. Extruded Alum. Case/Board

PLASTIC PROJECT CABINETS & PERF BOARDS

Black plastic project boxes with Aluminum lids. Internal posts for holding PC boards. Includes cover & perf board screws. Solderable Perf. Board has .1" hole grid pattern, copper one side. All Dimn. Approxmate.

Large Box; L: 5-1/4" W: 3-1/4" D: 1-9/16" Large Box: L: 5-1/4" W: 3-1/4" D: 1-9/16" WT: .02 Large Perf. Board: L: 4-1/4" W: 3-1/8" T: 1/16" WT: .04 Med Box:L: 4-1/8" W: 2-5/8" D: 1-9/16" WT: .15 Med Perf. Board: L: 3-1/8" W: 2-1/2" T: 1/16" WT: .02 Small Box: L: 3-5/16" W:2-1/8" D: 1-3/8" WT: .12 Small Perf. Board: L: 2-1/4" W: 1-7/8" T: 1/16" WT: .02 Mini Box: L: 2-11/16" W: 1-11/16" D: 1-3/16" WT: .08 Mini Perf. Board: L: 1-3/4" W:1-1/2" T: 1/16" WT: .007

STOCK #	DESC.	NEA.	10+EA
15911-BX	Large Project Box	\$4.95	\$3.25
15912-PB	Large Perf. Board	\$1.75	\$1.25
15913-BX	Medium Project Box	\$3.50	\$2.49
15914-PB	Medium Perf. Board	\$1.10	\$0.89
15915-BX	Small Project Box	\$2.75	\$1.85
16227-PB	Small Perf. Board	\$0.79	\$0.69
15917-BX	Mini Project Box	\$2.50	\$1.69
15918-PB	Mini Perf. Board	\$0.59	\$0.49

SEALED PROJECT BOXES

Gray ABS plastic project boxes with lids. Tongue & grove sealing meet IP-65 & NEMA 4 requirements. 4 stand-offs on base for holding PC boards. Includes stainless cover screws & neoprene gasket material. Outside Dimn.

17390 391 17400-17407 NO Internal Guides

17000,001,	17400-17407 NO Internal	adiaco	
STOCK #	DrM. (L/W/Hin)	WT.	TEA
17390-BX	2.52 x 2.28 x 1.38 Box	.13	\$3.95
17391-BX	7.24 x 1.42 x 1.38 Box	.23	\$6.95
17392-BX	4.53 x 3.54 x 2.17 Box	.35	\$6.95
17393-BX	6.73 x 4.76 x 2.17 Box	.54	\$9.95
17394-BX	8.74 x 5.75 x 2.17 Box	.83	\$11.95
17395-BX	6.73 x 4.76 x 3.15 Box	.73	\$10.95
17396-BX	7.68 x 3.15 x 2.17 Box	.49	\$7.95
17397-BX	8.74 x 5.74 x 2.95 Box	.97	\$11.95
17398-BX	10.43 x 7.28 x 3.74 Box	1.5	\$19.95
17399-BX	2.05 x 1.97 x 1.38 Box	.09	\$3.95
17400-BX	3.23 x 3.15 x 2.17 Box	.27	\$5 .95
17401-BX	6.3 x 3.15 x 3.35 Box	.53	\$8.95
17402-BX	7.87 x 4.72 x 2.95 Box	.8	\$11.95
17403-BX	4.72 x 4.72 x 3.54 Box	.6	\$9.95
17404-BX	6.3 x 6.3 x 3.54 Box	.85	\$12.95
17405-BX	9.45 x 6.3 x 4.72 Box	1.5	\$19.95
17406-BX	11.81 x 9.06 x 4.37 Box	2.4	\$32.95
17407-BX	14.17 x 7.87 x 5.91 Box	3.1	\$39.95



DIE CAST ALUMINUM BOXES

Cover & M3.5 Screws included, Natural Bare Aluminum Finish AVAILABLE ON-LINE Sealing Gasket to make box weather resistant to IP-66 Specs.



WT: 002

WT: .005

WT: 1.85

WT: 3.1

Weather lesi	Starit to ir	-00 Spec	,S.		
STOCK #	L	W	H"	WT.	TEA
16281-BX	2.36	2.17	1.18	.18	\$3.60
16282-BX	3.15	2.17	0.98	.2	\$3.90
16283-BX	3.50	1.37	1.18	.16	\$3.54
16284-BX	4.49	2.52	1.18	.28	\$5.34
16285-BX	4.49	2.52	2.17	.36	\$6.54
16286-BX	4.49	3.50	2.17	1.30	\$8.01
16287-BX	4.72	3.94	1.38	.56	\$7.77
16288-BX	5.51	3.94	2.95	.86	\$11.22
16289-BX	6.50	5.00	2.95	1.12	\$14.79
16290-BX	6.73	4.76	2.17	.96	\$13.41
16291-BX	6.73	4.76	4.17	1.40	\$16.62
16292-BX	8.74	5.75	2.17	1.44	\$17.91
16293-BX	8.74	5.75	4.17	1.94	\$24.27
16294-BX	9.84	9.84	3.94	3.50	\$44.88
16295-BX	10.83	6.89	2.56	2.08	\$26.91

BLACK/CLEAR FEET

Black rubber or Clear polyurethane stick-on feet

Sold in strip of 4pcs BLACK Dia: 6mm (.236")

H: 3mm (.118") H: 2.6mm (.1") CLEAR Dia: 8.3mm (.32")

17552-HD \$0.49 **Black Rubber Feet Clear Rubber Feet** \$0.49 17551-HD

STORAGE/TRANSIT CASE

Molded Bright Yellow ABS plastic equipment case with handle, latches and hinges. Silicone rubber gasket for water resistance. Pressure relief screw. Foam insert in Top & Bottom.

Inside: L: 9.3" W: 6.2" HT: 3.5 W: 8 L: 10.23 H: 4

Small Yellow Transit Case 17813-BX \$17.95

LARGER STORAGE TRANSIT CASE

Molded Bright Yellow, ABS plastic equipment case with handle, latches and hinges. Silicone rubber gasket for water resistance Pressure relief screw. Foam insert in Top & Bottom.

Inside: L: 12" W: 7.4" L: 13 W: 8.25" " HT: 4.4" H: 4.7"

18351-BX Medium Yellow Transit Case \$29.95

RACK SCREWS


Pack of 10-32 Heat Treated Steel Phillips screws 3/4" long with nylon



STOCK	DESC,	WT.	1-EA
17246-RK	50pk 10-32 Rack Screws	.3	\$4.95
17247-RK	100pk 10-32 Rack Screws	.6	\$8.95

ESD BOX

USED Black Plastic ESD safe Transport box with hinge & latch. Internal Easily removed Stainless plate with a special ZIF socket. 5-1/8" X2-7/8" X1" internal space



WALL PANEL BRACKETS

VIDEO MOUNT PRODUCTS

Hinged Wall brackets used to support & provide easy access to backs of 19" rack panels. Black, static resistant Powder Coated steel. Left or right side swing. 4" depth. Includes 10 & 12-32 Rack Mount Screws.

STOCK#	PICT.	VMP#	HT.	WT.	1EA
17243-RK	Α	ER-HWB1	1U	1.5	\$16.95
17244-RK	В	ER-HWB2	2U	2.3	\$18.95

EQUIPMENT SLIDES

Accuride, 3 section, Zinc plated steel, ball bearing equipment/drawer slides. Front disconnect allows removal of chassis from cabinet. Side mounting. Side Space: 3/8". Closed Position: 20", Fully Extended: 42", Slide Travel: 22", Max Load: 100lbs/pair. Sold as pairs.

H: 1-3/8" T: 3/4 WT: 5/pair 17418-RK Pair Equipment/Drawer Slides

> STEEL **19" RACK PANELS**

VIDEO MOUNT PRODUCTS

Cold rolled steel drilled & notched for standard rails, Black Powder coat finish

STOCK#	VMP #	HEIGHT	WT.	1EA
17237-RK	ER-1B	1U (1-3/4")	.7	\$4.95
17238-RK	ER-2B	2U (3-1/2")	1.3	\$7.95
17239-RK	ER-4B	4U (7")	2.7	\$13.95
17240-RK	ER-8B	8U(14")	5	\$19.95

LCD MONITOR RACK MOUNT

VIDEO MOUNT PRODUCTS

Rack mount or monitors with 75 & 100mm VESA mounting pattern. Recess mounts10-17" monitors and can be inverted for up to 23" models, 50lbs. max weight. Black, static resistant Powder Coated steel. Mounting hardware

17245-RK	ER-LCD1017	9U	12	\$66.95	
5TOCK#	VMPII	HT.	W.T.	YEA	i

19" RACK MOUNT **CABINETS**

Black plastic rack mount clamshell cases. Vented sides with removable front & rear panels. Internal standoffs on top & bottom. Assembly required.

internal space: 17086-BX 16-3/16" X 7-11/16" X 1" 17087-BX 16-3/16" X 7-11/16" X 2-7/8" 17088-BX 16-3/16" X 7-11/16" X 4-1/2"

STOCK#	DESC.	WT	1EA
17086-BX	1U Rack Cabinet	1.9	\$19.95
17087-BX	2U Rack Cabinet	2.5	\$29.95
17088-BX	3U Rack Cabinet	3.0	\$39.95

19" RACK CABINETS

19in. rack mount cases. 1/8in Aluminum Front Panel with steel chassis & covers. Satin black textured paint. 17811-BX: W: 19" **D:** 11.8" H: 1-3/4" WT: 5.8 H: 3-1/2" WT: 7.2 D: 11.9" 17812-BX: W: 19"

STOCKE	DESC.	JEA
17811-BX	1U Metal Rack Cabinet	\$34.95
17812-BX	2U Metal Rack Cabinet	\$39.95

RELAY RACKS

VIDEO MOUNT PRODUCTS

All Aluminum

9ga. Raiis Drilled & Tapped 10-32, EIA std. spacing, 5ga. "L" base plates. Available in: Black Powder Coat finish

Shipped unassembled with hardware

STOCK#	COLOR	VMP P/N	HEIGH	T W	T. TEA
17226-RK		ER-72	72		\$159.95
17227-RK	Black	ER-84	84	28	\$172.95

BOXESICABINETSIRACKS

19" HEADEND **RACKS**

VIDEO MOUNT PRODUCTS

13ga. Steel Rails Drilled & Tapped 10-32, EIA std. spacing, 16ga. Base, Black static resistant Powder Coat finish.

Shipped unassembled with hardware

STOCK#	COLOR	VMP P/N	HEIGHT	W	T. JEA
17228-RK	Black	ER-148	48	30	\$110.95
17229-RK	Black	ER-1	71	40	\$139.95
17230-RK	Black	ER-184	84	45	\$145.95

19" HEADEND **EXPANSION RAILS**

VIDEO MOUNT PRODUCTS

13ga. Steel Rails and side stabilizing bars to convert Headend rack to 4 posts. Black static resistant Powder Coat finish.

Shipped unassembled with hardware

17231-RK Black ER-1-4PKIT 25 \$82 95 17232-RK Black ER-184-4PKIT 84 28 \$92.95



VIDEO MOUNT PRODUCTS

Black Powder coat finished Steel. Drilled for standard rails. 50lb. MAX Load

17235 Center mount & Vented

STOCK#	PICT.	VMP#	DEPTH	WT.	1EA
17233-RK	Α	ER-S1	12"	5	\$22.95
17234-RK	В	ER-S2U	14-3/4"	7.5	\$29.95
17235-RK	C	ER-S2CM	19	10	\$48.95

CABLE **BRACKETS**



VIDEO MOUNT PRODUCTS

Black, static resistant Powder Coated steel panels for 19" racks or wall brackets. Large slotted metal rings manage all types of cables.Includes 10 & 12-32 Rack Mount Screws.

STOCK#	VMP#	Hi	WT.	1EA
17241-RK	ER-DRCM1	1U	1.2	\$17.95
17242-RK	ER-DRCM2	2U	2	\$21.95

TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764

17812-BX

MPJA@MPJA.COM



Panel lamps with Non replaceable bulb rated 12V. Tapered square top (.6"sq. X .5" tall). Solder terminals. Mounts in round hole

Mtg. Hole:	.0" L	-: 1-1/2	AA 1::010
STOCK	DESC.	1EA	10+EA
7117-LA	Red Panel Lan	np \$0.95	\$0.89
7118-LA	Yellow Panel La	mp \$0.95	\$0.89
7119-LA	Green Panel La	mp \$0.95	\$0.89
14183-LA	Blue Panel Lan	np \$0.95	\$0.89
14184-LA	Clear Panel Lai	mp \$0.95	\$0.89

12V G-4 BI-PIN LED LAMPS

Bi-pin bulb replacement assembly features: 14 super brite LEDs, 12VAC or DC operation, 55deg, beam angle. Replacement for most G-4 lamps. .9mm dia. X 8mm Steel Pins, plastic body T: 11mm

Dia.: 22.5mm	T: 11mm	W	Γ: .009
STOCK #	DESC.	1EA	10+EA
17352-OP Red	LED Bi-Pin Lamp	\$8.95	\$6.95
17353-OP Gree	n LED Bi-Pin Lamp	\$8.95	\$6.95
17354-OPAmbe	er LED Bi-Pin Lamp	\$8.95	\$6.95
17355-OP Blue	LED Bi-Pin Lamp	\$8.95	\$6.95
17356-OP Whit	e I FD Bi-Pin Lamp	\$8.95	\$6.95

12" NEON ACCENT LIGHT

Mini, green neon tube light originally made for computer cases but has many uses in accent & automotive lighting. 12.5" long plastic housing with hook & loop fastners on each end. Includes a 3"X 1-1/2" X 1" power module, mini rocker switch on plate, interconnect wiring to a set of IDE power "Y" connectors for 12VDC/.32A power.

L: 12-1/2"(tube)		WT: .45
STOCK #	DESC.	
18946-MI	Neon Tube Light	\$9.95

TRAILER TAIL LIGHTS

12VDC LED Trailer light kit for trailers up to 80in. wide. 40 Super

bright LEDs in Left side 35 in Right. Includes plastic License bracket for Left side. 23Ft. split "Y" wires & 4ft. trunk harness. Includes Mounting hardware.

Not recommended for immersion in water.

	er i so	*****
STOCK	DESC	1EA
17903-MI	Trailer Tail Lights	\$16.95

MINI LAMPS

Grain-of-Wheat" lamps, Only 1/8"dia X 1/4". 10" leads. Ideal for hobbists! Use in model cars, boats, trains etc.

L: 1/4"	Dia: 1/8"		WT:.001
STOCK #	DESC	1EA	10*EA
8980-LA 8981-LA 8982-LA 8983-LA	1.5V Mini Lamp 3.0V Mini Lamp 6.0V Mini Lamp 12V Mini Lamp	\$0.59 \$0.59 \$0.59 \$0.59	\$0.49 \$0.49 \$0.49 \$0.49

12V HIGH INTENSITY LIGHT

USED, Plastic case with a GE #789 or eq. 12V @ 1.2A bi-pin lamp, mirror reflector, power switch, and com-

pound lens. 5.5mm X 2.5mm Coaxial jack on back. Light dia.approx. 5" @ 12in. /10" @ 24in. H: 4-3/4"

W: 2-3/8" D: 2-7/8

STOCK	DESC	TEA	10+EA
16304-LA	12V Hi-Intensity Light	\$7.95	\$6.95

LED12VDC PANEL **INDICATORS**

Panel mount LED indicators Internal resistor for 3-12VDC operation. Internal LED matches lens color. Solder terminals Lens Dimn. shown, O/A size 2mm larger

Mtg Hole: 8/10/12mm L: 1-3/8" WT: .005

Round

STOCK #	DESC.	1EA	10+EA
17301-LE	8mm Red Indicator	\$0.79	\$0.69
17302-LE	8mm Blue Indicator	\$0.79	\$0.69
17303-LE	8mm Green Indicator	\$0.79	\$0.69
17304-LE	8mm Amber Indicator	\$0.79	\$0.69
16961-LE	10mm Red Indicator	\$0.89	\$0.79
16962-LE	10mm Blue Indicator	\$0.89	\$0.79
16963-LE	10mm Green Indicator	\$0.89	\$0.79
16964-LE	10mm Amber Indicator	\$0.89	\$0.79
16981-LE	12mm Red Indicator	\$0.99	\$0.89
16982-LE	12mm Blue Indicator	\$0.99	\$0.89
16983-LE	12mm Green Indicator	\$0.99	\$0.89
16984-LE	12mm Amber Indicator	\$0.99	\$0.89
	0		

Square

STOCK #	DESC.	EA	10+EA
17305-LE	8mm Sq. Red Indicator	\$0.79	\$0.69
17306-LE	8mm Sq. Blue Indicator	\$0.79	\$0.69
17307-LE	8mm Sq. Green Indicator	\$0.79	\$0.69
17308-LE	8mm Sq. Amber Indicator	\$0.79	\$0.69
16965-LE	10mm Sq. Red Indicator	\$0.89	\$0.79
16966-LE	10mm Sq. Blue Indicator	\$0.89	\$0.79
16967-LE	10mm Sq. Green Indicator	\$0.89	\$0.79
16968-LE	10mm Sq. Amber Indicator	\$0.89	\$0.79
16985-LE	12mm Sq. Red Indicator	\$0.99	\$0.89
16986-LE	12mm Sq. Blue Indicator	\$0.99	\$0.89
16987-LE	12mm Sq. Green Indicator	\$0.99	\$0.89
16988-LE	12mm Sq. Amber Indicator	\$0.99	\$0.89

Rectanglar

" was all the country of		-	A COURSE
STOCK #	DESC.	IEA .	10+EA
17309-LE	8x11 Rect. Red Indicator	\$0.79	\$0.69
17310-LE	8x11 Rect. Blue Indicator	\$0.79	\$0.69
17311-LE	8x11 Rect. Green Indicator	\$0.79	\$0.69
17312-LE	8x11 Rect. Amber Indicator	\$0.79	\$0.69
16969-LE	10x14 Rect. Red Indicator	\$0.89	\$0.79
16970-LE	10x14 Rect. Blue Indicator	\$0.89	\$0.79
16971-LE	10x14 Rect. Green Indicator	\$0.89	\$0.79
16972-LE	10x14 Rect. Amber Indicator	\$0.89	\$0.79
16989-LE	12x16 Rect. Red Indicator	\$0.99	\$0.89
16990-LE	12x16 Rect. Blue Indicator	\$0.99	\$0.89
16991-LE	12x16Rect. Green Indicator	\$0.99	\$0.89
16992-LE	12x16Rect. Amber Indicator	\$0.99	\$0.89

FRONT SURFACE MIRROR

Because of their low distortion; front surface mirrors are used for laser scanners and other optical equipment. Made of 1/8" flat plate glass. May have some slight imperfections. REMOVE "PINK" PROTECTIVE COAT-ING OVER FRONT SURFACE BEFORE USE

L: 4-1/2"	W: 1-1/8"	T: 1/8"	٧	/T: .55
STOCKY	0	DESC.	TEA	100+EA
15173-MI	Front St	urface Mirror	\$1.50	\$0.99

GLASS PRISM

Equilateral optical quality clear glass prism. Ideal for classroom use, science projects optical experimemnts

L: 50mm W: 50mm H: 45mm 17933-LN Equilateral Glass Prism

LASER

Stylish pen style LASER pointer contains visible red laser diode, lens & 2 AAA batteries in metal case. <4mW class III-A output power, Momentary push button switch for easy use. Visibility exceeds 300ft, when used with projection/display screens.

Dia: .45"	L: 5.7"	V	/T: .3
STOCK	DESC.	120	DIEA
8689-LZ	LASER Pointer	\$12.95	\$11.95

NEON BULB

Standard Neon Lamp, Max. current:1mA; Min. Firing Voltage: 60VAC, 1" long Solid Wire Leads.

18285-LA	Mini Neon Lamp	\$0.29
STOCK #	DESC.	TEN
Dia: 5.7mm	L: 12mm (Body)	WT:.009
voitage. ouvito.	long cond trill Loads	•

LIGHT FIXTURE & LAMP

Originally mfg. for use in signage & display cases. Surface mount fixture for PL-S2 Compact Fluorescent Lamps (Includes a 13W PL-S Compact Fluorescent Lamp), 10in. leads with molded 3 pin special connector

for "Daisy Chaining" units. 120VAC 60Hz, .35A. UL listed L: 9-1/8" H: 2-3/4" W: 2-1/4" WT: 1.6

18098-MI 120VAC Compact Fluorescent



12V LED AUTO LAMPS



1141Type keyed bayonet base lamp with 12 top aimed hi-intensity Red or Yellow LEDs (12 total). Rated 12VDC @ 100mA. Used for signal, parking etc lite. Single

L: 1-7/8" O//	A Dia: 1"O/A	WT: .04
STOCK	DESC.	1EA
18752-TL	Red LED Auto Lamp	\$4.50
18753-TL	Yellow LED Auto Lamp	\$4.95


FRONT SURFACE MIRROR **ASSEMBLY**



Removed from new equipment. Assembly with 2 front surface mirrors that measure 6-1/4" X 1" X 3/16" thick. Steel frame with plastic hardware. Removeable mirrors held in place by spring clips & glue.

L: 8-3/4" O/A W: 2-1/2"O/A H: 2" O/A WT: .6 17368-MI Dual F/S Mirror Assembly \$3.95

FRONT SURFACE



Front surface mirror made by OCLI for laser photo printers or copiers. Minimum reflectivity greater than 85%, 10mm thick plate glass for durability

NOTE: Shipped with protective Film on front surface, Remove before use T: 3/81

L: 12-1/2" W: 1-15/16" Shp WT: 1 17156-MI Front Surface Mirror \$4,50

PAGE MAGNIFIER

L: 11"

Acrylic 3X Fresnel type mag nifier for viewing full pages Great wide view of Maps. Drawings etc.



\$3.95

17938-LN **Full Page Magnifier**

54

ORDERS: CALL 800-652-6733

WT: .6

FAX 800-432-9937

WT: .4

\$7.95

WWW.MPJA.COM

"DELI" COUNTER KIT

DO IT YOURSELF "Deli" Counter kit. Kit contains a 0-99 Up counter

board/display assembly, power supply and pushbutton Switch. Just about any momentary type contact will operate the

You supply a case, solder and labor to solder the power supply & switch to the attached leads. 2-3/4" tall super brits Pod LED

tall super brite Red LED make up the digits. Each contact closer causes counter to increase 1 count. There is no reset function, and unit will remember last count for a couple days so to get to "00" you must complete the count.

Display: W: 5" Driver: W: 4-5/16" H: 4-3/16' H: 2'

WT: .5 "Deli" Counter Kit \$10.95 17511-KT



IR ILLUMINATOR KIT

Small circuit board holds 36 I/R leds. Designed to provide "light" for CCD cameras. Depending on how you mount the LEDs, unit will project up to a 6ft spot at 10ft. Plug supply included.

DIA: 2"	T: 3/9"	WT: .4
STOCK #	DESC.	TEA
11665-OP	IR Illuminator Kit	\$15.95

"SWEET 16" DTMF DECODER

This kit decodes all DTMF tones including 0-9,#,*, A-D. Can use any source for the DTMF tone, such as phone line, scanner, etc. You use a jumper to connect 1 of 16 outputs to drive the internal relay. When selected digit is detected the relay is energized. By adding additional external relays you can control up to 16 different devices. Relay is energized as long as tone is detected. By adding external flip-flops or delay circuits you obtain "toggle" or time out actions. Ideal building block for more complicated circuits. Turn on your AC unit from your office. Use your cell phone to activate an outside light. Internal relay is rated DPDT 1A max @ 12VDC/115VAC resistive; so if a heavy or high power load is expected you should use the internal relay to control a heavier external relay. Operates on 7.5-18VDC (9V battery) TT-16

W: 2-1/8 H: 5/8' WT: .15 8838-RB DTMF Sweet-16 Kit \$34.95 \$29.95

SUPER **BIG-EAR** AMPLIFIER



hear through walls etc. Couple to a parabolic reflector & earphones to hear for blocks. Based on the LM386 ChipCan be used as a general purpose 1.5W amp. Supplied with a mini-microphone. Runs on 6-12V DC. AA-1D

L: 1-3/4" H: 3/8" WT: .2

3378-RB **Big Ear Kit** \$10.95 \$9.95

SNAP TOGETHER ELECTRONIC FUNDAMENTALS PROJECT KITS

FUN & EDUCATIONAL

"Snapcircuits"For adults or children wanting to learn the fundamentals of electronics while doing basic, working projects. Parts simply "snap" together. Interlocking, stack ing parts such as resistors, diodes, switches, motors, capacitors, interconnects on plastic pieces. Plastic base supports the parts. Build simple electronic "Doorbell", Siren, logic circuits etc. No knowledge of electronics is needed. Simple color drawings in workbook take you through the setup, Ideal for children science classes and demos. Additional/replacement parts available from Mfg. Requires 4 "AA" batteries (not supplied.
NOT for children under 3, Recommended age 8+



KIT 14264-KT contains 30+ pieces and simple expriments

WT: 2 Snapcircuits Jr. Project Kit \$29.95 14264-KT



KIT 14263 contains 60+ pieces, Including parts not available in 14264-KT, Experiments 1-101 & 102-305.

		V	11: 3.3
STOCK	DESC.		1EA
14263-MI Snar	ocircuits Deluxe Project	et Kit	\$49.95

INFRARED **ANALYZER KIT**

Kit uses Motorola's MC3373 Remote control amp/detector. This kit allows you to display

& analyze code patterns from any infared device. Software allows you to save to disc compare current display with one stored on disc, & print screen. 2 second sampling is displayed and you can "zoom" in on any 8 millisecond portion. The on screen trace can be saved in ASCII comma-delimited format for import into spreadsheets. Kit connects to your computers parallel port and the software runs on any P.C. compatable 386 or later machine with VGA graphics & DOS 3.3 or higher. TIR-1

L: 2-7/8" W: 1-1/2 H: 3/41 WT: 3 \$89.95 \$79.95 8837-RB I/R AnalyzerKit

DUAL PROBE DIGITAL THERMOMETER KIT

Kit uses a 3-1/2 digit LCD Digital Panel Meter & a pair of National LM34 temperature sensors to construct an accurate thermometer with .1° resolution & +-1-1/2° accuracy from -20° to +199.9° "F". The TO-92 size sensors can be remotely located. Uses flat 4 conductor "phone" type cable to connect sensors so their's no stiff cable or wires. Switch controls power & which sensor is read. Ideal for monitoring inside vs outside temperature, Photographic chem baths, equipment temperatures in cabinet. Requires 9V battery. LCD-T1

Pre drilled box with cutout available separately

8836-RB Predrilled Plastic Box

*****	L: 1-1/ L: 3"		H: 1/2" H: 1-5/8		T: .17 T: .13
STU	CK #	DESC.		1EA	5-EA
883	5-RB	Digital Thermo.	Kit	\$34.95	\$29.95

\$9.95

\$8,95

ELECTRONIC TIMER KIT

Dual mode timer kit has many uses. Dual LM 555 timing circuits plus a relay driver (100mA Max. Current Sink). In the astable mode the circuit produces a continous train of pulses; in the mono stable mode produces a triggered time delay useful for

debouncing switches. Can be cascaded for compound applications. Operates from 4.5-12V DC. EBTD-9 0 40/400384 0 4/40

STOCK & DESC. TEA 5+6A	
16916-RB 555 Timer Kit \$12.95 \$11.95	

VOICE ACTIVATED SWITCH

Voice activated switch circuit. Will operate a 100mA load. Can be used to drive a light, a relay for higher loads, etc. Use for alarms, ham radios, etc. Operates from audio source or from crystal, ceramic or electret mike. Operates on 5-15V DC. VOX-1

L: 1-1/2" W: 1-1/4" H: 3/8" WT: .2 \$6.95 \$5.95 3373-RB **VOX Switch Kit**

BATTERY MONITOR KIT

Voltage monitor kit monitors voltages using 7 LEDs (2 red, 2 yellow, 3green). Change resistors to select voltage ranges and indicated steps: 5V or 8V in 1/4V steps or 12V in 1/ 4, 1/2 or 1V steps. All parts included. VM-1

L: 2-3/4" W: 1-7/16" H: 3/8"

STOCK	DESC	TEA	5+EA
4210-RB Bat	tery Monitor Kit	\$7.95	\$6.95

TEMPERATURE CONTROLLER KIT

Circuit output is open collector transistor that sinks up to 80mA to operate external relay (NOT SUPPLIED). Holds relay closed until temperature rises to adjustable set point. Range Approx. -20 to +300"F".7.5-15V DC Operation. TG-2D L: 2"

W: 1-5/16' WT: .2 H: 1/2 5289-RB Tem. Control Kit \$6.95

WATER DETECTOR KIT

555 Osc circuit drives speaker (INCLUDED) to sound alarm when water level rises on remote sensor board and changes the conductivity between the 2 contacts. 6-12V DC Operation.

Main Board .8" X .75" Sensor board 1.25" sq. WD2

WT: .4

5292-RB Water Detector Kit \$8.95

DC MOTOR & SPEED CONTROL

MFG: BUEHLER (motor) P/N: 13.65.054.08 Voltage: 24VDC

Current: .07NL /.9A Stall Board: 3-1/2" X 1-3/8". 18-24VDC Power with 5V input to control direction. 1250-1650

speed range. Motor: L: 2-1/4" Dia: 1-1/4" with 2.5mm dia. X 16mm steel shaft with a press fit 1/2" dia. 3 start plastic worm gear. Bronze bearings, 8" motor leads, 13" board leads. 2 mounting holes on motor. WT: .4

18591-MD Motor with Speed Control \$7.95

FAX 561-844-8764 TECH. & INFO: CALL 561-848-8236

NEW FANS THERMOCOOL AC FANS



















D

UL/TUV/CE RoHS Compliant

STOCK#	FIG	. MFG.	P/N	DIMN.	VOLTS/AMP	CFM	NOISE	BEARING	CONNECT	APPROVAL	WT	1EA	12+EA
17771-FN	Α	THERMOCOOL	G8025HAS	3-1/8 SQ X 1	125AC/.13	23	30	SLV.	WIRE	uULc/TUV/CE	.6	\$9.95	\$8.95
17772-FN	В	THERMOCOOL	G8038HAS	3-1/8 SQ X 1-1/2	125AC/.14	28	33	SLV.	WIRE	uULc/TUV/CE	.6	\$14.95	\$12.95
17773-FN	C	THERMOCOOL	G9225HAS	3-5/8 SQ X 1	125AC/.14	34	40	SLV.	TERMINALS	uULc/TUV/CE	.5	\$9.95	\$8.95
17774-FN	D	THERMOCOOL	G12025HAS	4-11/16 SQ X 1	125AC/.20	66	42	SLV.	TERMINALS	uULc/TUV/CE	.75	\$9.95	\$8.95
17775-FN	E	THERMOCOOL	G12038HAS	4-11/16 SQ X 1-1/2	125AC/.28	95	48	SLV.	TERMINALS	uULc/TUV/CE	1.1	\$12.95	\$10.95
17776-FN	E	THERMOCOOL	G12038MAB	4-11/16 SQ X 1-1/2	125AC/.22	85	44	BALL	TERMINALS	uULc/TUV/CE	1 1	\$15.95	\$12.95
17777-FN	E	THERMOCOOL	G12038MAS	4-11/16 SQ X 1-1/2	125AC/.22	85	44	SLV.	TERMINALS	υULc/TUV/CE	1.1	\$11.95	\$9.95
17778-FN	F	THERMOCOOL	G13538HAS	5-5/16 SQ X 1-1/2	125AC/.34	122	53	SLV	WIRE	uULc/TUV/CE	1.2	\$14.95	\$12.95
17779-FN	G	THERMOCOOL	G15050HAS	6 SQ X 2	125AC/.40	198	58	SLV	WIRE	uULc/TUV/CE	1.9	\$22.95	\$19.95
17780-FN	Н	THERMOCOOL	G17050HASB	6-3/4 RND X 2	125AC/.40	198	59	BALL	TERMINALS	UULc/TUV/CE	1.8	\$22.95	\$19.95
17781-FN	ı	THERMOCOOL	G17050HAST	6-3/4 X 6 X 2	125AC/.40	198	59	BALL	TERMINALS	uULc/TUV/CE	1.9	\$22.95	\$19.95

















MISC. DC FANS

PICTURES ARE REPRESENTIVE OF THE STYLE AND ARE NOT EXACT

VISIT WWW.MPJA.COM, ENTER STOCK # TO SEE ACTUAL PICTURE

000001	STOCK# FIG. MFG. P/N DIMN. VOLTS/AMP CFM NOISE BEARING CONNECT APPROVAL WT 1E4 12-EA							10000					
	FIG		P/N	DIMN.	VOLTS/AMP	CFM			CONNECT	APPROVAL	WT	1EA	12+EA
18043-FN	_	COMAIR	ST05B3	3-1/8" SQ X 1-1/4"	5DC/.58	34	41	HYD	9" LEADS	UL/CSA	.42	\$5.95	
15357-FN	_	ADDA	ADD4050HB-G70	1-9/16"SQ X 3/8"	5DC/.19	6.7	25	BALL	11" LEADS	ULCAN/US/TUV	.04	\$2.95	\$2.49
18488-FN	_	DELTA	1AFB0312MD	1-3/16" X 3/8"	12DC/.15	3.5	25	BALL	3" LEADS	UL/CSA/VDE/CE	.02	\$3.95	
18489-FN		DELTA	1AFB0412MD	1-9/16" X 3/4"	12DC/.14	8.1	24.5	BALL	12" LEADS	UL/CSA/VDE/CE	.02	\$3.49	\$2.95
18841-FN		NMB	1606KL-04W-B50	1-9/16" X 5/8"	12DC/.11	8.1	34	BALL	12" LEADS	UL/CSA/VDE/CE	.05	\$2.95	\$2.49
12773-FN		T&T	MW-510H12C	2" SQ X 3/8"	12DC/.14	9	27	BALL	10" LEADS	UL/TUV/CE	.05	\$1.65	\$1.49
17526-FN	_	JAMICON	JF0625S1L	2-3/8" SQ X 1"	12DC/.17	17	28	SLV	4" LEADS	ULCAN/TUV	.13	\$2.95	\$2.50
18696-FN		COMAIR	FS12H3-31158	2-3/8" SQ X 1"	12DC/.06	12	28.5	BALL	2" LEADS	UL/CSA/TUV	.24	\$2.95	100 No. (cf. 100)
15841-FN	D	JAPAN SERVO	PUDC12Z4-042	3-1/8" X 1"	12DC/.16	42	37	BALL	14" LEADS	UL/CSA/TUV	.2	\$3.95	\$3.49
15717-FN	D	AROMAT	AIF80	3-1/8" SQ X 1"	12DC/.07	-	-	BALL	8" LEADS	UL/CSA	.23	\$2.95	\$2.49
18596-FN	D	DELTA	FFB0812VHE	3-1/8" SQ X 1-1/2"	12DC/.57	57	45	BALL	9" LEADS	UL/CSA/VDE	.4	\$3.95	year his son and
			Stall Sensor Output										
16724-FN	D	COOLTRON	FD8025S12W3-17	3-1/8" SQ X 1"	12DC/.083	25.6	22	SLV	10" LEADS	ULCAN/us/TUV	.15	\$1.49	
18223-FN	D	JAPAN SERVO	PUDC12Z7RP	3-1/8" SQ X 1"	12DC/.16	42	35	BALL	10" LEADS	UL/CSA/TUV	.2	\$3.95	THE RE GA SHE
			Stall Sensor Output										
18049-FN	D	PANASONIC	FBA09A12H	3-5/8" SQ X 1"	12DC/.29	57	35	HYD	9" LEADS	UL/CSA	.22	\$5.95	
18088-FN	D	DELTA	FFB0912VHE-R00	3-5/8" SQ X 1-1/2"	12DC/.75	85	47.5	BALL	11" LEADS	UL/CSA/VDE/CE	.42	\$3.95	and and the part
			Stall Sensor Output										
16543-FN	D	AVC	C9025S12H	3-5/8" SQ X 1"	12DC/.3	52	34	SLV	6" LEADS	UL/CSA/TUV/CE	.16	\$3.95	\$3.50
			Stall Sensor Output										
18222-FN	G	JAPAN SERVO	CNDC12Z7RP	4-11/16" SQ X 1-1/2"	12DC/.71	124	49	BALL	10" LEADS	UL/CSA/TUV	.6	\$4.95	\$3.95 (40)
			Tach Sensor Output										
18221-FN	G	JAPAN SERVO	PADC12X7P	6-3/4" RND, X 2"	12DC/1.9	250	59	BALL	10" LEADS	ULCAN/US/TUV	1.6	\$19.95	\$17.95
			Stall Sensor Output										
18016-FN	J	DELTA		4-11/16" SQ X 1-3/8"	24DC/.5	23	46	BALL	9" LEADS	UL/CSA/VDE/CE	- 10	\$4.95	one married size
17194-FN	C	SANYO	109P0624HE7K3	2-3/8" SQ X 5/8"	24DC/.06	13.5/6.8	3 -	BALL	4" LEADS	-	.13	\$3.95	\$3.75
			Dual speed fan									-	40
18593-FN	C	JAPAN SERVO		3-1/8" SQ X 1"	24DC/.16	47	40	BALL	9" LEADS	UL/CSA/TUV	.2	\$3.95	orize flore great enter
18845-FN	C	NIDEC T	A350DC-M33423-68	,	24DC/.19	148	34.8	BALL	10" LEADS	UL	.22	\$3.95	
	Ť		Stall Sensor Output		5/110		2 7.0					45100	
15718-FN	J	JAPAN SERVO		5" SQ X 1"	24DC/.55	30	, 'pa	BALL	5" LEADS		.66	\$4.95	\$4.49(5)
18592-FN	-	JAPAN SERVO		5" SQ X 1-1/2"	24DC/.042	34	51	BALL	5" LEADS	UL/CSA	.64	\$4.95	φτιτο(ο)
		State of the last		5 5477 172	_ 100/.012	0.1			O MILITOR	ODOOA	.0-7	4-100	

FAN GUARDS

















D E G

PICTURES ARE REPRESENTIVE OF THE STYLE AND MAY NOT BE EXACT

١.	STOCKY	EIG.	FAN SIZE	STYLE	MIDUNTING	MAT	EMISH	W1.	TEA	10+EA
	18383-FN	A	1-9/16"/40MM	OFFSET	4 CORNERS	STEEL	CHROME	.01	\$0.99	\$0.89
	18384-FN	В	2-3/8"/60MM	OFFSET	4 CORNERS	STEEL	CHROME	.03	\$0.99	\$0.89
	8660-FN	C	2-3/8"/60MM	OFFSET	4 CORNERS	STEEL	BLACK	.03	\$1.25	\$0.99
	18386-FN	D	3-1/8"/80MM	OFFSET	4 CORNERS	STEEL	CHROME	.04	\$1.25	\$0.99
	18387-FN	E	3-5/8"/90MM	OFFSET	4 CORNERS	STEEL	CHROME	.05	\$1.25	\$0.99
	18388-FN	F	4-11/16"/120MM	OFFSET	4 CORNERS	STEEL	CHROME	.08	\$1.39	\$1.25
	17815-FN	G	5"/127MM	OFFSET	4 CORNERS	STEEL	CHROME	.13	\$1.29	\$0.99
	18390-FN	Н	6-3/4"/172MM	OFFSET	4 CORNERS	STEEL	CHROME	.1	\$1.50	\$1.29
-									-	


4-11/16" 12V COMPAQ **SERVER FAN**

MFG: NIDEC FOR COMPAQ MODEL: TA450DC P/N: C33211-71A Compaq: 122394-006 Volts: 12VDC Current: 49A CFM: NA



Replacement fan used in Proliant 3000 servers. Plastic blades & housing. Thermistor controlled Variable speed fan with stall sensor out. UL/CSA/CE listed. 15" leads with 5 pin Compaq connector.

Sq: 4-11/16" T: 1-1/2 16718-FN 4-11/16" Compaq Fan \$4.95



Current: 1.23A CFM: 26.7 1-U Server fan with dual counter

rotating plastic blades in single plastic housing. 66.6dB noise. Ball bearings. Each motor has separate 3" leads. UL/canada/usa/TUV/CE listed. NO INFOAVAIL L: 2-3/16" WT: .19

SQ: 1-9/16' 18476-FN 12V Sunon Server Fan \$4.95

24VDC BLOWER

MFG: JAPAN SERVO P/N: E1540H24BYAZ-10 Input: 24VDC Current: 1A



Ball bearing blower With Plastic body & blades. 50+ db Noise, 3260RPM, 3.58"dia. intake, 1.32" X 1.34 Outlet. 2 in, leads to 2 Pin male header connector, UL/CSA/TUV

W: 5-7/8 " L: 6" T: 1-9/161 WT: .9 \$4.95 18207-FN 24VDC 1A Blower/Baffle

12VDC SERVER FANS

MFG: AVC for H/P P/N: DB0404812U Volts: 12 VDC

Current: 1.14A/subassembly CFM: 25+/subassembly

Server fan unit has 4 removable dual 1-9/16" (40mm) 12V fan subassemblies. Each subassembly consists of a 3 blade fan mechanically mounted in series with a 5 blade fan and cannot be separated. Both sets of fan leads brought out to a connector (NO Mate available). 2" leads. All fans have stall sensor output. UL/CSA/TUV/CE listed

L: 7-3/4" H: 1-9/16" (40mm) D: 3-1/8"

Server 12V Fan Assembly 15839-FN

12VDC TURBO FAN

MFG: DELTA P/N: GFB0412SHE-FOO Volts: 12VDC Current: .68A CFM: 22.25

1-U Server fan with dual counter rotating plastic blades in single plastic housing. 57dB noise. Ball bearings. Each motor has separate 3" leads. Tach. output for each. UL/CSA/VDE/CE listed. L: 1-31/32" H: 1-9/16" WT: .11

18470-FN 12V Delta Server Fan

12VDC 3-1/8" FAN

MFG: JAPAN SERVO P/N: DC PIXIE25 (PUDC12Z4-042) Volts: 12 VDC Current: 160mA

CFM: 42 Plastic blades & housing, 37db noise, Ball bearing. UL/CSA/TUV listed. 14" leads.

WT: .2 Sq: 3-1/81 15841-FN 12V Pixie 3-1/8" Fan \$3.49

4-11/16" 230VAC FAN

MFG: COMAIR/ROTRON P/N: GAA1238-230BB Volts: 230VAC

Current: .2A **CFM:** 111

Plastic blades with metal housing. 44dB noise. Ball bearings. Solder/Fan Plug. UL/canada/usa/TUV/CE listed.

SQ: 4-11/16 T: 1-1/2' WT: 1.2 \$12.95

18834-FN 230VAC Comair Fan

12VDC BLOWER

MFG: JAPAN SERVO P/N: FBDC12H7P-949 Volts: 12VDC Current: .68A

CFM: 23 Ball bearing blower With Plastic body & blades. 56 db Noise, 2 pulse/RPM Tach output. 2.12"dia. intake, 2.12" X 1.1 Outlet. 12 in. leads. UL/CSA/TUV Listed.

T: 1-5/16 L: 3-3/4" W: 3-5/8 WT: .32

12VDC Japan Servo Blower

\$4.95

5in. AC FAN

18224-FN

\$9.95

MFG: ORION P/N: OA119AP-11-1TB Voltage: 120VAC 50/60 Current: 120mA **CFM: 130**

Plastic blades, metal housing. 46db noise, Ball bearing. UL listed. Fan plug/solder terminals WT: 1.4 L: 5" W: 5' T: 1-9/16

Orion 5in Sq. AC Fan \$12.95 18767-FN

12VDC FAN


MFG: JAPAN SERVO P/N: SCNDM12B4 Volts: 12VDC Current: .5A **CFM:** 106

Unique Square/Round fan, Square side is same size & mounting as a Std. 4.7" (120mm) fan, Other side is 5" (128mm) Dia. Plastic blades & housing. 40dB noise. Ball bearing. 9" leads. UL/CSA/TUV listed. SQ: 4-11/16"/5" Dia T: 1-1/2 WT: .6

18015-FN 12VDC Japan Servo Fan

12VDC 3-1/8" FAN

MFG: AVANT-GARDE P/N: AV-825H12S Volts: 12VDC Current: .14A




SQ: 3-1/8" WT: .24 18720-FN 12V AV 3-1/8" Used Fan

LAPTOP FAN

MFG: SUNON P/N: GB0545AFV1-8 Volts: 5VDC Current: 07A **CFM:** 2.2

Laptop mini blower with plastic impeller & metal housing. Tach. output lead (4Pulse/revolution) 29 db noise. Vapo



17866-FN Sunon Laptop Blower

115VAC BLOWER

MFG: JAPAN SERVO P/N: CB2B4-608 Voltage: 115VAC 60Hz Current: 210mA

New, but pre-assembled with removable plastic filter housing & steel standoffs. Metal shell with Plastic blades. 55 db noise, Ball bearing. Outlet: 2-1/2" X 1". CSA listed. 10" leads

L: 6" W: 5-5/8" T: 3-5/8" WT: 1.7

18961-FN JapanServo 115VAC Blower \$12.95

24" STRAIGHT **FAN CORD**

ZIP Fan cord designed to plug onto most fans with .100in quick connect/solder terminals. Straight molded fan plug on one end

L: 24" WT: .04

18833-FN 24" Straight Fan cord \$1.49

FAN CORD FOR 3 FANS

18/2 ZIP Fan cord designed to plug onto most fans with .100in quick connect/ solder terminals. Three 90 Deg. angled molded fan plugs separated by 7-1/2 in. of cord. 8in. of pig tail to 1st. fan. 1 . 24 WT: .06

\$2.95 18057-FN 24" 90 Deg. 3X Fan cord

12" ANGLED FAN

CORD 18/2 ZIP Fan cord designed to plug onto most fans with

.100in quick connect/solder terminals. 45 Deg. angled molded fan plug on one end. WT: .03 L: 12"

12" 45Deg. Fan cord \$0.79

57

MPJA@MPJA.COM TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764

12V LIGHTED SAFETY SWITCH

SPST, Auto type full toggle with Red LED iluminated toggle handle. Cover must be opened to activate switch. Closing cover forces switch to original position (OFF). This switch has 3 terminals: +12 for contact

Ground for LED Contact for Load & LED. Terminals: .25" Quick connect. Rated: 25A @ 12VDC

Mounts in 1/2" hole. 18496-SW 12V Lighted Safety Switch \$2.95

FOOT SWITCH

Plastic case, General use foot switch ULusa/canada listed Switch. Contacts: SPST-NO 125/250VAC @ 6A. Actuation pressure: Approx. 3 lbs. **Cord Not Included**

WT: .23 L: 4-1/8" W: 2-7/8" H: 11 1EA 18151-SW General Use Foot Switch

FOOT SWITCH

Metal case, Medium duty foot switch for industrial use.

Contacts: SPDT 380VAC/220VDC @ 54

Actuation pressure: Approx. 4lbs. **Cord Not Included**

L: 5-1/4"	W: 2-5/8"	H: 1-5/8"	WT: .34
STOCK #	DES	C.	1EA
18152-SW	Medium Fo	oot Switch	\$7.95

ROCKER FOOT SWITCH

Metal case, Rocker action Heavy duty foot switch for industrial use. Momentary in either direction, spring return to center OFF. Contacts: DPDT Mom-Off-Mom 380VAC/220DC @ 5A

Actuation pressure: Approx. 2.5lbs. either side **Cord Not Included**

L: 5-5/8"	W: 2-3/4"	H: 2"	WT: .7
STOCK #	DESC		1EA
18153-SW	Bocker Foo	t Switch	\$13.95

FOOT SWITCH

Metal case, top protected Heavy duty foot switch for industrial use. Peďal protected from dropped material, UL/CSA Listed Switch. Contacts: SPDT 125/180VAC@15A. 1/4hp@ 250VAC

Actuation pressure: Approx. 4lbs. **Cord Not Included**

L: 7-3/4"	W: 3-7/8"	H: 5"	WT: 1.6
STOCK #	DES	C.	1EA
18154-SW	Protected	Foot Switch	\$19.95

SAFETY FOOT **SWITCH**

Metal case, enclosed Heavy duty foot switch for industrial use. Pedal protected on 3 sides. UL/CSA/TUV/CE Listed Switch. [Contacts:] SPDT 125/480VAC @ 15A. 1/4hp@ 250VAC

[Actuation pressure:] Approx. 4lbs. **Cord Not included**

L: 8-1/8"	W: 5-7/8"	H: 4-7/8"	WT: 2.4
STOCK #	DES	C.	1EA
18155-SW	Safety Fo	ot Switch	\$24.95

12V LIGHTED **TOGGLE SWITCHES**

SPST, 12VDC lighted standard sized toggle switches, Mounts in a 1/2in. hole with .25 Quick Connect terminals. Rated 10 Amps @ 12VDC.

Lamp is internally connected between the load contact (ACC) and "+" terminal. Switch contact between "ACC" "Ground" terminal

Terminal "+" = +12V in (Lamp) Terminal "ACC" = Load Terminal "Gnd" = - 12V (common)

H: 2-1/2" O//	4 L: 1"	W: 11/16"		W1: .02	
STOCK #	DESC.		1EA	10+EA	
7125-SW	Red Lighted	Toggle	\$1.95	\$1.54	
7126-SW	Yellow Lighter	d Toggle	\$1.95	\$1.54	
7127-SW	Green Lighted	d Toggle	\$1.95	\$1.54	

12V BATTERY SWITCH

AMP Rating listed are NON-SWITCHING SPST-NO Heavy Duty 12VDC battery cut-off switch with removable actuator "key" for security & safety.

WT: .3

8373-SW 500 \$12.95 \$11.75 **Battery Switch Battery Switch** 100 \$10.95 \$10.25

SPST PUSH BUTTON **SWITCH**

MEC, SPST-NO super small PC board mount switch used as a Limit or sense switches in VCRs, Tape players, etc. 1/8" black plastic push button. Rated: < 10gm activation force, .2VA @ 24V DC

L: 5/16"	W: 3/8"	T: 1/8"	W	WT: .001	
STOCK #	D	ESC.	1EA	5+EA	
15567-SV	W MEC F	P/B Switch	\$0.25	\$0.20	

MINI KEY SWITCH

MFG: SIEMENS PN: V42266-C4499-A162 Mini SPST Key Switch Rated: .1VA@ 125VAC. 6 Dimple lock with 2 plated brass keys. 90deg. Index, key removable in both positions. ALL KEYED ALIKE. P.C Board mounting. Includes 2 keys. Key removable in both positions **WT:** .04 SQ: 19mm HT: 19mm (Ex Pins)

\$3.95 18071-SW Mini Key Switch

MICRO RIGHT ANGLE PUSH BUTTON SWITCH

Right angle PC mount, SPDT-NO micro push button switch with black plastic actuator. Contacts rated .4VA

Mounting: P.C. Board WT: .001 12505-SW Rt. Ang. P/B Switch \$0.75 \$0.69

OPTICAL SWITCH

3 way bi-directional optical switch with 3.5mm optical in/outputs. Select from 3 different audio sources, or receivers. Includes TOSLINK to 3.5mm optical adapters



		WT: .23
STOCK #	DESC.	TEA
15189-FO	Fiber Optic Switch	\$4.99



VACUUM SWITCH

MFG: GOLDTECH P/N: PS100-A1310-A002 Range: Fixed, .07Pa/.0025PSI Decreasing Ports: 1 High/1Low; Barbed for 1/4" or 3/8" ID Switch: SPDT125VA/120VAC; 3A 120VAC/30VDC

Specifications/Features: Vertical mount vacuum switch for sensing pressure drops across fans, vents, filters, dampers etc. Max pressure: 6Kpa (8.5 PSI). .25" quick connect terminals. Silicone diaphram, PPO Housing. UL/ canada/us Listed

H: 3-7/8" W: 3-1/8" T: 2" WT: .17 \$8.95 18257-SW Vacuum Switch

MINI PRESSURE SWITCH

MFG: MICRO PNEUMATIC LOGIC P/N: 601-G-300mmHg PRESSURE: 300mmHg/5.8PSI Gage CONTACT RATING: 10A/.3Hp@125/250VAC

ACTION: SPDT

Plastic body, 5/32" Barbed hose port parallel to switch, pressure only. Burst Rating: 50psi. .187" quick connect switch terminals

L: 1-3/4" O/A W: 1-1/2" H: 1-1/8" WT: .04

18484-SW MPL Pressure Switch \$4.95 \$3.95



Lighted, large plastic body, panel mount SPDT push button switches. Mount in a 15/16" hole. 1/4" quick connect terminals. Switch Contacts: 5A @ 250 VAC. Replaceable wedge base Lamp: rated 12V @ 3W,

L: 2-1/2" WT: .065 17051-SW Green Game Switch \$2.95 \$2,49 \$2.95 \$2.49 17052-SW White Game Switch 17053-SW Yellow Game Switch \$2.95 \$2.49 17054-SW **Red Game Switch** \$2,49

SPST PUSH BUTTON SWITCH

Keyboard/Keypad, SPST-NO push button switch with white .25in. Sq. plastic actuator. PC terminals, can be face plate mounted in .578in. Sq. hole. Contacts rated .1VA. **H:** 11/16" Body **W:** 5/8" **L:** 43/64"

Mounting: P.C. Board /Face Plate

WT: .005 18018-SW Keypad P/B Switch

DPDT PUSH BUTTON SWITCH

Right angle PC mount, DPDT Alternate action (Push On/Push Off) push button switch with black .25in. Dia. plastic actuator. Contacts rated .4VA. Pin Spacing: .125" Row Spacing .087

Mounting: P.C. Board L: 1-1/8" O/A WT: .005 18017-SW Rt. Ang. P/B Switch \$0.29 \$0.25

FOOT SWITCH

FATAR PS-100 SPST-NO foot switch used with musical keyboards etc. Low current/Voltage "Sustain Pedal" Designed for Casio. Fatar Studios, Korg, & Ensonic etc. Hard plastic with rubber overcoat 6ft, cord with 1/4in. mono Phone plug on end.

WT: .6 W: 3-1/2" H: 1-1/2" "Sustain" Switch \$14.95 18029-SW



100+EA

UL MINI TOGGLE SWITCH

UL Listed Mini toggle switch, Mounts in a 1/4" hole with Solder tabs. Rated 5 Amps @ 125VAC.



STOCK #	STYLE	DESC.	TEA	100 + EA
5005-SW	SPST	On-None-Off	\$0.75	\$0.66
5006-SW	SPDT	On-None-On	\$0.35	\$0.27
16071-SW	SPDT	On-None-(Mom)	\$0.58	\$0.44
5010-SW	SPDT	On-Off-On	\$0.38	\$0.29
5009-SW	SPDT	(Mom)-Off-(Mom)	\$0.58	\$0.44
16072-SW	SPDT	On-Off-(Mom)	\$0.58	\$0.44
5011-SW	DPDT	On-None-On	\$0.41	\$0.30
16073-SW	DPDT	On-None- (Mom)	\$0.69	\$0.52
5014-SW	DPDT	On-Off-On	\$0.46	\$0.35
16074-SW	DPDT	On-Off-(Mom)	\$0.69	\$0.52
5016-SW	DPDT	(Mom)-Off-(Mom)	\$0.69	\$0.52

FULL SIZE 15A TOGGLE SWITCH

Standard toggle switches, Mounts in a 1/2" hole. Rated: 10 Amps @ 250VAC. 15A @125VAC. Screw terminals.

			W	/T: .03
STOCK #	STYLE	DESC.	1EA	100+EA
16081-SW	SPDT	On-None-On	\$0.88	\$0.66
16082-SW	SPDT	On-Off-On	\$0.95	\$0.71
16083-SW	SPDT	On-None-(Mom)	\$1.05	\$0.79
16084-SW	SPDT	On-Off-(Mom)	\$1.05	\$0.79
16085-SW	SPDT	(Mom)-Off-(Mom)	\$1.05	\$0.79
16086-SW	DPDT	On-None-On	\$1.24	\$0.93
16087-SW	DPDT	On-Off-On	\$1.24	\$0.93
16088-SW	DPDT	On-None-(Mom)	\$1.49	\$1.12
16089-SW	DPDT	On-Off-(Mom)	\$1.49	\$1.12
16090-SW	DPDT	(Mom)-Off-(Mom)	\$1.49	\$1.12

5019-SW	SPST Normally Open Red \$0.29	\$0.26
5020-SW	SPSTNormally Closed Blk \$0.29	\$0.26
360° WEB	Con Contract	

PUSH BUTTON SWITCH

Mini push button switch, Momentary, Mounts in a 1/4"

hole with Solder tabs. Rated 3 Amps @ 125VAC

STOCK # STYLE DESC.

FULL SIZE TOGGLE SAFETY COVERS

Plastic, Snap action safety covers for standard (1/2" Dia.) sized toggle switches. Cover must be opened to activate switch. Closing cover forces switch to original

position.		W	T: .02
STOCK #	DESC	TEA	TO+EA
16100-SW	Red Safety Cover	\$0.69	\$0.59
16101-SW	Green Safety Cover	\$0.69	\$0.59
16102-SW	Blue Safety Cover	\$0.69	\$0.59
16103-SW	Yellow Safety Cover	\$0.69	\$0.59
16104-SW	Purple Safety Cover	\$0.69	\$0.59
16105-SW	Black Safety Cover	\$0.69	\$0.59
16106-SW	Clear Safety Cover	\$0.69	\$0.59
16107-SW	Chrome Safety Cover	\$0.69	\$0.59

MINI TOGGLE SWITCH

Mini toggle switch, Mounts in a 1/4" hole with Solder tabs. Rated 5 Amps @ 125VAC.



WT: .02

STOCK #	STYLE	DESC.	1EA	100+EA
16075-SW	3PDT	On-None-On	\$0.74	\$0.55
16076-SW	3PDT	On-Off-On	\$0.88	\$0.66
16077-SW	4PDT	On-None-On	\$1.42	\$1.07
16078-SW	4PDT	On-Off-On	\$1.75	\$1.31

FULL SIZE 15A TOGGLE SWITCH

.25"Quick Connect terminals.

Standard toggle switches, Mounts in a 15/32" hole. Rated: 10 Amps @ 250VAC. 15A @125VAC.

1250/	٦٥.		WT:
K #	STYLE	DESC.	
-SW	SPDT	On-None-On	9

STOCK # STYLE DESC. 16	٨
18371-SW SPDT On-None-On \$1.	95
18372-SW SPDT (Mom)-Off-(Mom) \$1.	95
18373-SW DPDT On-None-On \$1.	95
18374-SW DPDT On-Off-On \$1.	95
18375-SW DPDT (Mom)-Off-(Mom) \$1.	95

UL SUB-MINI TOGGLE SWITCH

UL Listed Sub-Mini toggle switch, Mounts in a 1/8" hole with Solder tabs. Rated 1 Amp @ 250VAC.



WT: .02

STOCK #	STYLE	DESC.	1EA	200+EA
16110-SW	SPST	On-Off	\$0.45	\$0.35
16111-SW	SPDT	On-None-On	\$0.49	\$0.39
16112-SW	SPDT	On-Off-On	\$0.59	\$0.49

HEAVY DUTY 20A TOGGLE SWITCHES

Standard toggle switches, Mounts in a 1/2" hole. Rated: 15 Amps @ 250VAC. 20A @125VAC. Screw terminals.



				• • • • • • • • • • • • • • • • • • • •
STOCK #	STYLE	DESC	1EA	100+EA
12216-SW	SPST	On-Off	\$0.95	\$0.89
12217-SW	SPDT	On-On	\$1.15	\$0.90
12218-SW	SPDT	On-Off-On	\$1.50	\$1.22
12219-SW	DPST	On-Off	\$1.10	\$0.94
12220-SW	DPDT	On-On	\$1.80	\$1.44
12221-SW	DPDT	On-Off-On	\$1.95	\$1.56

SUB-MINI **TOGGLE SWITCH**

Sub-Mini toggle switch, Mounts in a 1/8" hole with Solder tabs. Rated 1 Amps @ 250VAC. TUV Listed



WT: .02

STOCK #	STYLE	DESC.	1EA	100+EA
18398-SW	SPST	On-Off	\$0.75	\$0.60
18677-SW	SPDT	On-None-On	\$0.43	\$0.32
18725-SW	SPDT	On-Off-On	\$0.54	\$0.40
18175-SW	DPDT	On-Off	\$0.75	\$0.60
18676-SW	DPDT	On-Off-On	\$0.72	\$0.54

MINI TOGGLE SWITCH WITH FULL TOGGLE

Mini toggle switches with full sized togg actuator. Mounts in a 15/32" hole. Rated: 6 @125V/3A@250VAC. UL Listed. Solder to



BA er-	1	
	A/T-	U3

			WT: .03
STOCK #	STYLE	DESC.	1EA
18376-SW	SPDT	On-None-On	\$1.49
18377-SW	SPDT	On-Off-On	\$1.49

MINI TOGGLE WATERPROOF BOOT

Molded rubber toggle boot with molded in nut & "O" ring panel seal for mini toggle switches.

WII Th

LL NOT FIT 5	016 Switches.		
read: M6X0.	75	WT:	.00
TOCK #	DESC.	IEA 1	DEA

16311-SW Mini Toggle Boot \$1.95 \$1.75

LARGE PUSHBUTTON SWITCH

SPST-Normally open, Full size, metal body, Pushbutton switch, Mounts in a 3/4" hole. Rated 2A @ 250VAC/4A @ 125VAC. Screw Terminals.





WATERPROOF BOOT Molded rubber toggle boot with molded in nut. Forfull sized toggle switches 16081 16090 & 12216-12221

Thread: M12	K0.75	W	T: .009
STOCK #	DESC:	TEA	10EA
16312-SW	Full Toggle Boot	\$2.49	\$2.25

SPDT SLIDE SWITCH

PC mount, super mini slide switch. Contacts rated .4VA. Pin Spacing: 2mm. Sold in Packs of 10pcs.

FULL TOGGLE

18453-SW Mini Slide Switch \$1.00 \$0.80	L: 11/32" W: 3	3/16"	H: 5/1	6" Body	/ + Act.	WT:	.009/10
	STOCK #		DESC		110		10+FIC
					\$1	.00	\$0.80

MISC. TOGGLE SWITCHES



5001-SW



5004-SW



Full size toggle switch, Amp Ratings are @ 125VAC. 5001: Wire leads 5002: Solder tab 5004 & 12223: Screw Mtg.: 1/2" hole WT: .07 5

		On-None-Off	_		
004-SW	DPDT	On-Off-On	10	\$1.95	\$1.75
2223-SW	SPST	On-None-Off	10	\$1.25	\$0.96

LEVER/ROLLER SNAP SWITCH

SPDT Lever/roller switch. Contacts rated: 5A @ 250VAC 1" lever requires 35gm force. .187" quick connect terminals. 2 hole mounting. CE Listed.

L: 1-1/8"	(body) W	V: 5/8"	T: 3/8"	W	/T: .015
STOCK #	Carlotta de la care	DESC.		TEA	50EA
16315-SW	Rolle	r Micro	Switch	\$1.25	\$0.99

MINI SNAP SWITCH WITH ROLLER

SPDT micro switch with roller. Contacts rated 3A@125/250VAC.55gmactuation force. Sol-

16317-	SW	Mi	ni Sna	p Switch	\$0.89	\$0.79
SIDC	KI		DES	5G.	TEA	10EA
L: 3/4"	(body)	W:	3/8"	T: 1/4"	W	T: .005
der term	nnais. 2	mtg	. noies.	. 3/4 lever.	4	

SNAP SWITCH

SPST-NO Cherry switch. Contacts rated: 15A @ 125/250VAC. Button requires approx. 250gm force. solder terminals. 2 hole mounting. UL/us/canada Listed

WT: .011 L: 1-1/16"(body) W: 5/8"

STOCK #	DESC.	TEA	10EA
18084-SW	Cherry Snap Switch	\$0.99	\$0.79
CONTRACTOR AND ADDRESS OF	AND A COUNTY OF THE PARTY OF TH	CONTRACTOR	- Company of the property of the states and

COLOR MINI CAMERAS

Small cameras with metal case. Connects to any monitor or VCR with A/V inputs. Extension cable available

Element1/4in. Color, CCD Lens:Fixed 3.6mm/3.7mm pinhole Scanning: EIA 525 lines- 60 fields, S/N Ratio: >46dB Auto shutter: 1/60-1/100,000 Sec.

Resolution: 380 TV lines, Sensitivity: 2lux. @ F: 2 Video output: NTSC std.

75 Ohm, 2/l interlace1.0V P/P composite video Connections: 12" Video & Power leads Video: RCA Female, Power: Male Coaxial

Power: 12VDC +-.5V @ 100mA Sa: 1-3/8"W/O bracket D: 1-3/8"may WT: 4

Oq. 1 0/0 1	W/O Bracket Bill of	O III CON TOTAL
STOCK	DESC.	TEA 5+EA
14383-ST 14384-ST	3.6mm Clr. Camera Pinhole Clr. Camera	\$89.95 \$79.95 \$99.95 \$89.95

B/W MINI CAMERAS WITH AUDIO

Small cameras with metal case. Connects to any monitor or VCR with A/V inputs. Extension cable available.

With bracket & power supply.

Element: 1/3in. Monochrome, CCD Lens: Fixed 3.6mm/3.7mm pinhole Scanning: EIA 525 lines- 60 fields Auto shutter: 1/60-1/100,000 Sec. S/N Ratio: >46dB

Resolution: 380 TV lines Illumination: Ambient light Sensitivity: .1lux. @ F: 2 Power: 12VDC +-.5V @ 110mA Video output: EIA std.

75 Ohm, 2/I interlace 1.0V P/P composite video Audio: 2V P/P max Connections: 12" Video,audio & Power leads Video/Audio: RCA Female Power: Male Coaxial

Sq: 1-3/16"W/O bracket D: 1-3/16"max WT: .4

STOCK #	DESC.	TEA	5+EA
14248-ST	3.6mm Clr. Camera/Audio	\$49.95	\$44.95
14249-ST	Pinhole Clr. CameraAudio	\$49.95	\$44.95

ENCLOSED B/W CAMERA

1/3" CCD, Fixed 3.6mm pinhole lens. Scanning 525 lines-60 feilds S/N ratio:>35dB, Resolution: 400 TV lines, Sensitivity: .1

lux @ F:1.2, Video output : EIA 75 Ohm, 2/1 interlace 1.0V P/P composite video. Metal housing with removable mounting bracket. Auto iris/shutter: 1/60/-1/100,000 sec. Connections: 18" leads Video/ RCA Female, Power/ Coaxial. Power 12Vdc +-

1V @ 120mA. Plug supply included

Sq: 1" W/O	bracket" D: 9/16"		WT: .17
STOCK	DESC	JEA	5ea
12018-ST	Enc. B/W Camera	\$59.95	\$54.95



www.briefcasetools.com

WIRELESS COLOR BABY MONITOR



Designed for use as a child monitor; this unique item as many security applications. 2.4GHz Wireless Pan/Tilt Color Camera with I/R LEDs and a 2.4" Color LCD Receiver. Intercom function. Battery/AC operation.

Camera: 510X492 Color CMOS 380 lines NTSC 3Lux/F1.2

Reverts to B/W at low light with IR LEDs LEDs: 9 pcs. IR. range: up to 30ft.

Transmit Power: <10mW Range: 200M Unobstructed

Power: 3.7V Rechargable Battery (3Hrs Operating)

5VDC Plug Supply Mic/Speaker: Built-In

RECEIVER:

2.4" Color TFT LCD Display

Sensitivity: <85dBm

Power: 3.7V Rechargable Battery (3Hrs Operating) 5VDC Plug Supply

3.5mm earphone jack

Controls:

Power, Up, Left, Right, Down, Menu, Talk

Oper. Temp: -20-+50 C camera /-10-+50C Recv. Includes 2 Chargers, Earphones for receiver Power: 3.7V Rechargable

Cam.: H: 41 Dia.: 2.75'

		W 1: 1.0
STOCK #	DESC.	1EA
18416-ST	Baby Monitor System	\$119.95

Sign-up for our email ON MPJA.COM

PRO **BLACK & WHITE** SECURITY CAMERA



L: 4"	W: 2"		H: 2"		WT: 2	
STOCK #		DESC.		1EA	5EA	
14363-ST	Pro Se	curity C	amera	\$79.95	\$74.95	

CAMERA VIDEO/POWER CABLE

Siamese cable for cameras. Cable splits out 8" from ends into a video cable with a BNC male on one end and a RCA male on other and a

power cable with a 2.1mm I/D coaxial power Plug on end (same end as video RCA) and a 2.5mm I/D power Jack on other. Includes a BNC Male to RCA Female adapter.

STOCK #	DESC.	WT.	1EA
15460-WI	25ft. Camera Cable	0.6	\$6.95
15461-WI	50ft. Camera Cable 1	.8	\$9.95
15462-WI	100ft. Camera Cable	3.4	\$17.95
15463-WI	150ft. Camera Cable	4.9	\$22.95

FIRE ALARM



UNITED SECURITY PRODUCTS FHS-24 Remote Signaling Device. Contains Audable & Xeon flash. Produces 96dB sound and approx. 1 flash every 3 seconds. Requires 24 VDC @ 65mA. Fits on a 4"Sq. X 1-1/2" deep electrical box. Red color, UL listed

W: 5-1/4" H: 4" D: 2"

STOCK N	DESC.	1EA
18040-MI	24VDC USP Fire Alarm	\$9.90

ALARM SWITCH

Security system door or window mag switch & Magnet. SPDT switch can be wired for NO or NC contacts. Foam tape or 2 hole mounting, Screw terminals. Approx, 1in. needed to activate.

L: 2-9/16" W: 5/8" HT: 9/16" WT: .06 18548-SC **SPDT Security Mag Switch** \$4.95

4 OUTPUT 12VDC **CAMERA SUPPLY**

P/N: 264-2250-4 Input: 100-240 VAC 50/60Hz Output: +12V @ 5A

Specifications/Features: Desktop switching supply Over current protection. Std. IEC input connector. 5ft. output cable with 4 12mm X 5.5/2.1mm coaxial connectors split off 18" from ends. UL/TUV/CE Listed.

H: 4-5/8"	W: 2-1/4"	D: 1-1/2"	WT: .6
STOCK		DESC;	TEA
18682-PS	12VDC C	amera Supply	\$17.95

MOTION DETECTOR

Portable mini motion detector, 10 superbrite white LEDs light for approx. 30sec. when motion is detected. Detection range: approx. 10ft+. Requires 3 "AA" cells. (Not supplied). Can be wall mounted or placed on flat surface

SO - 3-3/8" T- 1-1/2"

04.100,0	** 1 1/2	***************************************
STOCK	DESC	TEA
17923-MI	Portable Motion Detector	\$11.95

UV MARKING

Unique marking & identifying system. Includes a pen that dispenses a clear, permanent ink visable only under UV

light from the mini UV LED Flashlight. Mark documents, pictures, cell phones, I-Pods & other electronics. Prove ownership of lost or stolen items. Uses 3 LR44 coin cells (Included) includes Key/Belt loop chain.

L: 2-1/2" (Light) WT: .24

UV Marking System 17936-MI \$5.95

CURRENCY DETECTOR

World wide forgery detector contains a 400nm UV LED and Magnetic thread/lnk detector. Requires 4 LR44/AG13 cells (included) push button switches for functions. For currency/document/ art examination, chemicial analysis, gem indentification

: 3-1/2	W: 1"	T: 7/8"	WT: .1
STOCK #		DESC.	THEA
18328-MI	UV/Ma	ag. Forgery Detector	\$5.99

BLACK HEATSHRINK TUBING

Listed dia. before shrinking, 2X min shrink ratio. Rated 125deg. " C", 600V. UL/CSA Listed. Available in 4ft lengths or 100ft. Rolls

L: 4π.				
STOCK#		DESC.	WT.	1PC
16325-HS	3/64	Black Shrink	.004	\$0.49
16326-HS	1/16	Black Shrink	.007	\$0.59
16327-HS	3/32	Black Shrink	.009	\$0.69
16328-HS	1/8	Black Shrink	.011	\$0.75
16329-HS	1/4	Black Shrink	.022	\$0.95
16330-HS	3/8	Black Shrink	.033	\$1.10
16331-HS	1/2	Black Shrink	.047	\$1.25
16332-HS	3/4	Black Shrink	.09	\$1.99

HEATSHRINK ROLLS

16333-HS



Flexable

3/16"

3/8"

35pcs.

18pcs.

8pcs



3.6

\$48,17

WT: .4

COLOR HEATSHRINK TUBING



Polyolefin (Clear-CYG-KYNAR) Listed dia. before shrinking 2X min shrink ratio. Rated 125deg. " C", 600V. Available in 4ft lengths Only **UL/CSA Listed**

RED HEATSHRINK

4.00	
4ft.	
 T16.	

- TIC.				
STOCK #		DESC.	WT.	1PC
16601-HS	3/64	Red Shrink	.004	\$0.49
16602-HS	1/16	Red Shrink	.007	\$0.59
16603-HS	3/32	Red Shrink	.009	\$0.69
16604-HS	1/8	Red Shrink	.011	\$0.75
16605-HS	1/4	Red Shrink	.022	\$0.95
16606-HS	3/8	Red Shrink	.033	\$1.10
16607-HS	1/2	Red Shrink	.047	\$1.25
16608-HS	3/4	Red Shrink	.09	\$1.99
16609-HS	1	Red Shrink	.15	\$2.29

BLUE HEATSHRINK

L:	4ft.	
_		

L: 4ft

	DESC.	WT,	1PC
3/64	Blue Shrink	.004	\$0.49
1/16	Blue Shrink	.007	\$0.59
3/32	Blue Shrink	.009	\$0.69
1/8	Blue Shrink	.011	\$0.75
1/4	Blue Shrink	.022	\$0.95
3/8	Blue Shrink	.033	\$1.10
1/2	Blue Shrink	.047	\$1.25
3/4	Blue Shrink	.09	\$1.99
1	Blue Shrink	.15	\$2.29
	1/16 3/32 1/8 1/4 3/8 1/2 3/4	3/64 Blue Shrink 1/16 Blue Shrink 3/32 Blue Shrink 1/8 Blue Shrink 1/4 Blue Shrink 3/8 Blue Shrink 1/2 Blue Shrink 3/4 Blue Shrink	3/64 Blue Shrink .004 1/16 Blue Shrink .007 3/32 Blue Shrink .009 1/8 Blue Shrink .011 1/4 Blue Shrink .022 3/8 Blue Shrink .033 1/2 Blue Shrink .047 3/4 Blue Shrink .09

16481-HS \$12.95 \$10.95 Color Shrink Kit **BLACK HEATSHRINK**

Includes hinged plastic box with latches

ASSORTMENT 154 pc. of 4in. Shrink tubing.

1

HEATSHRINK ASSORTMENT 154 pc. of 4in. Shrink tubing in assorted colors. Flexa polyolefin rated for 135 deg.

Listed dia. before shrinking, 1/16" 56pcs. 3/32"

28pcs.

9pcs.

1/8"

COLOR

Flexable polyolefin rated for 135 deg. "C". Listed dia. before shrink-

ing, 1/16" 1/8" 56pcs. 3/32" 35pcs 3/16" 28pcs. 18pcs. 1/4" 9pcs. 8pcs Includes hinged plastic box with latches

			W 11.4
STOCK #	DESC.	TEA	12+EA
16482-HS	Black Shrink Kit	\$12.95	\$10.95

HEATSHRINK MARKER ASSORTMENT

360 pc. of 1/2in. long Shrink tubing. 300 black + 60 un-numbered

Flexable black polyolefin rated for 135 deg. "C". Listed dia. before shrinking, Numbered 0-9. In the following tubing sizes 1/8" 3/16

1/4" 3/81 1/2"

Includes hinged plastic box

WT: .4 16483-HS Heatshrink Marker Kit \$12.95 \$10.95

YELLOW HEATSHRINK

L: 4π.				
STOCK #		DESC.	WT.	1PC
16621-HS	3/64	Yellow Shrink	.004	\$0.49
16622-HS	1/16	Yellow Shrink	.007	\$0.59
16623-HS	3/32	Yellow Shrink	.009	\$0.69
16624-HS	1/8	Yellow Shrink	.011	\$0.75
16625-HS	1/4	Yellow Shrink	.022	\$0.95
16626-HS	3/8	Yellow Shrink	.033	\$1.10
16627-HS	1/2	Yellow Shrink	.047	\$1.25
16628-HS	3/4	Yellow Shrink	.09	\$1.99
16629-HS	1	Yellow Shrink	.15	\$2.29

CLEAR HEATSHRINK

CYG-KYNAR

STOCK #		DESC.	WT.	1PC
16631-HS	3/64	Clear Shrink	.004	\$0.49
16632-HS	1/16	Clear Shrink	.007	\$0.59
16633-HS	3/32	Clear Shrink	.009	\$0.69
16634-HS	1/8	Clear Shrink	.011	\$0.75
16635-HS	1/4	Clear Shrink	.022	\$0.95
16636-HS	3/8	Clear Shrink	.033	\$1.10
16637-HS	1/2	Clear Shrink	.047	\$1.25
16638-HS	3/4	Clear Shrink	.09	\$1.99
16639-HS	1	Clear Shrink	.15	\$2.29

GREEN HEATSHRINK

L: 4ft.				
STOCK #		DESC.	WT.	1PC
16641-HS	3/64	Green Shrink	.004	\$0.49
16642-HS	1/16	Green Shrink	.007	\$0.59
16643-HS	3/32	Green Shrink	.009	\$0.69
16644-HS	1/8	Green Shrink	.011	\$0.75
16645-HS	1/4	Green Shrink	.022	\$0.95
16646-HS	3/8	Green Shrink	.033	\$1.10
16647-HS	1/2	Green Shrink	.047	\$1.25
16648-HS	3/4	Green Shrink	.09	\$1.99
16649-HS	1	Green Shrink	.15	\$2.29

WHITE HEATSHRINK

:	4ft.	

STOCK #		DESC.	WT.	1PC
16651-HS	3/64	White Shrink	.004	\$0.49
16652-HS	1/16	White Shrink	.007	\$0.59
16653-HS	3/32	White Shrink	.009	\$0.69
16654-HS	1/8	White Shrink	.011	\$0.75
16655-HS	1/4	White Shrink	.022	\$0.95
16656-HS	3/8	White Shrink	.033	\$1.10
16657-HS	1/2	White Shrink	.047	\$1.25
16658-HS	3/4	White Shrink	.09	\$1.99
16659-HS	1	White Shrink	.15	\$2.29

VIOLET HEATSHRINK

L: 4π.				
STOCK #		DESC.	WT.	1PC
16661-HS	3/64	Violet Shrink	.004	\$0.49
16662-HS	1/16	Violet Shrink	.007	\$0.59
16663-HS	3/32	Violet Shrink	.009	\$0.69
16664-HS	1/8	Violet Shrink	.011	\$0.75
16665-HS	1/4	Violet Shrink	.022	\$0.95
16666-HS	3/8	Violet Shrink	.033	\$1.10
16667-HS	1/2	Violet Shrink	.047	\$1.25
16668-HS	3/4	Violet Shrink	.09	\$1.99
16669-HS	1	Violet Shrink	.15	\$2.29

DUAL WALL HEATSHRINK

4ft. long black, adhesive lined shrink

Flexable polyolefin rated for 135 deg. "C' Listed dia. before shrinking,

			MT.	
16674-HS	1/8	Dual Wall Shrink	.015	\$2.95
16673-HS	3/16	Dual Wall Shrink	.017	\$3.95
16675-HS	1/4	Dual Wall Shrink	.025	\$4.95
16676-HS	3/8	Dual Wall Shrink	.041	\$6.95
16677-HS	1/2	Dual Wall Shrink	.055	\$7.95
16678-HS	3/4	Dual Wall Shrink	.12	\$9.95
16679-HS	1	Dual Wall Shrink	.2	\$12. 95

DUAL WALL HEATSHRINK ASSORTMENT

37 pc. of 4in. long black, adhesive lined shrink tubing. Flexable polyolefin rated for 135 deg. "C" Listed dia. before shrinking,

1/8" 12pcs. 10pcs 1/2" 3/8" 6pcs. 4pcs. 3/4" 3pcs. 2pcs. Includes hinged plastic box with latches

WT: .52 16484-HS Dual Wall Shrink Kit \$16.95 \$14.95

HEATSHRINK TUBINGIFUSE Visit www.mpja.com for our Complete Products Lines.


6" BLACK HEATSHRINK ASSORTMENT



24 pc. of 6in. long Black Shrink tubing in assorted Dia. Flexable polyolefin rated for 125 deg. "C"/600V. Listed dia. before shrinking. 4 pcs. each of following sizes: 3/32", 1/8", 3/16", 1/4", 3/8" &1/2"

L: 6°		WT: .2
STOCK	DESC	1EA
16830-HS	Black 6" long Shrink Bagged	\$3.95

6" COLOR 1/8"HEATSHRINK ASSORTMENT



L: 6"	poo. •	vinto ipo	WT: .2	
STOCK		DESC.	VEA	
16831-H	S Color	1/8" Shrink	Bagged \$2.25	

6" COLOR 3/16"HEATSHRINK ASSORTMENT



10 pc. of 6in. long X 3/16" Dia. Shrink tubing in assorted colors. Flexable polyolefin rated for 125 deg. "C"/600V Blue Yellow 1pc. Black 2pcs. 1pc. 2pcs. Clear 1pc Green Red 2pcs White 1pc

L: 6"		WT: .2
STOCK #	DESC	TEA
16832-HS	Color 3/16" Shrink Bagged	\$2.50

6" COLOR 1/4"HEATSHRINK **ASSORTMENT**




\$2.95

10 pc. of 6in. long X 1/4" Dia. Shrink tubing in assorted colors. Flexable polyolefin rated for 125 deg. "C"/600V Black 2pcs. Blue 1pc. Yellow 1pc. Black Clear 2pcs Green 1pc

L: 6"	5. Willo 100.	WT: .2
STOCK #	DESC.	TEA
16833-HS	Color 1/4" Shrink Bagged	\$2.75

6" COLOR 3/8"HEATSHRINK **ASSORTMENT**



1100	2p00.	***************************************	100.		
L: 6"				WT: .2	
5100	iK #	D	ESC.	1FA	

Color 3/8" Shrink Bagged

12" COLOR **HEATSHRINK**

16834-HS



12in. lenghts of Red, White, & Black shrink tubing. 1each color in 1/8", 3/16" & 1/4" pre shrink sizes. 9pcs

L: 12"		WT: .04
STOCK	0E50:	TEA
18787-HS	12" Color Shrink	\$1.95

2-1/2" BLACK **HEATSHRINK ASSORTMENT**

158 pc. of 2-1/2in. Black Shrink tubing in assorted colors. Flexable polyolefin rated for 125 deg. "C"/600V. Listed dia. before shrinking, 60pcs. 40pcs. 1/8"

1/4" 3/16" 20pcs. 18pcs 3/8" 1/2" 10pcs 10pcs Includes hinged plastic box with latches

L: 2-1/2"		WT: .2
STOCK II	DESC.	188
16835-HS	2-1/2" Black Shrink Kit	\$10.95

2-1/2" RED **HEATSHRINK ASSORTMENT**



158 pc. of 2-1/2in. Red Shrink tubing in assorted colors. Flexable polyolefin rated for 125 deg. 'C"/600V. Listed dia. before shrinking, 60pcs. 1/8" 40pcs.

3/16" 20pcs. 1/4" 18pcs 3/8" 10pcs 1/2" 10pcs Includes hinged plastic box with latches

L: 2-1/2"		WT: .4
STOCK #	DESC.	1EA
16836-HS	2-1/2" Red Shrink Kit	\$10.95

4" **HEATSHRINK ASSORTMENT**

160 pc. of 4in. long shrink tubing. Includes Black, Blue, Clear, Green, Red, White & Yellow colors. Flexable polyolefin rated for 125 deg. "C"/600V. Listed dia. before shrinking,

1/16' 60pcs. 3/32 35pcs 3/16" 20pcs. 10pcs. 1/8 25pcs. 1/4" 3/8" 10pcs. Includes hinged plastic box with latches

L: 4" WT: .4 16843-HS 4" Assort. Color Shrink Kit

WIRING **ASSCESSORY**



Each set contains: 1ea. pocket flat blade screwdriver/AC/DC neon voltage

checker 100-250V Flexable 4in. long polyolefin shrink tubing rated for 135

deg. "C' 8pcs. ea. 1/16 8pcs. ea. 3/32" clear & black 6pcs. ea. 1/8 clear & black 4pcs. ea. 3/16' clear & black 2pcs. ea. 1/4 clear & black 3/8" clear & black 2pcs. ea. 20pcs. ea 3in. black & natural wire tyes

10pcs. ea 7in. black & natural wire tyes 4pcs. ea 1/8in. black & natural cable clamps 2pcs. ea 1/4n, black & natural cable clamps 2pcs. ea 5/16in. black & natural cable clamps 2pcs. ea 7/16in. black & natural cable clamps 1pc. ea 1/2in. black & natural cable clamp 1pc. ea 5/8in. black & natural cable clamp

20ea. assort. rubber grommits 40+pcs. ea 2.5mm X 10mm black & silver screws 40+pcs. ea 3.5mm X 12mm black & silver screws

Includes hinged plastic box with latch.

			** 11.0
STOCK #	DESC.	1EA	12+Ea
16485-HD	Wiring Asscesory Kit	\$16.95	\$14.95

4FT, BLACK **HEATSHRINK ASSORTMENT**



Polyolefin, Rated 125deg. " C",600V. Size listed is before shrinking, 2X min shrink ratio. One each of: 3/64",1/16", 1/32", 1/8", 1/4", 3/8", 1/2", 3/4",1".UL/CSA Listed.

L: 4	, O, (E)	otou.		WT: .45
STOCK #			DESC	1.65
18896-HS	4ft.	Black	Shrink Assort.	\$5.95

SPLASHPROOF FUSE BLOCK



L: 7-1/2"	W: 2-1/8"	H: 1-1/2"		WT: .9
STOCK #	DESC		1EA	S-EA
15526-FH	Splashproof A	ANE Holder	\$8.99	\$8.25

HEAVY DUTY FUSE BLOCK

Heavy duty Type ANE (ANL) fuse block. All metal parts are 24K Gold plated. Holds single ANE/ANL fuse up to 500A. Accepts up to 1AWG cable, Set screw clamp, clear snap

L: 4"	W: 1-7/8"	H: 1-1/2	2" V	VT: .2
STOCK		DESC.	1EA	SHEA
14948-FI	ANE FL	se Holder	\$10.95	\$9.95

2 POSITION FUSE BLOCK

Distribution block for Type AUE (AGU) fuses. All metal parts are 24K Gold plated. Holds 2 AUE (AGU) fuses up to 80A each. One 3 way #4 AWG input, Two 8AWG output. Inner steps to allow insulation into block. Set screw clamps, clear housing. L: 4" W: 1-7/8" WT: .4 H: 1-1/4' 14952-FH 2 Pos. Fused Block \$7.49 \$6.95

3 POSITION FUSE BLOCK

Distribution block for Type AUE (AGU) fuses. All metal parts are 24K Gold plated. Holds 3 AUE (AGU) fuses up to 80A each. One 3 way #4 AWG input, Three 8AWG output. Inner steps to allow insulation into block. Set screw clamps, clear housing.

L: 4"	W: 2-3/8"	H: 1-1/4"	1	NT: .6
STOCI	1 V	DESC.	1EA	5+EA
14953.	FH 3 Pos	Fused Block	\$9.75	\$8.95

POWER ENTRY MODULE/FUSE

DELTA 06L4, snap-in power inlet. Rated: 15A@250VAC. Standard male 3 blade IEC cord connector, fuse holder for 1-1/14" X 1/4' fuse & input voltage programming card (used to select power transformer taps). Solder terminals for output. For panels .04-.063in. thick. UL/CSA listed. NO RFI filter. W: 2-11/16" H: 1-1/8" D: 1"(body) WT: .09

****		2. ((2003)	********
STOCK #	D	SC.	16A
18467-FH	Power	Entry Module	\$4.95

POWER ENTRY MODULE

SCHURTER KD14.1101.151, power inlet. Rated: 10A @ 125VAC. Standard male 3 blade IEC cord connector, fuse holder for 5 X 20mm fuse, DPST Power Switch. .187" quick connect terminals for output. 2 mounting holes. UL/CSA listed. Includes 3.15A fuse. Does

NŎT contain RFI filter. W: 3-1/4" H: 1-3/16 WT: .12

18567-FH Schurter Power Entry Module

ATC/ATO AUTOMOTIVE FUSE **ASSORTMENT**

120 auto fuses in plastic storage box Each kit contains:

20pcs. 5A (Orange) 20pcs. 10A (Red) 20pcs. 15A (Blue) 20pcs. 20A (Yellow) 20pcs. 25A (Clear) 20pcs. 30A (Green)



15706-FU 120pc. Fuse Assort. \$13.95 \$12.95

FUSEHOLDER FOR GMA FUSES

Panel mount fuseholder for GMA.787' X.197" (20mm X5mm) type fuses. Rated 10A @ 250VAC. Multi-turn cap, solder terminals

Mounting H	ole: 1/2"		WT: .033
STOCK #	DESC.	1EA	5+EA
5585-FH	GMA Fuse Holder	\$0.50	\$0.40

CHASSIS FUSEHOLDER FOR STANDARD FUSES

Panel mount fuseholder for standard AGC (1-1/4" X 1/4") type fuses. Rated 15A @ 125 VAC/10A @ 250VAC. Multiturn cap, solder terminals



Mounting H		WT:.033	
STOCK #	DESC.	1EA	5+EA
4476-FH	Std. Fuse Holder	\$0.75	\$0.65

FUSE HOLDER FOR ATQ/ATC **BLADE FUSE**

Fiber reinforced nylon in line fuse holder with attached cover to keep out dirt. water resistant but not water proof. For

full size ATQ type blade fuses, 8" AWG12 wire loop. 30A max. current.

L: 9.5 U/A	l .	VV	1:.1
STOCK #	DESC.	1EA	5+EA
8878-FH	ATQ Blade Fuseholder	\$1.65	\$1.49

FUSE HOLDER FOR ATQ BLADE FUSE

Molded rubber In line fuse holder for full size ATQ blade fuses, Overall length is 9" (8" AWG12 wire loop). 30A max. current.

L: 9.5" O/A		W	T: .04
STOCK #	DESC.	1EA	5+EA
8879-FH	ATQ Blade Fuseholder	\$1.25	\$0.95

FUSEHOLDER & FUSE



Plastic in line fuse holder with 10A fuse installed. Holds a standard AGC (3AG) 1/4" Dia fuse. 16AWG Wire . 13" O/A

18082-FH	Fuseholder/10A Fuse	\$0.99	\$0.89
STOCK #	DESC.	1EA	10+EA
L. 13 O/A			CO.: 1 VV

2A SUB MINI FUSE

12130-FU	2	Submini Fuer	\$2.00	\$1.60
STOCK #	AMPS	DESC.	1PK	10+PK
L: 3/8"(Bod		Dia: 1/8"	WT:	.06/pack
		1/4W resistor. \ F 5 SAME VAL		
			Name and Associate Associate Street S	

TY-RAPS

UL listed Natural or Black Nylon ties Sold in packs of 100

STOCK #	DESC.	3.77	198	10±P%
0200-TY	5-1/2" Ty-Rap	.1	\$1.70	\$1.50
4529-TY	7-1/2"Ty-Rap	.2	\$2.80	\$2.00
4530-TY	11" Ty-Rap	.5	\$5.00	\$3.90
11630-TY	4" Black Ty-Rap	.1	\$1.30	\$1.10
11508-TY	7-1/2" Black Ty-Rap	.2	\$2.50	\$2.00
11633-TY	11" Black Ty-Rap	.5	\$6.90	\$5.50
0199-TY	4" Ty-Rap	.1	\$1.10	\$0.90

STAINLESS STEEL TIES

6pc. steel wire ties. For wire, cable or pipes 17545 W: 3/16" WT: .05 17873: L: 12" W: 6/161 WT: .1 17545-TY 6 Pack 7in. Wire Ties \$1.95 17873-TY 6 Pack 12in. Wire Ties \$3.50

GMA FUSES


.787" X .197"dia. (20mm X 5mm) Metric fuses for use in equipment designed for world wide use

SOLD IN PACKS OF 10 SAME VALUE.

L: .787"	Dia: .	197"	WT : .02/pk	
STOCK #	AMPS	DESC.	1PK	10±PK
15761-FU	.5	GMA Fuse	\$0.80	\$0.60
15762-FU	1	GMA Fuse	\$0.80	\$0.60
15763-FU	1.5	GMA Fuse	\$0.80	\$0.60
15764-FU	2	GMA Fuse	\$0.80	\$0.60
15765-FU	3	GMA Fuse	\$0.80	\$0.60
15766-FU	4	GMA Fuse	\$0.80	\$0.60
15767-FU	5	GMA Fuse	\$0.80	\$0.60
15768-FU	6	GMA Fuse	\$0.80	\$0.60
15769-FU	8	GMA Fuse	\$0.80	\$0.60
15770-FU	10	GMA Fuse	\$0.80	\$0.60
15771-FU	15	GMA Fuse	\$0.80	\$0.60

AGU/AUE FUSES

Audio System Distribution **Fuses** High performance Gold



L: 1-1/2"	Dia: 13/32"		WT: .02	
STOCK #	AMPS	DESC.	1EA	5+EA
14990-FU	30	AGU/AUE Fuse	\$2.25	\$1.90
14991-FU	40	AGU/AUE Fuse	\$2.25	\$1.90
14992-FU	50	AGU/AUE Fuse	\$2.25	\$1.90
14993-FU	60	AGU/AUE Fuse	\$2.25	\$1.90
14994-FU	80	AGU/AUE Fuse	\$2.25	\$1.90

ANL/ANE FUSES

Audio System Distribution **Fuses** High performance Gold Plated

L: 3-1/8"	W: 7/8		W	T: .06	
STOCK	AMPS	DESC	1EA	5+EA	
14998-FU	80	ANE/ANL Fuse	\$3.49	\$2.95	
14999-FU	100	ANE/ANL Fuse	\$3.49	\$2.95	
15000-FU	130	ANE/ANL Fuse	\$3.49	\$2.95	
15001-FU	150	ANE/ANL Fuse	\$3.49	\$2.95	
15002-FU	175	ANE/ANL Fuse	\$3.49	\$2.95	
15003-FU	200	ANE/ANL Fuse	\$3.49	\$2.95	

STANDARD **FUSES**



General use electronic fuses. SOLD IN PACKS OF 10 SAME VALUE

L: 1-1/4"	Dia:	1/4"	WT:	.03/pk
STOCK ¥	AMPS	DESC	IPK	10+PK
15775-FU	.25	Std. Blow Fuse	\$0.99	\$0.80
15776-FU	.50	Std. Blow Fuse	\$0.99	\$0.80
15777-FU	1	Std. Blow Fuse	\$0.99	\$0.80
15778-FU	1.5	Std. Blow Fuse	\$0.99	\$0.80
15779-FU	2	Std. Blow Fuse	\$0.99	\$0.80
15780-FU	4	Std. Blow Fuse	\$0.99	\$0.80
15781-FU	5	Std. Blow Fuse	\$0.99	\$0.80
15782-FU	6	Std. Blow Fuse	\$0.99	\$0.80
15783-FU	8	Std. Blow Fuse	\$0.99	\$0.80
15784-FU	10	Std. Blow Fuse	\$0.99	\$0.80
15785-FU	20	Std. Blow Fuse	\$0.99	\$0.80
	_			

ATC AUTOMOTIVE

ATC (ATQ) Blade type fuses used in

SOLD IN BOXES OF 10 OF SAME VALUE



STOCK &	AMP5	DESC.	TEK	10+PK
4215-FU	3	Automotive Fuse	\$1.50	\$1.20
3613-FU	5	Automotive Fuse	\$1.50	\$1.20
3615-FU	10	Automotive Fuse	\$1.50	\$1.20
3616-FU	15	Automotive Fuse	\$1.50	\$1.20
3617-FU	20	Automotive Fuse	\$1.50	\$1.20
3618-FU	25	Automotive Fuse	\$1.50	\$1.20
3619-FU	30	Automotive Fuse	\$1.50	\$1.20

AST MINI AUTOMOTIVE

AST Mini Blade type fuses used in cars SOLD IN BOXES OF 10 OF SAME VALUE.



WT: .05/pk

STOCK #	AMP5	DESC.	SPR	10+PK
15721-FU	5	Automotive Fuse	\$1.90	\$1.75
15722-FU	7.5	Automotive Fuse	\$1.90	\$1.75
15723-FU	10	Automotive Fuse	\$1.90	\$1.75
15725-FU	20	Automotive Fuse	\$1.90	\$1.75
15726-FU	25	Automotive Fuse	\$1.90	\$1.75
15727-FU	30	Automotive Fuse	\$1.90	\$1.75

10A DC BREAKER

P & B P/N W28-XT1A-10 snap in Thermal breaker rated 10A@ 32 VDC/250VAC max. 1/4 quick connect terminals. Mounts in 5/8" hole. Designed to fit into same size space as a Std. Fuesholder. For panels: .075"-.105" thick. UL/CSAVDE listed

L: 2" O/A		WT: .018
STOCK #	DESC	1EA
19100 EII	10A Circuit Breaker	\$0.00

IN LINE FUSE HOLDER



Plastic in line fuse holder. Holds a standard AGC (3AG) 1/ 4" dia fuse. Overall length is 9-1/2". Ideal for automotive uses etc. Max current is 3A continuous, 5A surge. 1 · 9 5" O/A

E. O.O O// (102
STOCK	DESG	TEA	5+EA
4477-FH	InlineFuseholder	\$0.75	\$0.60

MPJA@MPJA.COM

RECTIFIERSIREGULATORS


Visit www.mpja.com for our Complete Products Lines.

1A RECTIFIER DIODES

1N4000 series 1 Amp Axial diodes. DO-04 Case

STOCK #	DESC.	PIV	1EA	200EA	1000+EA
5211-DI	1N4001	50	\$0.05	\$0.04	\$0.03
5212-DI	1N4002	100	\$0.05	\$0.04	\$0.03
5213-DI	1N4003	200	\$0.06	\$0.05	\$0.03
5214-DI	1N4004	400	\$0.06	\$0.05	\$0.04
5215-DI	1N4005	600	\$0.06	\$0.05	\$0.04
5216-DI	1N4006	800	\$0.06	\$0.05	\$0.04
5217-DI	1N4007	1000	\$0.07	\$0.06	\$0.04

3A RECTIFIER DIODES




STOCK #	DESC.	PIV	10EA	200EA	800+EA
4991-DI	1N5400	50	\$0.25	\$0.18	\$0.16
4992-DI	1N5401	100	.19	.14	.12
4993-DI	1N5402	200	.20	.14	.13
4995-DI	1N5404	400	.21	.15	.13
4996-DI	1N5405	500	.21	.15	.13
4997-DI	1N5406	600	,22	.16	.14
4998-DI	1N5407	800	.23	.16	.15
4999-DI	1N5408	1000	.23	.17	.15

6A RECTIFIER DIODES



	Dia59				44.1	.002
I	STOCK #	DESC.	PIV	10EA	200EA	800+EA
	5218-DI	P600A	50	\$0.54	\$0.39	\$0.35
	5219-DI	P600B	100	\$0.60	.43	.38
	5220-DI	P600D	200	\$0.65	.47	.42
	5221-DI	P600G	400	\$0.70	.51	.45
	5222-DI	P600J	600	\$0.76	.55	.49
	5223-DI	P600K	800	\$0.76	.55	.49
	5224-DI	P600M	1000	\$0.76	.55	.49

IN-LINE **BRIDGES** WIRE LEADS



				** 1	001
STOCK #	AMP.	PIV	FIG.	1EA	25+EA
5234-BR	2	50	Α	\$0.44	\$0.39
5235-BR	2	400	Α	\$0.54	\$0.48
5236-BR	2	1000	Α	\$0.62	\$0.55
5237-BR	4	50	В	\$0.75	\$0.67
5238-BR	4	200	В	\$0.88	\$0.79
5239-BR	4	400	В	\$0.98	\$0.88
5203-BR	4	1000	В	\$1.49	\$1.34

6A Bridge

6A SQ. BRIDGE

5241-BR

5243-BR

Wire Leads for PC Board Mtg



	1
The state of the s	3
- Anna contract of the foundation of the foundat	25
建 2000年	B
縣 源 思。	lis.
ALCOHOLOGICA COLONIA	30
Carrier 12-17	6
The second second	

WT: 001 6A Bridge \$0.88 \$0.79

\$1.21

BRIDGE RECTIFIERS

Square package, .250" Quick connect



WT: .05 15-30A / .1 50A


STOCK #	AMP.	PIV	1EA	25+EA
5244-BR	15	100	\$1.91	\$1.70
5245-BR	15	400	\$2.65	\$2.38
5246-BR	15	1000	\$3.44	\$3.09
5247-BR	25	50	\$1.95	\$1.75
5248-BR	25	400	\$2.70	\$2.43
5249-BR	25	1000	\$3.49	\$3.14
5250-BR	35	50	\$2.25	\$1.99
5251-BR	35	400	\$2.99	\$2.69
5252-BR	35	1000	\$3.99	\$3.59
5254-BR	50	400	\$5.75	\$4.95
5255-BR	50	1000	\$6.45	\$5.95

1A MINI DIP BRIDGES

4 pin Mini DIP Package for socket or PC board mounting

, o board i	i curicii	19	V	VT: .001
STOCK #	PIV	DESC,	1EA	50+EA
5225-BR	50	1A DIP Bridge	\$0.39	\$0.35
5226-BR	200	1A DIP Bridge	\$0.42	\$0.37
5227-BR	400	1A DIP Bridge	\$0.44	\$0.39
5228-BR	800	1A DIP Bridge	\$0.50	\$0.45

1.5A ROUND BRIDGE



WT- 001

1.5 Amp. Wire Leads for PC Board Mtg

			44	1001
STOCK #	PIV	DESC.	1EA	50*E#
5230-BR	50	1.5A Bridge	\$0.35	\$0.32
5231-BR	200	1.5A Bridge	\$0.37	\$0.33
5232-BR	400	1.5A Bridge	\$0.39	\$0.35
5233-BR	800	1.5A Bridge	\$0.48	\$0.43

40A STUD RECTIFIERS

Silicon stud diodes rated 40A 600PIV. Available standard Cathode case or Reverse; Anode Case for ease in heatsinking. Includes 1/4-28 Nut.

	VV	1:.04
OCK #	DESC.	1+EA
ום פו	1N11100A 40A Cath Case Diede	23 60

STOCK	DESG.	1+EA
18392-DI	1N1190A 40A Cath. Case Diode	\$3.50
18393-DI	1N1190AR 40A Anode Case Diode	\$3.50

12V/3A **VOLTAGE** REGULATOR



T.I. PT6304N, "Point Of Load" Switching regulator. Rated: 16-30VDC input; 12VDC Output at 3A. Line/Load Reg: 0.5%. Output V can be adjusted with the addition of external resistor. 12Pin SIP

L: 1-11/16	W: 3/8	H: 0/8	W1:.02
STOCK #		DESC.	TEA
18659-RG	T.I. Sw	itching Regulato	r \$10.95

LOGIC DIODES

General purpose silicon logic diodes at OEM prices.

WT: .05/15 .16/100 DESC. 15+EA STOCK # 100+EA 1670-DI 1N4148 Diode \$0.04 0614-DI 1N914 Diode \$0.05 \$0.03

VOLTAGE REGULATORS

TO-220 CASE

32VDC Max input Voltage 1Amp Output, three terminal regulators WT: .001

STOCK #	IND, #	OUT V	1EA	25+EA
0359-RG	7805/340-5	+5	\$0.50	\$0.35
0366-RG	7905	-5	\$0.50	\$0.35
0361-RG	7812	12	\$0.50	\$0.35
0367-RG	7912	-12	\$0.50	\$0.35
0368-RG	7915	-15	\$0.50	\$0.35
0364-RG	7824	+24	\$0.50	\$0.35

LM-317 ADJ. **VOLTAGE** REGULATOR

One of the most popular Adjustable regulator of all time. Rated: 3-37VDC input; 1.2-35V adjustable output at 1A.

0365-RG LM317 Adj. Regulator \$0.75	\$0.49


800V @ 30A 1/2 BRIDGE

MFG: PRX P/N: CD410830 Rated 30ARMS @ 800V. 3 terminals with isolated case.

Dual Diode connected as a 1/2 bridge (Cathode of connected to Anode of other as 1 terminal). L: 3-5/8" W: 1"

STOCK #	DESC.		10+EA
18837-DI	30A Half Bridge	e Module \$10.95	\$9.96

TRANSISTOR SPECIAL



General purpose, small signal amplifiers in TO-226 plas-WT- 001

			, ,	
STOCK II	IND. #	1EA	100EA	2000+EA
2030-QT	PN-2222A	\$0.25	\$0.12	\$0.06
2224-QT	2N3906	\$0.25	\$0.12	\$0.06
4024-QT	2N4401	\$0.25	\$0.12	\$0.06

NE555 TIMER IC

Work horse of all timing circuits. 8 Pin Mini DIP.

WT: .001

2350-IC NE555 Timer IC \$0.50 \$0.42

PLL MOTOR CONTROL IC

Toshiba TC9203P Phase Lock Loop IC.Designed to control the spindle motor in Floppy Drives. Built in Oscilator, Auto Phase control, Auto Frequency control, many features needed to control motor speed.

			44101				
	STOCK	DESC.	1EA	25.EA			
	8381-IC	Toshiba PLL IC	\$1.25	\$1.00			
				_			

OPTO INTERRUPTER

MFG: LITEON P/N: LTH-301-23 LED: 60mA max 5VDC max reverse volts

OUTPUT TRANSISTOR: 20mAmax /30Vceo max Ic on state: .4mA @ Vce=5V

CONNECTION: PC Mount .197" Wide X .30" deep gap, Opto transistor output.

	18028-OP	Liteon	Opto-Interr	upter \$0.45	\$0.38
	STOCK a		DESC.	1EA	10EA
J	L: .54"	H: .39"	T: .22"	WT:	.0015

50

12V LED STRIPS



Water resistant, PVC encapsulated, flexible strip of 12 LEDs on 25mm C/C. 12VDC operation 75mA max current draw. 120 deg. view angle. Header sockets at both ends allowing interconnection of up to 50 strips.

Individual LED Intensity: Red: 80mcd Green: 180mcd Amber: 80mcd Blue: 70mcd White: 230mcd

W: 10mm

L.: 29.5cm WT: .022 10+EA 17358-OP **Red LED Flex Strip** 17359-OP **Green LED Flex Strip** \$12.95 \$8.95

17360-OP Amber LED Flex Strip \$12.95 \$8.95 17361-OP Blue LED Flex Strip \$12.95 17362-OP White LED Flex Strip \$12.95 \$8.95

12V RGB LED STRIP

Water resistant, PVC encapsulated,

flexible strip of 36 LEDs Grouped 1 each color on 25mm C/C. Total of 12ea Red/Green & Blue. Each color can be powered independently or concurrently. 12VDC operation, 220mA max draw. 120deg. view angle. Header sockets at both ends allowing interconnection of 15 Individual LED Intensity:

Green: 180mcd Blue: 70mcd Red: 80mcd When used with 18137-OP Controller; strip will slowly cycle through combinations of the 3 colors. Approx. cycle time is 16sec

NOTE: Cannot be connected to Single Color Strips

L.: 29.5cm W: 10mm WT: .022 17363-OP R/G/B LED Flex Strip \$16.95 \$12.95

12V RGB STRIP DRIVER



NEW SMT Driver module that plugs directly into the 17363-OP RGB LED strip. Controller will slowly cycle through combinations of the 3 colors. Approx. cycle time is 16sec.24in Power cord with a 5.5/2.5mm Jack on end 12VDC operation. Max Drive 15 strips NOTE: Cannot be connected to Single Color Strips

L: 24"			WT: .02
STOCK	DESC.	TEA	1/I+EA
	R/G/B Driver Module	\$8.95	\$6.95

3MM YELLOW/GREEN LED

3mm (T1) Bi-Color Yellow/Green LED, 3 leads. Transparent, non-diffused case. Common Cathode with separate Anode for each color. 1" Leads.
Wavelength: Y585/G565nM
Output: 19mcd typ.

Max forward current 20mA continuous. Forward Drop: Y2.6/G2.5V typ Max reverse Voltage: 5VDC.

WT: .0001 18037-OP C/C 3mm Bi-Color LED \$0.10 \$0.07

NEAR U/V LED

5mm (T1-3/4) Near Ultra Violet LED. Transparent, non-diffused, Water Clear case. 1" Leads. Wavelength: 400nM Output: 80mcd typ.

Max forward current 20mA continuous. Forward Drop: 3.6V typ

Max reverse Voltage: 5VDC.

WT: 001

14143-OP Near UV LED \$0.29 \$0.22

12V G-4 BI-PIN LED LAMPS

Bi-pin bulb replacement assembly features: 14 super brite LEDs,12VAC or DC operation, 55deg. beam angle. Replacement for most G-4 lamps. .9mm dia. X 8mm Steel Pins, plastic body.

Dia.: 22.5mm T: 11mm WT: .009

STOCK #	DESC.	1EA	10+EA
17352-OP Red LE	D Bi-Pin Lamp	\$8.95	\$6.95
17353-OP Green I	ED Bi-Pin Lamp	\$8.95	\$6.95
17354-OPAmber I	ED Bi-Pin Lamp	\$8.95	\$6.95
17355-OP Blue LI		\$8.95	\$6.95
17356-OP White L	ED Bi-Pin Lamp	\$8.95	\$6.95

HIGH LUMEN LED ENGINES

On Board Regulator 8-30V, AC/DC input.

LED light engines features: 6 high lumen LEDs. 120 deg. beam angle. Solder pads for linking of up to 30 modules. 5" leads

White: Color Temp:~4500 87 Lumens Red: 624nM 29 Lumens

Green: 525nM 65Lumens

L.: 1-1/4" W: 1 T: 3/16" WT: .002

18879-OP 18880-OP White 87 Im Light Engine \$12.99 Red 29 Im Light Engine \$12.99 18881-OP Green 65 Im Light Engine \$12.99

HIGH LUMEN LED ENGINES

12V, +-.5V AC/DC input Only.

LED light engines features: 6 high lumen LEDs. 120 deg. beam angle. Solder pads for linking of up to 30 modules. 5" leads

White: Color Temp:~4500 87 Lumens Red: 624nM 29 Lumens

Green: 525nM 65Lumens

L.: 1-1/4" T: 3/16" WT: .002


18875-OP White 87 Im Light Engine \$9.95 18876-OP Red 29 lm Light Engine \$9.95 18877-OP Green 65 Im Light Engine \$9.95

I/R PHOTO **TRANSISTOR**

STANLEY PS5022 Silicon NPN photo transistor in 3.4mm Sq. flat package. Rated: BVceo=30V, Ic=20mA, Vcesat= 100mV, Max sensitivity wavelength= 880nM, 1/2 angle=+- 20deg, photo current @ 1mW/cm2 @ 880nM= .4mA min/2mA typ. .4" leads.

STOCK #	DESC:	1EA	10sea
17756-QT	Stanley Phototransistor	\$0.19	\$0.18

I/R PHOTO TRANSISTOR



Siemens SFH309FA4 Silicon NPN photo transistor in T-1 LED case with I/R filter. Rated: BVceo= 35V, Ic=15mA, Vcesat= 200mV, Max sensitivity wavelength= 900nM, Photosensitivity range= 730-1120nM, 1/2 angle=+-12°, photo current @ .5mW/cm² @ 950nM= 1-2mA. 1" leads WT: 001

STOCK #	DESC.	TEA.	25+6A
8949-OP	Photo Transistor	\$0.30	\$0.25

BE SURE TO CHECK OUR WEB SITE FOR NEW ITEMS & SPECIALS

5MM TRI-COLOR **LEDS**



5mm (T1-3/4) Tri-Color Red/Green/Blue LED 4 leads. Transparent, diffused case. Available Common Anode (C/A) with separate Anode lead for each color. 1" leads Wavelength: R630/G525/B430nM,

Min. output: R200/G300/B150mcd

Max forward current 20mA continuous. Max Forward Drop: R2.5/G4.5/B4.5V. Max reverse Voltage =5VDC

2: Com 3: Blue 4: Green WT: .001

17137-OP C/A 5mm Tri-Color LED \$0.99 \$0.74

5MM **TRI-COLOR LEDS**



5mm (T1-3/4) Tri-Color Red/Green/Blue LED 4 leads Transparent, diffused case. Common Cathode (C/C) 1: Green

with separate Anode lead for each color. 1" leads
Wavelength: R630/G525/B430nM,
Min. output: R200/G300/B150mcd .
Max forward current 20mA continuous.
Max Forward Drop: R2.5/G4.5/B4.5V.


Have a continuous and the color of the c

2: Com 3: Blue 4: Red

Max reverse Voltage =5VDC

WT: .001 18605-OP C/C 5mm Tri-Color LED \$0.99 \$0.74

5MM RED/GREEN



5mm (T1-3/4) Bi-Color Red/Green LED 3 leads. Transparent, diffused case. Common Cathode with separate Anode for each color. 1" Leads.

Wavelength: R635/G570nM Min. output: R8/G5mcd

Max forward current 20mA continuous.

Max Forward Drop: R2.5/G2.5V. Max reverse Voltage =5VDC.

WT: .001

17136-OP C/C 5mm Bi-Color LED \$0.15 \$0.11

5MM RED/GREEN **BI-POLAR LEDS**

5mm (T1-3/4) Bi-Color, Bi-Polar, Red/Green LED 2 leads. Transparent, diffused case. Red & Green Leds connected in Anti-Parallel.. 1" Leads. Wavelength: R635/G570nM

Min. output: R8/G5mcd


Max forward current 20mA continuous. Max Forward Drop: R2.5/G2.5V.

Max reverse Voltage =5VDC.

WT: .001

17135-OP C/C 5mm Bi-Polar LED \$0.15 \$0.11

10MM WHITE 15000mcd LED



output. Max forward current 30mA continuous, 20mA recommended. 5VDC Max reverse Voltage. 3.8VDC typ. 4.5V max. Forward voltage drop. 15deg. View angle, 1"

WT:.004 100+EA

65

DESC 15415-OP 10mm WHITE LED \$0.43 \$0.30 LED


SPECIAL

Jumbo diffused red LEDs and mounting clips, rated current= 20mA, max current=30mA, buy your LEDs and get mounting clips for one low price

Sold in Packs of 10

WT:.001 1413-OP LEDs & Holders \$1.75 \$1.65

TECH. & INFO: CALL 561-848-8236 FAX 561-844-8764 MPJA@MPJA.COM



3MM/T1 WATER CLEAR

COLORED 5MM/T1-3/4

COLORED 3MM/T1

COLORED 10MM

	WATER CLEAR		OCEONE	D OIMINI, I I O/ T		LONED SIVIN	1/ 1 1		COLOR	ED TOW	IVI
STOCK	COLOR/WAVELENGTH	INTENSITY	SIZE	CASE	VF.	VRev max	IF cont.	WT	1EA	10+EA	100 EA
0206-OP	Red/660nM	2mcd Typ	3mm/T1	Red Non Diffused	1.8V	5V	20mA	.001	\$0.09	\$0.07	\$0.06
0972-OP	Green/565nM	3mcd Typ	3mm/T1	Green Non Diffused	2.2V	5V	20mA	.001	\$0.10	\$0.08	\$0.07
0973-OP	Yellow/585nM	3mcd Typ	3mm/T1	Yellow Non Diffused	2.1V	5V	20mA	.001	\$0.10	\$0.08	\$0.07
14143-OP	Near UV/400nM	80mcd Typ	5mm/T1-3/4	Water Clear	3.6V	5V	20mA	.001	\$0.29	\$0.22	\$0.20
12568-OP	Blue/470nM	3900mcd Typ	5mm/T1-3/4	Water Clear	4.0V	5V	20mA	.001	\$0.34	\$0.25	\$0.23
17145-OP	White	10000 Typ	5mm/T1-3/4	Water Clear	3.2V	5V	20mA	.001	\$0.34	\$0.25	\$0.23
16798-OP	IR /940nM/20deg.	17mW/sr	5mm/T1-3/4	Water Clear	1.2V	5V	20mA	.001	\$0.20	****	
17139-OP	Red/630nM	690mcd Min	5mm/T1-3/4	Water Clear	2.0V	5V	20mA	.001	\$0.18	\$0.16	\$0.14
11017-OP	Red/630nM	3000mcd Typ	5mm/T1-3/4	Water Clear	2.1V	5V	20mA	.001	\$0.29	\$0.22	\$0.20
15109-OP	Red/635nM	3000mcd Typ	5mm/T1-3/4	Red Non Diffused	2.0V	5V	20mA	.001	\$0.25	\$0.20	\$0.15
17142-OP	YellowGreen/574nM	460mcdmin	5mm/T1-3/4	Water Clear	2.1V	5V	20mA	.001	\$0.18	\$0.16	\$0.14
17143-OP	Pure Green/525nM	5000mcd Min	5mm/T1-3/4	Water Clear	3.4V	5V	20mA	.001	\$0.39	\$0.30	\$0.28
15111-OP	Yellow/585nM	3000mcd Typ	5mm/T1-3/4	Yellow Non Diffused	2.2V	5V	20mA	.001	\$0.25	\$0.20	\$0.15
18036-OP	Yellow/585nM	40Тур	5mm/T-1-3/4	Yellow Non Diffused	2.6V	5V	20mA	.001	\$0.10	\$0.07	\$0.05
17141-OP	Yellow/590nM	2000mcd Min	5mm/T1-3/4	Water Clear	2.5V	5V	20mA	.001	\$0.18	\$0.16	\$0.14
0641-OP	Red/700nM	3.2mcd Typ	5mm/T1-3/4	Red Diffused	1.7V	5V	20mA	.001	\$0.10	\$0.09	\$0.08
4085-OP	Green/565nM	5mcd Typ	5mm/T1-3/4	Green Diffused	2.2V	5V	20mA	.001	\$0.15	\$0.14	\$0.12
18053-OP	Green/565nM/.5"Leads	19mcd Typ	5mm/T1-3/4	Green Diffused	2.2V	5V	20mA	.001	\$0.10	\$0.07	\$0.05
4086-OP	Yellow/590nM	5mcd Typ	5mm/T1-3/4	Yellow Diffused	2.1V	5V	20mA	.001	\$0.15	\$0.14	\$0.12
18038-OP	Red/Orange/630	19mcd/Typ	5mm/T1-3/4	Red Diffused	2.0V	5V	20mA	.001	\$0.10	\$0.07	\$0.05
18039 OP	Red/Orange/630	20Тур	5mm/T1-3/4	Water Clear	2.0V	5V	20mA	.001	\$0.10	\$0.07	\$0.05
17140-OP	Red/Orange/630nM	1500mcd Min	5mm/T1-3/4	Water Clear	2.1V	5V	20mA	.001	\$0.18	\$0.16	\$0.14
15132-OP	Red/660nM	450mcd Typ	10mm	Red Diffused	1.8V	5V	20mA	.001	\$0.25	\$0.20	\$0.15
15133-OP	Green/568nM	300mcd Typ	10mm	Green Diffused	2.2V	5V	20mA	.001	\$0.30	\$0.25	\$0.20
15134-OP	Yellow/590nM	600mcd Typ	10mm	Yellow Diffused	2.1V	5V	20mA	.001	\$0.30	\$0.25	\$0.20

BULK PACK LEDS 100PCS/PACK

STOCK#	COLOR/WAVELENGT	H INTENSITY	SIZE	CASE	VF	VRev max	IF cont.	WT	1PKG
15101-OP	Red/635nM	20mcd Typ	3mm/T1	Red Diffused	1.8V	5V	20mA	.1	\$1.95
15102-OP	Green/568nM	10mcd Typ	3mm/T1	Green Diffused	2.2V	5V	20mA	.1	\$1.95
15103-OP	Yellow/590nM	10mcd Typ	3mm/T1	Yellow Diffused	2.1V	5V	20mA	-1	\$1.95
15108-OP	Red/635nM	50 mcd Typ	5mm/T1-3/4	Red Diffused	1.8V	5V	20mA	.1	\$1.95
15308-OP	Green/568nM	5mcd Typ	5mm/T1-3/4	Green Diffused	2.2V	5V	20mA	.1	\$1.95
15309-OP	Yellow/590nM	5mcd Typ	5mm/T1-3/4	Yellow Diffused	2.1V	5V	20mA	.1	\$1.95



LED KIT #1

110 Piece, LED assortment packed in a plastic divider box, contains: 5pcs. 5mm Hi intensity White; 10ea. of the following: 5mm red, green, yellow & infrared; 3mm red, green & yellow; 30ea. black mounting clips for 5mm LEDs.

WT: .3 DESC. 10+EA 16313-OP LED Assortment Kit 1

7SEGMENT DISPLAYS

Red, Common Anode OR Common Cathode 7 seg-ment display. 660nm, 3-4.5mcd, 20mA max forward current, 5V max reverse

voltage. Typ. Forward Drop: 1.8V for .5in. /3.6V for 1". Gray face color

			44102
STOCK #	DESC.	1EA	10+EA
15118-OP	.5" Com. Anode Display	\$1.30	\$1.09
15119-OP	.5" Com. Cath. Display	\$1.30	\$1.09
15120-OP	1" Com. Anode Display	\$0.95	\$0.89
15121-OP	1" Com. Cath. Display	\$0.95	\$0.89

2" DOT MATRIX DISPLAYS

Red, Anode Column OR Cathode Column, 5 X 7 Dot Matrix display. 660nm, 5-9 mcd, 20mA max forward current, 5 max reverse voltage, 1.8V (typ) forwar drop. Gray face color

rd			
	WT	: .02	
		10+EA	

15124-OP 2" Col. Cathode Dot Matrix \$4.59 \$3.39 15125-OP 2" Col. Anode Dot Matrix \$4.59 \$3.39

LED KIT #2

110 Piece, LED assortment packed in a plastic divider box, contains: 5pcs. 5mm Red/Green Bipolar (2 lead); 10ea. of the following: 5mm red, green, yellow & infrared; 3mm red, green & yellow; 30ea black mounting clips for 5mm LEDs.

DUAL ALPHA-NUMERIC

DISPLAYS

Dual. .54" Red, Common Anode OR Common Cathode, 16 Segment display.

660nm, 2.5-5 mcd, 20mA max forward

WT: .3 DESC. 10+FA 3770-OP LED Assortment Kit 2

5X7RED & GREEN LED MATRIX

Liteon LTP-2757AA LED Matrix. Connected Anode Column/Cathode Row Fwd current/Dot: 100mA max/13mA Ave Max reverse Volts: 5V

Fwd. Drop: 2.6V @ 20ma Max 2.1V Green 2.0V Red Typ. Two color: red/orange (630nM) & Green (565nM) in separate Row/column matrix.

2in height, stackable horizontally. DATA H: 2

W: 1-1/2" WT: .05 16784-OP **5X7 LED Matrix**

4" DOT MATRIX DISPLAY


Red, AlGaAs, Anode Row, Cathode Column, 5 X 7 Dot Matrix display. 660nm, 10000 mcd, 100mA max, 20mA typ. forward current, 10V max reverse voltage. 4.8V(typ) forward drop. Black face color, Edge Stackable.



WT: .22 18460-OP 4" Red 5X7 Dot Matrix Display \$7.95

JUMBO LED MOUNTING CLIPS

Two part black plastic mounting clips for .200" LEDs, use to panel mount LEDs.



15128-OP .54" Com. Anode Alpha. 15129-OP .54" Com. Cath. Alpha.

current, 5V max reverse voltage, 1.8V (typ) forward

ORDERS: CALL 800-652-6733 FAX 800-432-9937



drop. Gray face color

5X7 GREEN LED MATRIX

Liteon LTP-2057AG 565nm Green LED Matrix. Connected Anode Column/Cathode Row Fwd current/Dot: 100mA max. 13mA Ave Max reverse Volts: 5V Fwd. Drop: 2.6V @ 20ma Max/ 2.1V Typ.

2in height, stackable horizontally. DATA

H: 2"

W: 1-1/2" W: 1-1/2 WT: .05

16786-OP 5X7 Green LED Matrix \$3.95 \$2.95

5X7 ORANGE LED MATRIX

Liteon LTP-2057AE 630nm Orange LED Matrix. Connected Anode Column/Cathode Row Fwd current/Dot: 100mA max. 13mA Ave Max reverse Volts: 5V Fwd. Drop: 2.6V @ 20ma Max/ 2.1V Typ.

2in height, stackable horizontally. DATA H: 2" W: 1-1/2"

WT: .05 16794-OP 5X7 Orange LED Matrix \$3.95 \$2.95

5 X 7 RED & GREEN LED MATRIX

Liteon LTP-2N57M LED Matrix. Connected Anode Row/Cathode Column Fwd current/Dot: 100mA max/13mA Ave Max reverse Volts: 5V

Fwd. Drop: 2.6V@20ma Max 2.1V Green 2.0V Red Typ. Two color: red/orange (630nM) & Green (565nM) in separate Row/column matrix

2in height, stackable horizontally. DATA W: 1-1/2

H: 2" **WT:** .05 18459-OP **5X7 LED Matrix** \$2.95

LED MATRIX DISPLAY

Unique LED graphical display with rectanglar LEDs in a 10X12 matrix. TYPE: X/YY Matrix. Colors as shown Color

mCd Dominant RED 1.9 Typ @ 20mA 3-7 660nM GREEN 2.1 Typ @ 20mA 565nM YELLOW 2.2 Typ @ 20mA Dot Size: Rect. 5.5mm X 3mm 3-5 585nM


Spacing: 2mmH/V between Dots DATA Gray Face/Diffused White Lens

L: 66mm H: 48mm T: 15mm WT: .057

18050-OP 10 X 12 LED Matrix Display \$1.95

LED TESTER

Compact, pocket sized checker/comparator for LEDs. 12 position test socket strip provides test currents of 2.5, 10,20,30 & 50mA. 7 center positions provide 10mA test current allowing you to compare several LED at the



H: 3-1/8" W: 2-3/8" T: 7/8" STOCK # DESC

WT: .1 **LED Tester** \$5.95 14371-TE

19" COLOR LCD DISPLAY

MFG: SHARP P/N: LQ190E1LW01 Type: SXGA Size: 19" Dia Colors: 16777216 Resolution:1280X1024 Brightness: 300cd/m2 (NITS)

Contrast: 700:1 Specifications/Features: New, ColorTFT-LCD display for Sharp computers. 5/4 aspect ratio, 5VDC Power, LVDS Data signal levels. CCFT backlight requires Inverter (LQ0DZC5016) Not Supplied.

W: 16 H: 13" T: 3/4 ShipWT: 7

18856-OP Sharp 19" LCD Display

SNAP-ON **NOISE FILTERS**

TIA-TECH P/N W5 SRH ferrite snapon filters. Black Plastic case with type W5 split core material. Clamps around 3/8" cable and blocks noise. Frequencies from 25MHz to above 500MHz. impedance: 100+@25MHz/200+@100MHz

STOCK #	CABLE	DESC.	WT	1EA
18466-FL	.25"	Clam Noise Filter	.07	\$0.99
18461-FL	.37"	Clam Noise Filter	.09	\$2.49
18462-FL	.5"	Clam Noise Filter	.18	\$1.25

SNAP-ON **NOISE FILTERS**

Fair-Rite P/N 0443167281 ferrite snap on filters. Plastic case with type 44 split core material. Clamps around cable up to .4in Dia. and blocks noise. Frequencies from 30MHz to500MHz. Permeability=500, impedance: 125@25MHz/210@100MHz L: 1.55" W: .94' H: .94" WT: .08

17842-FL .4" Clam Noise Filter \$1.95

POWER CHOKES

DALE IH Series high current filter chokes. 1in. Radial tinned leads for P.C. mount. Rated: +-10% Ind. tol., -55-+75° "C" operating temp, at full load.

IH-3-10uH/.018 ohm DC res./9A cont. L: 1" Dia: .631 IH-5-50uH/.03 ohm DC res./8A cont. L: 1"

STOCK #	DESC.	WT.	1EA
18059-CH	IH-3 10uH Choke	.03	\$0.75
18048-CH	IH-5 50uH Choke		\$1.25

FILTER CAP

P.C Mount electrolytic Filter cap rated: 1000uF @ 100VDC. P.C. Mount Snap-in pins. For

power supplies, Amps etc. Dia: 13/16" H: 1-9/16

18070-CR 1000uF Filter Cap

MONO CERAMIC CAPS

These small size monolythic ceramic caps are ideal for bypassing, filtering etc.



THERMOELECTRIC **ASSEMBLY**

Peltier Effect cooling assembly. Contains module with 127 Pairs of couples mounted to a heatsink assembly. Optimized for 12VDC. 65-70W (~170 BTU). 8A max, 16V max, Draws 6A @ 12VDC. Approx. 50Deg "C" temp. differance with hot side fan (Not

included) and insulated cold side. Designed for recreational coolers.

PELTIERIRESISTORICAP

STOCK #	Spirit Commen	DESC.	1EA	24+EA	
15312-PM	Peltier	Cooler Unit	\$29.95	\$27.95	

LARGER THERMOELECTRIC ASSEMBLY

Peltier Effect cooling assembly with larger, more efficent heatsink. Uses module with 127 Pairs of couples

mounted to a heatsink assembly. Optimized for 12VDC. 65-70W (~170 BTU). 8A max, 16V max, Draws 6A @ 12VDC. Approx. 50Deg "C" temp. differance with hot side fan (Not included) and insulated cold side. Designed for recreational coolers.

L: 6"	W: 4-5/8	8" T: 4-	1/4"	WT: 3.4
STOCK #		DESC.	1EA	24+EA
15513-PM	Peltier	Cooler Unit	\$37.95	\$34.95

100 WATT RESISTOR

Dale aluminum cased, chassis mt. power resistor rated: 3K ohm, 100 Watts,

1%. Non-Inductive. Aluminum housing with 2 mounting ears. 12-24 threaded stainless steel stud terminals with nickel plated brass nuts.

L: 3-1/2" Body W: 2-7/8" O/A H: 2-3/4" O/A WT: 8

STOCK #	DESC.	1EA
17868-RS	100W 3K Ohm Resistor	\$9.95

120 WATT RESISTORS

1.0 1/0 " 141.1 1/4"

WT: .04

\$0.99

Power resistors rated: 120 Watts, 5% Use for power supply or audio loads. Solder terminals and steel Mtg. brackets

H. 0 1/08 0/A WT. F

L. 0-1/2	AA. 1-11-4	11. 2-1/2	U/A	441
STOCK #		DESC.	1EA	50+EA
17785-RS	1 Ohm	120W Resistor	\$5.95	\$4.95
17786-RS	2 Ohm	120W Resistor	\$5.95	\$4.95
17787-RS	4 Ohm	120W Resistor	\$6.95	\$5.95
17788-RS	8 Ohm	120W Resistor	\$6.95	\$5.95
17789-RS	16 Ohm	120W Resistor	\$6.95	\$5.95

5 WATT RESISTORS

Ceramic Block, Power resistors rated: 5 Watts, 5%. Use for shunts, ballast resistors etc. 1-1/4" leads

L: 7/8"	W: 3/8"	H: 3/8"	1	NT: .01
STOCK #	į C	ESC.	1EA	100+EA
17790-R	S 0.1 Ohm	5W Resistor	\$0.35	\$0.29
17791-R	S 1.0 Ohm	5W Resistor	\$0.35	\$0.29

1000 WATT RESISTOR



and slotted steel Mtg. brackets

L: 23-1/4" O/A	H: 4" O/A	W: 2-1/2" O/A WT: 5
STOCK #	DESC.	1EA

MPJA@MPJA.COM

GBUY 1 GET 1 FREE

LIMITED TIME & QUANTITIES

WIRE TIE TOOL

SEE 18353 TL for SPECIFICATIONS

Tool tightens & cuts nylon ties in one operation.



830 TIE POINT BREADBOARD

SEE 4443 TE for **SPECIFICATIONS**

solderless breadboard with 2 distribution strips

19047-TE 2 BREADBOARDS

\$4.95

12V LED INDICATORS

SEE 16986 LE for SPECIFICATIONS

12mm Square Lens.LED & Lens Color the same



19056-TL 2 TIE WRAP TOOLS \$4.95 18997-LE 2 LED INDICATORS \$0.99

12V 3-3/8" FANS

SEE 18088 FN for SPECIFICATIONS

12VDC @ .75A 85CFM with Plastic Blades & Frame and Stall sensor output

18998-FN

2 3-5/8" FANS

SUCTION MOUNT

SEE 18521 MI for SPECIFICATIONS

Adjustable Plastic bracket with 2-3/4" suction cup

19055-MI

2 MOUNTS



24V RUNNING TIME METER

SEE 17906 PS for SPECIFICATIONS

ENM T33 series low power, Non-Resetable Time meter. 7digit, crystal contolled impulse counter



18982-MI **2 RUNNING TIME**

Limited Time Specials

MINI 0-30V/3A SUPPLY

P/N: 9615

Input: 110 VAC 60Hz

Output: 0-30VDC @ 0-3A Constant Voltage/Current Specifications/Features: True Constant Current (Can drive a short). Enclosed Switching bench supply with backlit LCD display for output Volts & Amps. .01% +5mV Line /.2%+5mV Load regulation, <200mV RMS max ripple. Front banana jacks. Internal fan. CE/RoHS

L: 6" W: 2-7/8"

H: 6-3/4"

9615-PS Mini 0-30V/3A Bench Supply

\$49.95

1/6" Black Shrink Tubing

LIMITED QUANTITY

Polyolefin, 1/16" dia. before shrinking with a 2X min shrink ratio. Rated 125deg. " C", 600V. UL/CSA Listed. L: 100ft. Roll

1/16" BLACK

HEATSHRINK

TUBING

HEADPHONE & MIKE



Small, light weight communication headset for Motorola V3688, V8088, L2000 & P3689 phones. Dynamic earpiece. FET mike in the interconnecting cord. Ideal for hands free operation, 4ft cord with 2.5mm stereo phone plug

WT: .07

24VDC DPST-NO RELAY

MFG: MAGNECRAFT P/N: 199QX-5 COIL: 24VDC/290 ohms

CONTACT RATING: 30A@28VDC

ACTION: DPST-NO

New but made in 1980s. General purpose contactor with .250" Quick connect terminals for contacts & coil. UL listed. 2-1/2" sq. mounting base

W: 3" H: 2-1/4" L: 3-1/2" WT: .6 18955-RL 30A Magecraft 24V Relay

PUSH BUTTON SWITCHES

BACK IN STOCK

Mini push button switches, Momentary, Mounts in a 1/4" hole with Solder tabs. Rated 3 Amps @ 125VAC



WT: .01

STOCK # STYLE DESC. 100+EA 5019-SW SPST Normally Open Red \$0.29 5020-SW SPSTNormally Closed Blk \$0.29

TRIPLE OUTPUT **BENCH SUPPLY**

MFG: MPJA Inc Input: 110 VAC 60Hz Outputs: #1: 0-30VDC @ 0-5A #2: 0-30VDC @ 0-5A #3: 5VDC @ 3A

Specifications/Features: Dual Constant Voltage or Current supply with dual backlit LCD meters. Selectable Series/Parallel operation of Adj. supplies.10 turn Voltage control, Push button Current control (30ma resolution) <.05% Line/Load regulation (CV) .05% line/load (CC). Front panel output Banana Jacks' & Terminal strips.

W: 10-3/4" D: 13"

H: 7-1/2"

WT: 28.7

9335-PS Three Output BenchSupply

68

CALL 800-652-6733

FAX 800-432-9937

WWW.MPJA.COM

PRODUCT & MANUFACTURES INDEX

	e Filter Cookbook" Web
710101	Air
Air	
Ampl	Cylinders
Annu	ifiérs Video WEB nciators 67
	ator Clips
Audio	
	Adapters 32 Cables 29,31 Connectors 32
	Microphones 00
	Speakers 67,68
Batte Bits.	ry
BNC	Connectors 37
Bore	Web Scope Camera 46 Cabinet 22,52,53 Cabinet 50,51 Jes 64 Cabinet 64 Cab
Brea	dboards 50,51
Brusi	les 19
Buzz	ers 67 es
	Audio
	Coax 30
	Cat-5E 34,35 Coax 30 Computer 27-29 Cutters 16-18
	Fiber Optic
	HDMI/DVI
	Phone 34,35 Power 33,34 Printer 27,28 Ribbon 31
	Ribbon
	Testers 48 USB 28 Video 29-31
Cam	eras
	Board
	Enclosed
	Board 60 Brackets 60 Enclosed 60 Inspection 46 Lens Web Weatherproof 60 acitors 67 %Cabinet 52,53
Capa	acitors
Cat-	5e
	Cable 34,35 Connectors 35 Hardware 34,35 Patch Cords 35
	Patch Cords
CA/C	1ester 48
	Amplifiers Web
	Cable 30
	Cameras 60 Connectors 37,39 Lens Web
	Lens Web Modulators Web Power Supplies 12,13 (es 67
Chok	Power Supplies 12,13 (es 67
Coax	Cable 30
Com	Strippers 16 puter
00111	Adaptors 27,28
	Boards 28 Cables 27-31 Gender Changers 28 Keyboard 28
	Gender Changers
	Gerider Changers 26 Keyboard 28 Monitor Tester 48 Power Supplies 9,10 RS232 Port Cards 28 Surge Protectors 34 Switch Boxes 27 USB 28
	Power Supplies 9,10 RS232 Port Cards 28
	Surge Protectors
	USB
Conr	nectors
	Audio 27,28 BNC 37,39 Cat-5 35
	DB 36
	DIN 36

Conn	ectors (Cont.)
	F (TV)
	HĎMÍ 30 IDC 36 Mini UHF Web N 38 RCA 32
	Mini UHF Web
	RCA 32 SMA 38
	SMA
	SMA 38 Telephone 35 UHF 39 XLR 32
Contr	
	DC Motor
Coun	ters, Impulse 40 o Terminals Web o Tools 16
Crimp	Tools16
Cylind	ders
Data:	Switches 27
JATAI	PC Board Supplies 51,52
DC/D	C Converters 8,11
Digita	Il Volt Meters
	Hand Held46,47 Panel48,49
Diodes	
	Rectifier
Displa	01/0
	LCD 67 LED 65,66
DTMF	
	Decoders/Display 55
Enclo	Caller ID Web Decoders/Display 55 sers, Boxes 52,53 FRONIC RAINBOW
	Kits 55
ELEN	Power Supplies 5
"F" C Fans	onnectors 39
i di is	AC/DC 56,57
	Blowers 56,57 Finger Guards 57
	Laptop 57
FET	Microphones 68
Fiber	Optic
	Audio 29 Accessories Web 3 13
Filters	62 63
Flash	62,63 lights 24,25,54
	sets 68
Heats	sink 40
Heats	shrink 61,62
HENG	
	Power Supplies 3
I/R Ed	quipment
	Analyzer 55 Camera 60
	Detector
	Motion Detector 60
Integ	Detector
	DC Power supplies 4,5
Jump	er Wire 55
Kits	Electronic Rainbow 55
	Electronic Rainbow 55 Thames & Kosmos Web Other 55
Lamp	OS 54
Laser	54
200	Displays 71 Panel Meters 48,49
LED's	
	Accortment Kit 65
	Blue/white 65-67 Displays 65,66
	Driver 67 Flashliights 24,25
	mi-Lumen
	Panel Meters 48,49 Panel Lights 54
	r direct Ligitio

LED's	(Cont.)	
	(Cont.) Strips	65 64
Lens	UV	65
Locks	S W	eb
MAST	ECH Power Supplies	2
Magn	net 21, nifiers/Lens/Optics 22-24,	45
MEAN	IVVELL	
Mete	Power Suppliesrs Digital Test	
Miore	Panel 48	49
Modu	phones W ulators W tor Tester	eb
Motio	on Detectors	bU
IVIOLO	AC	45
	rs AC AC DC Controller/Driver Pager Step 41-	41
	Step41-	43
MPJA		
	Digital Volt Meters 46, Panel Meters 48,	49
	Panel Meters 48, Power Supplies 2 Solder Stations 14, IR Thermometers	15
"\\"	onnectors	
	cs 22-24,	
Oscil	loscopes 22-24, probes 49,	50
	Probes 49,	
Dana	lo 50	49 53
"PC I	il Lights	eb
Phon	er i nermoeiectric Modules ne Cable 34,	35
PIC	o DetectorsW Controller Books W	DO.
Piezo	Alarms 60,	67
PIRE	Speakers Detectors Strips/Centers	68
Dilla	Cumpline	
-	AC Output	12
Pneu	er Cords	45
		eb
	ER SUPPLY-1 Switching Power Supplies	. 3
Powe	er Supplies Bench2-7,	46
	DC/DC Converters 8,	10
	Bench	45
PRO N		
	Camera Mounts Security Cameras	60
Rack	S 52,	53
Rare	Earth Magnets	
Rect	Kits	55
Date	Bridges Diodes Proce Books W	64
Rela	ys Control Madulas	26
	ys Control Modules Mechanical Solid State	26
Relay	Solid State	53
		0/
SAML	Power supplies	. 5
Secu	rity Equipment	00

Board	Cameras	
nent (Video Switchers Web	
Sirono	Digital Video Rec Web Weatherproof Cameras 60	
Sirens	Piezo	
Solde	Irone 1/-16	
	Rework 14,15 Solder 16 Stations 14-16 Suckers 15	
	Suckers	
Spea	State Relays	
Step	Motors 41,42	
	Battery 58	
	Data 27 Keyboard/Pad 28 Micro 58	
	Push Button	
Telep	hone Category 5e	
	Cable, Bulk 34 Terminated 34,35 Connectors 35 Equipment 34,35 Jacks 34,35 Keystone 34,35 Tone Decoder 55 Tools 16 perature Probe Kit 55 actions 55 guip 45-50	
	Jacks	
	Tone Decoder 55	
Temp	Tools 16 perature Probe Kit 55	
Term Test I	inals, Crimp	
Therr	noelectric Modules 67	
Tools	Brushes 19	
	Crimp	
	Pliers	
	Screwdrivers 20-22	
	Pliers 16-19 Magnifiers 22-24 Screwdrivers 20-22 Solder Stations 14,15 Strippers 16	
Trans	refere 64.65	
Trans	Plug	
TV	Chassis 13	
	Adaptors	
	Amplifiers Web Cable 29-31,60 Connectors 39	
	Connectors 39 HDMI/DVI 30 Modulators Web	
	Splitters Web	
Tv \\	Modulators Web Splitters Web Switchers/switches Web Security 61 Iraps 63	
	Connectors	
Video		
Vidoc	Board Cameras	
	Balun	
	Modulators Web Recorders Web	
VIDEO	MOUNT PRODUCTS	
Switches Web VIDEO MOUNT PRODUCTS Rack Equipment 52,53 Voltage Regulator IC 64		
Wire	(Also see Cables/Cords) Cat-5 34,35	
	Jumper	
	Power	
	11000 111111111111111111111111111111111	

STATEMENT OF THE PARTY OF THE P

CATALOG# 12-03H

SIHIL BOX 530400, PLACE AN ORDER OR REQUEST ANOTHER CATALOG

0 FLORIDA 33403-8906 lu

PRESORTED STANDARD U.S. POSTAGE PAID P JONES Z

WT: .34

PGS 58.59

\$0.69

12VDC 4-3/4" FAN

008620 P-130

MFG: JAPAN SERVO P/N: CNDC12Z7RP Input: 12VDC

Current: .71A **CFM: 124**

Specifications/Features: Ball bearing fan with plastic body & blades. 49 db Noise.

Tach sensor output. 10 in. leads. UL/CSA/TUV Listed. SQ: 4-3/4 T: 1-1/2 WT: .6

18222-FN 12VDC Japan Servo Fan \$4.95

MORE

PGS

FOOT SWITCH

58.59 Metal case, Medium duty foot switch for industrial use. Contacts: SPDT 380VAC/220VDC @ 5A. Actuation pressure: Approx. 4lbs


Cord Not Included L: 5-1/4" W: 2-5/8" H: 1-5/8 STOCK # DES

1EA \$7.95 18152-SW **Medium Foot Switch**

TOGGLE SWITCH SAFETY COVER

Red Plastic Snap action safety covers for standard (1/2" Dia.) sized toggle switch. Cover must be open to activate switch. Closing cover forces switch to original position.

16100-SW Red Safety Toggle Cover



SURGE PROTECTED

Wall mount surge protector with 4 outlets protected L/N, L/Gnd & N/Gnd. 1875 W max Load. Protect electronic equipment from electrical spikes Built in status indicator light. Clamp Volts: 330V. 4ft. line cord. UL listed.

WT:.22 \$8.95 18971-MI 4 Outles Surge Protector

1.8Deg. STEP MOTOR

MFG: SANYO DENKI P/N: 103G770-1856 COIL: 3.5V/1.5A/2.4ohm/2.9mH TYPE: 2 Phase Bi-Polar 6 lead STEP ANGLE: 1.8 deg

6.5mm dia. X 18mm steel shaft with a pressfit 3/4" dia. 25 tooth, plastic cog belt gear. Ball bearings, 5in leads. Removable anti-vibration bracket

with mtg. ears. 4 corner mounting holes (motor) L: 2-1/8"(Body) SQ: 2-3/16" WT: 1.3 16321-MS 1.8 Sanyo Step Motor \$9.95 \$8.95

2.0 USB CABLE

USB 2.0 cable with a TYPE A male on one end and a Type B Male on the other. Black jacket.

L: 36

36in. USB 2 Cable 18976-CB \$1.25 \$1.49

WT: .1

WT: .03

ROCKER SWITCH

MFG: C-H P/N: 56002-01 Action: ON/ON Contacts: 25A@12VDC

Snap-in panel mount rocker switch with screw terminals Bright metal bezel, mounts in 5/8in. X 1-9/16in. cutout L: 1-/8in W: 15/16in. Ht. 2in WT: .04

19017-SW 12VDC Rocker Switch \$1.50

FULL SIZE 15A TOGGLE SWITCH

Standard toggle switches, Mounts in a 1/2" hole. Rated: 10 Amps @ 250VAC. 15A @125VAC. Screw terminals.

16081-SW SPDT Full Toggle \$0.66 \$0.88

12VDC ACME **GEAR MOTOR**

P/N: 5503740 D


COIL: 12VDC 90Deg. Angled gearhead DC motor rated: 88/178/380RPM @ 6/12/24VDC, 1.5A No Load /17A Stall @ 12V.

.187 male quick connect terminals 4-1/8" long 7/16"-8 Modified class 4G single thread

Leadscrew with the custom traveler nut. L: 5-1/2" (OA) H: 2-1/4" (OA) H: 6 WT: 1.8 19007-MD 12VDC Acme Motor & Nut \$14.95

12V GEARMOTOR

COIL: 12VDC Gearhead DC motor rated: 6V= 65RPM/.1A no load/.5A Stall 12V=140RPM/.12A no load/1A Stall 15V=178RPM/.13A no load/1.2A Stall 5mm dia. X 10mm flatted steel shaft. 3 metric (M3) threaded mounting holes. 2" leads.





LIGHTED **MIRROR**

Telescoping, rectangular inspection mirror with 2 super brite mini white LEDs. Mirror head is 2-1/2" X 1-5/8". 11" collapsed (max), 34" extended (max). Uses two Coin Cells

WT: .28

\$9.95

\$0.10

360° VIEW @MPJA.COM

L: 11-34" W: 2-1/4'

Telescoping Lighted Mirror 18916-TL

2W SUPERBRIGHT **FLASHLIGHT**

Heavy Duty Flashlight with a single 2W OSRAM W5AM White super bright white LED Rated 70-80Lumens. Black, water re tant machined aluminum case. Fixed focus tor. Requires 2 "AA" cells (Not supplied). Al push button switch on back. Includes beli L: 6-1/4" D: 1-3/8"

18920-TL 2W Osram LED Flashligh

HEX **BIT DRIVER**

FOR A LIMITED TIME RECIEVE A FREE 4 PIECE BIT SET! While supplies last

Cordless driver for 1/4" (6.35mm) HEX shaft Uses 4 "AA" cells (not supplied) L: 8-1/4" DIA: 1-5/8"

18706-TL **HEX Bit Driver**

SUPER MINI PUSHBUTTON SWITCH

MFG: ALPS P/N: SKEYAB028A Action: SPST-NO Contacts: 5mA,12VDC

Small P.C. mount elastometric pushbutt Ohm contact resistance max. 120gm act

SQ: 7.8mm H: 5mm

18983-SW Mini PB Switch

MULTI FUNCTION PANEL METER

Compact, Auto polarity, 3-1/2 Digit, character height, reflective LCD panel meter with black plastic bezel & face plate. Adj. decimal point, .8% accuracy (1% AC). >100Mohminput imp.Chip On Board

design for economy & compactness.
For battery powered monitoring or test equipment.

RANGES: (jumper selected) ADC: 200mA VAC: VAC: 200V/500V

VDC: 200mV/2V/20V/200V/500V Selectable Power: 9VDC (Isolated power) or 5VDC (input & power can share common Ground)

W: 2-5/8" H: 1-3/4" D: 3/8 WT: .1

16177-ME Multi.LCD Panel Meter

24V TO 13.8V DC/ DC CONVERTER

Input: 20-35VDC Output: 13.8VDC @ 15A peak (1-2Min)

10A for 7Min/5A continuous.

Heavy duty, linear down converter. Used in applications where truck/boat etc. electrical system is 24V to provide 13.8VDC for Radios, and other communication systems. Isolated metal case, 6in input leads, binding posts for output. For direct connection to batteries only Series 2 units for up to 50VDC Input, Parallel units for higher current

W: 5-3/8 H: 1-1/2' WT: 2.3 L: 8 9610-PS 24/12V Down Converter \$29.95